

BEE 4750 Homework 5: Mixed Integer and Stochastic Programming

Name: Adrián Cardona Young

ID: alc354

Due Date

Thursday, 12/04/24, 9:00pm

Overview

Instructions

- In Problem 1, you will use mixed integer programming to solve a waste load allocation problem.
- In Problem 2, you will formulate a stochastic optimization problem.

Load Environment

The following code loads the environment and makes sure all needed packages are installed. This should be at the start of most Julia scripts.

```
import Pkg
Pkg.activate(@__DIR__)
Pkg.instantiate()
```

Activating project at `c:\Users\adric\OneDrive - Cornell University\Documents\3. Env Sys A

```
import Pkg; Pkg.add("CSV")
```

```

Resolving package versions...
No Changes to `C:\Users\adric\OneDrive - Cornell University\Documents\3. Env Sys Analysis\
No Changes to `C:\Users\adric\OneDrive - Cornell University\Documents\3. Env Sys Analysis\

```

```

using JuMP
using HiGHS
using DataFrames
using GraphRecipes
using Plots
using Measures
using CSV
using MarkdownTables

```

Problems (Total: 30 Points)

Problem 1 (24 points)

Three cities are developing a coordinated municipal solid waste (MSW) disposal plan. Three disposal alternatives are being considered: a landfill (LF), a materials recycling facility (MRF), and a waste-to-energy facility (WTE). The capacities of these facilities and the fees for operation and disposal are provided below.

- **LF:** Capacity 200 Mg, fixed cost \$2000/day, tipping cost \$50/Mg;
- **MRF:** Capacity 350 Mg, fixed cost \$1500/day, tipping cost \$7/Mg, recycling cost \$40/Mg recycled;
- **WTE:** Capacity 210 Mg, fixed cost \$2500/day, tipping cost \$60/Mg;

Transportation costs are \$1.5/Mg-km, and the relative distances between the cities and facilities are provided in the table below.

City/Facility	Landfill (km)	MRF (km)	WTE (km)
1	5	30	15
2	15	25	10
3	13	45	20
LF	-	32	18
MRF	32	-	15
WTE	18	15	-

The fixed costs associated with the disposal options are incurred only if the particular disposal option is implemented. The three cities produce 100, 90, and 120 Mg/day of solid waste, respectively, with the composition provided in the table below.

Component	% of total mass	Combustion ash (%)	MRF Recycling rate (%)
Food Wastes	15	8	0
Paper & Cardboard	40	7	55
Plastics	5	5	15
Textiles	3	10	10
Rubber, Leather	2	15	0
Wood	5	2	30
Yard Wastes	18	2	40
Glass	4	100	60
Ferrous	2	100	75
Aluminum	2	100	80
Other Metal	1	100	50
Miscellaneous	3	70	0

The information in the above table will help you determine the overall recycling and ash fractions. Note that the recycling residuals, which may be sent to either landfill or the WTE, have different ash content than the ash content of the original MSW. You will need to determine these fractions to construct your mass balance constraints.

Reminder: Use `round(x; digits=n)` to report values to the appropriate precision!

Problem 1.1

Based on the information above, calculate the overall recycling and ash fractions for the waste produced by each city.

City 1:

\$ W_1 = 100 \$ Mg/day

City 2:

\$ W_2 = 90 \$ Mg/day

City 3:

\$ W_3 = 120 \$ Mg/day

```
cities = ["City 1", "City 2", "city 3"]
cat = ["Food Wastes", "Paper & Cardboard", "Plastics", "Textiles", "Rubber, Leather", "Wood"]
mass = [100, 90, 120]
pcnt_mass = [0.15, 0.40, 0.05, 0.03, 0.02, 0.05, 0.18, 0.04, 0.02, 0.02, 0.01, 0.03]
pcnt_ash = [0.08, 0.07, 0.05, 0.10, 0.15, 0.02, 0.02, 1, 1, 1, 1, 0.7]
pcnt_recyclable = [0, 0.55, 0.15, 0.10, 0, 0.30, 0.40, 0.60, 0.75, 0.80, 0.50, 0]
```

```

#Finding mass of each waste for each city
city1 = zeros(12)
city2 = zeros(12)
city3 = zeros(12)
for i in 1:12
    city1[i] = mass[1]*pcnt_mass[i]
    city2[i] = mass[2]*pcnt_mass[i]
    city3[i] = mass[3]*pcnt_mass[i]
end

#Mass recycled

rmass1 = 0
rmass2 = 0
rmass3 = 0

for i in 1:12
    rmass1 += city1[i]*pcnt_recyclable[i]
    rmass2 += city2[i]*pcnt_recyclable[i]
    rmass3 += city3[i]*pcnt_recyclable[i]
end

println("Recyclable mass for City 1 = ", round(rmass1; digits=2), " Mg/day")
println("Recyclable mass for City 2 = ", round(rmass2; digits=2), " Mg/day")
println("Recyclable mass for City 3 = ", round(rmass3; digits=2), " Mg/day")

println("-"^40)

#Ash Fraction
#Percent of mass that is recycling residuals
pcnt_resid = zeros(12)
for i in 1:12
    pcnt_resid[i] = 1 - pcnt_recyclable[i]
end

res1 = zeros(12)
res2 = zeros(12)
res3 = zeros(12)

#Residual mass of each waste
for i in 1:12
    res1 = city1[i]*pcnt_resid

```

```

    res2 = city2[i]*pcnt_resid
    res3 = city3[i]*pcnt_resid
end

#Ash mass from recycling residuals for each city for each waste
ramass1 = 0
ramass2 = 0
ramass3 = 0

for i in 1:12
    ramass1 += city1[i]*pcnt_resid[i]*pcnt_ash[i]
    ramass2 += city2[i]*pcnt_resid[i]*pcnt_ash[i]
    ramass3 += city3[i]*pcnt_resid[i]*pcnt_ash[i]
end

println("Ash mass for City 1", round(ramass1; digits=1), " Mg/day")
println("Ash mass for City 2", round(ramass1; digits=1), " Mg/day")
println("Ash mass for City 3", round(ramass1; digits=1), " Mg/day")

```

Recyclable mass for City 1 = 37.75 Mg/day

Recyclable mass for City 2 = 33.98 Mg/day

Recyclable mass for City 3 = 45.3 Mg/day

Ash mass for City 18.6 Mg/day

Ash mass for City 28.6 Mg/day

Ash mass for City 38.6 Mg/day

Problem 1.2

What are the decision variables for your optimization problem? Provide notation and variable meaning.

$I = \{1, 2, 3\}$ (cities)

$J = \{1, 2, 3\}$, where 1 is WTE, 2 is MRF, and 3 is LF

$W_{i,j}$ indicates waste stream from city i in I to waste disposal site j in J .

Decision variables:

$W_{1,1}, W_{1,2}, W_{1,3}, W_{2,1}, W_{2,2}, W_{2,3}, W_{3,1}, W_{3,2}, W_{3,3}$ \$ waste streams from cities to disposal sites in Mg/day

$R_{1,3}$ \$ residual amount sent from WTE to LF in Mg/day

$R_{2,3}$ \$ residual amount sent from MRF to LF in Mg/day

\$ R_{2,1} \$ residual amount sent from MRF to WTE in Mg/day
 \$ Y_1, Y_2, Y_3 \$ operational status of facility j in J (unitless)

Problem 1.3

Formulate the objective function. Make sure to include any needed derivations or justifications for your equation(s).

Objective: Minimize cost

Transport costs

Transportation cost: \$1.5/Mg-km

\$ T = 1.5 \sum_{i \in I} \sum_{j \in J} W_{i,j} l_{i,j} \$ where \$ W_{i,j} = \$ waste transported from i to j and
 \$ l_{i,j} = \$ distance between i and j

Disposal costs

\$ D = \sum_{j \in J} c_j Y_j + b_j \sum_{i \in I} W_{i,j} \$ where \$ c_j = \$ fixed operating costs, \$ b_j = \$ variable disposal cost, and \$ Y_j = \$ indicator variable for facility operation

Objective min \$ Z = \sum_{i \in I} \sum_{j \in J} 1.5 l_{i,j} W_{i,j} + \sum_{j \in J} (c_j Y_j + b_j \sum_{i \in I} W_{i,j}) \$

Problem 1.4

Derive all relevant constraints. Make sure to include any needed justifications or derivations.

LF, MRF, WTE

\$ I = \{1, 2, 3\} \$ (cities)

\$ J = \{1, 2, 3\} \$, where 1 is WTE, 2 is MRF, and 3 is LF

Non-exceedence of plant capacity:

WTE: \$ W_{1,1} + W_{2,1} + W_{3,1} + R_{2,1} \leq 210 \$

MRF: \$ W_{1,2} + W_{2,2} + W_{3,2} \leq 350 \$

LF: \$ W_{1,3} + W_{2,3} + W_{3,3} + R_{1,3} + R_{2,3} \leq 200 \$

Treatment of all waste:

\$ W_{1,1} + W_{1,2} + W_{1,3} = 100 \$

\$ W_{2,1} + W_{2,2} + W_{2,3} = 90 \$

\$ W_{3,1} + W_{3,2} + W_{3,3} = 120 \$

$Y_1 = 0$ if $W_{1,1} + W_{2,1} + W_{3,1} + R_{2,1} = 0$, else $Y_1 = 1$
 $Y_2 = 0$ if $W_{1,2} + W_{2,2} + W_{3,2} = 0$, else $Y_2 = 1$
 $Y_3 = 1$

Non-negativity:

$W_{i,j}, R_{j,j^*} \geq 0$ where j^* indicates a different j in J .

Problem 1.5

Find the optimal solution (using JuMP to solve the problem). Report the optimal objective value.

```

cities = [1, 2, 3]
facilities = [:LF, :MRF, :WTE]

struct waste
    name::Symbol
    percent::Float64
    ash::Float64
    recycle::Float64
end

#Waste type, percentage of total waste, ash fraction, recycling fraction:
components = [waste(:Food, 0.15, 0.08, 0.00),
    waste(:Paper, 0.40, 0.07, 0.55),
    waste(:Plastics, 0.05, 0.05, 0.15),
    waste(:Textiles, 0.03, 0.10, 0.10),
    waste(:Rubber, 0.02, 0.15, 0.00),
    waste(:Wood, 0.05, 0.02, 0.30),
    waste(:Yard, 0.18, 0.02, 0.40),
    waste(:Glass, 0.04, 1.00, 0.60),
    waste(:Ferrous, 0.02, 1.00, 0.75),
    waste(:Aluminum, 0.02, 1.00, 0.80),
    waste(:OtherMetal, 0.01, 1.00, 0.50),
    waste(:Misc, 0.03, 0.70, 0.00)]

prod = Dict{1 => 100, 2 => 90, 3 => 120} #waste produced
cap = Dict{(:LF => 200, :MRF => 350, :WTE => 210)} #treatment capacity
fc = Dict{(:LF => 2000, :MRF => 1500, :WTE => 2500)} #fixed costs
vc = Dict{(:LF => 50, :MRF => 7, :WTE => 60)} #variable costs
r_cost = 40 #$/Mg, recycling cost
t_cost = 1.5 #$/Mg-km, transport cost
recycle_factor = sum(c.percent * c.recycle for c in components)

```

```

ash_factor = 0.0
for c in components
    ash_factor += c.percent * c.ash
end

dist = Dict(
    (1, :LF) => 5,
    (1, :MRF) => 30,
    (1, :WTE) => 15,
    (2, :LF) => 15,
    (2, :MRF) => 25,
    (2, :WTE) => 10,
    (3, :LF) => 13,
    (3, :MRF) => 45,
    (3, :WTE) => 20,
    (:MRF, :LF) => 32,
    (:MRF, :WTE) => 15,
    (:WTE, :LF) => 18,
)

#Initiating model

model = Model(HiGHS.Optimizer)
set_silent(model)

#Indicator
@variable(model, Y[1:3], Bin)
@constraint(model, force_LF, Y[3] == 1)

# 1 is WTE, 2 is MRF, and 3 is LF

# Waste Streams:
# City i to facility f
@variable(model, 0 <= stream[i in cities, f in facilities])

# MRF residuals to LF/WTE
@variable(model, 0 <= R23) #to LF
@variable(model, 0 <= R21) #to WTE

# WTE ash to LF
@variable(model, 0 <= R13)

```



```

# Recycled material from MRF
@variable(model, 0 <= r_tot)

# Mass balance helper variables
@variable(model, 0 <= mrf_in) # Total waste entering MRF
@variable(model, 0 <= mrf_res) # Non-recycled portion from MRF
@variable(model, 0 <= wte_in) # Total waste entering WTE

###Constraints

for i in cities
    @constraint(model, sum(stream[i, f] for f in facilities) == prod[i])
end

#### Facilities Cap
# WTE capacity (Y[1] = WTE)
@constraint(model, sum(stream[i, :WTE] for i in cities) + R21 <= cap[:WTE] * Y[1])

# MRF capacity (Y[2] = MRF)
@constraint(model, sum(stream[i, :MRF] for i in cities) <= cap[:MRF] * Y[2])

# LF Capacity (Y[3] = LF)
@constraint(model, sum(stream[i, :LF] for i in cities) + R23 + R13 <= cap[:LF] * Y[3])

##### MRF Mass Balance
#Total waste entering MRF
@constraint(model, mrf_in == sum(stream[i, :MRF] for i in cities))

# Recycling amount (using AVERAGE recycling rate from table)
@constraint(model, r_tot == mrf_in * recycle_factor)

# MRF residuals (non-recycled portion)
@constraint(model, mrf_res == mrf_in - r_tot)

# MRF residuals must go to LF or WTE
@constraint(model, mrf_res == R23 + R21)

#### WTE Mass Balance
# Total waste entering WTE
@constraint(model, wte_in == sum(stream[i, :WTE] for i in cities) + R21)

```

```

# Ash from WTE goes to landfill
@constraint(model, R13 == wte_in * ash_factor)

### Developing Objective Function

# Transportation costs
# City to facility transport
t_city = t_cost * sum(stream[i, f] * dist[(i, f)] for i in cities, f in facilities)
t_mrf = t_cost * (R23 * dist[:,MRF, :LF]) + R21 * dist[:,MRF, :WTE])
t_wte = t_cost * R13 * dist[:,WTE, :LF])

tc_tot = t_city + t_mrf + t_wte

# Tipping fees
tipc_tot = (
    sum(stream[i, :LF] for i in cities) * vc[:,LF] +
    sum(stream[i, :MRF] for i in cities) * vc[:,MRF] +
    sum(stream[i, :WTE] for i in cities) * vc[:,WTE] +
    R23 * vc[:,LF] + R21 * vc[:,WTE] + R13 * vc[:,LF])

# Recycling cost at MRF
rc_tot = r_tot * r_cost

# Fixed costs
fc_tot = fc[:,LF] * Y[3] + fc[:,MRF] * Y[2] + fc[:,WTE] * Y[1]

# Total cost minimization
@objective(model, Min, fc_tot + tipc_tot + rc_tot + tc_tot)

```

$$2000Y_3 + 1500Y_2 + 2500Y_1 + 57.5stream_{1,LF} + 72.5stream_{2,LF} + 69.5stream_{3,LF} + 52stream_{1,MRF} + 44.5stream_{2,MRF} + 74.5stream_{3,MRF} + 82.5stream_{1,WTE} + 75stream_{2,WTE} + 90stream_{3,WTE} + 98R23 + 82.5R21 + 77R13 + 40r_{tot}$$

```

optimize!(model)

total_cost = objective_value(model)
println("Optimal Objective Value: \$", Int(round(total_cost)))

```

Optimal Objective Value: \$27855

```

# Check facility decisions
println("\nFacility Use (Y variables):")
println("WTE: ", value(Y[1]))
println("MRF: ", value(Y[2]))
println("LF: ", value(Y[3]))

# Check waste flows
println("\nWaste flows (Mg/day):")
total_waste_flow = 0
for i in cities
    println("City $i:")
    for f in facilities
        flow = value(stream[i, f])
        println("    to $f: $(round(flow, digits=2)) Mg")
        total_waste_flow += flow
    end
end
end

```

Facility Use (Y variables):

WTE: 1.0

MRF: -0.0

LF: 1.0

Waste flows (Mg/day):

City 1:

to LF: 100.0 Mg

to MRF: 0.0 Mg

to WTE: 0.0 Mg

City 2:

to LF: -0.0 Mg

to MRF: -0.0 Mg

to WTE: 90.0 Mg

City 3:

to LF: 78.41 Mg

to MRF: 0.0 Mg

to WTE: 41.59 Mg

Problem 1.6

Draw a diagram showing the flows of waste between the cities and the facilities. Which facilities (if any) will not be used? Does this solution make sense?




Figure 1: Waste stream distribution.png

Problem 2 (6 points)

Consider a two-period economic dispatch problem, based on the multi-period example from Lecture 14 (on 10/29). The generator data, including ramping constraints for each generator, is provided in 'data/generators.csv.' In period 1, the demand is $d_1 = 1100$ MW. In period 2, the demand is projected to be $d_2 = 1200$ MW, but there is a 25% probability that it is 1500 MW. In the first period, the solar capacity factor is 0.9 and the wind capacity factor is 0.45, but in the second period, there is some uncertainty: the forecasted solar and wind capacity factors are 0.95 and 0.4, respectively, but there is a 30% probability that they are 0.75 and 0.5. Your goal is to identify how to dispatch your generators to minimize the cost of meeting demand.

Problem 2.1

Draw a scenario tree for this problem.




Figure 2: Scenario tree.png

Problem 2.2

Formulate a stochastic linear program for this problem based on your scenario tree from Problem 2.1 and the data in `data/generators.csv`.

```
gens = DataFrame(CSV.File("data/generators.csv"))
```

	Plant	Resource	Pmin	Pmax	VarCost	Ramp
	String15	String15	Int64	Int64	Int64	Int64
1	Biomass	Biomass	0	100	5	100
2	Hydroelectric	Hydroelectric	0	500	0	500
3	Geothermal	Geothermal	0	400	0	400
4	NG CCGT	NG CCGT	220	500	23	100
5	NG CT	NG CT	100	250	38	200
6	Wind	Wind	0	300	0	300
7	Solar	Solar	0	500	0	500

G = geothermal

H = hydroelectric

C = coal

CCGT = natural gas combined cyclone gas turbine

CT = natural gas combustion turbine

W = wind

S = solar

Four scenarios:

1: $d_{1,2} = 1200$ \$ MW, $c_s = 0.95$, $c_w = 0.4$ \$

2: $d_{2,2} = 1200$ \$ MW, $c_s = 0.75$, $c_w = 0.5$ \$

3: $d_{3,2} = 1500$ \$ MW, $c_s = 0.95$, $c_w = 0.4$ \$

4: $d_{4,2} = 1500$ \$ MW, $c_s = 0.75$, $c_w = 0.5$ \$

For the values d, the subscript indicates the time period and the superscript indicates the scenario.

Variable cost: VC_g = \$ variable cost of production for generator g in G

Ramping constraints: R_g = \$ ramping limit between time periods for generator g in G

Capacity factor: $c_{s,t}$ = \$ capacity factor for scenario s and time period

Calculating probabilities of each scenario:

1: $p_1 = 0.75$ $0.7 = 0.525$ \$

2: $p_2 = 0.75$ $0.3 = 0.225$ \$

3: $p_3 = 0.25$ $0.7 = 0.175$ \$

4: $p_4 = 0.25$ $0.3 = 0.075$ \$

$G = \{G, H, C, CCGT, CT, W, S\}$, generators

$T = \{1, 2\}$, time periods

$S = \{1, 2, 3, 4\}$, scenarios

Decision variables:

$y_{s,g,t}$ = \$ power output from generator g in G at time t in T for scenario s in S

Objective: minimize Z:

$Z = \sum_{g \in G} VC_g \sum_{t \in T} y_{g,t} + \sum_{s \in S} p_s \sum_{g \in G} VC_g \sum_{t \in T} y_{s,g,t}$ \$

Constraints:

Period 1:

$\sum_{g \in G} y_{g,1} \leq 1100$ \$

Period 2:

$\sum_{g \in G} y_{s,g,2} \leq d_s$ \$, where $d_1 = d_2 = 1200$ \$ and $d_3 = d_4 = 1500$ \$

General:

$P_{\min, g} \leq y_{s,g,t} \leq c_{s,t} P_{\max, g}$ \$

$-R_g \leq y_{s,g,2} - y_{s,g,1} \leq R_g$ \$

$y_{s,g,t} \geq 0$ \$

Calculating maximum solar and wind outputs for period 1:

Solar: \$ 500 $\cdot 0.9 = 450$ \$ MW

Wind: \$ 300 $\cdot 0.45 = 135$ \$ MW

Calculating maximum solar and wind outputs based on each scenario for period 2:

1 and 3: \$ 500 $\cdot 0.95 = 475$ \$ MW solar, \$ 300 $\cdot 0.4 = 120$ \$ MW wind

2 and 4: \$ 500 $\cdot 0.75 = 375$ \$ MW solar, \$ 300 $\cdot 0.5 = 150$ \$ MW wind

References

List any external references consulted, including classmates.