

Audit Report Bernard betting

January 2022

Type BEP20

Network BSC

Address 0x98Ab3bCB0E81daef369514113429Dc782C756F65

Audited by © coinscope



Table of Contents

| Table of Contents | 1 |
|--|----|
| Contract Review | 3 |
| Audit Updates | 3 |
| Contract Analysis | 4 |
| Contract Owner Drain Lottery Amount | 4 |
| Description | 4 |
| Recommendation | 4 |
| Exceed Limit Fees Manipulation | 5 |
| Description | 5 |
| Recommendation | 5 |
| Contract Diagnostics | 6 |
| CO - Code Optimization | 7 |
| Description | 7 |
| Recommendation | 7 |
| CR - Code Repetition | 8 |
| Description | 8 |
| Recommendation | 8 |
| L01 - Public Function could be Declared External | 9 |
| Description | 9 |
| Recommendation | 9 |
| L04 - Conformance to Solidity Naming Conventions | 10 |
| Description | 10 |
| Recommendation | 10 |
| L11 - Unnecessary Boolean equality | 11 |
| Description | 11 |
| Recommendation | 11 |



| L06 - Missing Events Access Control | 12 |
|-------------------------------------|----|
| Description | 12 |
| Recommendation | 12 |
| Contract Functions | 13 |
| Contract Flow | 16 |
| Summary | 17 |
| Disclaimer | 18 |
| About Coinscope | 19 |



Contract Review

| Contract Name | SBetting |
|------------------|---|
| Compiler Version | v0.6.12+commit.27d51765 |
| Optimization | 1 runs |
| Licence | |
| Explorer | https://bscscan.com/address/0x98Ab3bCB0E81daef3 69514113429Dc782C756F65 |
| Source | /Users/patrick/Documents/TRON/Bernie/bones/contracts/Betting.sol, @openzeppelin/contracts/utils/ReentrancyGuard.sol, @openzeppelin/contracts/utils/Pausable.sol, @openzeppelin/contracts/utils/Context.sol, @openzeppelin/contracts/utils/Address.sol, @openzeppelin/contracts/token/ERC20/SafeERC20.sol, @openzeppelin/contracts/token/ERC20/IERC20.sol, @openzeppelin/contracts/math/SafeMath.sol, @openzeppelin/contracts/access/Ownable.sol |

Audit Updates

| Initial Audit | 29th January 2022 |
|---------------|-------------------|
| Corrected | |



Contract Analysis

Contract Owner Drain Lottery Amount

| Criticality | medium |
|-------------|-------------------|
| Location | contract.sol#L332 |

Description

The users that place bets are transferring tokens to the contract. These tokens can be drained by the contract owner anytime by calling the *inCaseTokensGetStuck()* function with the bones address as argument. As a result the winners may not be able to claim their rewards.

```
function inCaseTokensGetStuck(address _token,uint256 _amount) public onlyAdmin{
    require(IERC20(_token).balanceOf(address(this)) > 0, 'Error, contract has
insufficent balance');
    IERC20(_token).safeTransfer(address(adminAddress), _amount);
}
```

Recommendation

There could be some limitation regarding the contract owner's access. For instance, the contract owner should be allowed to drain tokens only on legacy bets.

The owner should carefully manage the credentials of the owner's account. We advised considering an extra-strong security mechanism that the actions may be quarantined by many users instead of one.



Exceed Limit Fees Manipulation

```
Criticality minor

Location contract.sol#L133
```

Description

The contract owner has the authority to increase the fees. The owner may take advantage of it by calling the function *setRewardRate* with a high percentage value. The rewardRate amount accumulates fees that are transferred to the owner's wallet.

```
function setRewardRate(uint256 _rewardRate) external onlyAdmin {
    require(_rewardRate <= TOTAL_RATE, "rewardRate cannot be more than 100%");
    rewardRate = _rewardRate;
    treasuryRate = TOTAL_RATE.sub(_rewardRate);

emit RatesUpdated(rewardRate, treasuryRate);
}</pre>
```

```
function claimTreasury() external onlyAdmin {
    uint256 currentTreasuryAmount = treasuryAmount;
    treasuryAmount = 0;
    bones.safeTransfer(address(adminAddress), currentTreasuryAmount);
    emit ClaimTreasury(currentTreasuryAmount);
}
```

Recommendation

The contract could embody a check for the maximum acceptable value.

The owner should carefully manage the credentials of the owner's account. We advised considering an extra-strong security mechanism that the actions may be quarantined by many users instead of one.



Contract Diagnostics

CriticalMediumMinor

| Severity | Code | Description |
|----------|------|--|
| • | CO | Code Optimization |
| • | CR | Code Repetition |
| • | L01 | Public Function could be Declared External |
| • | L04 | Conformance to Solidity Naming Conventions |
| • | L11 | Unnecessary Boolean equality |
| • | L06 | Missing Events Access Control |



CO - Code Optimization

| Criticality | minor |
|-------------|-------------------|
| Location | contract.sol#L282 |

Description

There are code segments that could be optimized. A segment may be optimized so that it becomes a smaller size, consumes less memory, executes more rapidly, or performs fewer operations.

The side number can only be a number between 0 to 3. Hence, the else if statement is not required since the only possible value is 3.

```
else if (side == 3){
    round.refundable = true;
    rewardBaseCalAmount = 0;
    treasuryAmt = 0;
    rewardAmount = 0;
}
```

Recommendation

Rewrite some code segments so the runtime will be more performant.



CR - Code Repetition

| Criticality | minor |
|-------------|-------------------|
| Location | contract.sol#L269 |

Description

There are code segments that are repetitive in the contract. Those segments increase the code size of the contract unnecessarily.

```
if (side == 0) {
    rewardBaseCalAmount = round.homeAmount;
    rewardAmount = round.totalAmount.mul(rewardRate).div(TOTAL_RATE);
    treasuryAmt = round.totalAmount.mul(treasuryRate).div(TOTAL_RATE);
}
else if (side == 1 ) {
    rewardBaseCalAmount = round.drawAmount;
    rewardAmount = round.totalAmount.mul(rewardRate).div(TOTAL_RATE);
    treasuryAmt = round.totalAmount.mul(treasuryRate).div(TOTAL_RATE);
}
else if (side == 2 ) {
    rewardBaseCalAmount = round.awayAmount;
    rewardAmount = round.totalAmount.mul(rewardRate).div(TOTAL_RATE);
    treasuryAmt = round.totalAmount.mul(treasuryRate).div(TOTAL_RATE);
}
```

Recommendation

Create an internal function that contains the code segment and remove it from all the sections.



L01 - Public Function could be Declared External

| Criticality | minor |
|-------------|--|
| Location | contracts/Betting.sol#L332,L163,L85 and 1 more |

Description

Public functions that are never called by the contract should be declared external to save gas.

```
inCaseTokensGetStuck
bet
unpause
...
```

Recommendation

Use the external attribute for functions never called from the contract



L04 - Conformance to Solidity Naming Conventions

| Criticality | minor |
|-------------|---|
| Location | contracts/Betting.sol#L332,L149,L141 and 4 more |

Description

Solidity defines a naming convention that should be followed. Rule exceptions:

- Allow constant variable name/symbol/decimals to be lowercase.
- Allow _ at the beginning of the mixed_case match for private variables and unused parameters.

```
_amount
_token
_minBetAmount
...
```

Recommendation

Follow the Solidity naming convention. https://docs.soliditylang.org/en/v0.4.25/style-guide.html#naming-conventions



L11 - Unnecessary Boolean equality

| Criticality | minor |
|-------------|---|
| Location | contracts/Betting.sol#L298,L246,L232 and 1 more |

Description

The comparison to boolean constants is redundant. Boolean constants can be used directly and do not need to be compared to true or false.

```
require(bool,string)(rounds[epoch].oracleCalled == true,game not ended)
require(bool,string)(rounds[epoch].oracleCalled == false,game ended)
rounds[epoch].startBlock != 0 && block.number > rounds[epoch].startBlock &&
rounds[epoch].oracleCalled == false && block.timestamp < rounds[epoch].endEpoch
...</pre>
```

Recommendation

Remove the equality to the boolean constant.



L06 - Missing Events Access Control

| Criticality | minor |
|-------------|---------------------------------|
| Location | contracts/Betting.sol#L128,L119 |

Description

Detected missing events for critical access control parameters. There are functions that have no event emitted, so it is difficult to track off-chain changes.

```
operatorAddress = _operatorAddress
adminAddress = _adminAddress
```

Recommendation

Emit an event for critical parameter changes.



Contract Functions

| Contract | Туре | Bases | | |
|----------|-------------------------------------|------------|------------|-----------|
| | Function Name | Visibility | Mutability | Modifiers |
| Ownable | Implementation | Context | | |
| Ownable | <constructor></constructor> | Internal | ✓ | |
| | owner | Public | V | _ |
| | | Public | ✓ | |
| | renounceOwnership transferOwnership | Public | <i>y</i> | onlyOwner |
| | transferownership | T ubile | <u> </u> | OnlyOwner |
| SafeMath | Library | | | |
| | tryAdd | Internal | | |
| | trySub | Internal | | |
| | tryMul | Internal | | |
| | tryDiv | Internal | | |
| | tryMod | Internal | | |
| | add | Internal | | |
| | sub | Internal | | |
| | mul | Internal | | |
| | div | Internal | | |
| | mod | Internal | | |
| | sub | Internal | | |
| | div | Internal | | |
| | mod | Internal | | |
| | | | | |
| IERC20 | Interface | | | |
| | totalSupply | External | | - |
| | balanceOf | External | | - |
| | transfer | External | ✓ | - |
| | allowance | External | | - |
| | approve | External | ✓ | - |
| | transferFrom | External | ✓ | - |




| SafeERC20 | Library | | | |
|---------------------|-----------------------------|----------|----------|-------------------|
| | safeTransfer | Internal | 1 | |
| | safeTransferFrom | Internal | 1 | |
| | safeApprove | Internal | 1 | |
| | safeIncreaseAllowance | Internal | 1 | |
| | safeDecreaseAllowance | Internal | 1 | |
| | _callOptionalReturn | Private | 1 | |
| Address | Library | | | |
| | isContract | Internal | | |
| | sendValue | Internal | 1 | |
| | functionCall | Internal | 1 | |
| | functionCall | Internal | 1 | |
| | functionCallWithValue | Internal | 1 | |
| | functionCallWithValue | Internal | 1 | |
| | functionStaticCall | Internal | | |
| | functionStaticCall | Internal | | |
| | functionDelegateCall | Internal | ✓ | |
| | functionDelegateCall | Internal | 1 | |
| | _verifyCallResult | Private | | |
| Context | Implementation | | | |
| | _msgSender | Internal | | |
| | _msgData | Internal | | |
| Pausable | Implementation | Context | | |
| Tuususie | <constructor></constructor> | Internal | 1 | |
| | paused | Public | | - |
| | _pause | Internal | ✓ | whenNotPause d |
| | _unpause | Internal | 1 | whenPaused |
| ReentrancyGu ard | Implementation | | | |
| | <constructor></constructor> | Internal | 1 | |
| | | | | |



| SBetting | Implementation | Ownable, Reentrancy Guard, Pausable | | |
|----------|-----------------------------|--|----------|--|
| | <constructor></constructor> | Public | ✓ | - |
| | pause | Public | ✓ | onlyAdminOrO perator whenNotPause d |
| | unpause | Public | √ | onlyAdmin whenPaused |
| | _isContract | Internal | | |
| | setAdmin | External | ✓ | onlyOwner |
| | setOperator | External | ✓ | onlyOwner |
| | setRewardRate | External | ✓ | onlyAdmin |
| | setTreasuryRate | External | ✓ | onlyAdmin |
| | setMinBetAmount | External | ✓ | onlyAdmin |
| | _bettable | Internal | | |
| | bet | Public | Payable | nonReentrant notContract whenNotPause d |
| | getUserRounds | External | | - |
| | claimable | Public | | - |
| | refundable | Public | | - |
| | endRound | External | 1 | onlyAdminOrO perator whenNotPause d |
| | startRound | External | 1 | onlyAdminOrO perator whenNotPause d |
| | _calculateRewards | Internal | ✓ | |
| | claim | External | √ | nonReentrant notContract |
| | claimTreasury | External | ✓ | onlyAdmin |
| | inCaseTokensGetStuck | Public | ✓ | onlyAdmin |



Contract Flow





Summary

Bernard betting is a betting application that is built in the BSC chain. The basic logic is that users are able to bet on three possible values on every round. The admin defines the winning value for the current round. The winners can claim their rewards that is the proportional amount from all the round's bets. There are some functions that can be abused by the contract owner. We state that the owner privileges are necessary and required for proper operation of the betting application. Thus, we emphasise the contract owner to be extra careful with the credentials.



Disclaimer

All the content provided in this document is for general information only and should not be used as financial advice or a reason to buy any investment.

Coinscope team provides no guarantees against the sale of team tokens or the removal of liquidity by the project audited in this document. Always Do your own research and protect yourselves from being scammed.

The Coinscope team has audited this project for general information and only expresses their opinion based on similar projects and checks from popular diagnostic tools. Under no circumstances did Coinscope receive a payment to manipulate those results or change the awarding badge that we will be adding in our website.

Always Do your own research and protect yourselves from scams. This document should not be presented as a reason to buy or not buy any particular token.

The Coinscope team disclaims any liability for the resulting losses.



About Coinscope

Coinscope is the leading early coin listing, voting and auditing authority firm. The audit process is analyzing and monitoring many aspects of the project. That way, it gives the community a good sense of security using an informative report and a generic score.

Coinscope is aiming to make crypto discoverable and efficient globally. It provides all the essential tools to assist users draw their own conclusions.



The Coinscope.co team

https://www.coinscope.co