SERVICENOW MATERIAL · BEGIN TO END

# Alhamis_65 receives 30, gives 10 to Alhamis_66, uses 20, then 66 returns 10 to original

Use the exact SWO names in your site (Alhamis_65 / Alhamis__65, Alhamis_66). Needs **synarete_wms v0.1.60** or later. HTT is not used. Do not type qty fields on the work order.

> **How 66 “receives” the 10**
> Alhamis_66 does not Receive Material from the warehouse. It gets 10 as **Qty Interchanged In** (Issued 10, Remaining 10, Received 0). That is the receive. Then those 10 must stay on 66 until you send them back to 65.

## Quantity story

| After this step | 65 warehouse | 65 remaining | 65 consumed | 66 interchanged in | 66 remaining |
|---|---|---|---|---|---|
| 1. Create both SWOs | 0 | 0 | 0 | 0 | 0 |
| 2. 65 receives 30 | 30 | 0 | 0 | 0 | 0 |
| 3. 65 gives 10 to 66 | 20 | 0 | 0 | 10 | 10 |
| 4. 65 issues + consumes the 20 | 0 | 0 | 20 | 10 | 10 |
| 5. 66 returns 10 to 65 | 0 | 10 | 20 | 10 | 0 |
| 6. 65 consumes the returned 10 | 0 | 0 | 30 | 10 | 0 |

**End:** 65 requested/used 30. 66 received 10 by interchange and returned them. 66 did not consume.

## Step 1 — Create the two work orders

- New ServiceNow Site Work Order **Alhamis_65**, Order Type Material, qty **30**, item Servicenow 011. Save.
- New ServiceNow Site Work Order **Alhamis_66**, Material, qty **10**, same item. Save.
- If qty fields look wrong: Material → Recalculate Quantities (only a refresh, not a stock move).

## Step 2 — Receive 30 on Alhamis_65 only

- Open **Alhamis_65** → Material → Receive Material → item qty **30** → Save → Submit.
- 65: Qty Received = 30, Warehouse Remaining = 30.
- 66: Qty Received = 0. Do not receive 10 on 66 from the warehouse.

**Expected:** Main Warehouse Stock Balance does not change.

## Step 3 — 65 gives 10 to 66 (this is 66 receiving)

- Open **Alhamis_65** → Material → Issue Material.
- Original = Alhamis_65. Received For = Alhamis_65. **Issued To = Alhamis_66**.
- Item qty = **10**. Reason required, e.g. *Lend 10 to Alhamis_66.* MP Stock = No.
- Save (type becomes Interchange) → Submit.
- Open **Alhamis_66**: Interchanged In = 10, Issued = 10, Remaining = 10, Received = 0.
- 65: Warehouse Remaining = 20, Interchanged Out = 10, Issued still 0.

**Do not consume on 66.** Those 10 must come back to 65.

## Step 4 — Use the leftover 20 on 65 first (before 66 returns)

- Open **Alhamis_65**. Warehouse Remaining must be 20. Remaining on site = 0 — you cannot Consume yet.
- Material → Issue Material. Issued To = **Alhamis_65** (same order). Qty = **20**. No interchange reason.
- Submit. 65: Issued = 20, Warehouse Remaining = 0, Remaining on site = 20.
- If Consume still offers 10 instead of 20: Material → Recalculate Quantities, then Consume.
- Material → Consume Material, qty **20**. Submit. 65 Consumed = 20, Remaining = 0.

**Why two steps:** Receive puts stock in warehouse remaining. Consume only uses issued remaining. Issue 20 to 65, then Consume 20.

## Step 5 — 66 brings 10 back to original (Alhamis_65)

- Confirm 66 still has Remaining = 10 (not consumed).
- Open **Alhamis_66** → Material → Issue Material.
- Original = **Alhamis_66**. Received For = Alhamis_66. **Issued To = Alhamis_65**.
- Qty = **10**. Reason, e.g. *Return 10 to Alhamis_65 original request.* MP Stock = No.
- Save (Interchange) → Submit.
- 66: Remaining = 0, Interchanged Out = 10, Interchanged In still 10 (history).
- 65: Interchanged In = 10, Remaining on site = 10. Do not Receive 10 again.

**If return fails**
66 already consumed the 10 — cannot return. Issued To must be Alhamis_65. Original must be Alhamis_66. Install v0.1.60+.

## Step 6 — 65 uses the returned 10 (original 30 matches)

- Open **Alhamis_65**. Remaining should be 10. Consumed already 20.
- Material → Consume Material, qty **10**. Submit.
- 65 Consumed = 30. Remaining = 0. Requested 30 matches used 30.
- Optional: Recalculate Quantities to confirm figures.
- Optional Reconcile (sign-off only). Then Complete Work Order on 65 and on 66.

## What the fields mean at the end

| Field | Alhamis_65 | Alhamis_66 | Meaning |
|---|---|---|---|
| Qty Received | 30 | 0 | Only 65 received from warehouse |
| Qty Interchanged Out | 10 | 10 | 65 lent 10. 66 returned 10 |
| Qty Interchanged In | 10 | 10 | 65 got 10 back. 66 got 10 from 65 |
| Qty Issued | 30 | 10 | 65: 20 self-issue + 10 returned. 66: the 10 it held |
| Qty Consumed | 30 | 0 | All 30 used on original 65. 66 did not consume |
| Qty Remaining | 0 | 0 | Nothing left on site |
| Warehouse remaining | 0 | 0 | Nothing left in SWO warehouse bucket |

## Short click path

1. Create **Alhamis_65** (30) and **Alhamis_66** (10).
2. 65 → Receive 30.
3. 65 → Issue to **66**, qty 10, reason → Submit. **66 receives 10 as Interchanged In.**
4. 65 → Issue to itself 20 → Consume 20. **Use 20 before anything comes back.**
5. 66 → Issue to **65**, qty 10, reason → Submit. **Bring 10 back to original.**
6. 65 → Consume 10. Consumed 30 = original 30.

## Do not

| Wrong | Do this instead |
|---|---|
| Receive 10 on Alhamis_66 from warehouse | Only Receive on 65. 66 gets Interchanged In |
| Consume the 10 on 66 | Leave them on 66 until you return to 65 |
| Consume the 20 on 65 before issuing them to 65 | Issue 20 to Alhamis_65, then Consume 20 |
| Type remaining qty on the work order | Quantities are calculated. Recalculate if they look wrong |
| Use Issue MP Stock for this story | This 30 is received SWO stock, not MP warehouse stock |

Recalculate Quantities only refreshes the numbers. It is not a receive/issue/consume step.