Lab No: 05

Lab Title: **while Loop**

- **Learning objectives:**

The following types will be covered in this lab session

- While Loop
- Nested While Loop
- Do-While Loop

Loop

Loops are used to repeat a block of code. Being able to have your program repeatedly execute a block of code is one of the most basic but useful tasks in programming -- many programs or websites that produce extremely complex output are really only executing a single task many times. Now, think about what this means: a loop lets you write a very simple statement to produce a significantly greater result simply by repetition.

While Loop

The most basic loop in C++ is the while loop. A while statement is like a repeating if statement. Like an If statement, if the test condition is true: the statements get executed. The difference is that after the statements have been executed, the test condition is checked again. If it is still true the statements get executed again. This cycle repeats until the test condition evaluates too false.

A **while loop** is a control flow statement that allows code to be executed repeatedly based on a given condition. The *while* consists of a block of code and a condition. The condition is first evaluated and if the condition is true the code within the block is then executed. This repeats until the condition becomes false

- Syntax

Basic syntax of while loop is as follows:

```
while (expression)
{
Single statement
        Or
Block of statements;
}
```

- The expression can be any combination of Boolean statements that are legal. Even, (while x ==5 || v == 7) which says execute the code while x equals five or while v equals 7.

- **Example:**

Write a program using while loop who print the values from 10 to 1.

```
/

//This program prints 10 to 1 using while loop

#include <iostream.h>
#include <conio.h>
void main ()
{
        clrscr();
        int i=10; //loop control variable
      while (i>0)
        {
                cout<<i<<"\n";
                i=i-1;
        }
      cout<<"outside loop now";
        getch();

}
```

- **Example:**

- Printing the numbers you entered using a while loop. Exit the loop if the number entered is -1

```
//Prints the number entered by the user and
exits if the number entered is -1

#include <iostream.h>
#include <conio.h>

void main()
{
        clrscr();
        int num=5;
        while (num!=-1)
{
cout<<"Enter a number to print: -1 to quit\n";
cin>>num;
cout<<"You entered: "<<num<<"\n";
}

cout<<"outside loop now";
getch();

}
```

➢ Nested While Loop:

- A While loop inside another while loop is called nested while loop

➢ **Example:** Write a program that prints the following pattern.

1 2 3 4 5 6 7

1 2 3 4 5 6

1 2 3 4 5

1 2 3 4

1 2 3

1 2

1

```
#include <iostream.h>
#include <conio.h>

void main ()
{
        clrscr ();
        int num=7;
        int j;

while (num>0)
{
        j=1;
        while (j<=num) //nested loop
        {
                cout<<j<<"\t";
                j++; //its equivalent to j=j+1;
        }
        cout<<""\n;
        num--;
}

cout<<"outside loop now";
getch();

}
```

- **Its format is:**
  do statement while (condition);

Its functionality is exactly the same as the while loop, except that condition in the do-while loop is evaluated after the execution of statement instead of before, granting at least one execution of statement even if condition is never fulfilled.

Do...While Loop

The **do...while loop** executes the body first and then checks the condition.

Syntax

```
do
{
  //                                                    statements
}
while(condition);
```

This guarantees that the loop body will execute **at least one time**.

Lab Tasks

- **Task 1: While Loop**

  1. Write a C program that uses a while loop to display numbers from 1 to 10.
  2. Display each number on a separate line.

- **Input:**

```
#include <iostream>
using namespace std;
int main() {
    int i = 1;
do
{
   cout<<i<<endl;
   i++; /* code */
} while (i<=10);
    return 0;
}
```

- **Output:**

```
1
2
3
4
5
6
7
8
10
```

- **Task 2: Do-While Loop**

  Repeat the first task using do... while loop.

- **Input:**

```
#include <iostream>
using namespace std;
int main() {
    int i = 1;
do
{
   cout<<i<<endl;
   i++; /* code */
} while (i<=10);
    return 0;
}
```

output:

- **Task 3: Sum using While Loop**

  1. Write a C program that prompts the user to enter a positive integer.
  2. Use a while loop to calculate the sum of all numbers from 1 to the entered integer.
  3. Display the calculated sum.

- **Input:**

```
#include<iostream>
using namespace std;
int main(){
    int num, sum=0, i=1;
    cout<<"Enter positive integer: "<<endl;
    cin>>num;
    while(i<=num){
    sum+=i;
    i++;}
```

```
    cout<<"The sum is "<<sum<<endl;
    return 0;
}
```

- **Output:**

Conclusion

In this lab, we successfully implemented **while loops** and **do...while loops** in C++. The while loop was used to print numbers from 1 to 10, while the do...while loop demonstrated how a loop executes at least once before checking the condition. Additionally, we used a while loop to calculate the sum of numbers up to a user-entered integer. This lab improved our understanding of loop control structures and their practical applications in programming.