

Package ‘Giotto’

December 15, 2019

Title Spatial single-cell transcriptomics pipeline.

Version 0.1.4

Description Pipeline to process, analyze and visualize (spatial) single-cell expression data.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 7.0.1

Depends data.table (>= 1.12.2),
ggplot2 (>= 3.1.1),
base (>= 3.5.1),
utils (>= 3.5.1),
R (>= 3.5.1)

Imports Rtsne (>= 0.15),
uwot (>= 0.0.0.9010),
multinet (>= 3.0.2),
FactoMineR (>= 1.34),
factoextra (>= 1.0.5),
cowplot (>= 0.9.4),
grDevices,
RColorBrewer (>= 1.1-2),
jackstraw (>= 1.3),
dbscan (>= 1.1-3),
ggalluvial (>= 0.9.1),
scales (>= 1.0.0),
ComplexHeatmap (>= 1.20.0),
qvalue (>= 2.14.1),
lfa (>= 1.12.0),
igraph (>= 1.2.4.1),
plotly,
reticulate,
magrittr,
limma,
ggdendro,
smfishHmrf,
matrixStats (>= 0.55.0),
IRanges,
devtools,
reshape2,

ggraph
Suggests knitr,
 rmarkdown,
 MAST,
 scran ($\geq 1.10.1$),
 png,
 tiff,
 biomaRt
biocViews
VignetteBuilder knitr
Remotes lambdamoses/smfishhmr-r

R topics documented:

addCellMetadata	7
addCellStatistics	7
addGeneMetadata	8
addGeneStatistics	9
addHMRF	10
addNetworkLayout	11
addStatistics	12
adjustGiottoMatrix	12
aes_string2	13
allCellCellcommunicationsScores	14
all_plots_save_function	15
annotateGiotto	16
annotateSpatialNetwork	17
annotate_spatlocs_with_spatgrid_2D	17
annotate_spatlocs_with_spatgrid_3D	18
average_gene_gene_expression_in_groups	18
binGetSpatialGenes	19
calculateHVG	20
calculateMetaTable	22
calculateMetaTableCells	23
calculate_spatial_genes_python	23
cellProximityBarplot	24
cellProximityEnrichment	25
cellProximityHeatmap	26
cellProximityNetwork	27
cellProximitySpatPlot	29
cellProximitySpatPlot2D	30
cellProximitySpatPlot3D	32
cellProximityVisPlot	34
cellProximityVisPlot_2D_ggplot	36
cellProximityVisPlot_2D_plotly	38
cellProximityVisPlot_3D_plotly	40
changeGiottoInstructions	41
clusterCells	42
clusterSpatialCorGenes	45
combineMetadata	45

convertEnsemblToGeneSymbol	46
createGiottoInstructions	46
createGiottoObject	47
createHeatmap_DT	49
createMetagenes	50
createNearestNetwork	51
createSpatialEnrich	53
createSpatialGrid	54
createSpatialGrid_2D	55
createSpatialGrid_3D	56
createSpatialNetwork	57
create_average_detection_DT	58
create_average_DT	58
create_cell_type_random_cell_IDs	59
create_cluster_matrix	60
create_dimObject	60
decide_cluster_order	61
detectSpatialCorGenes	62
detectSpatialPatterns	63
dimCellPlot	64
dimCellPlot2D	67
dimGenePlot	69
dimGenePlot2D	71
dimGenePlot3D	73
dimPlot	75
dimPlot2D	78
dimPlot2D_single	81
dimPlot3D	83
direction_test_CPG	85
doHclust	86
doHMRF	87
doKmeans	88
doLeidenCluster	90
doLeidenSubCluster	91
doLouvainCluster	93
doLouvainCluster_community	94
doLouvainCluster_multinet	95
doLouvainSubCluster	96
doLouvainSubCluster_community	98
doLouvainSubCluster_multinet	100
doRandomWalkCluster	101
doSNNCluster	103
do_spatial_grid_averaging	104
do_spatial_knn_smoothing	105
dt_to_matrix	106
exportGiottoViewer	106
exprOnlyCellCellcommunicationScores	107
extended_gini_fun	108
extractNearestNetwork	109
fDataDT	109
filterCombinations	110
filterCPGscores	111

filterDistributions	112
filterGiotto	113
findGiniMarkers	114
findGiniMarkers_one_vs_all	115
findMarkers	116
findMarkers_one_vs_all	118
findMastMarkers	119
findMastMarkers_one_vs_all	120
findScranMarkers	121
findScranMarkers_one_vs_all	122
find_grid_2D	123
find_grid_3D	123
find_grid_x	123
find_grid_y	124
find_grid_z	124
fish_function	124
fish_function2	124
FSV_show	125
GenePattern_show	126
general_save_function	127
get10Xmatrix	128
getCellProximityGeneScores	128
getClusterSimilarity	130
getDendrogramSplits	131
getDistinctColors	132
getGeneToGeneScores	132
get_cell_to_cell_sorted_name_conversion	133
get_interaction_gene_enrichment	134
get_specific_interaction_gene_enrichment	134
ggplot_save_function	135
giotto-class	136
heatmSpatialCorGenes	137
hyperGeometricEnrich	138
kmeans_binarize	139
loadHMRf	139
makeSignMatrixPAGE	140
makeSignMatrixRank	140
make_simulated_network	141
mergeClusters	141
mygini_fun	143
nnDT_to_kNN	143
node_clusters	143
normalizeGiotto	144
OR_function2	145
PAGEEnrich	146
pDataDT	147
plotCPGscores	147
plotGTGscores	148
plotHeatmap	150
plotly_axis_scale_2D	152
plotly_axis_scale_3D	152
plotly_grid	153

plotly_network	154
plotMetaDataCellsHeatmap	154
plotMetaDataHeatmap	156
plotPCA	158
plotPCA_2D	160
plotPCA_3D	162
plotTSNE	163
plotTSNE_2D	165
plotTSNE_3D	167
plotUMAP	169
plotUMAP_2D	171
plotUMAP_3D	173
plot_network_layer_ggplot	174
plot_point_layer_ggplot	175
plot_spat_point_layer_ggplot	177
print.giotto	179
rankEnrich	179
rankSpatialCorGroups	180
rank_binarize	181
readGiottoInstructions	181
removeCellAnnotation	182
removeGeneAnnotation	182
replaceGiottoInstructions	183
runPCA	183
runTSNE	184
runUMAP	186
selectPatternGenes	187
select_expression_values	188
show,giotto-method	188
showClusterDendrogram	189
showClusterHeatmap	190
showCPGscores	191
showGeneExpressionProximityScore	192
showGiottoInstructions	193
showGTGscores	193
showIntExpressionProximityScore	194
showPattern	195
showPattern2D	196
showPattern3D	197
showPatternGenes	198
showProcessingSteps	199
showSpatialCorGenes	200
showTopGeneToGene	201
signPCA	202
spatCellPlot	203
spatCellPlot2D	206
spatDimCellPlot	208
spatDimCellPlot2D	212
spatDimGenePlot	216
spatDimGenePlot2D	219
spatDimGenePlot3D	221
spatDimPlot	223

spatDimPlot2D	227
spatDimPlot3D	231
spatGenePlot	235
spatGenePlot2D	237
spatGenePlot3D	239
Spatial_AEH	240
Spatial_DE	241
spatPlot	242
spatPlot2D	245
spatPlot2D_single	248
spatPlot3D	251
specificCellCellcommunicationScores	253
split_dendrogram_in_two	254
stitchFieldCoordinates	255
subClusterCells	256
subsetGiotto	258
subsetGiottoLocs	258
viewHMRFresults	259
viewHMRFresults2D	260
viewHMRFresults3D	261
violinPlot	262
visDimGenePlot	263
visDimGenePlot_2D_ggplot	265
visDimGenePlot_3D_plotly	266
visDimPlot	268
visDimPlot_2D_ggplot	270
visDimPlot_2D_plotly	272
visDimPlot_3D_plotly	274
visForceLayoutPlot	275
visGenePlot	277
visGenePlot_2D_ggplot	279
visGenePlot_3D_plotly	280
visPlot	282
visPlot_2D_ggplot	284
visPlot_2D_plotly	287
visPlot_3D_plotly	288
visSpatDimGenePlot	290
visSpatDimGenePlot_2D	293
visSpatDimGenePlot_3D	295
visSpatDimPlot	297
visSpatDimPlot_2D	299
visSpatDimPlot_3D	302
writeHMRFresults	304
write_giotto_viewer_annotation	304
write_giotto_viewer_dim_reduction	305
write_giotto_viewer_numeric_annotation	306

addCellMetadata	<i>addCellMetadata</i>
-----------------	------------------------

Description

adds cell metadata to the giotto object

Usage

```
addCellMetadata(  
  gobject,  
  new_metadata,  
  by_column = FALSE,  
  column_cell_ID = NULL  
)
```

Arguments

gobject	giotto object
new_metadata	new cell metadata to use (data.table, data.frame, ...)
by_column	merge metadata based on cell_ID column in pDataDT (default = FALSE)
column_cell_ID	column name of new metadata to use if by_column = TRUE

Details

You can add additional cell metadata in two manners: 1. Provide a data.table or data.frame with cell annotations in the same order as the cell_ID column in pDataDT(gobject) 2. Provide a data.table or data.frame with cell annotations and specify which column contains the cell IDs, these cell IDs need to match with the cell_ID column in pDataDT(gobject)

Value

giotto object

Examples

```
addCellMetadata(gobject)
```

addCellStatistics	<i>addCellStatistics</i>
-------------------	--------------------------

Description

adds cells statistics to the giotto object

Usage

```
addCellStatistics(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  detection_threshold = 0,
  return_gobject = TRUE
)
```

Arguments

gobject giotto object

expression_values expression values to use

detection_threshold detection threshold to consider a gene detected

return_gobject boolean: return giotto object (default = TRUE)

Details

This function will add the following statistics to cell metadata:

- nr_genes: Denotes in how many genes are detected per cell
- perc_genes: Denotes what percentage of genes is detected per cell
- total_expr: Shows the total sum of gene expression per cell

Value

giotto object if return_gobject = TRUE

Examples

```
addCellStatistics(gobject)
```

addGeneMetadata	<i>addGeneMetadata</i>
-----------------	------------------------

Description

adds gene metadata to the giotto object

Usage

```
addGeneMetadata(gobject, new_metadata, by_column = F, column_gene_ID = NULL)
```

Arguments

gobject giotto object

new_metadata new metadata to use

by_column merge metadata based on gene_ID column in fDataDT

column_cell_ID column name of new metadata to use if by_ID = TRUE

Details

You can add additional gene metadata in two manners: 1. Provide a data.table or data.frame with gene annotations in the same order as the gene_ID column in fDataDT(gobject) 2. Provide a data.table or data.frame with gene annotations and specify which column contains the gene IDs, these gene IDs need to match with the gene_ID column in fDataDT(gobject)

Value

giotto object

Examples

```
addGeneMetadata(gobject)
```

addGeneStatistics	<i>addGeneStatistics</i>
-------------------	--------------------------

Description

adds gene statistics to the giotto object

Usage

```
addGeneStatistics(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  detection_threshold = 0,
  return_gobject = TRUE
)
```

Arguments

gobject giotto object

expression_values expression values to use

detection_threshold detection threshold to consider a gene detected

return_gobject boolean: return giotto object (default = TRUE)

Details

This function will add the following statistics to gene metadata:

- nr_cells: Denotes in how many cells the gene is detected
- per_cells: Denotes in what percentage of cells the gene is detected
- total_expr: Shows the total sum of gene expression in all cells
- mean_expr: Average gene expression in all cells
- mean_expr_det: Average gene expression in cells with detectable levels of the gene

Value

giotto object if return_gobject = TRUE

Examples

```
addGeneStatistics(gobject)
```

addHMRF	<i>addHMRF</i>
---------	----------------

Description

Add selected results from doHMRF to the giotto object

Usage

```
addHMRF(gobject, HMRFOutput, k = NULL, betas_to_add = NULL, hmrf_name = NULL)
```

Arguments

- | | |
|--------------|---|
| gobject | giotto object |
| HMRFOutput | HMRF output from doHMRF() |
| k | number of domains |
| betas_to_add | results from different betas that you want to add |
| name | specify a custom name |

Details

Description ...

Value

giotto object

Examples

```
addHMRF(gobject)
```

addNetworkLayout	<i>addNetworkLayout</i>
------------------	-------------------------

Description

Add a network layout for a selected nearest neighbor network

Usage

```
addNetworkLayout(  
  gobject,  
  nn_network_to_use = "sNN",  
  network_name = "sNN.pca",  
  layout_type = c("drl"),  
  options_list = NULL,  
  layout_name = "layout",  
  return_gobject = TRUE  
)
```

Arguments

gobject	giotto object
nn_network_to_use	kNN or sNN
network_name	name of NN network to be used
layout_type	layout algorithm to use
options_list	list of options for selected layout
layout_name	name for layout
return_gobject	boolean: return giotto object (default = TRUE)

Details

This function creates layout coordinates based on the provided kNN or sNN. Currently only the force-directed graph layout "drl", see [layout_with_drl](#), is implemented. This provides an alternative to tSNE or UMAP based visualizations.

Value

giotto object with updated layout for selected NN network

Examples

```
addNetworkLayout(gobject)
```

addStatistics	<i>addStatistics</i>
---------------	----------------------

Description

adds genes and cells statistics to the giotto object

Usage

```
addStatistics(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  detection_threshold = 0,
  return_gobject = TRUE
)
```

Arguments

gobject giotto object

expression_values
 expression values to use

detection_threshold
 detection threshold to consider a gene detected

return_gobject boolean: return giotto object (default = TRUE)

Details

See [addGeneStatistics](#) and [addCellStatistics](#)

Value

giotto object if return_gobject = TRUE, else a list with results

Examples

```
addStatistics(gobject)
```

adjustGiottoMatrix	<i>adjustGiottoMatrix</i>
--------------------	---------------------------

Description

normalize and/or scale expresion values of Giotto object

Usage

```
adjustGiottoMatrix(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  batch_columns = NULL,
  covariate_columns = NULL,
  return_gobject = TRUE,
  update_slot = c("custom")
)
```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	expression values to use
<code>batch_columns</code>	metadata columns that represent different batch (max = 2)
<code>covariate_columns</code>	metadata columns that represent covariates to regress out
<code>return_gobject</code>	boolean: return giotto object (default = TRUE)
<code>update_slot</code>	expression slot that will be updated (default = custom)

Details

This function implements the [limma::removeBatchEffect](#) function to remove known batch effects and to adjust expression values according to provided covariates.

Value

giotto object

Examples

```
adjustGiottoMatrix(gobject)
```

aes_string2

aes_string2

Description

makes sure aes_string can also be used with names that start with numeric values

Usage

```
aes_string2(...)
```

```
allCellCellcommunicationsScores
      allCellCellcommunicationsScores
```

Description

All Cell-Cell communication scores based on spatial expression of interacting cells

Usage

```
allCellCellcommunicationsScores(
  gobject,
  spatial_network_name = "spatial_network",
  cluster_column = "cell_types",
  random_iter = 100,
  gene_set_1,
  gene_set_2,
  log2FC_addendum = 0.1,
  min_observations = 2,
  verbose = c("a little", "a lot", "none")
)
```

Arguments

<code>gobject</code>	giotto object to use
<code>spatial_network_name</code>	spatial network to use for identifying interacting cells
<code>cluster_column</code>	cluster column with cell type information
<code>random_iter</code>	number of iterations
<code>gene_set_1</code>	first specific gene set from gene pairs
<code>gene_set_2</code>	second specific gene set from gene pairs
<code>log2FC_addendum</code>	addendum to add when calculating log2FC
<code>min_observations</code>	minimum number of interactions needed to be considered
<code>verbose</code>	verbose

Details

Statistical framework to identify if pairs of genes (such as ligand-receptor combinations) are expressed at higher levels than expected based on a reshuffled null distribution of gene expression values in cells that are spatially in proximity to eachother.. More details will follow soon.

Value

Cell-Cell communication scores for gene pairs based on spatial interaction

Examples

```
allCellCellcommunicationsScores(gobject)
```

```
all_plots_save_function
    all_plots_save_function
```

Description

Function to automatically save plots to directory of interest

Usage

```
all_plots_save_function(
  gobject,
  plot_object,
  save_dir = NULL,
  save_folder = NULL,
  save_name = NULL,
  default_save_name = "giotto_plot",
  save_format = NULL,
  show_saved_plot = F,
  ncol = 1,
  nrow = 1,
  scale = 1,
  base_width = NULL,
  base_height = NULL,
  base_aspect_ratio = NULL,
  units = NULL,
  dpi = NULL,
  limitsize = TRUE,
  ...
)
```

Arguments

gobject	giotto object
plot_object	object to plot
save_dir	directory to save to
save_folder	folder in save_dir to save to
save_name	name of plot
save_format	format (e.g. png, tiff, pdf, ...)
show_saved_plot	load & display the saved plot
ncol	number of columns
nrow	number of rows
scale	scale
base_width	width
base_height	height
base_aspect_ratio	aspect ratio

units	units
dpi	Plot resolution
limitsize	When TRUE (the default), ggsave will not save images larger than 50x50 inches, to prevent the common error of specifying dimensions in pixels.
...	additional parameters to ggplot_save_function or general_save_function

See Also

[general_save_function](#)

Examples

```
all_plots_save_function(gobject)
```

annotateGiotto	<i>annotateGiotto</i>
----------------	-----------------------

Description

Converts cluster results into provided annotation.

Usage

```
annotateGiotto(
  gobject,
  annotation_vector = NULL,
  cluster_column = NULL,
  name = "cell_types"
)
```

Arguments

gobject	giotto object
annotation_vector	named annotation vector (names = cluster ids)
cluster_column	cluster column to convert to annotation names
name	new name for annotation column

Details

You need to specify which (cluster) column you want to annotate and you need to provide an annotation vector like this:

- 1. identify the cell type of each cluster
- 2. create a vector of these cell types, e.g. `cell_types = c('T-cell', 'B-cell', 'Stromal')`
- 3. provide original cluster names to previous vector, e.g. `names(cell_types) = c(2, 1, 3)`

Value

giotto object

Examples

```
annotateGiotto(gobject)
```

```
annotateSpatialNetwork
```

```
annotateSpatialNetwork
```

Description

Annotate spatial network with cell metadata information.

Usage

```
annotateSpatialNetwork(  
  gobject,  
  spatial_network_name = "spatial_network",  
  cluster_column  
)
```

Arguments

gobject giotto object
spatial_network_name name of spatial network to use
cluster_column name of column to use for clusters

Value

annotated network in data.table format

Examples

```
annotateSpatialNetwork(gobject)
```

```
annotate_spatlocs_with_spatgrid_2D
```

```
annotate_spatlocs_with_spatgrid_2D
```

Description

annotate spatial locations with 2D spatial grid information

Usage

```
annotate_spatlocs_with_spatgrid_2D(spatloc, spatgrid)
```

Arguments

spatloc spatial_locs slot from giotto object
spatgrid selected spatial_grid slot from giotto object

Value

annotated spatial location data.table

Examples

```
annotate_spatlocs_with_spatgrid_2D()
```

```
annotate_spatlocs_with_spatgrid_3D
```

```
annotate_spatlocs_with_spatgrid_3D
```

Description

annotate spatial locations with 3D spatial grid information

Usage

```
annotate_spatlocs_with_spatgrid_3D(spatloc, spatgrid)
```

Arguments

spatloc spatial_locs slot from giotto object

spatgrid selected spatial_grid slot from giotto object

Value

annotated spatial location data.table

Examples

```
annotate_spatlocs_with_spatgrid_3D()
```

```
average_gene_gene_expression_in_groups
```

```
average_gene_gene_expression_in_groups
```

Description

calculate average expression per cluster

Usage

```
average_gene_gene_expression_in_groups(
  gobject,
  cluster_column = "cell_types",
  gene_set_1,
  gene_set_2
)
```

Arguments

<code>gobject</code>	giotto object to use
<code>cluster_column</code>	cluster column with cell type information
<code>gene_set_1</code>	first specific gene set from gene pairs
<code>gene_set_2</code>	second specific gene set from gene pairs

Details

Details will follow soon.

Value

data.table with average expression scores for each cluster

Examples

```
average_gene_gene_expression_in_groups(gobject)
```

<code>binGetSpatialGenes</code>	<i>binGetSpatialGenes</i>
---------------------------------	---------------------------

Description

Rapid computation of genes that are spatially clustered

Usage

```
binGetSpatialGenes(
  gobject,
  bin_method = c("kmeans", "rank"),
  expression_values = c("normalized", "scaled", "custom"),
  subset_genes = NULL,
  spatial_network_name = "spatial_network",
  nstart = 3,
  iter_max = 10,
  percentage_rank = 10,
  do_fisher_test = F,
  community_expectation = 5,
  verbose = F
)
```

Arguments

<code>gobject</code>	giotto object
<code>bin_method</code>	method to binarize gene expression
<code>expression_values</code>	expression values to use
<code>subset_genes</code>	only select a subset of genes to test
<code>spatial_network_name</code>	name of spatial network to use (default = 'spatial_network')

nstart	kmeans: nstart parameter
iter_max	kmeans: iter.max parameter
do_fisher_test	perform fisher test
community_expectation	cell degree expectation in spatial communities
verbose	be verbose
rank_percentage	percentage of top cells for binarization

Details

We provide two ways to identify spatial genes based on gene expression binarization. Both methods are identical except for how binarization is performed.

- 1. binarize: Each gene is binarized (0 or 1) in each cell with **kmeans** ($k = 2$) or based on **rank** percentile
- 2. network: All cells are connected through a k-nearest neighbor network
- 3. contingency table: A contingency table is calculated based on all pairwise cell-cell interactions (0-0, 0-1, 1-0 or 1-1)
- 4. For each gene an odds-ratio (OR) and fisher.test (optional) is calculated

Additionally 2 other statistics are provided:

- Number of cells with high expression (binary = 1)
- total and ratio of highly connected cells: Cells with a connectivity higher than community_expectation

By selecting a subset of likely spatial genes (e.g. highly variable genes) the function will be much faster.

Value

data.table with results (see details)

Examples

```
binGetSpatialGenes(gobject)
```

calculateHVG

calculateHVG

Description

compute highly variable genes

Usage

```
calculateHVG(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  method = c("cov_groups", "cov_loess"),
  reverse_log_scale = FALSE,
  logbase = 2,
  expression_threshold = 0,
  nr_expression_groups = 20,
  zscore_threshold = 1.5,
  HVGname = "hvg",
  difference_in_cov = 0.1,
  show_plot = NA,
  return_plot = NA,
  save_plot = NA,
  save_param = list(),
  default_save_name = "HVGplot",
  return_gobject = TRUE
)
```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	expression values to use
<code>method</code>	method to calculate highly variable genes
<code>reverse_log_scale</code>	reverse log-scale of expression values (default = FALSE)
<code>logbase</code>	if <code>reverse_log_scale</code> is TRUE, which log base was used?
<code>expression_threshold</code>	expression threshold to consider a gene detected
<code>nr_expression_groups</code>	number of expression groups for <code>cov_groups</code>
<code>zscore_threshold</code>	zscore to select hvg for <code>cov_groups</code>
<code>HVGname</code>	name for highly variable genes in cell metadata
<code>difference_in_cov</code>	minimum difference in coefficient of variance required
<code>show_plot</code>	show plot
<code>return_plot</code>	return ggplot object
<code>save_plot</code>	directly save the plot [boolean]
<code>save_param</code>	list of saving parameters from all_plots_save_function
<code>default_save_name</code>	default save name for saving, don't change, change <code>save_name</code> in <code>save_param</code>
<code>return_gobject</code>	boolean: return giotto object (default = TRUE)

Details

Currently we provide 2 ways to calculate highly variable genes: **1. high coeff of variance (COV) within groups:**

First genes are binned (*nr_expression_groups*) into average expression groups and the COV for each gene is converted into a z-score within each bin. Genes with a z-score higher than the threshold (*zscore_threshold*) are considered highly variable.

2. high COV based on loess regression prediction:

A predicted COV is calculated for each gene using loess regression ($\text{COV} \sim \log(\text{mean expression})$). Genes that show a higher than predicted COV (*difference_in_cov*) are considered highly variable.

Value

giotto object highly variable genes appended to gene metadata (fDataDT)

Examples

```
calculateHVG(gobject)
```

calculateMetaTable	<i>calculateMetaTable</i>
--------------------	---------------------------

Description

calculates the average gene expression for one or more (combined) annotation columns.

Usage

```
calculateMetaTable(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  metadata_cols = NULL,
  selected_genes = NULL
)
```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	expression values to use
<code>metadata_cols</code>	annotation columns found in <code>pDataDT(gobject)</code>
<code>selected_genes</code>	subset of genes to use

Value

data.table with average expression values for each gene per (combined) annotation

Examples

```
calculateMetaTable(gobject)
```

```
calculateMetaTableCells
      calculateMetaTableCells
```

Description

calculates the average metadata values for one or more (combined) annotation columns.

Usage

```
calculateMetaTableCells(
  gobject,
  value_cols = NULL,
  metadata_cols = NULL,
  spat_enr_names = NULL
)
```

Arguments

```
gobject      giotto object
value_cols   metadata or enrichment value columns to use
metadata_cols annotation columns found in pDataDT(gobject)
spat_enr_names which spatial enrichment results to include
```

Value

data.table with average metadata values per (combined) annotation

Examples

```
calculateMetaTableCells(gobject)
```

```
calculate_spatial_genes_python
      calculate_spatial_genes_python
```

Description

Calculate spatial genes using distance matrix.

Usage

```
calculate_spatial_genes_python(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  metric = "euclidean",
  subset_genes = NULL,
  rbp_p = 0.95,
  examine_top = 0.3,
  python_path = NULL
)
```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	expression values to use
<code>metric</code>	distance metric to use
<code>subset_genes</code>	only run on this subset of genes
<code>rbp_p</code>	fractional binarization threshold
<code>examine_top</code>	top fraction to evaluate with silhouette
<code>python_path</code>	specify specific path to python if required

Details

Description of how we compute spatial pattern genes.

Value

data.table with spatial scores

Examples

```
calculate_spatial_genes_python(gobject)
```

`cellProximityBarplot` *cellProximityBarplot*

Description

Create barplot from cell-cell proximity scores

Usage

```
cellProximityBarplot(
  gobject,
  CPscore,
  min_orig_ints = 5,
  min_sim_ints = 5,
  p_val = 0.05,
  show_plot = NA,
  return_plot = NA,
  save_plot = NA,
  save_param = list(),
  default_save_name = "cellProximityBarplot"
)
```


Arguments

<code>gobject</code>	giotto object
<code>CPscore</code>	CPscore, output from <code>cellProximityEnrichment()</code>
<code>min_orig_ints</code>	filter on minimum original cell-cell interactions
<code>min_sim_ints</code>	filter on minimum simulated cell-cell interactions
<code>p_val</code>	p-value
<code>show_plot</code>	show plot
<code>return_plot</code>	return ggplot object
<code>save_plot</code>	directly save the plot [boolean]
<code>save_param</code>	list of saving parameters from all_plots_save_function
<code>default_save_name</code>	default save name for saving, don't change, change <code>save_name</code> in <code>save_param</code>

Details

This function creates a barplot that shows the spatial proximity enrichment or depletion of cell type pairs.

Value

ggplot barplot

Examples

```
cellProximityBarplot(CPscore)
```

```
cellProximityEnrichment
```

```
cellProximityEnrichment
```

Description

Compute cell-cell interaction enrichment (observed vs expected)

Usage

```
cellProximityEnrichment(
  gobject,
  spatial_network_name = "spatial_network",
  cluster_column,
  number_of_simulations = 100
)
```

Arguments

<code>gobject</code>	giotto object
<code>spatial_network_name</code>	name of spatial network to use
<code>cluster_column</code>	name of column to use for clusters
<code>number_of_simulations</code>	number of simulations to create expected observations

Details

Spatial proximity enrichment or depletion between pairs of cell types is calculated by calculating the observed over the expected frequency of cell-cell proximity interactions. The expected frequency is the average frequency calculated from a number of spatial network simulations. Each individual simulation is obtained by reshuffling the cell type labels of each node (cell) in the spatial network.

Value

List of cell Proximity scores (CPscores) in data.table format. The first data.table (raw_sim_table) shows the raw observations of both the original and simulated networks. The second data.table (enrichm_res) shows the enrichment results.

Examples

```
cellProximityEnrichment(gobject)
```

cellProximityHeatmap	<i>cellProximityHeatmap</i>
----------------------	-----------------------------

Description

Create heatmap from cell-cell proximity scores

Usage

```
cellProximityHeatmap(
  gobject,
  CPscore,
  scale = T,
  order_cell_types = T,
  color_breaks = NULL,
  color_names = NULL,
  show_plot = NA,
  return_plot = NA,
  save_plot = NA,
  save_param = list(),
  default_save_name = "cellProximityHeatmap"
)
```

Arguments

gobject	giotto object
CPscore	CPscore, output from cellProximityEnrichment()
scale	scale cell-cell proximity interaction scores
order_cell_types	order cell types based on enrichment correlation
color_breaks	numerical vector of length 3 to represent min, mean and maximum
color_names	character color vector of length 3
show_plot	show plot

return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function
default_save_name	default save name for saving, don't change, change save_name in save_param

Details

This function creates a heatmap that shows the spatial proximity enrichment or depletion of cell type pairs.

Value

ggplot heatmap

Examples

```
cellProximityHeatmap(CPscore)
```

cellProximityNetwork	<i>cellProximityNetwork</i>
----------------------	-----------------------------

Description

Create network from cell-cell proximity scores

Usage

```
cellProximityNetwork(
  gobject,
  CPscore,
  remove_self_edges = FALSE,
  self_loop_strength = 0.1,
  color_depletion = "lightgreen",
  color_enrichment = "red",
  rescale_edge_weights = TRUE,
  edge_weight_range_depletion = c(0.1, 1),
  edge_weight_range_enrichment = c(1, 5),
  layout = "Fruchterman",
  only_show_enrichment_edges = F,
  edge_width_range = c(0.1, 2),
  node_size = 4,
  node_text_size = 6,
  show_plot = NA,
  return_plot = NA,
  save_plot = NA,
  save_param = list(),
  default_save_name = "cellProximityNetwork"
)
```

Arguments

<code>gobject</code>	giotto object
<code>CPscore</code>	CPscore, output from <code>cellProximityEnrichment()</code>
<code>remove_self_edges</code>	remove enrichment/depletion edges with itself
<code>self_loop_strength</code>	size of self-loops
<code>color_depletion</code>	color for depleted cell-cell interactions
<code>color_enrichment</code>	color for enriched cell-cell interactions
<code>rescale_edge_weights</code>	rescale edge weights (boolean)
<code>edge_weight_range_depletion</code>	numerical vector of length 2 to rescale depleted edge weights
<code>edge_weight_range_enrichment</code>	numerical vector of length 2 to rescale enriched edge weights
<code>layout</code>	layout algorithm to use to draw nodes and edges
<code>only_show_enrichment_edges</code>	show only the enriched pairwise scores
<code>edge_width_range</code>	range of edge width
<code>node_size</code>	size of nodes
<code>node_text_size</code>	size of node labels
<code>show_plot</code>	show plot
<code>return_plot</code>	return ggplot object
<code>save_plot</code>	directly save the plot [boolean]
<code>save_param</code>	list of saving parameters from all_plots_save_function
<code>default_save_name</code>	default save name for saving, don't change, change <code>save_name</code> in <code>save_param</code>

Details

This function creates a network that shows the spatial proximity enrichment or depletion of cell type pairs.

Value

igraph plot

Examples

```
cellProximityNetwork(CPscore)
```

cellProximitySpatPlot *cellProximitySpatPlot*

Description

Visualize 2D cell-cell interactions according to spatial coordinates in ggplot mode

Usage

```
cellProximitySpatPlot(gobject, ...)
```

Arguments

<code>gobject</code>	giotto object
<code>interaction_name</code>	cell-cell interaction name
<code>cluster_column</code>	cluster column with cell clusters
<code>sdimx</code>	x-axis dimension name (default = 'sdimx')
<code>sdimy</code>	y-axis dimension name (default = 'sdimy')
<code>cell_color</code>	color for cells (see details)
<code>cell_color_code</code>	named vector with colors
<code>color_as_factor</code>	convert color column to factor
<code>show_other_cells</code>	decide if show cells not in network
<code>show_network</code>	show underlying spatial network
<code>network_color</code>	color of spatial network
<code>spatial_network_name</code>	name of spatial network to use
<code>show_grid</code>	show spatial grid
<code>grid_color</code>	color of spatial grid
<code>spatial_grid_name</code>	name of spatial grid to use
<code>coord_fix_ratio</code>	fix ratio between x and y-axis
<code>show_legend</code>	show legend
<code>point_size_select</code>	size of selected points
<code>point_select_border_col</code>	border color of selected points
<code>point_select_border_stroke</code>	stroke size of selected points
<code>point_size_other</code>	size of other points

point_other_border_col	border color of other points
point_other_border_stroke	stroke size of other points
show_plot	show plots
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function
default_save_name	default save name for saving, don't change, change save_name in save_param

Details

Description of parameters.

Value

ggplot

See Also

[cellProximitySpatPlot2D](#) and [cellProximitySpatPlot3D](#) for 3D

Examples

```
cellProximitySpatPlot(gobject)
```

```
cellProximitySpatPlot2D
      cellProximitySpatPlot2D
```

Description

Visualize 2D cell-cell interactions according to spatial coordinates in ggplot mode

Usage

```
cellProximitySpatPlot2D(
  gobject,
  interaction_name = NULL,
  cluster_column = NULL,
  sdimx = "sdimx",
  sdimy = "sdimy",
  cell_color = NULL,
  cell_color_code = NULL,
  color_as_factor = T,
  show_other_cells = F,
  show_network = F,
  show_other_network = F,
  network_color = NULL,
```

```

    spatial_network_name = "spatial_network",
    show_grid = F,
    grid_color = NULL,
    spatial_grid_name = "spatial_grid",
    coord_fix_ratio = 1,
    show_legend = T,
    point_size_select = 2,
    point_select_border_col = "black",
    point_select_border_stroke = 0.05,
    point_size_other = 1,
    point_alpha_other = 0.3,
    point_other_border_col = "lightgrey",
    point_other_border_stroke = 0.01,
    show_plot = NA,
    return_plot = NA,
    save_plot = NA,
    save_param = list(),
    default_save_name = "cellProximitySpatPlot2D"
)

```

Arguments

<code>gobject</code>	giotto object
<code>interaction_name</code>	cell-cell interaction name
<code>cluster_column</code>	cluster column with cell clusters
<code>sdimx</code>	x-axis dimension name (default = 'sdimx')
<code>sdimy</code>	y-axis dimension name (default = 'sdimy')
<code>cell_color</code>	color for cells (see details)
<code>cell_color_code</code>	named vector with colors
<code>color_as_factor</code>	convert color column to factor
<code>show_other_cells</code>	decide if show cells not in network
<code>show_network</code>	show underlying spatial network
<code>network_color</code>	color of spatial network
<code>spatial_network_name</code>	name of spatial network to use
<code>show_grid</code>	show spatial grid
<code>grid_color</code>	color of spatial grid
<code>spatial_grid_name</code>	name of spatial grid to use
<code>coord_fix_ratio</code>	fix ratio between x and y-axis
<code>show_legend</code>	show legend
<code>point_size_select</code>	size of selected points

point_select_border_col	border color of selected points
point_select_border_stroke	stroke size of selected points
point_size_other	size of other points
point_other_border_col	border color of other points
point_other_border_stroke	stroke size of other points
show_plot	show plots
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function
default_save_name	default save name for saving, don't change, change save_name in save_param

Details

Description of parameters.

Value

ggplot

Examples

```
cellProximitySpatPlot2D(gobject)
```

cellProximitySpatPlot3D	<i>cellProximitySpatPlot2D</i>
-------------------------	--------------------------------

Description

Visualize 3D cell-cell interactions according to spatial coordinates in plotly mode

Usage

```
cellProximitySpatPlot3D(
  gobject,
  interaction_name = NULL,
  cluster_column = NULL,
  sdimx = "sdimx",
  sdimy = "sdimy",
  sdimz = "sdimz",
  cell_color = NULL,
  cell_color_code = NULL,
  color_as_factor = T,
  show_other_cells = T,
```



```

show_network = T,
show_other_network = F,
network_color = NULL,
spatial_network_name = "spatial_network",
show_grid = F,
grid_color = NULL,
spatial_grid_name = "spatial_grid",
show_legend = T,
point_size_select = 4,
point_size_other = 2,
point_alpha_other = 0.5,
axis_scale = c("cube", "real", "custom"),
custom_ratio = NULL,
x_ticks = NULL,
y_ticks = NULL,
z_ticks = NULL,
show_plot = NA,
return_plot = NA,
save_plot = NA,
save_param = list(),
default_save_name = "cellProximitySpatPlot3D",
...
)

```

Arguments

<code>gobject</code>	giotto object
<code>interaction_name</code>	cell-cell interaction name
<code>cluster_column</code>	cluster column with cell clusters
<code>sdimx</code>	x-axis dimension name (default = 'sdimx')
<code>sdimy</code>	y-axis dimension name (default = 'sdimy')
<code>sdimz</code>	z-axis dimension name (default = 'sdimz')
<code>cell_color</code>	color for cells (see details)
<code>cell_color_code</code>	named vector with colors
<code>color_as_factor</code>	convert color column to factor
<code>show_other_cells</code>	decide if show cells not in network
<code>show_network</code>	show underlying spatial network
<code>network_color</code>	color of spatial network
<code>spatial_network_name</code>	name of spatial network to use
<code>show_grid</code>	show spatial grid
<code>grid_color</code>	color of spatial grid
<code>spatial_grid_name</code>	name of spatial grid to use
<code>show_legend</code>	show legend

point_size_select	size of selected points
point_size_other	size of other points
show_plot	show plots
return_plot	return plotly object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function
default_save_name	default save name for saving, don't change, change save_name in save_param

Details

Description of parameters.

Value

plotly

Examples

```
cellProximitySpatPlot3D(gobject)
```

cellProximityVisPlot	<i>cellProximityVisPlot</i>
----------------------	-----------------------------

Description

Visualize cell-cell interactions according to spatial coordinates

Usage

```
cellProximityVisPlot(
  gobject,
  interaction_name = NULL,
  cluster_column = NULL,
  sdimx = NULL,
  sdimy = NULL,
  sdimz = NULL,
  cell_color = NULL,
  cell_color_code = NULL,
  color_as_factor = T,
  show_other_cells = F,
  show_network = F,
  show_other_network = F,
  network_color = NULL,
  spatial_network_name = "spatial_network",
  show_grid = F,
  grid_color = NULL,
  spatial_grid_name = "spatial_grid",
```

```

    coord_fix_ratio = 1,
    show_legend = T,
    point_size_select = 2,
    point_select_border_col = "black",
    point_select_border_stroke = 0.05,
    point_size_other = 1,
    point_alpha_other = 0.3,
    point_other_border_col = "lightgrey",
    point_other_border_stroke = 0.01,
    axis_scale = c("cube", "real", "custom"),
    custom_ratio = NULL,
    x_ticks = NULL,
    y_ticks = NULL,
    z_ticks = NULL,
    plot_method = c("ggplot", "plotly"),
    ...
)

```

Arguments

<code>gobject</code>	giotto object
<code>interaction_name</code>	cell-cell interaction name
<code>cluster_column</code>	cluster column with cell clusters
<code>sdimx</code>	x-axis dimension name (default = 'sdimx')
<code>sdimy</code>	y-axis dimension name (default = 'sdimy')
<code>sdimz</code>	z-axis dimension name (default = 'sdimz')
<code>cell_color</code>	color for cells (see details)
<code>cell_color_code</code>	named vector with colors
<code>color_as_factor</code>	convert color column to factor
<code>show_network</code>	show underlying spatial network
<code>network_color</code>	color of spatial network
<code>spatial_network_name</code>	name of spatial network to use
<code>show_grid</code>	show spatial grid
<code>grid_color</code>	color of spatial grid
<code>spatial_grid_name</code>	name of spatial grid to use
<code>coord_fix_ratio</code>	fix ratio between x and y-axis
<code>show_legend</code>	show legend
<code>point_size_select</code>	size of selected points
<code>point_select_border_col</code>	border color of selected points

point_select_border_stroke
stroke size of selected points

point_size_other
size of other points

point_other_border_col
border color of other points

point_other_border_stroke
stroke size of other points

Details

Description of parameters.

Value

ggplot or plotly

Examples

```
cellProximityVisPlot(gobject)
```

```
cellProximityVisPlot_2D_ggplot  
cellProximityVisPlot_2D_ggplot
```

Description

Visualize 2D cell-cell interactions according to spatial coordinates in ggplot mode

Usage

```
cellProximityVisPlot_2D_ggplot(  
  gobject,  
  interaction_name = NULL,  
  cluster_column = NULL,  
  sdimx = NULL,  
  sdimy = NULL,  
  cell_color = NULL,  
  cell_color_code = NULL,  
  color_as_factor = T,  
  show_other_cells = F,  
  show_network = F,  
  show_other_network = F,  
  network_color = NULL,  
  spatial_network_name = "spatial_network",  
  show_grid = F,  
  grid_color = NULL,  
  spatial_grid_name = "spatial_grid",  
  coord_fix_ratio = 1,  
  show_legend = T,  
  point_size_select = 2,
```

```

    point_select_border_col = "black",
    point_select_border_stroke = 0.05,
    point_size_other = 1,
    point_alpha_other = 0.3,
    point_other_border_col = "lightgrey",
    point_other_border_stroke = 0.01,
    ...
)

```

Arguments

<code>gobject</code>	giotto object
<code>interaction_name</code>	cell-cell interaction name
<code>cluster_column</code>	cluster column with cell clusters
<code>sdimx</code>	x-axis dimension name (default = 'sdimx')
<code>sdimy</code>	y-axis dimension name (default = 'sdimy')
<code>cell_color</code>	color for cells (see details)
<code>cell_color_code</code>	named vector with colors
<code>color_as_factor</code>	convert color column to factor
<code>show_other_cells</code>	decide if show cells not in network
<code>show_network</code>	show underlying spatial network
<code>network_color</code>	color of spatial network
<code>spatial_network_name</code>	name of spatial network to use
<code>show_grid</code>	show spatial grid
<code>grid_color</code>	color of spatial grid
<code>spatial_grid_name</code>	name of spatial grid to use
<code>coord_fix_ratio</code>	fix ratio between x and y-axis
<code>show_legend</code>	show legend
<code>point_size_select</code>	size of selected points
<code>point_select_border_col</code>	border color of selected points
<code>point_select_border_stroke</code>	stroke size of selected points
<code>point_size_other</code>	size of other points
<code>point_other_border_col</code>	border color of other points
<code>point_other_border_stroke</code>	stroke size of other points

Details

Description of parameters.

Value

ggplot

Examples

```
cellProximityVisPlot_2D_ggplot(gobject)
```

```
cellProximityVisPlot_2D_plotly
```

```
cellProximityVisPlot_2D_plotly
```

Description

Visualize 2D cell-cell interactions according to spatial coordinates in plotly mode

Usage

```
cellProximityVisPlot_2D_plotly(
  gobject,
  interaction_name = NULL,
  cluster_column = NULL,
  sdimx = NULL,
  sdimy = NULL,
  cell_color = NULL,
  cell_color_code = NULL,
  color_as_factor = T,
  show_other_cells = F,
  show_network = F,
  show_other_network = F,
  network_color = NULL,
  spatial_network_name = "spatial_network",
  show_grid = F,
  grid_color = NULL,
  spatial_grid_name = "spatial_grid",
  show_legend = T,
  point_size_select = 2,
  point_size_other = 1,
  point_alpha_other = 0.3,
  axis_scale = c("cube", "real", "custom"),
  custom_ratio = NULL,
  x_ticks = NULL,
  y_ticks = NULL,
  ...
)
```

Arguments

<code>gobject</code>	giotto object
<code>interaction_name</code>	cell-cell interaction name
<code>cluster_column</code>	cluster column with cell clusters
<code>sdimx</code>	x-axis dimension name (default = 'sdimx')
<code>sdimy</code>	y-axis dimension name (default = 'sdimy')
<code>cell_color</code>	color for cells (see details)
<code>cell_color_code</code>	named vector with colors
<code>color_as_factor</code>	convert color column to factor
<code>show_other_cells</code>	decide if show cells not in network
<code>show_network</code>	show underlying spatial network
<code>network_color</code>	color of spatial network
<code>spatial_network_name</code>	name of spatial network to use
<code>show_grid</code>	show spatial grid
<code>grid_color</code>	color of spatial grid
<code>spatial_grid_name</code>	name of spatial grid to use
<code>show_legend</code>	show legend
<code>point_size_select</code>	size of selected points
<code>coord_fix_ratio</code>	fix ratio between x and y-axis

Details

Description of parameters.

Value

plotly

Examples

```
cellProximityVisPlot_2D_plotly(gobject)
```

```
cellProximityVisPlot_3D_plotly
      cellProximityVisPlot_3D_plotly
```

Description

Visualize 3D cell-cell interactions according to spatial coordinates in plotly mode

Usage

```
cellProximityVisPlot_3D_plotly(
  gobject,
  interaction_name = NULL,
  cluster_column = NULL,
  sdimx = NULL,
  sdimy = NULL,
  sdimz = NULL,
  cell_color = NULL,
  cell_color_code = NULL,
  color_as_factor = T,
  show_other_cells = F,
  show_network = F,
  show_other_network = F,
  network_color = NULL,
  spatial_network_name = "spatial_network",
  show_grid = F,
  grid_color = NULL,
  spatial_grid_name = "spatial_grid",
  show_legend = T,
  point_size_select = 2,
  point_size_other = 1,
  point_alpha_other = 0.5,
  axis_scale = c("cube", "real", "custom"),
  custom_ratio = NULL,
  x_ticks = NULL,
  y_ticks = NULL,
  z_ticks = NULL,
  ...
)
```

Arguments

<code>gobject</code>	giotto object
<code>interaction_name</code>	cell-cell interaction name
<code>cluster_column</code>	cluster column with cell clusters
<code>sdimx</code>	x-axis dimension name (default = 'sdimx')
<code>sdimy</code>	y-axis dimension name (default = 'sdimy')
<code>sdimz</code>	z-axis dimension name (default = 'sdimz')

cell_color	color for cells (see details)
cell_color_code	named vector with colors
color_as_factor	convert color column to factor
show_other_cells	decide if show cells not in network
show_network	show underlying spatial network
network_color	color of spatial network
spatial_network_name	name of spatial network to use
show_grid	show spatial grid
grid_color	color of spatial grid
spatial_grid_name	name of spatial grid to use
show_legend	show legend
point_size_select	size of selected points
coord_fix_ratio	fix ratio between x and y-axis

Details

Description of parameters.

Value

plotly

Examples

```
cellProximityVisPlot_3D_plotly(gobject)
```

changeGiottoInstructions

changeGiottoInstructions

Description

Function to change one or more instructions from giotto object

Usage

```
changeGiottoInstructions(
  gobject,
  params = NULL,
  new_values = NULL,
  return_gobject = TRUE
)
```

Arguments

<code>gobject</code>	giotto object
<code>params</code>	parameter(s) to change
<code>new_values</code>	new value(s) for parameter(s)
<code>return_gobject</code>	(boolean) return giotto object

Value

named vector with giotto instructions

Examples

```
changeGiottoInstructions()
```

<code>clusterCells</code>	<i>clusterCells</i>
---------------------------	---------------------

Description

cluster cells using a variety of different methods

Usage

```
clusterCells(
  gobject,
  cluster_method = c("leiden", "louvain_community", "louvain_multinet", "randomwalk",
    "sNNclust", "kmeans", "hierarchical"),
  name = "cluster_name",
  nn_network_to_use = "sNN",
  network_name = "sNN.pca",
  pyth_leid_resolution = 1,
  pyth_leid_weight_col = "weight",
  pyth_leid_part_type = c("RBConfigurationVertexPartition", "ModularityVertexPartition"),
  pyth_leid_init_memb = NULL,
  pyth_leid_iterations = 1000,
  pyth_louv_resolution = 1,
  pyth_louv_weight_col = NULL,
  python_louv_random = F,
  python_path = NULL,
  louvain_gamma = 1,
  louvain_omega = 1,
  walk_steps = 4,
  walk_clusters = 10,
  walk_weights = NA,
  sNNclust_k = 20,
  sNNclust_eps = 4,
  sNNclust_minPts = 16,
  borderPoints = TRUE,
  expression_values = c("normalized", "scaled", "custom"),
  genes_to_use = NULL,
```

```

dim_reduction_to_use = c("cells", "pca", "umap", "tsne"),
dim_reduction_name = "pca",
dimensions_to_use = 1:10,
distance_method = c("original", "pearson", "spearman", "euclidean", "maximum",
    "manhattan", "canberra", "binary", "minkowski"),
km_centers = 10,
km_iter_max = 100,
km_nstart = 1000,
km_algorithm = "Hartigan-Wong",
hc_agglomeration_method = c("ward.D2", "ward.D", "single", "complete", "average",
    "mcquitty", "median", "centroid"),
hc_k = 10,
hc_h = NULL,
return_gobject = TRUE,
set_seed = T,
seed_number = 1234
)

```

Arguments

<code>gobject</code>	giotto object
<code>cluster_method</code>	community cluster method to use
<code>name</code>	name for new clustering result
<code>nn_network_to_use</code>	type of NN network to use (kNN vs sNN)
<code>network_name</code>	name of NN network to use
<code>pyth_leid_resolution</code>	resolution for leiden
<code>pyth_leid_weight_col</code>	column to use for weights
<code>pyth_leid_part_type</code>	partition type to use
<code>pyth_leid_init_memb</code>	initial membership
<code>pyth_leid_iterations</code>	number of iterations
<code>pyth_louv_resolution</code>	resolution for louvain
<code>pyth_louv_weight_col</code>	python louvain param: weight column
<code>python_louv_random</code>	python louvain param: random
<code>python_path</code>	specify specific path to python if required
<code>louvain_gamma</code>	louvain param: gamma or resolution
<code>louvain_omega</code>	louvain param: omega
<code>walk_steps</code>	randomwalk: number of steps
<code>walk_clusters</code>	randomwalk: number of clusters
<code>walk_weights</code>	randomwalk: weight column
<code>sNNclust_k</code>	SNNclust: k neighbors to use

sNNclust_eps	SNNclust: epsilon
sNNclust_minPts	SNNclust: min points
borderPoints	SNNclust: border points
expression_values	expression values to use
genes_to_use	= NULL,
dim_reduction_to_use	dimension reduction to use
dim_reduction_name	name of reduction 'pca',
dimensions_to_use	dimensions to use
distance_method	distance method
km_centers	kmeans centers
km_iter_max	kmeans iterations
km_nstart	kmeans random starting points
km_algorithm	kmeans algorithm
hc_agglomeration_method	hierarchical clustering method
hc_k	hierachical number of clusters
hc_h	hierarchical tree cutoff
return_gobject	boolean: return giotto object (default = TRUE)
set_seed	set seed
seed_number	number for seed

Details

Wrapper for the different clustering methods.

Value

giotto object with new clusters appended to cell metadata

See Also

[doLeidenCluster](#), [doLouvainCluster_community](#), [doLouvainCluster_multinet](#), [doLouvainCluster](#), [doRandomWalkCluster](#), [doSNNCluster](#), [doKmeans](#), [doHclust](#)

Examples

```
clusterCells(gobject)
```

```
clusterSpatialCorGenes
      clusterSpatialCorGenes
```

Description

Cluster based on spatially correlated genes

Usage

```
clusterSpatialCorGenes(
  spatCorObject,
  name = "spat_clus",
  hclust_method = "ward.D",
  k = 10,
  return_obj = TRUE
)
```

Arguments

spatCorObject	spatial correlation object
name	name for spatial clustering results
hclust_method	method for hierarchical clustering
k	number of clusters to extract
return_obj	return spatial correlation object (spatCorObject)

Value

spatCorObject or cluster results

Examples

```
clusterSpatialCorGenes(gobject)
```

```
combineMetadata      combineMetadata
```

Description

This function combines the cell metadata with spatial locations and enrichment results from createSpatialEnrich

Usage

```
combineMetadata(gobject, spat_enr_names = NULL)
```

Arguments

gobject	Giotto object
spat_enr_names	names of spatial enrichment results to include

Value

Extended cell metadata in data.table format.

Examples

```
combineMetadata(gobject)
```

```
convertEnsemblToGeneSymbol
```

```
convertEnsemblToGeneSymbol
```

Description

This function convert ensembl gene IDs from a matrix to official gene symbols

Usage

```
convertEnsemblToGeneSymbol(matrix, species = c("mouse", "human"))
```

Arguments

<code>matrix</code>	an expression matrix with ensembl gene IDs as rownames
<code>species</code>	species to use for gene symbol conversion

Details

This function requires that the biomaRt library is installed

Value

expression matrix with gene symbols as rownames

Examples

```
convertEnsemblToGeneSymbol(matrix)
```

```
createGiottoInstructions
```

```
createGiottoInstructions
```

Description

Function to set global instructions for giotto functions

Usage

```
createGiottoInstructions(
  python_path = NULL,
  show_plot = NULL,
  return_plot = NULL,
  save_plot = NULL,
  save_dir = NULL,
  plot_format = NULL,
  dpi = NULL,
  units = NULL,
  height = NULL,
  width = NULL
)
```

Arguments

python_path	path to python binary to use
show_plot	print plot to console, default = TRUE
return_plot	return plot as object, default = TRUE
save_plot	automatically save plot, default = FALSE
save_dir	path to directory where to save plots
dpi	resolution for raster images
height	height of plots
width	width of plots

Value

named vector with giotto instructions

Examples

```
createGiottoInstructions()
```

createGiottoObject	<i>create Giotto object</i>
--------------------	-----------------------------

Description

Function to create a giotto object

Usage

```
createGiottoObject(
  raw_exprs,
  spatial_locs = NULL,
  norm_expr = NULL,
  norm_scaled_expr = NULL,
  custom_expr = NULL,
  cell_metadata = NULL,
```

```

gene_metadata = NULL,
spatial_network = NULL,
spatial_network_name = NULL,
spatial_grid = NULL,
spatial_grid_name = NULL,
spatial_enrichment = NULL,
spatial_enrichment_name = NULL,
dimension_reduction = NULL,
nn_network = NULL,
offset_file = NULL,
instructions = NULL
)

```

Arguments

raw_exprs	matrix with raw expression counts [required]
spatial_locs	data.table or data.frame with coordinates for cell centroids
norm_expr	normalized expression values
norm_scaled_expr	scaled expression values
custom_expr	custom expression values
cell_metadata	cell annotation metadata
gene_metadata	gene annotation metadata
spatial_network	list of spatial network(s)
spatial_network_name	list of spatial network name(s)
spatial_grid	list of spatial grid(s)
spatial_grid_name	list of spatial grid name(s)
spatial_enrichment	list of spatial enrichment score(s) for each spatial region
spatial_enrichment_name	list of spatial enrichment name(s)
dimension_reduction	list of dimension reduction(s)
nn_network	list of nearest neighbor network(s)
offset_file	file used to stitch fields together (optional)
instructions	list of instructions or output result from createGiottoInstructions

Details

[Requirements] To create a giotto object you need to provide at least a matrix with genes as row names and cells as column names. To include spatial information about cells (or regions) you need to provide a data.table or data.frame with coordinates for all spatial dimensions. This can be 2D (x and y) or 3D (x, y, x). The row order for the cell coordinates should be the same as the column order for the provided expression data.

[Instructions] Additionally an instruction file, generated manually or with [createGiottoInstructions](#) can be provided to instructions, if not a default instruction file will be created for the Giotto object.

[Multiple fields] In case a dataset consists of multiple fields, like seqFISH+ for example, an offset file can be provided to stitch the different fields together. [stitchFieldCoordinates](#) can be used to generate such an offset file.

[Processed data] Processed count data, such as normalized data, can be provided using one of the different expression slots (norm_expr, norm_scaled_expr, custom_expr).

[Metadata] Cell and gene metadata can be provided using the cell and gene metadata slots. This data can also be added afterwards using the [addGeneMetadata](#) or [addCellMetadata](#) functions.

[Other information] Additional information can be provided through the appropriate slots:

- spatial networks
- spatial girds
- spatial enrichments
- dimensions reductions
- nearest neighbours networks

Value

giotto object

Examples

```
createGiottoObject(raw_exprs, spatial_locs)
```

createHeatmap_DT	<i>createHeatmap_DT</i>
------------------	-------------------------

Description

creates order for clusters

Usage

```
createHeatmap_DT(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  genes,
  cluster_column = NULL,
  cluster_order = c("size", "correlation", "custom"),
  cluster_custom_order = NULL,
  cluster_cor_method = "pearson",
  cluster_hclust_method = "ward.D",
  gene_order = c("custom", "correlation"),
  gene_custom_order = NULL,
  gene_cor_method = "pearson",
  gene_hclust_method = "complete"
)
```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	expression values to use
<code>genes</code>	genes to use
<code>cluster_column</code>	name of column to use for clusters
<code>cluster_order</code>	method to determine cluster order
<code>cluster_custom_order</code>	custom order for clusters
<code>cluster_cor_method</code>	method for cluster correlation
<code>cluster_hclust_method</code>	method for hierarchical clustering of clusters
<code>gene_order</code>	method to determine gene order
<code>gene_custom_order</code>	custom order for genes
<code>gene_cor_method</code>	method for gene correlation
<code>gene_hclust_method</code>	method for hierarchical clustering of genes

Details

Creates input data.tables for plotHeatmap function.

Value

list

Examples

```
createHeatmap_DT(gobject)
```

createMetagenes	<i>createMetagenes</i>
-----------------	------------------------

Description

This function creates an average metagene for gene clusters.

Usage

```
createMetagenes(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  gene_clusters,
  name = "metagene",
  return_gobject = TRUE
)
```

Arguments

<code>gobject</code>	Giotto object
<code>expression_values</code>	expression values to use
<code>gene_clusters</code>	numerical vector with genes as names
<code>name</code>	name of the metagene results
<code>return_gobject</code>	return giotto object

Details

An example for the 'gene_clusters' could be like this: `cluster_vector = c(1, 1, 2, 2); names(cluster_vector) = c('geneA', 'geneB', 'geneC', 'geneD')`

Value

giotto object

Examples

```
createMetagenes(gobject)
```

```
createNearestNetwork    createNearestNetwork
```

Description

create a nearest neighbour (NN) network

Usage

```
createNearestNetwork(
  gobject,
  type = c("sNN", "kNN"),
  dim_reduction_to_use = "pca",
  dim_reduction_name = "pca",
  dimensions_to_use = 1:10,
  genes_to_use = NULL,
  expression_values = c("normalized", "scaled", "custom"),
  name = "sNN.pca",
  return_gobject = TRUE,
  k = 30,
  minimum_shared = 5,
  top_shared = 3,
  verbose = T,
  ...
)
```

Arguments

<code>gobject</code>	giotto object
<code>type</code>	sNN or kNN
<code>dim_reduction_to_use</code>	dimension reduction method to use
<code>dim_reduction_name</code>	name of dimension reduction set to use
<code>dimensions_to_use</code>	number of dimensions to use as input
<code>genes_to_use</code>	if <code>dim_reduction_to_use = NULL</code> , which genes to use
<code>expression_values</code>	expression values to use
<code>name</code>	arbitrary name for NN network
<code>return_gobject</code>	boolean: return giotto object (default = TRUE)
<code>k</code>	number of k neighbors to use
<code>minimum_shared</code>	minimum shared neighbors
<code>top_shared</code>	keep at ...
<code>verbose</code>	be verbose
<code>...</code>	additional parameters for kNN and sNN functions from dbscan

Details

This function creates a k-nearest neighbour (kNN) or shared nearest neighbour (sNN) network based on the provided dimension reduction space. To run it directly on the gene expression matrix set `dim_reduction_to_use = NULL`.

See also [kNN](#) and [sNN](#) for more information about how the networks are created.

Output for kNN:

- from: `cell_ID` for source cell
- to: `cell_ID` for target cell
- distance: distance between cells
- weight: $\text{weight} = 1/(1 + \text{distance})$

Output for sNN:

- from: `cell_ID` for source cell
- to: `cell_ID` for target cell
- distance: distance between cells
- weight: $1/(1 + \text{distance})$
- shared: number of shared neighbours
- rank: ranking of pairwise cell neighbours

For sNN networks two additional parameters can be set:

- `minimum_shared`: minimum number of shared neighbours needed
- `top_shared`: keep this number of the top shared neighbours, irrespective of `minimum_shared` setting

Value

giotto object with updated NN network

Examples

```
createNearestNetwork(gobject)
```

```
createSpatialEnrich     createSpatialEnrich
```

Description

Function to calculate gene signature enrichment scores per spatial position using a hypergeometric test.

Usage

```
createSpatialEnrich(
  gobject,
  enrich_method = c("PAGE", "rank", "hypergeometric"),
  sign_matrix,
  expression_values = c("normalized", "scaled", "custom"),
  reverse_log_scale = TRUE,
  logbase = 2,
  output_enrichment = c("original", "zscore"),
  name = "PAGE",
  return_gobject = TRUE
)
```

Arguments

<code>gobject</code>	Giotto object
<code>enrich_method</code>	method for gene signature enrichment calculation
<code>sign_matrix</code>	Matrix of signature genes for each cell type / process
<code>expression_values</code>	expression values to use
<code>reverse_log_scale</code>	reverse expression values from log scale
<code>logbase</code>	log base to use if <code>reverse_log_scale = TRUE</code>
<code>output_enrichment</code>	how to return enrichment output
<code>name</code>	to give to spatial enrichment results, default = PAGE
<code>return_gobject</code>	return giotto object

Details

For details see the individual functions:

- PAGE: [PAGEEnrich](#)
- PAGE: [rankEnrich](#)
- PAGE: [hyperGeometricEnrich](#)

Value

Giotto object or enrichment results if return_gobject = FALSE

Examples

```
createSpatialEnrich(gobject)
```

createSpatialGrid	<i>createSpatialGrid</i>
-------------------	--------------------------

Description

Create a spatial grid.

Usage

```
createSpatialGrid(
  gobject,
  sdimx_stepsize = NULL,
  sdimy_stepsize = NULL,
  sdimz_stepsize = NULL,
  minimum_padding = 1,
  name = "spatial_grid",
  return_gobject = TRUE
)
```

Arguments

gobject	giotto object
sdimx_stepsize	stepsize along the x-axis
sdimy_stepsize	stepsize along the y-axis
sdimz_stepsize	stepsize along the z-axis
minimum_padding	minimum padding on the edges
name	name for spatial grid (default = 'spatial_grid')
return_gobject	boolean: return giotto object (default = TRUE)

Details

Creates a spatial grid with defined x, y (and z) dimensions. The dimension units are based on the provided spatial location units.

Value

giotto object with updated spatial grid slot

Examples

```
createSpatialGrid(gobject)
```

createSpatialGrid_2D *createSpatialGrid_2D*

Description

create a spatial grid for 2D spatial data.

Usage

```
createSpatialGrid_2D(  
  gobject,  
  sdimx_stepsize = NULL,  
  sdimy_stepsize = NULL,  
  minimum_padding = 1,  
  name = "spatial_grid",  
  return_gobject = TRUE  
)
```

Arguments

<code>gobject</code>	giotto object
<code>sdimx_stepsize</code>	stepsize along the x-axis
<code>sdimy_stepsize</code>	stepsize along the y-axis
<code>minimum_padding</code>	minimum padding on the edges
<code>name</code>	name for spatial grid (default = 'spatial_grid')
<code>return_gobject</code>	boolean: return giotto object (default = TRUE)

Details

Creates a spatial grid with defined x, y (and z) dimensions. The dimension units are based on the provided spatial location units.

Value

giotto object with updated spatial grid slot

Examples

```
createSpatialGrid_2D(gobject)
```

```
createSpatialGrid_3D    createSpatialGrid_3D
```

Description

Create a spatial grid for 3D spatial data.

Usage

```
createSpatialGrid_3D(
  gobject,
  sdimx_stepsize = NULL,
  sdimy_stepsize = NULL,
  sdimz_stepsize = NULL,
  minimum_padding = 1,
  name = "spatial_grid",
  return_gobject = TRUE
)
```

Arguments

<code>gobject</code>	giotto object
<code>sdimx_stepsize</code>	stepsize along the x-axis
<code>sdimy_stepsize</code>	stepsize along the y-axis
<code>sdimz_stepsize</code>	stepsize along the z-axis
<code>minimum_padding</code>	minimum padding on the edges
<code>name</code>	name for spatial grid (default = 'spatial_grid')
<code>return_gobject</code>	boolean: return giotto object (default = TRUE)

Details

Creates a spatial grid with defined x, y (and z) dimensions. The dimension units are based on the provided spatial location units.

Value

giotto object with updated spatial grid slot

Examples

```
createSpatialGrid_3D(gobject)
```

```
createSpatialNetwork  createSpatialNetwork
```

Description

Create a spatial network based on cell centroid physical distances.

Usage

```
createSpatialNetwork(
  gobject,
  k = 4,
  dimensions = "all",
  maximum_distance = NULL,
  minimum_k = 0,
  name = "spatial_network",
  verbose = F,
  return_gobject = TRUE
)
```

Arguments

<code>gobject</code>	giotto object
<code>k</code>	number of nearest neighbors based on physical distance
<code>dimensions</code>	which spatial dimensions to use (default = all)
<code>maximum_distance</code>	distance cutoff for nearest neighbors to consider
<code>minimum_k</code>	minimum nearest neighbours if <code>maximum_distance</code> != NULL
<code>name</code>	name for spatial network (default = 'spatial_network')
<code>verbose</code>	verbose
<code>return_gobject</code>	boolean: return giotto object (default = TRUE)

Details

Creates a spatial network connecting single-cells based on their physical distance to each other. Number of neighbors can be determined by `k`, maximum distance from each cell with or without setting a minimum `k` for each cell.

dimensions: default = 'all' which takes all possible dimensions. Alternatively you can provide a character vector that specifies the spatial dimensions to use, e.g. `c("sdimx", "sdimy")` or a numerical vector, e.g. `2:3`

maximum_distance: to create a network based on maximum distance only, you also need to set `k` to a very high value, e.g. `k = 100`

Value

giotto object with updated spatial network slot

Examples

```
createSpatialNetwork(gobject)
```

```
create_average_detection_DT
      create_average_detection_DT
```

Description

calculates average gene detection for a cell metadata factor (e.g. cluster)

Usage

```
create_average_detection_DT(
  gobject,
  meta_data_name,
  expression_values = c("normalized", "scaled", "custom"),
  detection_threshold = 0
)
```

Arguments

```
gobject          giotto object
meta_data_name   name of metadata column to use
expression_values
                  which expression values to use
detection_threshold
                  detection threshold to consider a gene detected
```

Value

data.table with average gene expression values for each factor

```
create_average_DT      create_average_DT
```

Description

calculates average gene expression for a cell metadata factor (e.g. cluster)

Usage

```
create_average_DT(
  gobject,
  meta_data_name,
  expression_values = c("normalized", "scaled", "custom")
)
```

Arguments

```
gobject          giotto object
meta_data_name   name of metadata column to use
expression_values
                  which expression values to use
```

Value

data.table with average gene expression values for each factor

```
create_cell_type_random_cell_IDs  
  create_cell_type_random_cell_IDs
```

Description

creates randomized cell ids within a selection of cell types

Usage

```
create_cell_type_random_cell_IDs(  
  gobject,  
  cluster_column = "cell_types",  
  needed_cell_types  
)
```

Arguments

`gobject` giotto object to use

`cluster_column` cluster column with cell type information

`needed_cell_types`
 vector of cell type names for which a random id will be found

Details

Details will follow.

Value

list of randomly sampled cell ids with same cell type composition

Examples

```
create_cell_type_random_cell_IDs(gobject)
```

```
create_cluster_matrix    create_cluster_matrix
```

Description

creates aggregated matrix for a given clustering

Usage

```
create_cluster_matrix(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  cluster_column,
  gene_subset = NULL
)
```

Examples

```
create_cluster_matrix(gobject)
```

```
create_dimObject        create_dimObject
```

Description

Creates an object that stores a dimension reduction output

Usage

```
create_dimObject(
  name = "test",
  reduction_method = NULL,
  coordinates = NULL,
  misc = NULL,
  my_rownames = NULL
)
```

Arguments

name	arbitrary name for object
reduction_method	method used to reduce dimensions
coordinates	accepts the coordinates after dimension reduction
misc	any additional information will be added to this slot

Value

number of distinct colors

decide_cluster_order	<i>decide_cluster_order</i>
----------------------	-----------------------------

Description

creates order for clusters

Usage

```
decide_cluster_order(  
  gobject,  
  expression_values = c("normalized", "scaled", "custom"),  
  genes,  
  cluster_column = NULL,  
  cluster_order = c("size", "correlation", "custom"),  
  cluster_custom_order = NULL,  
  cor_method = "pearson",  
  hclust_method = "ward.D"  
)
```

Arguments

gobject	giotto object
expression_values	expression values to use
genes	genes to use
cluster_column	name of column to use for clusters
cluster_order	method to determine cluster order
cluster_custom_order	custom order for clusters
cor_method	method for correlation
hclust_method	method for hierarchical clustering

Details

Calculates order for clusters.

Value

custom

Examples

```
decide_cluster_order(gobject)
```

detectSpatialCorGenes *detectSpatialCorGenes*

Description

Detect genes that are spatially correlated

Usage

```
detectSpatialCorGenes(
  gobject,
  method = c("grid", "network"),
  expression_values = c("normalized", "scaled", "custom"),
  subset_genes = NULL,
  spatial_network_name = "spatial_network",
  network_smoothing = NULL,
  spatial_grid_name = "spatial_grid",
  min_cells_per_grid = 4,
  cor_method = c("pearson", "kendall", "spearman")
)
```

Arguments

gobject	giotto object
method	method to use for spatial averaging
expression_values	gene expression values to use
subset_genes	subset of genes to use
spatial_network_name	name of spatial network to use
network_smoothing	smoothing factor between 0 and 1 (default: automatic)
spatial_grid_name	name of spatial grid to use
min_cells_per_grid	minimum number of cells to consider a grid
b	smoothing factor between 0 and 1 (default: automatic)

Details

For method = network, it expects a fully connected spatial network. You can make sure to create a fully connected network by setting minimal_k > 0 in the [createSpatialNetwork](#) function.

- 1. grid-averaging: average gene expression values within a predefined spatial grid
- 2. network-averaging: smoothens the gene expression matrix by averaging the expression within one cell by using the neighbours within the predefined spatial network. b is a smoothening factor that defaults to $1 - 1/k$, where k is the median number of k-neighbors in the selected spatial network. Setting b = 0 means no smoothing and b = 1 means no contribution from its own expression.

The spatCorObject can be further explored with showSpatialCorGenes()

Value

returns a spatial correlation object: "spatCorObject"

See Also

[showSpatialCorGenes](#)

Examples

```
detectSpatialCorGenes(gobject)
```

detectSpatialPatterns *detectSpatialPatterns*

Description

Identify spatial patterns through PCA on average expression in a spatial grid.

Usage

```
detectSpatialPatterns(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  spatial_grid_name = "spatial_grid",
  min_cells_per_grid = 4,
  scale_unit = F,
  ncp = 100,
  show_plot = T,
  PC_zscore = 1.5
)
```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	expression values to use
<code>spatial_grid_name</code>	name of spatial grid to use (default = 'spatial_grid')
<code>min_cells_per_grid</code>	minimum number of cells in a grid to be considered
<code>scale_unit</code>	scale features
<code>ncp</code>	number of principal components to calculate
<code>show_plot</code>	show plots
<code>PC_zscore</code>	minimum z-score of variance explained by a PC

Details

Steps to identify spatial patterns:

- 1. average gene expression for cells within a grid, see createSpatialGrid
- 2. perform PCA on the average grid expression profiles
- 3. convert variance of principal components (PCs) to z-scores and select PCs based on a z-score threshold

Value

spatial pattern object 'spatPatObj'

Examples

```
detectSpatialPatterns(gobject)
```

dimCellPlot	<i>dimCellPlot</i>
-------------	--------------------

Description

Visualize cells according to dimension reduction coordinates

Usage

```
dimCellPlot(
  gobject,
  dim_reduction_to_use = "umap",
  dim_reduction_name = "umap",
  dim1_to_use = 1,
  dim2_to_use = 2,
  spat_enr_names = NULL,
  cell_annotation_values,
  show_NN_network = F,
  nn_network_to_use = "sNN",
  network_name = "sNN.pca",
  cell_color_gradient = c("blue", "white", "red"),
  gradient_midpoint = NULL,
  gradient_limits = NULL,
  select_cell_groups = NULL,
  select_cells = NULL,
  show_other_cells = T,
  other_cell_color = "lightgrey",
  other_point_size = 0.5,
  show_cluster_center = F,
  show_center_label = T,
  center_point_size = 4,
  center_point_border_col = "black",
  center_point_border_stroke = 0.1,
  label_size = 4,
  label_fontface = "bold",
```



```

    edge_alpha = NULL,
    point_size = 1,
    point_border_col = "black",
    point_border_stroke = 0.1,
    show_legend = T,
    legend_text = 8,
    axis_text = 8,
    axis_title = 8,
    cow_n_col = 2,
    cow_rel_h = 1,
    cow_rel_w = 1,
    cow_align = "h",
    show_plot = NA,
    return_plot = NA,
    save_plot = NA,
    save_param = list(),
    default_save_name = "dimCellPlot"
)

```

Arguments

<code>gobject</code>	giotto object
<code>dim_reduction_to_use</code>	dimension reduction to use
<code>dim_reduction_name</code>	dimension reduction name
<code>dim1_to_use</code>	dimension to use on x-axis
<code>dim2_to_use</code>	dimension to use on y-axis
<code>spat_enr_names</code>	names of spatial enrichment results to include
<code>cell_annotation_values</code>	numeric cell annotation columns
<code>show_NN_network</code>	show underlying NN network
<code>nn_network_to_use</code>	type of NN network to use (kNN vs sNN)
<code>network_name</code>	name of NN network to use, if <code>show_NN_network = TRUE</code>
<code>cell_color_gradient</code>	vector with 3 colors for numeric data
<code>gradient_midpoint</code>	midpoint for color gradient
<code>gradient_limits</code>	vector with lower and upper limits
<code>select_cell_groups</code>	select subset of cells/clusters based on <code>cell_color</code> parameter
<code>select_cells</code>	select subset of cells based on cell IDs
<code>show_other_cells</code>	display not selected cells
<code>other_cell_color</code>	color of not selected cells

other_point_size	size of not selected cells
show_cluster_center	plot center of selected clusters
show_center_label	plot label of selected clusters
center_point_size	size of center points
label_size	size of labels
label_fontface	font of labels
edge_alpha	column to use for alpha of the edges
point_size	size of point (cell)
point_border_col	color of border around points
point_border_stroke	stroke size of border around points
show_legend	show legend
legend_text	size of legend text
axis_text	size of axis text
axis_title	size of axis title
show_plot	show plot
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function
default_save_name	default save name for saving, don't change, change save_name in save_param
cell_color	color for cells (see details)
color_as_factor	convert color column to factor
cell_color_code	named vector with colors
title	title for plot, defaults to cell_color parameter

Details

Description of parameters. For 3D plots see [dimCellPlot2D](#)

Value

ggplot

Examples

```
dimCellPlot(gobject)
```

dimCellPlot2D

*dimCellPlot2D***Description**

Visualize cells according to dimension reduction coordinates

Usage

```
dimCellPlot2D(
  gobject,
  dim_reduction_to_use = "umap",
  dim_reduction_name = "umap",
  dim1_to_use = 1,
  dim2_to_use = 2,
  spat_enr_names = NULL,
  cell_annotation_values,
  show_NN_network = F,
  nn_network_to_use = "sNN",
  network_name = "sNN.pca",
  cell_color_gradient = c("blue", "white", "red"),
  gradient_midpoint = NULL,
  gradient_limits = NULL,
  select_cell_groups = NULL,
  select_cells = NULL,
  show_other_cells = T,
  other_cell_color = "lightgrey",
  other_point_size = 0.5,
  show_cluster_center = F,
  show_center_label = T,
  center_point_size = 4,
  center_point_border_col = "black",
  center_point_border_stroke = 0.1,
  label_size = 4,
  label_fontface = "bold",
  edge_alpha = NULL,
  point_size = 1,
  point_border_col = "black",
  point_border_stroke = 0.1,
  show_legend = T,
  legend_text = 8,
  axis_text = 8,
  axis_title = 8,
  cow_n_col = 2,
  cow_rel_h = 1,
  cow_rel_w = 1,
  cow_align = "h",
  show_plot = NA,
  return_plot = NA,
  save_plot = NA,
  save_param = list(),
```

```

    default_save_name = "dimCellPlot2D"
)

```

Arguments

```

gobject          giotto object
dim_reduction_to_use
                  dimension reduction to use
dim_reduction_name
                  dimension reduction name
dim1_to_use      dimension to use on x-axis
dim2_to_use      dimension to use on y-axis
spat_enr_names   names of spatial enrichment results to include
cell_annotation_values
                  numeric cell annotation columns
show_NN_network
                  show underlying NN network
nn_network_to_use
                  type of NN network to use (kNN vs sNN)
network_name     name of NN network to use, if show_NN_network = TRUE
cell_color_gradient
                  vector with 3 colors for numeric data
gradient_midpoint
                  midpoint for color gradient
gradient_limits
                  vector with lower and upper limits
select_cell_groups
                  select subset of cells/clusters based on cell_color parameter
select_cells     select subset of cells based on cell IDs
show_other_cells
                  display not selected cells
other_cell_color
                  color of not selected cells
other_point_size
                  size of not selected cells
show_cluster_center
                  plot center of selected clusters
show_center_label
                  plot label of selected clusters
center_point_size
                  size of center points
label_size       size of labels
label_fontface   font of labels
edge_alpha       column to use for alpha of the edges
point_size       size of point (cell)
point_border_col
                  color of border around points

```

point_border_stroke	stroke size of border around points
show_legend	show legend
legend_text	size of legend text
axis_text	size of axis text
axis_title	size of axis title
show_plot	show plot
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function
default_save_name	default save name for saving, don't change, change save_name in save_param
cell_color	color for cells (see details)
color_as_factor	convert color column to factor
cell_color_code	named vector with colors
title	title for plot, defaults to cell_color parameter

Details

Description of parameters. For 3D plots see [dimPlot3D](#)

Value

ggplot

Examples

```
dimCellPlot2D(gobject)
```

dimGenePlot	<i>dimGenePlot</i>
-------------	--------------------

Description

Visualize cells and gene expression according to dimension reduction coordinates

Usage

```
dimGenePlot(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  genes = NULL,
  dim_reduction_to_use = "umap",
  dim_reduction_name = "umap",
  dim1_to_use = 1,
  dim2_to_use = 2,
  show_NN_network = F,
```

```

nn_network_to_use = "sNN",
network_name = "sNN.pca",
network_color = "lightgray",
edge_alpha = NULL,
scale_alpha_with_expression = FALSE,
point_size = 1,
genes_high_color = "red",
genes_mid_color = "white",
genes_low_color = "blue",
point_border_col = "black",
point_border_stroke = 0.1,
midpoint = 0,
cow_n_col = 2,
cow_rel_h = 1,
cow_rel_w = 1,
cow_align = "h",
show_legend = T,
show_plot = NA,
return_plot = NA,
save_plot = NA,
save_param = list(),
default_save_name = "dimGenePlot"
)

```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	gene expression values to use
<code>genes</code>	genes to show
<code>dim_reduction_to_use</code>	dimension reduction to use
<code>dim_reduction_name</code>	dimension reduction name
<code>dim1_to_use</code>	dimension to use on x-axis
<code>dim2_to_use</code>	dimension to use on y-axis
<code>show_NN_network</code>	show underlying NN network
<code>nn_network_to_use</code>	type of NN network to use (kNN vs sNN)
<code>network_name</code>	name of NN network to use, if <code>show_NN_network = TRUE</code>
<code>edge_alpha</code>	column to use for alpha of the edges
<code>scale_alpha_with_expression</code>	scale expression with ggplot alpha parameter
<code>point_size</code>	size of point (cell)
<code>point_border_col</code>	color of border around points
<code>point_border_stroke</code>	stroke size of border around points

midpoint	size of point (cell)
cow_n_col	cowplot param: how many columns
cow_rel_h	cowplot param: relative height
cow_rel_w	cowplot param: relative width
cow_align	cowplot param: how to align
show_legend	show legend
show_plot	show plots
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function
default_save_name	default save name for saving, don't change, change save_name in save_param
...	parameters for cowplot::save_plot()

Details

Description of parameters.

Value

ggplot

See Also

[dimGenePlot3D](#)

Examples

dimGenePlot(gobject)

dimGenePlot2D	<i>dimGenePlot2D</i>
---------------	----------------------

Description

Visualize cells and gene expression according to dimension reduction coordinates

Usage

```
dimGenePlot2D(  
  gobject,  
  expression_values = c("normalized", "scaled", "custom"),  
  genes = NULL,  
  dim_reduction_to_use = "umap",  
  dim_reduction_name = "umap",  
  dim1_to_use = 1,  
  dim2_to_use = 2,  
  show_NN_network = F,  
  nn_network_to_use = "sNN",
```

```

network_name = "sNN.pca",
network_color = "lightgray",
edge_alpha = NULL,
scale_alpha_with_expression = FALSE,
point_size = 1,
genes_high_color = "red",
genes_mid_color = "white",
genes_low_color = "blue",
point_border_col = "black",
point_border_stroke = 0.1,
midpoint = 0,
cow_n_col = 2,
cow_rel_h = 1,
cow_rel_w = 1,
cow_align = "h",
show_legend = T,
show_plot = NA,
return_plot = NA,
save_plot = NA,
save_param = list(),
default_save_name = "dimGenePlot2D"
)

```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	gene expression values to use
<code>genes</code>	genes to show
<code>dim_reduction_to_use</code>	dimension reduction to use
<code>dim_reduction_name</code>	dimension reduction name
<code>dim1_to_use</code>	dimension to use on x-axis
<code>dim2_to_use</code>	dimension to use on y-axis
<code>show_NN_network</code>	show underlying NN network
<code>nn_network_to_use</code>	type of NN network to use (kNN vs sNN)
<code>network_name</code>	name of NN network to use, if <code>show_NN_network = TRUE</code>
<code>edge_alpha</code>	column to use for alpha of the edges
<code>scale_alpha_with_expression</code>	scale expression with ggplot alpha parameter
<code>point_size</code>	size of point (cell)
<code>point_border_col</code>	color of border around points
<code>point_border_stroke</code>	stroke size of border around points
<code>midpoint</code>	size of point (cell)

cow_n_col	cowplot param: how many columns
cow_rel_h	cowplot param: relative height
cow_rel_w	cowplot param: relative width
cow_align	cowplot param: how to align
show_legend	show legend
show_plot	show plots
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function
default_save_name	default save name for saving, don't change, change save_name in save_param
...	parameters for cowplot::save_plot()

Details

Description of parameters.

Value

ggplot

See Also

[dimGenePlot3D](#)

Examples

dimGenePlot2D(gobject)

dimGenePlot3D	<i>dimGenePlot3D</i>
---------------	----------------------

Description

Visualize cells and gene expression according to dimension reduction coordinates

Usage

```
dimGenePlot3D(  
  gobject,  
  expression_values = c("normalized", "scaled", "custom"),  
  genes = NULL,  
  dim_reduction_to_use = "umap",  
  dim_reduction_name = "umap",  
  dim1_to_use = 1,  
  dim2_to_use = 2,  
  dim3_to_use = 3,  
  show_NN_network = F,  
  nn_network_to_use = "sNN",
```

```

network_name = "sNN.pca",
network_color = "lightgray",
cluster_column = NULL,
select_cell_groups = NULL,
select_cells = NULL,
show_other_cells = T,
other_cell_color = "lightgrey",
other_point_size = 1,
edge_alpha = NULL,
point_size = 2,
genes_high_color = NULL,
genes_mid_color = "white",
genes_low_color = "blue",
show_legend = T,
show_plot = NA,
return_plot = NA,
save_plot = NA,
save_param = list(),
default_save_name = "dimGenePlot3D"
)

```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	gene expression values to use
<code>genes</code>	genes to show
<code>dim_reduction_to_use</code>	dimension reduction to use
<code>dim_reduction_name</code>	dimension reduction name
<code>dim1_to_use</code>	dimension to use on x-axis
<code>dim2_to_use</code>	dimension to use on y-axis
<code>dim3_to_use</code>	dimension to use on z-axis
<code>show_NN_network</code>	show underlying NN network
<code>nn_network_to_use</code>	type of NN network to use (kNN vs sNN)
<code>network_name</code>	name of NN network to use, if <code>show_NN_network = TRUE</code>
<code>edge_alpha</code>	column to use for alpha of the edges
<code>point_size</code>	size of point (cell)
<code>show_legend</code>	show legend
<code>show_plot</code>	show plots
<code>return_plot</code>	return ggplot object
<code>save_plot</code>	directly save the plot [boolean]
<code>save_param</code>	list of saving parameters from all_plots_save_function
<code>default_save_name</code>	default save name for saving, don't change, change <code>save_name</code> in <code>save_param</code>
<code>...</code>	parameters for <code>cowplot::save_plot()</code>

Details

Description of parameters.

Value

ggplot

Examples

```
dimGenePlot3D(gobject)
```

dimPlot	<i>dimPlot</i>
---------	----------------

Description

Visualize cells according to dimension reduction coordinates

Usage

```
dimPlot(
  gobject,
  group_by = NULL,
  group_by_subset = NULL,
  dim_reduction_to_use = "umap",
  dim_reduction_name = "umap",
  dim1_to_use = 1,
  dim2_to_use = 2,
  spat_enr_names = NULL,
  show_NN_network = F,
  nn_network_to_use = "sNN",
  network_name = "sNN.pca",
  cell_color = NULL,
  color_as_factor = T,
  cell_color_code = NULL,
  cell_color_gradient = c("blue", "white", "red"),
  gradient_midpoint = NULL,
  gradient_limits = NULL,
  select_cell_groups = NULL,
  select_cells = NULL,
  show_other_cells = T,
  other_cell_color = "lightgrey",
  other_point_size = 0.5,
  show_cluster_center = F,
  show_center_label = T,
  center_point_size = 4,
  center_point_border_col = "black",
  center_point_border_stroke = 0.1,
  label_size = 4,
  label_fontface = "bold",
  edge_alpha = NULL,
```

```

point_size = 1,
point_border_col = "black",
point_border_stroke = 0.1,
show_legend = T,
legend_text = 8,
axis_text = 8,
axis_title = 8,
title = NULL,
cow_n_col = 2,
cow_rel_h = 1,
cow_rel_w = 1,
cow_align = "h",
show_plot = NA,
return_plot = NA,
save_plot = NA,
save_param = list(),
default_save_name = "dimPlot"
)

```

Arguments

<code>gobject</code>	giotto object
<code>group_by_subset</code>	subset the <code>group_by</code> factor column
<code>dim_reduction_to_use</code>	dimension reduction to use
<code>dim_reduction_name</code>	dimension reduction name
<code>dim1_to_use</code>	dimension to use on x-axis
<code>dim2_to_use</code>	dimension to use on y-axis
<code>spat_enr_names</code>	names of spatial enrichment results to include
<code>show_NN_network</code>	show underlying NN network
<code>nn_network_to_use</code>	type of NN network to use (kNN vs sNN)
<code>network_name</code>	name of NN network to use, if <code>show_NN_network = TRUE</code>
<code>cell_color</code>	color for cells (see details)
<code>color_as_factor</code>	convert color column to factor
<code>cell_color_code</code>	named vector with colors
<code>cell_color_gradient</code>	vector with 3 colors for numeric data
<code>gradient_midpoint</code>	midpoint for color gradient
<code>gradient_limits</code>	vector with lower and upper limits
<code>select_cell_groups</code>	select subset of cells/clusters based on <code>cell_color</code> parameter

select_cells	select subset of cells based on cell IDs
show_other_cells	display not selected cells
other_cell_color	color of not selected cells
other_point_size	size of not selected cells
show_cluster_center	plot center of selected clusters
show_center_label	plot label of selected clusters
center_point_size	size of center points
label_size	size of labels
label_fontface	font of labels
edge_alpha	column to use for alpha of the edges
point_size	size of point (cell)
point_border_col	color of border around points
point_border_stroke	stroke size of border around points
show_legend	show legend
legend_text	size of legend text
axis_text	size of axis text
axis_title	size of axis title
title	title for plot, defaults to cell_color parameter
cow_n_col	cowplot param: how many columns
cow_rel_h	cowplot param: relative height
cow_rel_w	cowplot param: relative width
cow_align	cowplot param: how to align
show_plot	show plot
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function
default_save_name	default save name for saving, don't change, change save_name in save_param
groub_by	create multiple plots based on cell annotation column

Details

Description of parameters, see [dimPlot2D](#). For 3D plots see [dimPlot3D](#)

Value

ggplot

Examples

```
dimPlot(gobject)
```

dimPlot2D

dimPlot2D

Description

Visualize cells according to dimension reduction coordinates

Usage

```
dimPlot2D(
  gobject,
  group_by = NULL,
  group_by_subset = NULL,
  dim_reduction_to_use = "umap",
  dim_reduction_name = "umap",
  dim1_to_use = 1,
  dim2_to_use = 2,
  spat_enr_names = NULL,
  show_NN_network = F,
  nn_network_to_use = "sNN",
  network_name = "sNN.pca",
  cell_color = NULL,
  color_as_factor = T,
  cell_color_code = NULL,
  cell_color_gradient = c("blue", "white", "red"),
  gradient_midpoint = NULL,
  gradient_limits = NULL,
  select_cell_groups = NULL,
  select_cells = NULL,
  show_other_cells = T,
  other_cell_color = "lightgrey",
  other_point_size = 0.5,
  show_cluster_center = F,
  show_center_label = T,
  center_point_size = 4,
  center_point_border_col = "black",
  center_point_border_stroke = 0.1,
  label_size = 4,
  label_fontface = "bold",
  edge_alpha = NULL,
  point_size = 1,
  point_border_col = "black",
  point_border_stroke = 0.1,
  title = NULL,
  show_legend = T,
  legend_text = 8,
  axis_text = 8,
  axis_title = 8,
  cow_n_col = 2,
  cow_rel_h = 1,
  cow_rel_w = 1,
```

```

    cow_align = "h",
    show_plot = NA,
    return_plot = NA,
    save_plot = NA,
    save_param = list(),
    default_save_name = "dimPlot2D"
)

```

Arguments

<code>gobject</code>	giotto object
<code>group_by_subset</code>	subset the <code>group_by</code> factor column
<code>dim_reduction_to_use</code>	dimension reduction to use
<code>dim_reduction_name</code>	dimension reduction name
<code>dim1_to_use</code>	dimension to use on x-axis
<code>dim2_to_use</code>	dimension to use on y-axis
<code>spat_enr_names</code>	names of spatial enrichment results to include
<code>show_NN_network</code>	show underlying NN network
<code>nn_network_to_use</code>	type of NN network to use (kNN vs sNN)
<code>network_name</code>	name of NN network to use, if <code>show_NN_network = TRUE</code>
<code>cell_color</code>	color for cells (see details)
<code>color_as_factor</code>	convert color column to factor
<code>cell_color_code</code>	named vector with colors
<code>cell_color_gradient</code>	vector with 3 colors for numeric data
<code>gradient_midpoint</code>	midpoint for color gradient
<code>gradient_limits</code>	vector with lower and upper limits
<code>select_cell_groups</code>	select subset of cells/clusters based on <code>cell_color</code> parameter
<code>select_cells</code>	select subset of cells based on cell IDs
<code>show_other_cells</code>	display not selected cells
<code>other_cell_color</code>	color of not selected cells
<code>other_point_size</code>	size of not selected cells
<code>show_cluster_center</code>	plot center of selected clusters
<code>show_center_label</code>	plot label of selected clusters

center_point_size	size of center points
label_size	size of labels
label_fontface	font of labels
edge_alpha	column to use for alpha of the edges
point_size	size of point (cell)
point_border_col	color of border around points
point_border_stroke	stroke size of border around points
title	title for plot, defaults to cell_color parameter
show_legend	show legend
legend_text	size of legend text
axis_text	size of axis text
axis_title	size of axis title
cow_n_col	cowplot param: how many columns
cow_rel_h	cowplot param: relative height
cow_rel_w	cowplot param: relative width
cow_align	cowplot param: how to align
show_plot	show plot
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function
default_save_name	default save name for saving, don't change, change save_name in save_param
groub_by	create multiple plots based on cell annotation column

Details

Description of parameters. For 3D plots see [dimPlot3D](#)

Value

ggplot

Examples

```
dimPlot2D(gobject)
```

dimPlot2D_single	<i>dimPlot2D_single</i>
------------------	-------------------------

Description

Visualize cells according to dimension reduction coordinates

Usage

```
dimPlot2D_single(
  gobject,
  dim_reduction_to_use = "umap",
  dim_reduction_name = "umap",
  dim1_to_use = 1,
  dim2_to_use = 2,
  spat_enr_names = NULL,
  show_NN_network = F,
  nn_network_to_use = "sNN",
  network_name = "sNN.pca",
  cell_color = NULL,
  color_as_factor = T,
  cell_color_code = NULL,
  cell_color_gradient = c("blue", "white", "red"),
  gradient_midpoint = NULL,
  gradient_limits = NULL,
  select_cell_groups = NULL,
  select_cells = NULL,
  show_other_cells = T,
  other_cell_color = "lightgrey",
  other_point_size = 0.5,
  show_cluster_center = F,
  show_center_label = T,
  center_point_size = 4,
  center_point_border_col = "black",
  center_point_border_stroke = 0.1,
  label_size = 4,
  label_fontface = "bold",
  edge_alpha = NULL,
  point_size = 1,
  point_border_col = "black",
  point_border_stroke = 0.1,
  title = NULL,
  show_legend = T,
  legend_text = 8,
  axis_text = 8,
  axis_title = 8,
  show_plot = NA,
  return_plot = NA,
  save_plot = NA,
  save_param = list(),
  default_save_name = "dimPlot2D_single"
```

)

Arguments

<code>gobject</code>	giotto object
<code>dim_reduction_to_use</code>	dimension reduction to use
<code>dim_reduction_name</code>	dimension reduction name
<code>dim1_to_use</code>	dimension to use on x-axis
<code>dim2_to_use</code>	dimension to use on y-axis
<code>spat_enr_names</code>	names of spatial enrichment results to include
<code>show_NN_network</code>	show underlying NN network
<code>nn_network_to_use</code>	type of NN network to use (kNN vs sNN)
<code>network_name</code>	name of NN network to use, if <code>show_NN_network = TRUE</code>
<code>cell_color</code>	color for cells (see details)
<code>color_as_factor</code>	convert color column to factor
<code>cell_color_code</code>	named vector with colors
<code>cell_color_gradient</code>	vector with 3 colors for numeric data
<code>gradient_midpoint</code>	midpoint for color gradient
<code>gradient_limits</code>	vector with lower and upper limits
<code>select_cell_groups</code>	select subset of cells/clusters based on <code>cell_color</code> parameter
<code>select_cells</code>	select subset of cells based on cell IDs
<code>show_other_cells</code>	display not selected cells
<code>other_cell_color</code>	color of not selected cells
<code>other_point_size</code>	size of not selected cells
<code>show_cluster_center</code>	plot center of selected clusters
<code>show_center_label</code>	plot label of selected clusters
<code>center_point_size</code>	size of center points
<code>label_size</code>	size of labels
<code>label_fontface</code>	font of labels
<code>edge_alpha</code>	column to use for alpha of the edges
<code>point_size</code>	size of point (cell)

point_border_col	color of border around points
point_border_stroke	stroke size of border around points
title	title for plot, defaults to cell_color parameter
show_legend	show legend
legend_text	size of legend text
axis_text	size of axis text
axis_title	size of axis title
show_plot	show plot
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function
default_save_name	default save name for saving, don't change, change save_name in save_param

Details

Description of parameters. For 3D plots see [dimPlot3D](#)

Value

ggplot

Examples

```
dimPlot2D_single(gobject)
```

dimPlot3D	<i>dimPlot3D</i>
-----------	------------------

Description

Visualize cells according to dimension reduction coordinates

Usage

```
dimPlot3D(
  gobject,
  dim_reduction_to_use = "umap",
  dim_reduction_name = "umap",
  dim1_to_use = 1,
  dim2_to_use = 2,
  dim3_to_use = 3,
  select_cell_groups = NULL,
  select_cells = NULL,
  show_other_cells = T,
  other_cell_color = "lightgrey",
  other_point_size = 2,
```

```

show_NN_network = F,
nn_network_to_use = "sNN",
network_name = "sNN.pca",
color_as_factor = T,
cell_color = NULL,
cell_color_code = NULL,
show_cluster_center = F,
show_center_label = T,
center_point_size = 4,
label_size = 4,
edge_alpha = NULL,
point_size = 3,
show_plot = NA,
return_plot = NA,
save_plot = NA,
save_param = list(),
default_save_name = "dim3D"
)

```

Arguments

<code>gobject</code>	giotto object
<code>dim_reduction_to_use</code>	dimension reduction to use
<code>dim_reduction_name</code>	dimension reduction name
<code>dim1_to_use</code>	dimension to use on x-axis
<code>dim2_to_use</code>	dimension to use on y-axis
<code>dim3_to_use</code>	dimension to use on z-axis
<code>select_cell_groups</code>	select subset of cells/clusters based on <code>cell_color</code> parameter
<code>select_cells</code>	select subset of cells based on cell IDs
<code>show_other_cells</code>	display not selected cells
<code>other_cell_color</code>	color of not selected cells
<code>other_point_size</code>	size of not selected cells
<code>show_NN_network</code>	show underlying NN network
<code>nn_network_to_use</code>	type of NN network to use (kNN vs sNN)
<code>network_name</code>	name of NN network to use, if <code>show_NN_network = TRUE</code>
<code>color_as_factor</code>	convert color column to factor
<code>cell_color</code>	color for cells (see details)
<code>cell_color_code</code>	named vector with colors
<code>show_cluster_center</code>	plot center of selected clusters

show_center_label	plot label of selected clusters
center_point_size	size of center points
label_size	size of labels
edge_alpha	column to use for alpha of the edges
point_size	size of point (cell)
show_plot	show plot
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function
default_save_name	default save name for saving, don't change, change save_name in save_param
show_legend	show legend

Details

Description of parameters.

Value

plotly

Examples

```
dimPlot3D(gobject)
```

direction_test_CPG	<i>direction_test_CPG</i>
--------------------	---------------------------

Description

shows direction of change

Usage

```
direction_test(x, min_fdr = 0.05)
```

Examples

```
direction_test_CPG()
```

doHclust

*doHclust***Description**

cluster cells using hierarchical clustering algorithm

Usage

```
doHclust(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  genes_to_use = NULL,
  dim_reduction_to_use = c("cells", "pca", "umap", "tsne"),
  dim_reduction_name = "pca",
  dimensions_to_use = 1:10,
  distance_method = c("pearson", "spearman", "original", "euclidean", "maximum",
    "manhattan", "canberra", "binary", "minkowski"),
  agglomeration_method = c("ward.D2", "ward.D", "single", "complete", "average",
    "mcquitty", "median", "centroid"),
  k = 10,
  h = NULL,
  name = "hclust",
  return_gobject = TRUE,
  set_seed = T,
  seed_number = 1234
)
```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	expression values to use
<code>genes_to_use</code>	subset of genes to use
<code>dim_reduction_to_use</code>	dimension reduction to use
<code>dim_reduction_name</code>	dimensions reduction name
<code>dimensions_to_use</code>	dimensions to use
<code>distance_method</code>	distance method
<code>agglomeration_method</code>	agglomeration method for hclust
<code>k</code>	number of final clusters
<code>h</code>	cut hierarchical tree at height = h
<code>name</code>	name for hierarchical clustering
<code>return_gobject</code>	boolean: return giotto object (default = TRUE)
<code>set_seed</code>	set seed
<code>seed_number</code>	number for seed

Details

Description on how to use Kmeans clustering method.

Value

giotto object with new clusters appended to cell metadata

See Also

[hclust](#)

Examples

```
doHclust(gobject)
```

doHMRF	<i>doHMRF</i>
--------	---------------

Description

Run HMRF

Usage

```
doHMRF(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  spatial_network_name = "spatial_network",
  spatial_genes = NULL,
  spatial_dimensions = c("sdimx", "sdimy", "sdimz"),
  dim_reduction_to_use = NULL,
  dim_reduction_name = "pca",
  dimensions_to_use = 1:10,
  name = "test",
  k = 10,
  betas = c(0, 2, 50),
  tolerance = 1e-10,
  zscore = c("none", "rowcol", "colrow"),
  numinit = 100,
  python_path = NULL,
  output_folder = NULL,
  overwrite_output = TRUE
)
```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	expression values to use
<code>spatial_network_name</code>	name of spatial network to use for HMRF

spatial_genes spatial genes to use for HMRF
spatial_dimensions select spatial dimensions to use, default is all possible dimensions
dim_reduction_to_use use another dimension reduction set as input
dim_reduction_name name of dimension reduction set to use
dimensions_to_use number of dimensions to use as input
name name of HMRF run
k number of HMRF domains
betas betas to test for
tolerance tolerance
zscore zscore
numinit number of initializations
python_path python path to use
output_folder output folder to save results
overwrite_output overwrite output folder

Details

Description of HMRF parameters ...

Value

Creates a directory with results that can be viewed with viewHMRResults

Examples

doHMRF(gobject)

doKmeans	<i>doKmeans</i>
----------	-----------------

Description

cluster cells using kmeans algorithm

Usage

```
doKmeans(  
  gobject,  
  expression_values = c("normalized", "scaled", "custom"),  
  genes_to_use = NULL,  
  dim_reduction_to_use = c("cells", "pca", "umap", "tsne"),  
  dim_reduction_name = "pca",  
  dimensions_to_use = 1:10,  
  distance_method = c("original", "pearson", "spearman", "euclidean", "maximum",
```



```

    "manhattan", "canberra", "binary", "minkowski"),
    centers = 10,
    iter_max = 100,
    nstart = 1000,
    algorithm = "Hartigan-Wong",
    name = "kmeans",
    return_gobject = TRUE,
    set_seed = T,
    seed_number = 1234
)

```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	expression values to use
<code>genes_to_use</code>	subset of genes to use
<code>dim_reduction_to_use</code>	dimension reduction to use
<code>dim_reduction_name</code>	dimensions reduction name
<code>dimensions_to_use</code>	dimensions to use
<code>distance_method</code>	distance method
<code>centers</code>	number of final clusters
<code>iter_max</code>	kmeans maximum iterations
<code>nstart</code>	kmeans nstart
<code>algorithm</code>	kmeans algorithm
<code>name</code>	name for kmeans clustering
<code>return_gobject</code>	boolean: return giotto object (default = TRUE)
<code>set_seed</code>	set seed
<code>seed_number</code>	number for seed

Details

Description on how to use Kmeans clustering method.

Value

giotto object with new clusters appended to cell metadata

See Also

[kmeans](#)

Examples

```
doKmeans(gobject)
```

doLeidenCluster

*doLeidenCluster***Description**

cluster cells using a NN-network and the Leiden community detection algorithm

Usage

```
doLeidenCluster(
  gobject,
  name = "leiden_clus",
  nn_network_to_use = "sNN",
  network_name = "sNN.pca",
  python_path = NULL,
  resolution = 1,
  weight_col = "weight",
  partition_type = c("RBConfigurationVertexPartition", "ModularityVertexPartition"),
  init_membership = NULL,
  n_iterations = 1000,
  return_gobject = TRUE,
  set_seed = T,
  seed_number = 1234,
  ...
)
```

Arguments

<code>gobject</code>	giotto object
<code>name</code>	name for cluster
<code>nn_network_to_use</code>	type of NN network to use (kNN vs sNN)
<code>network_name</code>	name of NN network to use
<code>python_path</code>	specify specific path to python if required
<code>resolution</code>	resolution
<code>weight_col</code>	weight column to use for edges
<code>partition_type</code>	The type of partition to use for optimisation.
<code>init_membership</code>	initial membership of cells for the partition
<code>n_iterations</code>	number of iterations to run the Leiden algorithm. If the number of iterations is negative, the Leiden algorithm is run until an iteration in which there was no improvement.
<code>return_gobject</code>	boolean: return giotto object (default = TRUE)
<code>set_seed</code>	set seed
<code>seed_number</code>	number for seed

Details

This function is a wrapper for the Leiden algorithm implemented in python, which can detect communities in graphs of millions of nodes (cells), as long as they can fit in memory. See the <https://github.com/vtraag/leidenalg> github page or the <https://leidenalg.readthedocs.io/en/stable/index.html> readthedocs page for more information.

Partition types available and information:

- **RBConfigurationVertexPartition**: Implements Reichardt and Bornholdt's Potts model with a configuration null model. This quality function is well-defined only for positive edge weights. This quality function uses a linear resolution parameter.
- **ModularityVertexPartition**: Implements modularity. This quality function is well-defined only for positive edge weights. It does *not* use the resolution parameter

Set `weight_col = NULL` to give equal weight (=1) to each edge.

Value

giotto object with new clusters appended to cell metadata

Examples

```
doLeidenCluster(gobject)
```

doLeidenSubCluster	<i>doLeidenSubCluster</i>
--------------------	---------------------------

Description

Further subcluster cells using a NN-network and the Leiden algorithm

Usage

```
doLeidenSubCluster(
  gobject,
  name = "sub_pleiden_clus",
  cluster_column = NULL,
  selected_clusters = NULL,
  hvg_param = list(reverse_log_scale = T, difference_in_variance = 1, expression_values
    = "normalized"),
  hvg_min_perc_cells = 5,
  hvg_mean_expr_det = 1,
  use_all_genes_as_hvg = FALSE,
  min_nr_of_hvg = 5,
  pca_param = list(expression_values = "normalized", scale_unit = T),
  nn_param = list(dimensions_to_use = 1:20),
  k_neighbors = 10,
  resolution = 0.5,
  n_iterations = 500,
  python_path = NULL,
  nn_network_to_use = "sNN",
  network_name = "sNN.pca",
```

```

    return_gobject = TRUE,
    verbose = T
)

```

Arguments

<code>gobject</code>	giotto object
<code>name</code>	name for new clustering result
<code>cluster_column</code>	cluster column to subcluster
<code>selected_clusters</code>	only do subclustering on these clusters
<code>hvg_param</code>	parameters for calculateHVG
<code>hvg_min_perc_cells</code>	threshold for detection in min percentage of cells
<code>hvg_mean_expr_det</code>	threshold for mean expression level in cells with detection
<code>use_all_genes_as_hvg</code>	forces all genes to be HVG and to be used as input for PCA
<code>min_nr_of_hvg</code>	minimum number of HVG, or all genes will be used as input for PCA
<code>pca_param</code>	parameters for runPCA
<code>nn_param</code>	parameters for parameters for createNearestNetwork
<code>k_neighbors</code>	number of k for createNearestNetwork
<code>resolution</code>	resolution of Leiden clustering
<code>n_iterations</code>	number of iterations to run the Leiden algorithm.
<code>python_path</code>	specify specific path to python if required
<code>nn_network_to_use</code>	type of NN network to use (kNN vs sNN)
<code>network_name</code>	name of NN network to use
<code>return_gobject</code>	boolean: return giotto object (default = TRUE)
<code>verbose</code>	verbose

Details

This function performs subclustering using the Leiden algorithm on selected clusters. The systematic steps are:

- 1. subset Giotto object
- 2. identify highly variable genes
- 3. run PCA
- 4. create nearest neighbouring network
- 5. do Leiden clustering

Value

giotto object with new subclusters appended to cell metadata

See Also[doLeidenCluster](#)**Examples**

```
doLeidenSubCluster(gobject)
```

doLouvainCluster	<i>doLouvainCluster</i>
------------------	-------------------------

Description

cluster cells using a NN-network and the Louvain algorithm.

Usage

```
doLouvainCluster(
  gobject,
  version = c("community", "multinet"),
  name = "louvain_clus",
  nn_network_to_use = "sNN",
  network_name = "sNN.pca",
  python_path = NULL,
  resolution = 1,
  weight_col = NULL,
  gamma = 1,
  omega = 1,
  louv_random = F,
  return_gobject = TRUE,
  set_seed = F,
  seed_number = 1234,
  ...
)
```

Arguments

gobject	giotto object
version	implemented version of Louvain clustering to use
name	name for cluster
nn_network_to_use	type of NN network to use (kNN vs sNN)
network_name	name of NN network to use
python_path	[community] specify specific path to python if required
resolution	[community] resolution
gamma	[multinet] Resolution parameter for modularity in the generalized louvain method.
omega	[multinet] Inter-layer weight parameter in the generalized louvain method.
return_gobject	boolean: return giotto object (default = TRUE)
set_seed	set seed
seed_number	number for seed

Details

Louvain clustering using the community or multinet implementation of the louvain clustering algorithm.

Value

giotto object with new clusters appended to cell metadata

See Also

[doLouvainCluster_community](#) and [doLouvainCluster_multinet](#)

Examples

```
doLouvainCluster(gobject)
```

```
doLouvainCluster_community
doLouvainCluster_community
```

Description

cluster cells using a NN-network and the Louvain algorithm from the community module in Python

Usage

```
doLouvainCluster_community(
    gobject,
    name = "louvain_clus",
    nn_network_to_use = "sNN",
    network_name = "sNN.pca",
    python_path = NULL,
    resolution = 1,
    weight_col = NULL,
    louv_random = F,
    return_gobject = TRUE,
    set_seed = F,
    seed_number = 1234,
    ...
)
```

Arguments

gobject	giotto object
name	name for cluster
nn_network_to_use	type of NN network to use (kNN vs sNN)
network_name	name of NN network to use
python_path	specify specific path to python if required
resolution	resolution

weight_col	weight column to use for edges
louv_random	Will randomize the node evaluation order and the community evaluation order to get different partitions at each call
return_gobject	boolean: return giotto object (default = TRUE)
set_seed	set seed
seed_number	number for seed

Details

This function is a wrapper for the Louvain algorithm implemented in Python, which can detect communities in graphs of nodes (cells). See the <https://python-louvain.readthedocs.io/en/latest/index.html> readthedocs page for more information.

Set *weight_col* = *NULL* to give equal weight (=1) to each edge.

Value

giotto object with new clusters appended to cell metadata

Examples

```
doLouvainCluster_community(gobject)
```

```
doLouvainCluster_multinet
doLouvainCluster_multinet
```

Description

cluster cells using a NN-network and the Louvain algorithm from the multinet package in R.

Usage

```
doLouvainCluster_multinet(
  gobject,
  name = "louvain_clus",
  nn_network_to_use = "sNN",
  network_name = "sNN.pca",
  gamma = 1,
  omega = 1,
  return_gobject = TRUE,
  set_seed = F,
  seed_number = 1234,
  ...
)
```

Arguments

<code>gobject</code>	giotto object
<code>name</code>	name for cluster
<code>nn_network_to_use</code>	type of NN network to use (kNN vs sNN)
<code>network_name</code>	name of NN network to use
<code>gamma</code>	Resolution parameter for modularity in the generalized louvain method.
<code>omega</code>	Inter-layer weight parameter in the generalized louvain method.
<code>return_gobject</code>	boolean: return giotto object (default = TRUE)
<code>set_seed</code>	set seed
<code>seed_number</code>	number for seed

Details

See [glouvain_ml](#) from the `multinet` package in R for more information.

Value

giotto object with new clusters appended to cell metadata

Examples

```
doLouvainCluster_multinet(gobject)
```

<code>doLouvainSubCluster</code>	<i>doLouvainSubCluster</i>
----------------------------------	----------------------------

Description

subcluster cells using a NN-network and the Louvain algorithm

Usage

```
doLouvainSubCluster(
  gobject,
  name = "sub_louvain_clus",
  version = c("community", "multinet"),
  cluster_column = NULL,
  selected_clusters = NULL,
  hvg_param = list(reverse_log_scale = T, difference_in_variance = 1, expression_values
    = "normalized"),
  hvg_min_perc_cells = 5,
  hvg_mean_expr_det = 1,
  use_all_genes_as_hvg = FALSE,
  min_nr_of_hvg = 5,
  pca_param = list(expression_values = "normalized", scale_unit = T),
  nn_param = list(dimensions_to_use = 1:20),
  k_neighbors = 10,
  resolution = 0.5,
```



```

    gamma = 1,
    omega = 1,
    python_path = NULL,
    nn_network_to_use = "sNN",
    network_name = "sNN.pca",
    return_gobject = TRUE,
    verbose = T
)

```

Arguments

<code>gobject</code>	giotto object
<code>name</code>	name for new clustering result
<code>version</code>	version of Louvain algorithm to use
<code>cluster_column</code>	cluster column to subcluster
<code>selected_clusters</code>	only do subclustering on these clusters
<code>hvg_param</code>	parameters for calculateHVG
<code>hvg_min_perc_cells</code>	threshold for detection in min percentage of cells
<code>hvg_mean_expr_det</code>	threshold for mean expression level in cells with detection
<code>use_all_genes_as_hvg</code>	forces all genes to be HVG and to be used as input for PCA
<code>min_nr_of_hvg</code>	minimum number of HVG, or all genes will be used as input for PCA
<code>pca_param</code>	parameters for runPCA
<code>nn_param</code>	parameters for parameters for createNearestNetwork
<code>k_neighbors</code>	number of k for createNearestNetwork
<code>resolution</code>	resolution for community algorithm
<code>gamma</code>	gamma
<code>omega</code>	omega
<code>python_path</code>	specify specific path to python if required
<code>nn_network_to_use</code>	type of NN network to use (kNN vs sNN)
<code>network_name</code>	name of NN network to use
<code>return_gobject</code>	boolean: return giotto object (default = TRUE)
<code>verbose</code>	verbose

Details

This function performs subclustering using the Louvain algorithm on selected clusters. The systematic steps are:

- 1. subset Giotto object
- 2. identify highly variable genes
- 3. run PCA
- 4. create nearest neighbouring network
- 5. do Louvain clustering

Value

giotto object with new subclusters appended to cell metadata

See Also

[doLouvainCluster_multinet](#) and [doLouvainCluster_community](#)

Examples

```
doLouvainSubCluster(gobject)
```

```
doLouvainSubCluster_community
```

```
doLouvainSubCluster_community
```

Description

subcluster cells using a NN-network and the Louvain community detection algorithm

Usage

```
doLouvainSubCluster_community(  
  gobject,  
  name = "sub_louvain_comm_clus",  
  cluster_column = NULL,  
  selected_clusters = NULL,  
  hvg_param = list(reverse_log_scale = T, difference_in_variance = 1, expression_values  
    = "normalized"),  
  hvg_min_perc_cells = 5,  
  hvg_mean_expr_det = 1,  
  use_all_genes_as_hvg = FALSE,  
  min_nr_of_hvg = 5,  
  pca_param = list(expression_values = "normalized", scale_unit = T),  
  nn_param = list(dimensions_to_use = 1:20),  
  k_neighbors = 10,  
  resolution = 0.5,  
  python_path = NULL,  
  nn_network_to_use = "sNN",  
  network_name = "sNN.pca",  
  return_gobject = TRUE,  
  verbose = T  
)
```

Arguments

<code>gobject</code>	giotto object
<code>name</code>	name for new clustering result
<code>cluster_column</code>	cluster column to subcluster
<code>selected_clusters</code>	only do subclustering on these clusters

hvg_param	parameters for calculateHVG
hvg_min_perc_cells	threshold for detection in min percentage of cells
hvg_mean_expr_det	threshold for mean expression level in cells with detection
use_all_genes_as_hvg	forces all genes to be HVG and to be used as input for PCA
min_nr_of_hvg	minimum number of HVG, or all genes will be used as input for PCA
pca_param	parameters for runPCA
nn_param	parameters for parameters for createNearestNetwork
k_neighbors	number of k for createNearestNetwork
resolution	resolution
python_path	specify specific path to python if required
nn_network_to_use	type of NN network to use (kNN vs sNN)
network_name	name of NN network to use
return_gobject	boolean: return giotto object (default = TRUE)
verbose	verbose

Details

This function performs subclustering using the Louvain community algorithm on selected clusters. The systematic steps are:

- 1. subset Giotto object
- 2. identify highly variable genes
- 3. run PCA
- 4. create nearest neighbouring network
- 5. do Louvain community clustering

Value

giotto object with new subclusters appended to cell metadata

See Also

[doLouvainCluster_community](#)

Examples

```
doLouvainSubCluster_community(gobject)
```

```
doLouvainSubCluster_multinet
      doLouvainSubCluster_multinet
```

Description

subcluster cells using a NN-network and the Louvain multinet detection algorithm

Usage

```
doLouvainSubCluster_multinet(
  gobject,
  name = "sub_louvain_mult_clus",
  cluster_column = NULL,
  selected_clusters = NULL,
  hvg_param = list(reverse_log_scale = T, difference_in_variance = 1, expression_values
    = "normalized"),
  hvg_min_perc_cells = 5,
  hvg_mean_expr_det = 1,
  use_all_genes_as_hvg = FALSE,
  min_nr_of_hvg = 5,
  pca_param = list(expression_values = "normalized", scale_unit = T),
  nn_param = list(dimensions_to_use = 1:20),
  k_neighbors = 10,
  gamma = 1,
  omega = 1,
  nn_network_to_use = "sNN",
  network_name = "sNN.pca",
  return_gobject = TRUE,
  verbose = T
)
```

Arguments

<code>gobject</code>	giotto object
<code>name</code>	name for new clustering result
<code>cluster_column</code>	cluster column to subcluster
<code>selected_clusters</code>	only do subclustering on these clusters
<code>hvg_param</code>	parameters for calculateHVG
<code>hvg_min_perc_cells</code>	threshold for detection in min percentage of cells
<code>hvg_mean_expr_det</code>	threshold for mean expression level in cells with detection
<code>use_all_genes_as_hvg</code>	forces all genes to be HVG and to be used as input for PCA
<code>min_nr_of_hvg</code>	minimum number of HVG, or all genes will be used as input for PCA
<code>pca_param</code>	parameters for runPCA

nn_param	parameters for parameters for createNearestNetwork
k_neighbors	number of k for createNearestNetwork
gamma	gamma
omega	omega
nn_network_to_use	type of NN network to use (kNN vs sNN)
network_name	name of NN network to use
return_gobject	boolean: return giotto object (default = TRUE)
verbose	verbose
python_path	specify specific path to python if required

Details

This function performs subclustering using the Louvain multinet algorithm on selected clusters. The systematic steps are:

- 1. subset Giotto object
- 2. identify highly variable genes
- 3. run PCA
- 4. create nearest neighbouring network
- 5. do Louvain multinet clustering

Value

giotto object with new subclusters appended to cell metadata

See Also

[doLouvainCluster_multinet](#)

Examples

```
doLouvainSubCluster_multinet(gobject)
```

doRandomWalkCluster *doRandomWalkCluster*

Description

Cluster cells using a random walk approach.

Usage

```
doRandomWalkCluster(
  gobject,
  name = "random_walk_clus",
  nn_network_to_use = "sNN",
  network_name = "sNN.pca",
  walk_steps = 4,
  walk_clusters = 10,
  walk_weights = NA,
  return_gobject = TRUE,
  set_seed = F,
  seed_number = 1234,
  ...
)
```

Arguments

<code>gobject</code>	giotto object
<code>name</code>	name for cluster
<code>nn_network_to_use</code>	type of NN network to use (kNN vs sNN)
<code>network_name</code>	name of NN network to use
<code>walk_steps</code>	number of walking steps
<code>walk_clusters</code>	number of final clusters
<code>walk_weights</code>	cluster column defining the walk weights
<code>return_gobject</code>	boolean: return giotto object (default = TRUE)
<code>set_seed</code>	set seed
<code>seed_number</code>	number for seed

Details

See [cluster_walktrap](#) function from the `igraph` package in R for more information.

Value

giotto object with new clusters appended to cell metadata

Examples

```
doRandomWalkCluster(gobject)
```

doSNNCluster

*doSNNCluster***Description**

Cluster cells using a SNN cluster approach.

Usage

```
doSNNCluster(
  gobject,
  name = "sNN_clus",
  nn_network_to_use = "kNN",
  network_name = "kNN.pca",
  k = 20,
  eps = 4,
  minPts = 16,
  borderPoints = TRUE,
  return_gobject = TRUE,
  set_seed = F,
  seed_number = 1234,
  ...
)
```

Arguments

<code>gobject</code>	giotto object
<code>name</code>	name for cluster
<code>nn_network_to_use</code>	type of NN network to use (only works on kNN)
<code>network_name</code>	name of kNN network to use
<code>k</code>	Neighborhood size for nearest neighbor sparsification to create the shared NN graph.
<code>eps</code>	Two objects are only reachable from each other if they share at least <code>eps</code> nearest neighbors.
<code>minPts</code>	minimum number of points that share at least <code>eps</code> nearest neighbors for a point to be considered a core points.
<code>borderPoints</code>	should borderPoints be assigned to clusters like in DBSCAN?
<code>return_gobject</code>	boolean: return giotto object (default = TRUE)
<code>set_seed</code>	set seed
<code>seed_number</code>	number for seed

Details

See [sNNclust](#) from dbscan package

Value

giotto object with new clusters appended to cell metadata

Examples

```
doSNNCluster(gobject)
```

```
do_spatial_grid_averaging
      do_spatial_grid_averaging
```

Description

smooth gene expression over a defined spatial grid

Usage

```
do_spatial_grid_averaging(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  subset_genes = NULL,
  spatial_grid_name = "spatial_grid",
  min_cells_per_grid = 4
)
```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	gene expression values to use
<code>subset_genes</code>	subset of genes to use
<code>spatial_grid_name</code>	name of spatial grid to use
<code>min_cells_per_grid</code>	minimum number of cells to consider a grid

Value

matrix with smoothened gene expression values based on spatial grid

Examples

```
do_spatial_grid_averaging(gobject)
```

```
do_spatial_knn_smoothing
do_spatial_knn_smoothing
```

Description

smooth gene expression over a kNN spatial network

Usage

```
do_spatial_knn_smoothing(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  subset_genes = NULL,
  spatial_network_name = "spatial_network",
  b = NULL
)
```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	gene expression values to use
<code>subset_genes</code>	subset of genes to use
<code>spatial_network_name</code>	name of spatial network to use
<code>b</code>	smoothing factor between 0 and 1 (default: automatic)

Details

This function will smoothen the gene expression values per cell according to its neighbors in the selected spatial network.

`b` is a smoothening factor that defaults to $1 - 1/k$, where `k` is the median number of `k`-neighbors in the selected spatial network. Setting `b = 0` means no smoothing and `b = 1` means no contribution from its own expression.

Value

matrix with smoothened gene expression values based on kNN spatial network

Examples

```
do_spatial_knn_smoothing(gobject)
```

dt_to_matrix	<i>dt_to_matrix</i>
--------------	---------------------

Description

converts data.table to matrix

Usage

```
dt_to_matrix(x)
```

Examples

```
dt_to_matrix(x)
```

exportGiottoViewer	<i>exportGiottoViewer</i>
--------------------	---------------------------

Description

compute highly variable genes

Usage

```
exportGiottoViewer(
  gobject,
  output_directory = NULL,
  spat_enr_names = NULL,
  factor_annotations,
  numeric_annotations,
  dim_reductions,
  dim_reduction_names,
  expression_values = c("scaled", "normalized", "custom"),
  dim_red_rounding = NULL,
  dim_red_rescale = c(-20, 20),
  expression_rounding = 2,
  overwrite_dir = T,
  verbose = T
)
```

Arguments

gobject	giotto object
output_directory	directory where to save the files
spat_enr_names	spatial enrichment results to include for annotations
factor_annotations	giotto cell annotations to view as factor

```

numeric_annotations      giotto cell annotations to view as numeric
dim_reductions           high level dimension reductions to view
dim_reduction_names      specific dimension reduction names
expression_values        expression values to use in Viewer
dim_red_rounding         numerical indicating how to round the coordinates
dim_red_rescale          numerals to rescale the coordinates
expression_rounding      numerical indicating how to round the expression data
overwrite_dir            overwrite files in the directory if it already existed
verbose                 be verbose

```

Details

Giotto Viewer expects the results from Giotto Analyzer in a specific format, which is provided by this function. To include enrichment results from [createSpatialEnrich](#) include the provided spatial enrichment name (default PAGE or rank) and add the gene signature names (.e.g cell types) to the numeric annotations parameter.

Value

writes the necessary output to use in Giotto Viewer

Examples

```
exportGiottoViewer(gobject)
```

```

exprOnlyCellCellcommunicationScores
      exprOnlyCellCellcommunicationScores

```

Description

Cell-Cell communication scores based on expression only

Usage

```

exprOnlyCellCellcommunicationScores(
  gobject,
  cluster_column = "cell_types",
  random_iter = 100,
  gene_set_1,
  gene_set_2,
  log2FC_addendum = 0.1,
  verbose = T
)

```

Arguments

<code>gobject</code>	giotto object to use
<code>cluster_column</code>	cluster column with cell type information
<code>random_iter</code>	number of iterations
<code>gene_set_1</code>	first specific gene set from gene pairs
<code>gene_set_2</code>	second specific gene set from gene pairs
<code>log2FC_addendum</code>	addendum to add when calculating log2FC
<code>verbose</code>	verbose

Details

Statistical framework to identify if pairs of genes (such as ligand-receptor combinations) are expressed at higher levels than expected based on a reshuffled null distribution of gene expression values, without considering the spatial position of cells. More details will follow soon.

Value

Cell-Cell communication scores for gene pairs based on expression only

Examples

```
exprOnlyCellCellcommunicationScores(gobject)
```

<code>extended_gini_fun</code>	<i>extended_gini_fun</i>
--------------------------------	--------------------------

Description

calculate gini coefficient on a minimum length vector

Usage

```
extended_gini_fun(x, weights = rep(1, length = length(x)), minimum_length = 16)
```

Value

gini coefficient

extractNearestNetwork	<i>extractNearestNetwork</i>
-----------------------	------------------------------

Description

Extracts a NN-network from a Giotto object

Usage

```
extractNearestNetwork(  
  gobject,  
  nn_network_to_use = "sNN",  
  network_name = "sNN.pca",  
  output = c("igraph", "data.table")  
)
```

Arguments

gobject	giotto object
nn_network_to_use	kNN or sNN
network_name	name of NN network to be used
output	return a igraph or data.table object

Value

igraph or data.table object

Examples

```
extractNearestNetwork(gobject)
```

fDataDT	<i>fDataDT</i>
---------	----------------

Description

show gene metadata

Usage

```
fDataDT(gobject)
```

Arguments

gobject	giotto object
---------	---------------

Value

data.table with gene metadata

Examples

```
pDataDT(gobject)
```

filterCombinations	<i>filterCombinations</i>
--------------------	---------------------------

Description

Shows how many genes and cells are lost with combinations of thresholds.

Usage

```
filterCombinations(
  gobject,
  expression_values = c("raw", "normalized", "scaled", "custom"),
  expression_thresholds = c(1, 2),
  gene_det_in_min_cells = c(5, 50),
  min_det_genes_per_cell = c(200, 400),
  scale_x_axis = "identity",
  x_axis_offset = 0,
  scale_y_axis = "identity",
  y_axis_offset = 0,
  show_plot = TRUE
)
```

Arguments

gobject	giotto object
expression_values	expression values to use
expression_thresholds	all thresholds to consider a gene expressed
gene_det_in_min_cells	minimum number of cells that should express a gene to consider that gene further
min_det_genes_per_cell	minimum number of expressed genes per cell to consider that cell further
scale_x_axis	ggplot transformation for x-axis (e.g. log2)
x_axis_offset	x-axis offset to be used together with the scaling transformation
scale_y_axis	ggplot transformation for y-axis (e.g. log2)
y_axis_offset	y-axis offset to be used together with the scaling transformation
show_plot	show plot

Details

Creates a scatterplot that visualizes the number of genes and cells that are lost with a specific combination of a gene and cell threshold given an arbitrary cutoff to call a gene expressed. This function can be used to make an informed decision at the filtering step with filterGiotto.

Value

list of data.table and ggplot object

Examples

```
filterCombinations(gobject)
```

filterCPGscores	<i>filterCPGscores</i>
-----------------	------------------------

Description

visualize Cell Proximity Gene enrichment scores

Usage

```
filterCPGscores(
  CPGscore,
  min_cells = 5,
  min_fdr = 0.05,
  min_spat_diff = 0.2,
  min_log2_fc = 0.5,
  keep_int_duplicates = TRUE,
  direction = c("both", "up", "down")
)
```

Arguments

min_cells	min number of cells threshold
min_fdr	false_discovery threshold
min_spat_diff	spatial difference threshold
min_log2_fc	min log2 fold-change
keep_int_duplicates	keep both cell_A-cell_B and cell_B-cell_A
direction	expression changes to keep
method	visualization method

Details

This function filters the output from `getCellProximityGeneScores` based on false-discovery rate, minimum absolute difference, minimum log fold-change and direction of change.

Value

Gene to gene scores in data.table format

Examples

```
filterCPGscores(CPGscore)
```

filterDistributions	<i>filterDistributions</i>
---------------------	----------------------------

Description

show gene or cell distribution after filtering on expression threshold

Usage

```
filterDistributions(
  gobject,
  expression_values = c("raw", "normalized", "scaled", "custom"),
  expression_threshold = 1,
  detection = c("genes", "cells"),
  plot_type = c("histogram", "violin"),
  nr_bins = 30,
  fill_color = "lightblue",
  scale_axis = "identity",
  axis_offset = 0,
  show_plot = TRUE
)
```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	expression values to use
<code>expression_threshold</code>	threshold to consider a gene expressed
<code>detection</code>	consider genes or cells
<code>plot_type</code>	type of plot
<code>nr_bins</code>	number of bins for histogram plot
<code>fill_color</code>	fill color for plots
<code>scale_axis</code>	ggplot transformation for axis (e.g. log2)
<code>axis_offset</code>	offset to be used together with the scaling transformation
<code>show_plot</code>	show plot

Value

ggplot object

Examples

```
filterDistributions(gobject)
```

filterGiotto	<i>filterGiotto</i>
--------------	---------------------

Description

filter Giotto object based on expression threshold

Usage

```
filterGiotto(  
  gobject,  
  expression_values = c("raw", "normalized", "scaled", "custom"),  
  expression_threshold = 1,  
  gene_det_in_min_cells = 100,  
  min_det_genes_per_cell = 100,  
  verbose = F  
)
```

Arguments

gobject	giotto object
expression_values	expression values to use
expression_threshold	threshold to consider a gene expressed
gene_det_in_min_cells	minimum # of cells that need to express a gene
min_det_genes_per_cell	minimum # of genes that need to be detected in a cell
verbose	verbose

Details

The function [filterCombinations](#) can be used to explore the effect of different parameter values.

Value

giotto object

Examples

```
filterGiotto(gobject)
```

findGiniMarkers	<i>findGiniMarkers</i>
-----------------	------------------------

Description

Identify marker genes for selected clusters based on gini detection and expression scores.

Usage

```
findGiniMarkers(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  cluster_column,
  subset_clusters = NULL,
  group_1 = NULL,
  group_2 = NULL,
  min_expr_gini_score = 0.5,
  min_det_gini_score = 0.5,
  detection_threshold = 0,
  rank_score = 1
)
```

Arguments

gobject	giotto object
expression_values	gene expression values to use
cluster_column	clusters to use
subset_clusters	selection of clusters to compare
group_1	group 1 cluster IDs from cluster_column for pairwise comparison
group_2	group 2 cluster IDs from cluster_column for pairwise comparison
min_expr_gini_score	filter on minimum gini coefficient for expression
min_det_gini_score	filter on minimum gini coefficient for detection
detection_threshold	detection threshold for gene expression
rank_score	rank scores to include

Details

Detection of marker genes using the https://en.wikipedia.org/wiki/Gini_coefficient gini coefficient is based on the following steps/principles per gene:

- 1. calculate average expression per cluster
- 2. calculate detection fraction per cluster
- 3. calculate gini-coefficient for av. expression values over all clusters

- 4. calculate gini-coefficient for detection fractions over all clusters
- 5. convert gini-scores to rank scores
- 6. for each gene create combined gini score = av. expr gini x detection gini
- 7. for each gene create and sort on combined rank score = expr rank x detection rank

As a results "top gini" genes are genes that are very selectively expressed in a specific cluster, however not always expressed in all cells of that cluster. In other words highly specific, but not necessarily sensitive at the single-cell level.

To perform differential expression between cluster groups you need to specify cluster IDs to the parameters *group_1* and *group_2*.

Value

data.table with marker genes

Examples

```
findGiniMarkers(gobject)
```

```
findGiniMarkers_one_vs_all
      findGiniMarkers_one_vs_all
```

Description

Identify marker genes for all clusters in a one vs all manner based on gini detection and expression scores.

Usage

```
findGiniMarkers_one_vs_all(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  cluster_column,
  subset_clusters = NULL,
  min_expr_gini_score = 0.5,
  min_det_gini_score = 0.5,
  detection_threshold = 0,
  min_genes = 10,
  verbose = TRUE
)
```

Arguments

```
gobject      giotto object
expression_values
              gene expression values to use
cluster_column clusters to use
subset_clusters
              selection of clusters to compare
```

```

min_expr_gini_score      filter on minimum gini coefficient on expression
min_det_gini_score       filter on minimum gini coefficient on detection
detection_threshold      detection threshold for gene expression
min_genes                minimum genes to keep per cluster, overrides pval and logFC
verbose                  be verbose

```

Value

data.table with marker genes

See Also

[findGiniMarkers](#)

Examples

```
findGiniMarkers_one_vs_all(gobject)
```

findMarkers	<i>findMarkers</i>
-------------	--------------------

Description

Identify marker genes for selected clusters.

Usage

```

findMarkers(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  cluster_column,
  method = c("scrn", "gini", "mast"),
  subset_clusters = NULL,
  group_1 = NULL,
  group_2 = NULL,
  min_expr_gini_score = 0.5,
  min_det_gini_score = 0.5,
  detection_threshold = 0,
  rank_score = 1,
  group_1_name = NULL,
  group_2_name = NULL,
  adjust_columns = NULL,
  ...
)

```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	gene expression values to use
<code>cluster_column</code>	clusters to use
<code>method</code>	method to use to detect differentially expressed genes
<code>subset_clusters</code>	selection of clusters to compare
<code>group_1</code>	group 1 cluster IDs from <code>cluster_column</code> for pairwise comparison
<code>group_2</code>	group 2 cluster IDs from <code>cluster_column</code> for pairwise comparison
<code>min_expr_gini_score</code>	gini: filter on minimum gini coefficient for expression
<code>min_det_gini_score</code>	gini: filter minimum gini coefficient for detection
<code>detection_threshold</code>	gini: detection threshold for gene expression
<code>rank_score</code>	gini: rank scores to include
<code>group_1_name</code>	mast: custom name for <code>group_1</code> clusters
<code>group_2_name</code>	mast: custom name for <code>group_2</code> clusters
<code>adjust_columns</code>	mast: column in <code>pDataDT</code> to adjust for (e.g. detection rate)
<code>...</code>	additional parameters for the <code>findMarkers</code> function in <code>scrn</code> or <code>zlm</code> function in <code>MAST</code>

Details

Wrapper for all individual functions to detect marker genes for clusters.

Value

data.table with marker genes

See Also

[findScranMarkers](#), [findGiniMarkers](#) and [findMastMarkers](#)

Examples

```
findMarkers(gobject)
```

```
findMarkers_one_vs_all
      findMarkers_one_vs_all
```

Description

Identify marker genes for all clusters in a one vs all manner.

Usage

```
findMarkers_one_vs_all(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  cluster_column,
  subset_clusters = NULL,
  method = c("scrn", "gini", "mast"),
  pval = 0.01,
  logFC = 0.5,
  min_genes = 10,
  min_expr_gini_score = 0.5,
  min_det_gini_score = 0.5,
  detection_threshold = 0,
  rank_score = 1,
  adjust_columns = NULL,
  verbose = TRUE,
  ...
)
```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	gene expression values to use
<code>cluster_column</code>	clusters to use
<code>subset_clusters</code>	selection of clusters to compare
<code>method</code>	method to use to detect differentially expressed genes
<code>pval</code>	scrn & mast: filter on minimal p-value
<code>logFC</code>	scan & mast: filter on logFC
<code>min_genes</code>	minimum genes to keep per cluster, overrides pval and logFC
<code>min_expr_gini_score</code>	gini: filter on minimum gini coefficient for expression
<code>min_det_gini_score</code>	gini: filter minimum gini coefficient for detection
<code>detection_threshold</code>	gini: detection threshold for gene expression
<code>rank_score</code>	gini: rank scores to include
<code>adjust_columns</code>	mast: column in pDataDT to adjust for (e.g. detection rate)

verbose	be verbose
...	additional parameters for the findMarkers function in scan or zlm function in MAST

Details

Wrapper for all one vs all functions to detect marker genes for clusters.

Value

data.table with marker genes

See Also

[findScranMarkers_one_vs_all](#), [findGiniMarkers_one_vs_all](#) and [findMastMarkers_one_vs_all](#)

Examples

```
findMarkers_one_vs_all(gobject)
```

findMastMarkers	<i>findMastMarkers</i>
-----------------	------------------------

Description

Identify marker genes for selected clusters based on the MAST package.

Usage

```
findMastMarkers(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  cluster_column,
  group_1 = NULL,
  group_1_name = NULL,
  group_2 = NULL,
  group_2_name = NULL,
  adjust_columns = NULL,
  ...
)
```

Arguments

gobject	giotto object
expression_values	gene expression values to use
cluster_column	clusters to use
group_1	group 1 cluster IDs from cluster_column for pairwise comparison
group_1_name	custom name for group_1 clusters
group_2	group 2 cluster IDs from cluster_column for pairwise comparison

group_2_name custom name for group_2 clusters
 adjust_columns column in pDataDT to adjust for (e.g. detection rate)
 ... additional parameters for the zlm function in MAST

Details

This is a minimal convenience wrapper around the [zlm](#) from the MAST package to detect differentially expressed genes.

Value

data.table with marker genes

Examples

```
findMastMarkers(gobject)
```

```
findMastMarkers_one_vs_all  

findMastMarkers_one_vs_all
```

Description

Identify marker genes for all clusters in a one vs all manner based on the MAST package.

Usage

```
findMastMarkers_one_vs_all(  

  gobject,  

  expression_values = c("normalized", "scaled", "custom"),  

  cluster_column,  

  subset_clusters = NULL,  

  adjust_columns = NULL,  

  pval = 0.001,  

  logFC = 1,  

  min_genes = 10,  

  verbose = TRUE,  

  ...  

)
```

Arguments

gobject giotto object
 expression_values gene expression values to use
 cluster_column clusters to use
 subset_clusters selection of clusters to compare
 adjust_columns column in pDataDT to adjust for (e.g. detection rate)
 pval filter on minimal p-value

logFC	filter on logFC
min_genes	minimum genes to keep per cluster, overrides pval and logFC
verbose	be verbose
...	additional parameters for the zlm function in MAST

Value

data.table with marker genes

See Also

[findMastMarkers](#)

Examples

```
findMastMarkers_one_vs_all(gobject)
```

findScranMarkers	<i>findScranMarkers</i>
------------------	-------------------------

Description

Identify marker genes for all or selected clusters based on scran's implementation of findMarkers.

Usage

```
findScranMarkers(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  cluster_column,
  subset_clusters = NULL,
  group_1 = NULL,
  group_2 = NULL,
  ...
)
```

Arguments

gobject	giotto object
expression_values	gene expression values to use
cluster_column	clusters to use
subset_clusters	selection of clusters to compare
group_1	group 1 cluster IDs from cluster_column for pairwise comparison
group_2	group 2 cluster IDs from cluster_column for pairwise comparison
...	additional parameters for the findMarkers function in scran

Details

This is a minimal convenience wrapper around the [findMarkers](#) function from the `scrn` package.

To perform differential expression between cluster groups you need to specify cluster IDs to the parameters `group_1` and `group_2`.

Value

data.table with marker genes

Examples

```
findScranMarkers(gobject)
```

```
findScranMarkers_one_vs_all
  findScranMarkers_one_vs_all
```

Description

Identify marker genes for all clusters in a one vs all manner based on `scrn`'s implementation of `findMarkers`.

Usage

```
findScranMarkers_one_vs_all(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  cluster_column,
  subset_clusters = NULL,
  pval = 0.01,
  logFC = 0.5,
  min_genes = 10,
  verbose = TRUE,
  ...
)
```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	gene expression values to use
<code>cluster_column</code>	clusters to use
<code>subset_clusters</code>	subset of clusters to use
<code>pval</code>	filter on minimal p-value
<code>logFC</code>	filter on logFC
<code>min_genes</code>	minimum genes to keep per cluster, overrides <code>pval</code> and <code>logFC</code>
<code>verbose</code>	be verbose
<code>...</code>	additional parameters for the <code>findMarkers</code> function in <code>scrn</code>

Value

data.table with marker genes

See Also

[findScranMarkers](#)

Examples

```
findScranMarkers_one_vs_all(gobject)
```

find_grid_2D	<i>find_grid_2D</i>
--------------	---------------------

Description

find grid location in 2D

Usage

```
find_grid_2D(grid_DT, x_loc, y_loc)
```

find_grid_3D	<i>find_grid_3D</i>
--------------	---------------------

Description

find grid location in 3D

Usage

```
find_grid_3D(grid_DT, x_loc, y_loc, z_loc)
```

find_grid_x	<i>find_grid_x</i>
-------------	--------------------

Description

find grid location on x-axis

Usage

```
find_grid_x(grid_DT, x_loc)
```

find_grid_y	<i>find_grid_y</i>
-------------	--------------------

Description

find grid location on y-axis

Usage

find_grid_y(grid_DT, y_loc)

find_grid_z	<i>find_grid_z</i>
-------------	--------------------

Description

find grid location on z-axis

Usage

find_grid_z(grid_DT, z_loc)

fish_function	<i>fish_function</i>
---------------	----------------------

Description

perform fisher exact test

Usage

fish_function(x_to, x_from)

fish_function2	<i>fish_function2</i>
----------------	-----------------------

Description

perform fisher exact test

Usage

fish_function2(A, B, C, D)

FSV_show	<i>FSV_show</i>
----------	-----------------

Description

Visualize spatial variable genes caculated by spatial_DE

Usage

```
FSV_show(  
  results,  
  ms_results = NULL,  
  size = c(4, 2, 1),  
  color = c("blue", "green", "red"),  
  sig_alpha = 0.5,  
  unsig_alpha = 0.5  
)
```

Arguments

results	results caculated by spatial_DE
ms_results	ms_results caculated by spatial_DE
size	indicate different levels of qval
color	indicate different SV features
sig_alpha	transparency of significant genes
unsig_alpha	transparency of insignificant genes

Details

Description of parameters.

Value

nothing

Examples

```
FSV_show(results)
```

`GenePattern_show`*GenePattern_show*

Description

Visualize genes distribution patterns calculated by spatial_AEH

Usage

```
GenePattern_show(  
  gobject = NULL,  
  AEH_results = NULL,  
  sdimx = NULL,  
  sdimy = NULL,  
  point_size = 3,  
  point_alpha = 1,  
  low_color = "blue",  
  mid_color = "white",  
  high_color = "red",  
  midpoint = 0  
)
```

Arguments

<code>gobject</code>	giotto object
<code>AEH_results</code>	results from spatial_AEH
<code>sdimx</code>	x axis of spatial locus
<code>sdimy</code>	y axis of spatial locus
<code>point_size</code>	size of points to indicate cells
<code>point_alpha</code>	transparency of points to indicate cells
<code>low_color</code>	color to indicate low score level
<code>mid_color</code>	color to indicate middle score level
<code>high_color</code>	color to indicate high score level
<code>midpoint</code>	point to set mid_color

Details

Description of parameters.

Value

nothing

Examples

```
GenePattern_show(gobject,AEH_results)
```

general_save_function *general_save_function*

Description

Function to automatically save plots to directory of interest

Usage

```
general_save_function(
  gobject,
  plot_object,
  save_dir = NULL,
  save_folder = NULL,
  save_name = NULL,
  default_save_name = "giotto_plot",
  save_format = c("png", "tiff", "pdf", "svg"),
  show_saved_plot = F,
  base_width = NULL,
  base_height = NULL,
  base_aspect_ratio = NULL,
  units = NULL,
  dpi = NULL,
  ...
)
```

Arguments

<code>gobject</code>	giotto object
<code>plot_object</code>	non-ggplot object to plot
<code>save_dir</code>	directory to save to
<code>save_folder</code>	folder in <code>save_dir</code> to save to
<code>save_name</code>	name of plot
<code>save_format</code>	format (e.g. png, tiff, pdf, ...)
<code>show_saved_plot</code>	load & display the saved plot
<code>base_width</code>	width
<code>base_height</code>	height
<code>base_aspect_ratio</code>	aspect ratio
<code>units</code>	units
<code>dpi</code>	Plot resolution

Examples

```
general_save_function(gobject)
```

get10Xmatrix	<i>get10Xmatrix</i>
--------------	---------------------

Description

This function creates an expression matrix from a 10X structured folder

Usage

```
get10Xmatrix(path_to_data)
```

Arguments

path_to_data path to the 10X folder

Details

A typical 10X folder is named raw_feature_bc_matrix or raw_feature_bc_matrix. It has 3 files:

- barcodes
- features.tsv.gz
- matrix.mtx.gz

Value

expression matrix from 10X

Examples

```
get10Xmatrix(10Xmatrix)
```

getCellProximityGeneScores	<i>getCellProximityGeneScores</i>
----------------------------	-----------------------------------

Description

Compute cell-cell interaction enrichment (observed vs expected)

Usage

```
getCellProximityGeneScores(
  gobject,
  spatial_network_name = "spatial_network",
  cluster_column = "louvain_clus.1",
  selected_genes = NULL,
  expression_values = c("normalized", "scaled", "custom"),
  do_diff_test = TRUE,
  diff_test = c("t.test", "wilcox"),
  minimum_unique_cells = NA,
```



```

    fold_change_addendum = 0.1,
    in_two_directions = TRUE,
    exclude_selected_cells_from_test = F,
    verbose = T
)

```

Arguments

<code>gobject</code>	giotto object
<code>spatial_network_name</code>	name of spatial network to use
<code>cluster_column</code>	name of column to use for clusters
<code>selected_genes</code>	selection of genes to perform calculations for
<code>expression_values</code>	expression values to use
<code>do_diff_test</code>	perform differential test
<code>diff_test</code>	which differential expression test
<code>minimum_unique_cells</code>	minimum number of cells needed to proceed
<code>fold_change_addendum</code>	constant to add when calculating log2 fold-change
<code>in_two_directions</code>	shows enrichment in both directions: cell1-cell2, cell2-cell1
<code>exclude_selected_cells_from_test</code>	exclude certain cells from test
<code>verbose</code>	verbose

Details

Function to calculate if genes are differentially expressed in cell types when they interact (according to physical proximity) with other cell types. The results data.table contains the following columns:

- `genes`: All or selected list of tested genes
- `cell_expr_1`: average gene expression in cell type 1 from unified_int cell-cell interaction
- `cell_expr_2`: average gene expression in cell type 2 from unified_int cell-cell interaction
- `comb_expr`: combined average gene expression in cell type 1 and 2 from unified_int cell-cell interaction
- `all_cell_expr_1`: average gene expression for all cells from cell type 1
- `all_cell_expr_2`: average gene expression for all cells from cell type 2
- `all_comb_expr`: combined average gene expression for all cells from cell type 1 and 2
- `pval_1`: p-value from test between interacting cells and all cells from cell type 1
- `pval_2`: p-value from test between interacting cells and all cells from cell type 2
- `cell_type_1`: first cell type of cell-cell interaction
- `cell_type_2`: second cell type of cell-cell interaction
- `interaction`: the cell-cell interaction, based on physical proximity
- `nr_1`: number of cell type 1 in the unified cell-cell interaction
- `nr_2`: number of cell type 2 in the unified cell-cell interaction

- all_nr_1: number of all cell type 1 in the whole dataset
- all_nr_2: number of all cell type 2 in the whole dataset
- diff_spat: difference between comb_expr and all_comb_expr
- diff_spat_1: difference between cell_expr_1 and all_cell_expr_1
- diff_spat_2: difference between cell_expr_1 and all_cell_expr_1
- log2fc_spat_1: fold-change of diff_spat_1
- log2fc_spat_2: fold-change of diff_spat_2
- log2fc_spat: fold-change of diff_spat
- type_int: type of interaction
- unified_int: interaction with alphabetically sorted cell type 1 and cell type 2
- unif_int_rank: 1 or 2
- fdr_1: fdr from test between interacting cells and all cells from cell type 1
- fdr_2: fdr from test between interacting cells and all cells from cell type 2

Value

Cell Proximity Gene scores (CPGscores) in data.table format

Examples

```
getCellProximityGeneScores(gobject)
```

```
getClusterSimilarity    getClusterSimilarity
```

Description

Creates data.table with pairwise correlation scores between each cluster.

Usage

```
getClusterSimilarity(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  cluster_column,
  cor = c("pearson", "spearman")
)
```

Arguments

gobject	giotto object
expression_values	expression values to use
cluster_column	name of column to use for clusters
cor	correlation score to calculate distance

Details

Creates data.table with pairwise correlation scores between each cluster and the group size (# of cells) for each cluster. This information can be used together with mergeClusters to combine very similar or small clusters into bigger clusters.

Value

data.table

Examples

```
getClusterSimilarity(gobject)
```

```
getDendrogramSplits    getDendrogramSplits
```

Description

Split dendrogram at each node and keep the leave (label) information..

Usage

```
getDendrogramSplits(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  cluster_column,
  cor = c("pearson", "spearman"),
  distance = "ward.D",
  h = NULL,
  h_color = "red",
  show_dend = TRUE,
  verbose = TRUE
)
```

Arguments

gobject	giotto object
expression_values	expression values to use
cluster_column	name of column to use for clusters
cor	correlation score to calculate distance
distance	distance method to use for hierarchical clustering
h	height of horizontal lines to plot
h_color	color of horizontal lines
show_dend	show dendrogram
verbose	be verbose

Details

Creates a data.table with three columns and each row represents a node in the dendrogram. For each node the height of the node is given together with the two subdendrograms. This information can be used to determine in a hierarchical manner differentially expressed marker genes at each node.

Value

data.table object

Examples

getDendrogramSplits(gobject)

getDistinctColors	<i>getDistinctColors</i>
-------------------	--------------------------

Description

Returns a number of distinct colors based on the RGB scale

Usage

getDistinctColors(n)

Arguments

n number of colors wanted

Value

number of distinct colors

getGeneToGeneScores	<i>getGeneToGeneScores</i>
---------------------	----------------------------

Description

Compute gene-gene enrichment scores.

Usage

```
getGeneToGeneScores(  
  CPGscore,  
  selected_genes = NULL,  
  specific_genes_1 = NULL,  
  specific_genes_2 = NULL,  
  min_cells = 5,  
  min_fdr = 0.05,  
  min_spat_diff = 0.2,  
  min_log2_fc = 0.5,
```

```

    direction = c("both", "up", "down"),
    fold_change_addendum = 0.1,
    verbose = TRUE
  )

```

Arguments

CPGscore	CPGscore, output from getCellProximityGeneScores()
selected_genes	select subset of genes
specific_genes_1	specific source genes (see details)
specific_genes_2	specific target genes (see details)
min_cells	min number of cells threshold
min_spat_diff	spatial difference threshold
min_log2_fc	log2 fold-change threshold
direction	up or downregulation or both
fold_change_addendum	constant to add when calculating log2 fold-change
verbose	verbose
min_pval	p-value threshold

Details

This converts the single gene cell proximityscores into pairwise combinations of genes, which allows you to determine if 2 genes are differentially expressed in interacting cell types.

Value

Gene to gene scores in data.table format

Examples

```
getGeneToGeneScores(CPGscore)
```

```

get_cell_to_cell_sorted_name_conversion
      get_cell_to_cell_sorted_name_conversion

```

Description

creates unified cell-cell interaction names

Usage

```
get_cell_to_cell_sorted_name_conversion(all_cell_types)
```

Examples

```
get_cell_to_cell_sorted_name_conversion()
```

```
get_interaction_gene_enrichment  
    get_interaction_gene_enrichment
```

Description

Computes gene enrichment between all interactions

Usage

```
get_interaction_gene_enrichment(  
  spatial_network,  
  unified_int_col = "unified_int",  
  source_col = "source_clus",  
  source_IDs = "from",  
  neighb_col = "neighb_clus",  
  neighb_IDs = "to",  
  expression_matrix,  
  cell_annotation,  
  annotation_ID = "uniq_ID",  
  cell_type_col,  
  do_diff_test = T,  
  diff_test = c("t.test", "wilcox"),  
  minimum_unique_cells = NA,  
  exclude_selected_cells_from_test = T,  
  verbose = T  
)
```

Examples

```
get_interaction_gene_enrichment()
```

```
get_specific_interaction_gene_enrichment  
    get_specific_interaction_gene_enrichment
```

Description

Computes gene enrichment between specified interaction

Usage

```
get_specific_interaction_gene_enrichment(  
  sub_spatial_network,  
  source_col = "source_clus",  
  source_IDs = "from",  
  neighb_col = "neighb_clus",  
  neighb_IDs = "to",  
  expression_matrix,
```

```

    interaction_name = "to_specify",
    cell_annotation,
    annotation_ID = "uniq_ID",
    cell_type_col,
    do_diff_test = T,
    diff_test = c("t.test", "wilcox"),
    minimum_unique_cells = NA,
    exclude_selected_cells_from_test = T
  )

```

Examples

```
get_specific_interaction_gene_enrichment()
```

```
ggplot_save_function  ggplot_save_function
```

Description

Function to automatically save plots to directory of interest

Usage

```

ggplot_save_function(
  gobject,
  plot_object,
  save_dir = NULL,
  save_folder = NULL,
  save_name = NULL,
  default_save_name = "giotto_plot",
  save_format = NULL,
  show_saved_plot = F,
  ncol = 1,
  nrow = 1,
  scale = 1,
  base_width = NULL,
  base_height = NULL,
  base_aspect_ratio = NULL,
  units = NULL,
  dpi = NULL,
  limitsize = TRUE,
  ...
)

```

Arguments

<code>gobject</code>	giotto object
<code>plot_object</code>	ggplot object to plot
<code>save_dir</code>	directory to save to
<code>save_folder</code>	folder in <code>save_dir</code> to save to

save_name	name of plot
save_format	format (e.g. png, tiff, pdf, ...)
show_saved_plot	load & display the saved plot
ncol	number of columns
nrow	number of rows
scale	scale
base_width	width
base_height	height
base_aspect_ratio	aspect ratio
units	units
dpi	Plot resolution
limitsize	When TRUE (the default), ggsave will not save images larger than 50x50 inches, to prevent the common error of specifying dimensions in pixels.

See Also

[cowplot::save_plot](#)

Examples

```
ggplot_save_function(gobject)
```

giotto-class	<i>S4 giotto Class</i>
--------------	------------------------

Description

Framework of giotto object to store and work with spatial expression data

Slots

raw_exprs	raw expression counts
norm_expr	normalized expression counts
norm_scaled_expr	normalized and scaled expression counts
custom_expr	custom normalized counts
spatial_locs	spatial location coordinates for cells
cell_metadata	metadata for cells
gene_metadata	metadata for genes
cell_ID	unique cell IDs
gene_ID	unique gene IDs
spatial_network	spatial network in data.table/data.frame format
spatial_grid	spatial grid in data.table/data.frame format
dimension_reduction	slot to save dimension reduction coordinates

nn_network nearest neighbor network in igraph format
 parameters slot to save parameters that have been used
 instructions slot for global function instructions
 offset_file offset file used to stitch together image fields
 OS_platform Operating System to run Giotto analysis on

heatmSpatialCorGenes *heatmSpatialCorGenes*

Description

Create heatmap of spatially correlated genes

Usage

```
heatmSpatialCorGenes(
  gobject,
  spatCorObject,
  use_clus_name = NULL,
  show_cluster_annot = TRUE,
  show_row_dend = T,
  show_column_dend = F,
  show_row_names = F,
  show_column_names = F,
  show_plot = NA,
  return_plot = NA,
  save_plot = NA,
  save_param = list(),
  default_save_name = "heatmSpatialCorGenes",
  ...
)
```

Arguments

gobject	giotto object
spatCorObject	spatial correlation object
use_clus_name	name of clusters to visualize (from clusterSpatialCorGenes())
show_cluster_annot	show cluster annotation on top of heatmap
show_row_dend	show row dendrogram
show_column_dend	show column dendrogram
show_row_names	show row names
show_column_names	show column names
show_plot	show plot
return_plot	return ggplot object

save_plot directly save the plot [boolean]
 save_param list of saving parameters from [all_plots_save_function](#)
 default_save_name default save name for saving, don't change, change save_name in save_param
 ... additional parameters to the [Heatmap](#) function from ComplexHeatmap

Value

Heatmap generated by ComplexHeatmap

Examples

```
heatmSpatialCorGenes(gobject)
```

hyperGeometricEnrich	<i>hyperGeometricEnrich</i>
----------------------	-----------------------------

Description

Function to calculate gene signature enrichment scores per spatial position using a hypergeometric test.

Usage

```
hyperGeometricEnrich(
  gobject,
  sign_matrix,
  expression_values = c("normalized", "scaled", "custom"),
  reverse_log_scale = TRUE,
  logbase = 2,
  output_enrichment = c("original", "zscore")
)
```

Arguments

gobject Giotto object
 sign_matrix Matrix of signature genes for each cell type / process
 expression_values expression values to use
 reverse_log_scale reverse expression values from log scale
 logbase log base to use if reverse_log_scale = TRUE
 output_enrichment how to return enrichment output

Details

The enrichment score is calculated based on the p-value from the hypergeometric test, $-\log_{10}(\text{p-value})$.

Value

data.table with enrichment results

Examples

```
hyperGeometricEnrich(gobject)
```

kmeans_binarize	<i>kmeans_binarize</i>
-----------------	------------------------

Description

create binarized scores using kmeans

Usage

```
kmeans_binarize(x, nstart = 3, iter.max = 10)
```

loadHMRF	<i>loadHMRF</i>
----------	-----------------

Description

load previous HMRF

Usage

```
loadHMRF(  
  name_used = "test",  
  output_folder_used,  
  k_used = 10,  
  betas_used,  
  python_path_used  
)
```

Arguments

- name_used name of HMRF that was run
- output_folder_used output folder that was used
- k_used number of HMRF domains that was tested
- betas_used betas that were tested
- python_path_used python path that was used

Details

Description of HMRF parameters ...

Value

reloads a previous ran HMRF from doHRMF

Examples

```
loadHMRF(gobject)
```

makeSignMatrixPAGE	<i>makeSignMatrixPAGE</i>
--------------------	---------------------------

Description

Function to convert a list of signature genes (e.g. for cell types or processes) into a binary matrix format that can be used with the PAGE enrichment option.

Usage

```
makeSignMatrixPAGE(sign_names, sign_list)
```

Arguments

- sign_names vector with names for each provided gene signature
- sign_list list of genes (signature)

Value

matrix

See Also

[PAGEEnrich](#)

Examples

```
makeSignMatrixPAGE()
```

makeSignMatrixRank	<i>makeSignMatrixRank</i>
--------------------	---------------------------

Description

Function to convert a single-cell count matrix and a corresponding single-cell cluster vector into a rank matrix that can be used with the Rank enrichment option.

Usage

```
makeSignMatrixRank(sc_matrix, sc_cluster_ids, gobject = NULL)
```

Arguments

sign_names	vector with names for each provided gene signature
sign_list	list of genes (signature)

Value

matrix

See Also

[rankEnrich](#)

Examples

```
makeSignMatrixRank()
```

make_simulated_network	<i>make_simulated_network</i>
------------------------	-------------------------------

Description

Simulate random network.

Usage

```
make_simulated_network(  
  gobject,  
  spatial_network_name = "spatial_network",  
  cluster_column,  
  number_of_simulations = 100  
)
```

Examples

```
make_simulated_network(gobject)
```

mergeClusters	<i>mergeClusters</i>
---------------	----------------------

Description

Merge selected clusters based on pairwise correlation scores and size of cluster.

Usage

```
mergeClusters(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  cluster_column,
  cor = c("pearson", "spearman"),
  new_cluster_name = "merged_cluster",
  min_cor_score = 0.8,
  max_group_size = 20,
  force_min_group_size = 10,
  return_gobject = TRUE,
  verbose = TRUE
)
```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	expression values to use
<code>cluster_column</code>	name of column to use for clusters
<code>cor</code>	correlation score to calculate distance
<code>new_cluster_name</code>	new name for merged clusters
<code>min_cor_score</code>	min correlation score to merge pairwise clusters
<code>max_group_size</code>	max cluster size that can be merged
<code>force_min_group_size</code>	size of clusters that will be merged with their most similar neighbor(s)
<code>return_gobject</code>	return giotto object
<code>verbose</code>	be verbose

Details

Merge selected clusters based on pairwise correlation scores and size of cluster. To avoid large clusters to merge the `max_group_size` can be lowered. Small clusters can be forcibly merged with their most similar pairwise cluster by adjusting the `force_min_group_size` parameter. Clusters smaller than this value will be merged independent on the provided `min_cor_score` value. A giotto object is returned by default, if FALSE then the merging vector will be returned.

Value

Giotto object

Examples

```
mergeClusters(gobject)
```

mygini_fun	<i>mygini_fun</i>
------------	-------------------

Description

calculate gini coefficient

Usage

```
mygini_fun(x, weights = rep(1, length(x)))
```

Value

gini coefficient

nnDT_to_kNN	<i>nnDT_to_kNN</i>
-------------	--------------------

Description

Convert a nearest network data.table to a kNN object

Usage

```
nnDT_to_kNN(nnDT)
```

Arguments

nnDT	nearest neighbor network in data.table format
------	---

Value

kNN object

node_clusters	<i>node_clusters</i>
---------------	----------------------

Description

Merge selected clusters based on pairwise correlation scores and size of cluster.

Usage

```
node_clusters(hclus_obj, verbose = TRUE)
```

Arguments

hclus_obj	hclus object
verbose	be verbose

Value

list of splitted dendrogram nodes from high to low node height

Examples

```
node_clusters(hclus_obj)
```

normalizeGiotto	<i>normalizeGiotto</i>
-----------------	------------------------

Description

normalize and/or scale expresion values of Giotto object

Usage

```
normalizeGiotto(  
  gobject,  
  norm_methods = c("standard", "osmFISH"),  
  library_size_norm = TRUE,  
  scalefactor = 6000,  
  log_norm = TRUE,  
  logbase = 2,  
  scale_genes = T,  
  scale_cells = T,  
  scale_order = c("first_genes", "first_cells"),  
  verbose = F  
)
```

Arguments

gobject	giotto object
norm_methods	normalization method to use
library_size_norm	normalize cells by library size
scalefactor	scale factor to use after library size normalization
log_norm	transform values to log-scale
logbase	log base to use to log normalize expression values
scale_genes	z-score genes over all cells
scale_cells	z-score cells over all genes
scale_order	order to scale genes and cells
verbose	be verbose

Details

Currently there are two 'methods' to normalize your raw counts data.

A. The standard method follows the standard protocol which can be adjusted using the provided parameters and follows the following order:

- 1. Data normalization for total library size and scaling by a custom scale-factor.
- 2. Log transformation of data.
- 3. Z-scoring of data by genes and/or cells.

B. The normalization method as provided by the osmFISH paper is also implemented:

- 1. First normalize genes, for each gene divide the counts by the total gene count and multiply by the total number of genes.
- 2. Next normalize cells, for each cell divide the normalized gene counts by the total counts per cell and multiply by the total number of cells.

This data will be saved in the Giotto slot for custom expression.

Value

giotto object

Examples

```
normalizeGiotto(gobject)
```

OR_function2

OR_function2

Description

calculate odds-ratio

Usage

```
OR_function2(A, B, C, D)
```

PAGEEnrich

*PAGEEnrich***Description**

Function to calculate gene signature enrichment scores per spatial position using PAGE.

Usage

```
PAGEEnrich(
  gobject,
  sign_matrix,
  expression_values = c("normalized", "scaled", "custom"),
  reverse_log_scale = TRUE,
  logbase = 2,
  output_enrichment = c("original", "zscore")
)
```

Arguments

<code>gobject</code>	Giotto object
<code>sign_matrix</code>	Matrix of signature genes for each cell type / process
<code>expression_values</code>	expression values to use
<code>reverse_log_scale</code>	reverse expression values from log scale
<code>logbase</code>	log base to use if <code>reverse_log_scale = TRUE</code>
<code>output_enrichment</code>	how to return enrichment output

Details

`sign_matrix`: a binary matrix with genes as row names and cell-types as column names. Alternatively a list of signature genes can be provided to `makeSignMatrixPAGE`, which will create the matrix for you.

The enrichment Z score is calculated by using method (PAGE) from Kim SY et al., BMC bioinformatics, 2005 as $Z = ((Sm \sim \mu) * m^{1/2}) / \delta$. For each gene in each spot, μ is the fold change values versus the mean expression and δ is the standard deviation. Sm is the mean fold change value of a specific marker gene set and m is the size of a given marker gene set.

Value

data.table with enrichment results

See Also

[makeSignMatrixPAGE](#)

Examples

```
PAGEEnrich(gobject)
```

pDataDT

pDataDT

Description

show cell metadata

Usage

```
pDataDT(gobject)
```

Arguments

gobject giotto object

Value

data.table with cell metadata

Examples

```
pDataDT(gobject)
```

plotCPGscores

plotCPGscores

Description

Create heatmap from cell-cell proximity scores

Usage

```
plotCPGscores(
  CPGscores,
  selected_interactions = NULL,
  selected_genes = NULL,
  detail_plot = T,
  simple_plot = F,
  simple_plot_facet = c("interaction", "genes"),
  facet_scales = "fixed",
  facet_ncol = length(selected_genes),
  facet_nrow = length(selected_interactions),
  show_plot = F
)
```

Arguments

CPGscores CPGscores, output from getCellProximityGeneScores()
selected_interactions interactions to show
selected_genes genes to show
detail_plot show detailed info in both interacting cell types
simple_plot show a simplified plot
simple_plot_facet facet on interactions or genes with simple plot
facet_scales ggplot facet scales paramter
facet_ncol ggplot facet ncol parameter
facet_nrow ggplot facet nrow parameter
show_plot show plot

Details

Give more details ...

Value

ggplot barplot

Examples

plotCPGscores(CPGscores)

plotGTGscores	<i>plotGTGscores</i>
---------------	----------------------

Description

Create heatmap from cell-cell proximity scores

Usage

```
plotGTGscores(  
  gobject,  
  GTGscore,  
  selected_interactions = NULL,  
  selected_gene_to_gene = NULL,  
  detail_plot = T,  
  simple_plot = F,  
  simple_plot_facet = c("interaction", "genes"),  
  facet_scales = "fixed",  
  facet_ncol = length(selected_gene_to_gene),  
  facet_nrow = length(selected_interactions),  
  colors = c("blue", "red"),  
  show_plot = NA,  
  return_plot = NA,
```

```

    save_plot = NA,
    save_param = list(),
    default_save_name = "plotGTGscores"
  )

```

Arguments

gobject	giotto object
GTGscore	GTGscore, output from <code>getGeneToGeneScores()</code>
selected_interactions	interactions to show
detail_plot	show detailed info in both interacting cell types
simple_plot	show a simplified plot
simple_plot_facet	facet on interactions or genes with simple plot
facet_scales	ggplot facet scales paramter
facet_ncol	ggplot facet ncol parameter
facet_nrow	ggplot facet nrow parameter
colors	vector with 2 colors to represent respectively all and selected cells
show_plot	show plots
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function
default_save_name	default save name for saving, don't change, change save_name in save_param
selected_genes	genes to show

Details

Give more details ...

Value

ggplot barplot

Examples

```
plotGTGscores(GTGscore)
```

plotHeatmap

plotHeatmap

Description

Creates heatmap for genes and clusters.

Usage

```
plotHeatmap(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  genes,
  cluster_column = NULL,
  cluster_order = c("size", "correlation", "custom"),
  cluster_custom_order = NULL,
  cluster_color_code = NULL,
  cluster_cor_method = "pearson",
  cluster_hclust_method = "ward.D",
  gene_order = c("custom", "correlation"),
  gene_custom_order = NULL,
  gene_cor_method = "pearson",
  gene_hclust_method = "complete",
  show_values = c("rescaled", "z-scaled", "original"),
  size_vertical_lines = 1.1,
  gradient_colors = c("blue", "yellow", "red"),
  gene_label_selection = NULL,
  axis_text_y_size = NULL,
  legend_nrows = 1,
  show_plot = NA,
  return_plot = NA,
  save_plot = NA,
  save_param = list(),
  default_save_name = "plotHeatmap"
)
```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	expression values to use
<code>genes</code>	genes to use
<code>cluster_column</code>	name of column to use for clusters
<code>cluster_order</code>	method to determine cluster order
<code>cluster_custom_order</code>	custom order for clusters
<code>cluster_color_code</code>	color code for clusters
<code>cluster_cor_method</code>	method for cluster correlation

cluster_hclust_method	method for hierarchical clustering of clusters
gene_order	method to determine gene order
gene_custom_order	custom order for genes
gene_cor_method	method for gene correlation
gene_hclust_method	method for hierarchical clustering of genes
show_values	which values to show on heatmap
size_vertical_lines	sizes for vertical lines
gradient_colors	colors for heatmap gradient
gene_label_selection	subset of genes to show on y-axis
axis_text_y_size	size for y-axis text
legend_nrows	number of rows for the cluster legend
show_plot	show plot
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function
default_save_name	default save name

Details

If you want to display many genes there are 2 ways to proceed:

- 1. set axis_text_y_size to a really small value and show all genes
- 2. provide a subset of genes to display to gene_label_selection

Value

ggplot

Examples

```
plotHeatmap(gobject)
```

plotly_axis_scale_2D *plotly_axis_scale_2D*

Description

adjust the axis scale in 3D plotly plot

Usage

```
plotly_axis_scale_2D(
  cell_locations,
  sdimx = NULL,
  sdimy = NULL,
  mode = c("cube", "real", "custom"),
  custom_ratio = NULL
)
```

Arguments

cell_locations	spatial_loc in giotto object
sdimx	x axis of cell spatial location
sdimy	y axis of cell spatial location
mode	axis adjustment mode
custom_ratio	set the ratio artificially

Value

edges in spatial grid as data.table()

Examples

```
plotly_axis_scale_2D(gobject)
```

plotly_axis_scale_3D *plotly_axis_scale_3D*

Description

adjust the axis scale in 3D plotly plot

Usage

```
plotly_axis_scale_3D(
  cell_locations,
  sdimx = NULL,
  sdimy = NULL,
  sdimz = NULL,
  mode = c("cube", "real", "custom"),
  custom_ratio = NULL
)
```


Arguments

cell_locations spatial_loc in giotto object
 sdimx x axis of cell spatial location
 sdimy y axis of cell spatial location
 sdimz z axis of cell spatial location
 mode axis adjustment mode
 custom_ratio set the ratio artificially

Value

edges in spatial grid as data.table()

Examples

```
plotly_axis_scale_3D(gobject)
```

plotly_grid	<i>plotly_grid</i>
-------------	--------------------

Description

provide grid segment to draw in plot_ly()

Usage

```
plotly_grid(
  spatial_grid,
  x_start = "x_start",
  y_start = "y_start",
  x_end = "x_end",
  y_end = "y_end"
)
```

Arguments

spatial_grid spatial_grid in giotto object

Value

edges in spatial grid as data.table()

Examples

```
plotly_grid(gobject)
```

plotly_network	<i>plotly_network</i>
----------------	-----------------------

Description

provide network segment to draw in 3D plot_ly()

Usage

```
plotly_network(
  network,
  x = "sdimx_begin",
  y = "sdimy_begin",
  z = "sdimz_begin",
  x_end = "sdimx_end",
  y_end = "sdimy_end",
  z_end = "sdimz_end"
)
```

Arguments

gobject network in giotto object

Value

edges in network as data.table()

Examples

```
plotly_network(gobject)
```

plotMetaDataCellsHeatmap	<i>plotMetaDataCellsHeatmap</i>
--------------------------	---------------------------------

Description

Creates heatmap for numeric cell metadata within aggregated clusters.

Usage

```
plotMetaDataCellsHeatmap(
  gobject,
  metadata_cols = NULL,
  spat_enr_names = NULL,
  value_cols = NULL,
  first_meta_col = NULL,
  second_meta_col = NULL,
  show_values = c("zscores", "original", "zscores_rescaled"),
  custom_cluster_order = NULL,
```

```

clus_cor_method = "pearson",
clus_cluster_method = "complete",
custom_values_order = NULL,
values_cor_method = "pearson",
values_cluster_method = "complete",
midpoint = 0,
x_text_size = 8,
x_text_angle = 45,
y_text_size = 8,
strip_text_size = 8,
show_plot = NA,
return_plot = NA,
save_plot = NA,
save_param = list(),
default_save_name = "plotMetaDataCellsHeatmap"
)

```

Arguments

<code>gobject</code>	giotto object
<code>metadata_cols</code>	annotation columns found in <code>pDataDT(gobject)</code>
<code>spat_enr_names</code>	spatial enrichment results to include
<code>value_cols</code>	value columns to use
<code>first_meta_col</code>	if more than 1 metadata column, select the x-axis factor
<code>second_meta_col</code>	if more than 1 metadata column, select the facetting factor
<code>show_values</code>	which values to show on heatmap
<code>custom_cluster_order</code>	custom cluster order (default = NULL)
<code>clus_cor_method</code>	correlation method for clusters
<code>clus_cluster_method</code>	hierarchical cluster method for the clusters
<code>midpoint</code>	midpoint of <code>show_values</code>
<code>x_text_size</code>	size of x-axis text
<code>x_text_angle</code>	angle of x-axis text
<code>y_text_size</code>	size of y-axis text
<code>strip_text_size</code>	size of strip text
<code>show_plot</code>	show plot
<code>return_plot</code>	return ggplot object
<code>save_plot</code>	directly save the plot [boolean]
<code>save_param</code>	list of saving parameters from all_plots_save_function
<code>default_save_name</code>	default save name for saving, don't change, change <code>save_name</code> in <code>save_param</code>
<code>custom_gene_order</code>	custom gene order (default = NULL)

gene_cor_method
correlation method for genes

gene_cluster_method
hierarchical cluster method for the genes

Details

Creates heatmap for the average values of selected value columns in the different annotation groups.

Value

ggplot or data.table

See Also

[plotMetaDataHeatmap](#) for gene expression instead of numeric cell annotation data.

Examples

```
plotMetaDataCellsHeatmap(gobject)
```

plotMetaDataHeatmap	<i>plotMetaDataHeatmap</i>
---------------------	----------------------------

Description

Creates heatmap for genes within aggregated clusters.

Usage

```
plotMetaDataHeatmap(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  metadata_cols = NULL,
  selected_genes = NULL,
  first_meta_col = NULL,
  second_meta_col = NULL,
  show_values = c("zscores", "original", "zscores_rescaled"),
  custom_cluster_order = NULL,
  clus_cor_method = "pearson",
  clus_cluster_method = "complete",
  custom_gene_order = NULL,
  gene_cor_method = "pearson",
  gene_cluster_method = "complete",
  midpoint = 0,
  x_text_size = 10,
  x_text_angle = 45,
  y_text_size = 10,
  strip_text_size = 8,
  show_plot = NA,
  return_plot = NA,
  save_plot = NA,
```

```

    save_param = list(),
    default_save_name = "plotMetaDataHeatmap"
  )

```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	expression values to use
<code>metadata_cols</code>	annotation columns found in <code>pDataDT(gobject)</code>
<code>selected_genes</code>	subset of genes to use
<code>first_meta_col</code>	if more than 1 metadata column, select the x-axis factor
<code>second_meta_col</code>	if more than 1 metadata column, select the facetting factor
<code>show_values</code>	which values to show on heatmap
<code>custom_cluster_order</code>	custom cluster order (default = NULL)
<code>clus_cor_method</code>	correlation method for clusters
<code>clus_cluster_method</code>	hierarchical cluster method for the clusters
<code>custom_gene_order</code>	custom gene order (default = NULL)
<code>gene_cor_method</code>	correlation method for genes
<code>gene_cluster_method</code>	hierarchical cluster method for the genes
<code>midpoint</code>	midpoint of <code>show_values</code>
<code>x_text_size</code>	size of x-axis text
<code>x_text_angle</code>	angle of x-axis text
<code>y_text_size</code>	size of y-axis text
<code>strip_text_size</code>	size of strip text
<code>show_plot</code>	show plot
<code>return_plot</code>	return ggplot object
<code>save_plot</code>	directly save the plot [boolean]
<code>save_param</code>	list of saving parameters from all_plots_save_function
<code>default_save_name</code>	default save name

Details

Creates heatmap for the average expression of selected genes in the different annotation/cluster groups

Value

ggplot or data.table

See Also

[plotMetaDataCellsHeatmap](#) for numeric cell annotation instead of gene expression.

Examples

```
plotMetaDataHeatmap(gobject)
```

plotPCA	<i>plotPCA</i>
---------	----------------

Description

Short wrapper for PCA visualization

Usage

```
plotPCA(gobject, dim_reduction_name = "pca", default_save_name = "PCA", ...)
```

Arguments

- gobject giotto object
- dim_reduction_name dimension reduction name
- default_save_name default save name for saving, don't change, change save_name in save_param
- groub_by create multiple plots based on cell annotation column
- group_by_subset subset the group_by factor column
- dim1_to_use dimension to use on x-axis
- dim2_to_use dimension to use on y-axis
- spat_enr_names names of spatial enrichment results to include
- show_NN_network show underlying NN network
- nn_network_to_use type of NN network to use (kNN vs sNN)
- network_name name of NN network to use, if show_NN_network = TRUE
- cell_color color for cells (see details)
- color_as_factor convert color column to factor
- cell_color_code named vector with colors
- cell_color_gradient vector with 3 colors for numeric data
- gradient_midpoint midpoint for color gradient
- gradient_limits vector with lower and upper limits

<code>select_cell_groups</code>	select subset of cells/clusters based on <code>cell_color</code> parameter
<code>select_cells</code>	select subset of cells based on cell IDs
<code>show_other_cells</code>	display not selected cells
<code>other_cell_color</code>	color of not selected cells
<code>other_point_size</code>	size of not selected cells
<code>show_cluster_center</code>	plot center of selected clusters
<code>show_center_label</code>	plot label of selected clusters
<code>center_point_size</code>	size of center points
<code>label_size</code>	size of labels
<code>label_fontface</code>	font of labels
<code>edge_alpha</code>	column to use for alpha of the edges
<code>point_size</code>	size of point (cell)
<code>point_border_col</code>	color of border around points
<code>point_border_stroke</code>	stroke size of border around points
<code>show_legend</code>	show legend
<code>title</code>	title for plot, defaults to <code>cell_color</code> parameter
<code>legend_text</code>	size of legend text
<code>axis_text</code>	size of axis text
<code>axis_title</code>	size of axis title
<code>cow_n_col</code>	cowplot param: how many columns
<code>cow_rel_h</code>	cowplot param: relative height
<code>cow_rel_w</code>	cowplot param: relative width
<code>cow_align</code>	cowplot param: how to align
<code>show_plot</code>	show plot
<code>return_plot</code>	return ggplot object
<code>save_plot</code>	directly save the plot [boolean]
<code>save_param</code>	list of saving parameters from all_plots_save_function

Details

Description of parameters, see [dimPlot2D](#). For 3D plots see [plotPCA_3D](#)

Value

ggplot

Examples

```
plotPCA(gobject)
```

plotPCA_2D

plotPCA_2D

Description

Short wrapper for PCA visualization

Usage

```
plotPCA_2D(
  gobject,
  dim_reduction_name = "pca",
  default_save_name = "PCA_2D",
  ...
)
```

Arguments

<code>gobject</code>	giotto object
<code>dim_reduction_name</code>	dimension reduction name
<code>default_save_name</code>	default save name for saving, don't change, change <code>save_name</code> in <code>save_param</code>
<code>groub_by</code>	create multiple plots based on cell annotation column
<code>group_by_subset</code>	subset the <code>group_by</code> factor column
<code>dim1_to_use</code>	dimension to use on x-axis
<code>dim2_to_use</code>	dimension to use on y-axis
<code>spat_enr_names</code>	names of spatial enrichment results to include
<code>show_NN_network</code>	show underlying NN network
<code>nn_network_to_use</code>	type of NN network to use (kNN vs sNN)
<code>network_name</code>	name of NN network to use, if <code>show_NN_network = TRUE</code>
<code>cell_color</code>	color for cells (see details)
<code>color_as_factor</code>	convert color column to factor
<code>cell_color_code</code>	named vector with colors
<code>cell_color_gradient</code>	vector with 3 colors for numeric data
<code>gradient_midpoint</code>	midpoint for color gradient
<code>gradient_limits</code>	vector with lower and upper limits
<code>select_cell_groups</code>	select subset of cells/clusters based on <code>cell_color</code> parameter

<code>select_cells</code>	select subset of cells based on cell IDs
<code>show_other_cells</code>	display not selected cells
<code>other_cell_color</code>	color of not selected cells
<code>other_point_size</code>	size of not selected cells
<code>show_cluster_center</code>	plot center of selected clusters
<code>show_center_label</code>	plot label of selected clusters
<code>center_point_size</code>	size of center points
<code>label_size</code>	size of labels
<code>label_fontface</code>	font of labels
<code>edge_alpha</code>	column to use for alpha of the edges
<code>point_size</code>	size of point (cell)
<code>point_border_col</code>	color of border around points
<code>point_border_stroke</code>	stroke size of border around points
<code>title</code>	title for plot, defaults to <code>cell_color</code> parameter
<code>show_legend</code>	show legend
<code>legend_text</code>	size of legend text
<code>axis_text</code>	size of axis text
<code>axis_title</code>	size of axis title
<code>cow_n_col</code>	cowplot param: how many columns
<code>cow_rel_h</code>	cowplot param: relative height
<code>cow_rel_w</code>	cowplot param: relative width
<code>cow_align</code>	cowplot param: how to align
<code>show_plot</code>	show plot
<code>return_plot</code>	return ggplot object
<code>save_plot</code>	directly save the plot [boolean]
<code>save_param</code>	list of saving parameters from all_plots_save_function

Details

Description of parameters, see [dimPlot2D](#). For 3D plots see [plotPCA_3D](#)

Value

ggplot

Examples

```
plotPCA_2D(gobject)
```

plotPCA_3D

plotPCA_3D

Description

Visualize cells according to 3D PCA dimension reduction

Usage

```
plotPCA_3D(
  gobject,
  dim_reduction_name = "pca",
  default_save_name = "PCA_3D",
  ...
)
```

Arguments

<code>gobject</code>	giotto object
<code>dim_reduction_name</code>	pca dimension reduction name
<code>default_save_name</code>	default save name for saving, ideally change <code>save_name</code> in <code>save_param</code>
<code>dim1_to_use</code>	dimension to use on x-axis
<code>dim2_to_use</code>	dimension to use on y-axis
<code>dim3_to_use</code>	dimension to use on z-axis
<code>show_NN_network</code>	show underlying NN network
<code>nn_network_to_use</code>	type of NN network to use (kNN vs sNN)
<code>network_name</code>	name of NN network to use, if <code>show_NN_network</code> = TRUE
<code>cell_color</code>	color for cells (see details)
<code>color_as_factor</code>	convert color column to factor
<code>cell_color_code</code>	named vector with colors
<code>select_cell_groups</code>	select subset of cells/clusters based on <code>cell_color</code> parameter
<code>select_cells</code>	select subset of cells based on cell IDs
<code>show_other_cells</code>	display not selected cells
<code>other_cell_color</code>	color of not selected cells
<code>other_point_size</code>	size of not selected cells
<code>show_cluster_center</code>	plot center of selected clusters

show_center_label	plot label of selected clusters
center_point_size	size of center points
label_size	size of labels
edge_alpha	column to use for alpha of the edges
point_size	size of point (cell)
show_legend	show legend
show_plot	show plot
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function

Details

Description of parameters.

Value

plotly

Examples

```
plotPCA_3D(gobject)
```

plotTSNE	<i>plotTSNE</i>
----------	-----------------

Description

Short wrapper for tSNE visualization

Usage

```
plotTSNE(gobject, dim_reduction_name = "tsne", default_save_name = "tSNE", ...)
```

Arguments

gobject	giotto object
dim_reduction_name	dimension reduction name
default_save_name	default save name for saving, don't change, change save_name in save_param
groub_by	create multiple plots based on cell annotation column
group_by_subset	subset the group_by factor column
dim1_to_use	dimension to use on x-axis

dim2_to_use	dimension to use on y-axis
spat_enr_names	names of spatial enrichment results to include
show_NN_network	show underlying NN network
nn_network_to_use	type of NN network to use (kNN vs sNN)
network_name	name of NN network to use, if show_NN_network = TRUE
cell_color	color for cells (see details)
color_as_factor	convert color column to factor
cell_color_code	named vector with colors
cell_color_gradient	vector with 3 colors for numeric data
gradient_midpoint	midpoint for color gradient
gradient_limits	vector with lower and upper limits
select_cell_groups	select subset of cells/clusters based on cell_color parameter
select_cells	select subset of cells based on cell IDs
show_other_cells	display not selected cells
other_cell_color	color of not selected cells
other_point_size	size of not selected cells
show_cluster_center	plot center of selected clusters
show_center_label	plot label of selected clusters
center_point_size	size of center points
label_size	size of labels
label_fontface	font of labels
edge_alpha	column to use for alpha of the edges
point_size	size of point (cell)
point_border_col	color of border around points
point_border_stroke	stroke size of border around points
title	title for plot, defaults to cell_color parameter
show_legend	show legend
legend_text	size of legend text
axis_text	size of axis text
axis_title	size of axis title

cow_n_col	cowplot param: how many columns
cow_rel_h	cowplot param: relative height
cow_rel_w	cowplot param: relative width
cow_align	cowplot param: how to align
show_plot	show plot
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function

Details

Description of parameters, see [dimPlot2D](#). For 3D plots see [plotTSNE_3D](#)

Value

ggplot

Examples

```
plotTSNE(gobject)
```

plotTSNE_2D

plotTSNE_2D

Description

Short wrapper for tSNE visualization

Usage

```
plotTSNE_2D(
  gobject,
  dim_reduction_name = "tsne",
  default_save_name = "tSNE_2D",
  ...
)
```

Arguments

gobject	giotto object
dim_reduction_name	dimension reduction name
default_save_name	default save name for saving, don't change, change save_name in save_param
groub_by	create multiple plots based on cell annotation column
group_by_subset	subset the group_by factor column
dim1_to_use	dimension to use on x-axis

dim2_to_use	dimension to use on y-axis
spat_enr_names	names of spatial enrichment results to include
show_NN_network	show underlying NN network
nn_network_to_use	type of NN network to use (kNN vs sNN)
network_name	name of NN network to use, if show_NN_network = TRUE
cell_color	color for cells (see details)
color_as_factor	convert color column to factor
cell_color_code	named vector with colors
cell_color_gradient	vector with 3 colors for numeric data
gradient_midpoint	midpoint for color gradient
gradient_limits	vector with lower and upper limits
select_cell_groups	select subset of cells/clusters based on cell_color parameter
select_cells	select subset of cells based on cell IDs
show_other_cells	display not selected cells
other_cell_color	color of not selected cells
other_point_size	size of not selected cells
show_cluster_center	plot center of selected clusters
show_center_label	plot label of selected clusters
center_point_size	size of center points
label_size	size of labels
label_fontface	font of labels
edge_alpha	column to use for alpha of the edges
point_size	size of point (cell)
point_border_col	color of border around points
point_border_stroke	stroke size of border around points
title	title for plot, defaults to cell_color parameter
show_legend	show legend
legend_text	size of legend text
axis_text	size of axis text
axis_title	size of axis title

cow_n_col	cowplot param: how many columns
cow_rel_h	cowplot param: relative height
cow_rel_w	cowplot param: relative width
cow_align	cowplot param: how to align
show_plot	show plot
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function

Details

Description of parameters, see [dimPlot2D](#). For 3D plots see [plotTSNE_3D](#)

Value

ggplot

Examples

```
plotTSNE_2D(gobject)
```

plotTSNE_3D	<i>plotTSNE_3D</i>
-------------	--------------------

Description

Visualize cells according to dimension reduction coordinates

Usage

```
plotTSNE_3D(
  gobject,
  dim_reduction_name = "tsne",
  default_save_name = "TSNE_3D",
  ...
)
```

Arguments

gobject	giotto object
dim_reduction_name	tsne dimension reduction name
default_save_name	default save name for saving, don't change, change save_name in save_param
dim1_to_use	dimension to use on x-axis
dim2_to_use	dimension to use on y-axis
dim3_to_use	dimension to use on z-axis
show_NN_network	show underlying NN network

nn_network_to_use	type of NN network to use (kNN vs sNN)
network_name	name of NN network to use, if show_NN_network = TRUE
cell_color	color for cells (see details)
color_as_factor	convert color column to factor
cell_color_code	named vector with colors
select_cell_groups	select subset of cells/clusters based on cell_color parameter
select_cells	select subset of cells based on cell IDs
show_other_cells	display not selected cells
other_cell_color	color of not selected cells
other_point_size	size of not selected cells
show_cluster_center	plot center of selected clusters
show_center_label	plot label of selected clusters
center_point_size	size of center points
label_size	size of labels
edge_alpha	column to use for alpha of the edges
point_size	size of point (cell)
show_legend	show legend
show_plot	show plot
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function

Details

Description of parameters.

Value

plotly

Examples

```
plotTSNE_3D(gobject)
```

plotUMAP

plotUMAP

Description

Short wrapper for UMAP visualization

Usage

```
plotUMAP(gobject, dim_reduction_name = "umap", default_save_name = "UMAP", ...)
```

Arguments

gobject	giotto object
dim_reduction_name	dimension reduction name
default_save_name	default save name for saving, don't change, change save_name in save_param
groub_by	create multiple plots based on cell annotation column
group_by_subset	subset the group_by factor column
dim1_to_use	dimension to use on x-axis
dim2_to_use	dimension to use on y-axis
spat_enr_names	names of spatial enrichment results to include
show_NN_network	show underlying NN network
nn_network_to_use	type of NN network to use (kNN vs sNN)
network_name	name of NN network to use, if show_NN_network = TRUE
cell_color	color for cells (see details)
color_as_factor	convert color column to factor
cell_color_code	named vector with colors
cell_color_gradient	vector with 3 colors for numeric data
gradient_midpoint	midpoint for color gradient
gradient_limits	vector with lower and upper limits
select_cell_groups	select subset of cells/clusters based on cell_color parameter
select_cells	select subset of cells based on cell IDs
show_other_cells	display not selected cells
other_cell_color	color of not selected cells

other_point_size	size of not selected cells
show_cluster_center	plot center of selected clusters
show_center_label	plot label of selected clusters
center_point_size	size of center points
label_size	size of labels
label_fontface	font of labels
edge_alpha	column to use for alpha of the edges
point_size	size of point (cell)
point_border_col	color of border around points
point_border_stroke	stroke size of border around points
title	title for plot, defaults to cell_color parameter
show_legend	show legend
legend_text	size of legend text
axis_text	size of axis text
axis_title	size of axis title
cow_n_col	cowplot param: how many columns
cow_rel_h	cowplot param: relative height
cow_rel_w	cowplot param: relative width
cow_align	cowplot param: how to align
show_plot	show plot
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function

Details

Description of parameters, see [dimPlot2D](#). For 3D plots see [plotUMAP_3D](#)

Value

ggplot

Examples

```
plotUMAP(gobject)
```

plotUMAP_2D	<i>plotUMAP_2D</i>
-------------	--------------------

Description

Short wrapper for UMAP visualization

Usage

```
plotUMAP_2D(
  gobject,
  dim_reduction_name = "umap",
  default_save_name = "UMAP_2D",
  ...
)
```

Arguments

<code>gobject</code>	giotto object
<code>dim_reduction_name</code>	dimension reduction name
<code>default_save_name</code>	default save name for saving, don't change, change <code>save_name</code> in <code>save_param</code>
<code>groub_by</code>	create multiple plots based on cell annotation column
<code>group_by_subset</code>	subset the <code>group_by</code> factor column
<code>dim1_to_use</code>	dimension to use on x-axis
<code>dim2_to_use</code>	dimension to use on y-axis
<code>spat_enr_names</code>	names of spatial enrichment results to include
<code>show_NN_network</code>	show underlying NN network
<code>nn_network_to_use</code>	type of NN network to use (kNN vs sNN)
<code>network_name</code>	name of NN network to use, if <code>show_NN_network = TRUE</code>
<code>cell_color</code>	color for cells (see details)
<code>color_as_factor</code>	convert color column to factor
<code>cell_color_code</code>	named vector with colors
<code>cell_color_gradient</code>	vector with 3 colors for numeric data
<code>gradient_midpoint</code>	midpoint for color gradient
<code>gradient_limits</code>	vector with lower and upper limits
<code>select_cell_groups</code>	select subset of cells/clusters based on <code>cell_color</code> parameter

<code>select_cells</code>	select subset of cells based on cell IDs
<code>show_other_cells</code>	display not selected cells
<code>other_cell_color</code>	color of not selected cells
<code>other_point_size</code>	size of not selected cells
<code>show_cluster_center</code>	plot center of selected clusters
<code>show_center_label</code>	plot label of selected clusters
<code>center_point_size</code>	size of center points
<code>label_size</code>	size of labels
<code>label_fontface</code>	font of labels
<code>edge_alpha</code>	column to use for alpha of the edges
<code>point_size</code>	size of point (cell)
<code>point_border_col</code>	color of border around points
<code>point_border_stroke</code>	stroke size of border around points
<code>title</code>	title for plot, defaults to <code>cell_color</code> parameter
<code>show_legend</code>	show legend
<code>legend_text</code>	size of legend text
<code>axis_text</code>	size of axis text
<code>axis_title</code>	size of axis title
<code>cow_n_col</code>	cowplot param: how many columns
<code>cow_rel_h</code>	cowplot param: relative height
<code>cow_rel_w</code>	cowplot param: relative width
<code>cow_align</code>	cowplot param: how to align
<code>show_plot</code>	show plot
<code>return_plot</code>	return ggplot object
<code>save_plot</code>	directly save the plot [boolean]
<code>save_param</code>	list of saving parameters from all_plots_save_function

Details

Description of parameters, see [dimPlot2D](#). For 3D plots see [plotUMAP_3D](#)

Value

ggplot

Examples

```
plotUMAP_2D(gobject)
```

plotUMAP_3D

plotUMAP_3D

Description

Visualize cells according to dimension reduction coordinates

Usage

```
plotUMAP_3D(
  gobject,
  dim_reduction_name = "umap",
  default_save_name = "UMAP_3D",
  ...
)
```

Arguments

<code>gobject</code>	giotto object
<code>dim_reduction_name</code>	umap dimension reduction name
<code>default_save_name</code>	default save name for saving, don't change, change <code>save_name</code> in <code>save_param</code>
<code>dim1_to_use</code>	dimension to use on x-axis
<code>dim2_to_use</code>	dimension to use on y-axis
<code>dim3_to_use</code>	dimension to use on z-axis
<code>show_NN_network</code>	show underlying NN network
<code>nn_network_to_use</code>	type of NN network to use (kNN vs sNN)
<code>network_name</code>	name of NN network to use, if <code>show_NN_network</code> = TRUE
<code>cell_color</code>	color for cells (see details)
<code>color_as_factor</code>	convert color column to factor
<code>cell_color_code</code>	named vector with colors
<code>select_cell_groups</code>	select subset of cells/clusters based on <code>cell_color</code> parameter
<code>select_cells</code>	select subset of cells based on cell IDs
<code>show_other_cells</code>	display not selected cells
<code>other_cell_color</code>	color of not selected cells
<code>other_point_size</code>	size of not selected cells
<code>show_cluster_center</code>	plot center of selected clusters

show_center_label	plot label of selected clusters
center_point_size	size of center points
label_size	size of labels
edge_alpha	column to use for alpha of the edges
point_size	size of point (cell)
show_legend	show legend
show_plot	show plot
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function

Details

Description of parameters.

Value

plotly

Examples

```
plotUMAP_3D(gobject)
```

```
plot_network_layer_ggplot
      plot_network_layer_ggplot
```

Description

Visualize cells in network layer according to dimension reduction coordinates

Usage

```
plot_network_layer_ggplot(
  gobject,
  annotated_network_DT,
  edge_alpha = NULL,
  show_legend = T
)
```

Arguments

annotated_network_DT	annotated network data.table of selected cells
edge_alpha	alpha of network edges
show_legend	show legend
gobject	giotto object

Details

Description of parameters.

Value

ggplot

Examples

```
plot_network_layer_ggplot(gobject)
```

```
plot_point_layer_ggplot
```

```
plot_point_layer_ggplot
```

Description

Visualize cells in point layer according to dimension reduction coordinates

Usage

```
plot_point_layer_ggplot(
  ggobject,
  annotated_DT_selected,
  annotated_DT_other,
  cell_color = NULL,
  color_as_factor = T,
  cell_color_code = NULL,
  cell_color_gradient = c("blue", "white", "red"),
  gradient_midpoint = 0,
  gradient_limits = NULL,
  select_cell_groups = NULL,
  select_cells = NULL,
  point_size = 1,
  point_border_col = "black",
  point_border_stroke = 0.1,
  show_cluster_center = F,
  show_center_label = T,
  center_point_size = 4,
  center_point_border_col = "black",
  center_point_border_stroke = 0.1,
  label_size = 4,
  label_fontface = "bold",
  edge_alpha = NULL,
  show_other_cells = T,
  other_cell_color = "lightgrey",
  other_point_size = 0.5,
  show_legend = T
)
```

Arguments

annotated_DT_selected	annotated data.table of selected cells
annotated_DT_other	annotated data.table of not selected cells
cell_color	color for cells (see details)
color_as_factor	convert color column to factor
cell_color_code	named vector with colors
cell_color_gradient	vector with 3 colors for numeric data
gradient_midpoint	midpoint for color gradient
gradient_limits	vector with lower and upper limits
select_cell_groups	select subset of cells/clusters based on cell_color parameter
select_cells	select subset of cells based on cell IDs
point_size	size of point (cell)
point_border_col	color of border around points
point_border_stroke	stroke size of border around points
show_cluster_center	plot center of selected clusters
show_center_label	plot label of selected clusters
center_point_size	size of center points
label_size	size of labels
label_fontface	font of labels
edge_alpha	column to use for alpha of the edges
show_other_cells	display not selected cells
other_cell_color	color of not selected cells
other_point_size	size of not selected cells
show_legend	show legend
gobject	giotto object

Details

Description of parameters.

Value

ggplot

Examples

```
plot_point_layer_ggplot(gobject)
```

```
plot_spat_point_layer_ggplot
      plot_spat_point_layer_ggplot
```

Description

creat ggplot point layer for spatial coordinates

Usage

```
plot_spat_point_layer_ggplot(
  ggobject,
  sdimx = NULL,
  sdimy = NULL,
  cell_locations_metadata_selected,
  cell_locations_metadata_other,
  cell_color = NULL,
  color_as_factor = T,
  cell_color_code = NULL,
  cell_color_gradient = c("blue", "white", "red"),
  gradient_midpoint = NULL,
  gradient_limits = NULL,
  select_cell_groups = NULL,
  select_cells = NULL,
  point_size = 2,
  point_border_col = "lightgrey",
  point_border_stroke = 0.1,
  show_cluster_center = F,
  show_center_label = T,
  center_point_size = 4,
  center_point_border_col = "black",
  center_point_border_stroke = 0.1,
  label_size = 4,
  label_fontface = "bold",
  show_other_cells = T,
  other_cell_color = "lightgrey",
  other_point_size = 1,
  show_legend = TRUE
)
```

Arguments

sdimx	x-axis dimension name (default = 'sdimx')
sdimy	y-axis dimension name (default = 'sdimy')
cell_locations_metadata_selected	annotated location from selected cells

<code>cell_locations_metadata_other</code>	annotated location from non-selected cells
<code>cell_color</code>	color for cells (see details)
<code>color_as_factor</code>	convert color column to factor
<code>cell_color_code</code>	named vector with colors
<code>cell_color_gradient</code>	vector with 3 colors for numeric data
<code>gradient_midpoint</code>	midpoint for color gradient
<code>gradient_limits</code>	vector with lower and upper limits
<code>select_cell_groups</code>	select subset of cells/clusters based on <code>cell_color</code> parameter
<code>select_cells</code>	select subset of cells based on cell IDs
<code>point_size</code>	size of point (cell)
<code>point_border_col</code>	color of border around points
<code>point_border_stroke</code>	stroke size of border around points
<code>show_cluster_center</code>	plot center of selected clusters
<code>show_center_label</code>	plot label of selected clusters
<code>center_point_size</code>	size of center points
<code>label_size</code>	size of labels
<code>label_fontface</code>	font of labels
<code>show_other_cells</code>	display not selected cells
<code>other_cell_color</code>	color for not selected cells
<code>other_point_size</code>	point size for not selected cells
<code>show_legend</code>	show legend
<code>gobject</code>	giotto object

Details

Description of parameters.

Value

ggplot

Examples

```
plot_spat_point_layer_ggplot(gobject)
```

print.giotto	<i>print method for giotto class</i>
--------------	--------------------------------------

Description

print method for giotto class. Prints the chosen number of genes (rows) and cells (columns) from the raw count matrix. Also print the spatial locations for the chosen number of cells.

Usage

```
print.giotto(object, ...)
```

Arguments

nr_genes	number of genes (rows) to print
nr_cells	number of cells (columns) to print

rankEnrich	<i>rankEnrich</i>
------------	-------------------

Description

Function to calculate gene signature enrichment scores per spatial position using a rank based approach.

Usage

```
rankEnrich(
  gobject,
  sign_matrix,
  expression_values = c("normalized", "scaled", "custom"),
  reverse_log_scale = TRUE,
  logbase = 2,
  output_enrichment = c("original", "zscore")
)
```

Arguments

gobject	Giotto object
sign_matrix	Matrix of signature genes for each cell type / process
expression_values	expression values to use
reverse_log_scale	reverse expression values from log scale
logbase	log base to use if reverse_log_scale = TRUE
output_enrichment	how to return enrichment output

Details

sign_matrix: a rank-fold matrix with genes as row names and cell-types as column names. Alternatively a scRNA-seq matrix and vector with clusters can be provided to makeSignMatrixRank, which will create the matrix for you.

First a new rank is calculated as $R = (R1 * R2)^{(1/2)}$, where R1 is the rank of fold-change for each gene in each spot and R2 is the rank of each marker in each cell type. The Rank-Biased Precision is then calculated as: $RBP = (1 - 0.99) * (0.99)^{(R - 1)}$ and the final enrichment score is then calculated as the sum of top 100 RBPs.

Value

data.table with enrichment results

See Also

[makeSignMatrixRank](#)

Examples

```
rankEnrich(gobject)
```

rankSpatialCorGroups	<i>rankSpatialCorGroups</i>
----------------------	-----------------------------

Description

Rank spatial correlated clusters according to correlation structure

Usage

```
rankSpatialCorGroups(
  gobject,
  spatCorObject,
  use_clus_name = NULL,
  show_plot = NA,
  return_plot = FALSE,
  save_plot = NA,
  save_param = list(),
  default_save_name = "rankSpatialCorGroups"
)
```

Arguments

gobject	giotto object
spatCorObject	spatial correlation object
use_clus_name	name of clusters to visualize (from clusterSpatialCorGenes())
show_plot	show plot
return_plot	return ggplot object

save_plot directly save the plot [boolean]
 save_param list of saving parameters from [all_plots_save_function](#)
 default_save_name default save name for saving, don't change, change save_name in save_param

Value

data.table with positive (within group) and negative (outside group) scores

Examples

```
rankSpatialCorGroups(gobject)
```

rank_binarize	<i>rank_binarize</i>
---------------	----------------------

Description

create binarized scores using arbitrary rank of top genes

Usage

```
rank_binarize(x, max_rank = 200)
```

readGiottoInstructions	<i>readGiottoInstructions</i>
------------------------	-------------------------------

Description

Retrieves the instruction associated with the provided parameter

Usage

```
readGiottoInstructions(giotto_instructions, param = NULL)
```

Arguments

giotto_instructions giotto object or result from createGiottoInstructions()
 param parameter to retrieve

Value

specific parameter

Examples

```
readGiottoInstructions()
```

removeCellAnnotation	<i>removeCellAnnotation</i>
----------------------	-----------------------------

Description

removes cell annotation of giotto object

Usage

```
removeCellAnnotation(gobject, columns = NULL, return_gobject = TRUE)
```

Arguments

gobject	giotto object
columns	names of columns to remove
return_gobject	boolean: return giotto object (default = TRUE)

Details

if return_gobject = FALSE, it will return the cell metadata

Value

giotto object

Examples

```
removeCellAnnotation(gobject)
```

removeGeneAnnotation	<i>removeGeneAnnotation</i>
----------------------	-----------------------------

Description

removes gene annotation of giotto object

Usage

```
removeGeneAnnotation(gobject, columns = NULL, return_gobject = TRUE)
```

Arguments

gobject	giotto object
columns	names of columns to remove
return_gobject	boolean: return giotto object (default = TRUE)

Details

if return_gobject = FALSE, it will return the gene metadata

Value

giotto object

Examples

```
removeGeneAnnotation(gobject)
```

```
replaceGiottoInstructions
      replaceGiottoInstructions
```

Description

Function to replace all instructions from giotto object

Usage

```
replaceGiottoInstructions(gobject, instructions = NULL)
```

Arguments

<code>gobject</code>	giotto object
<code>instructions</code>	new instructions (e.g. result from <code>createGiottoInstructions</code>)

Value

named vector with giotto instructions

Examples

```
replaceGiottoInstructions()
```

```
runPCA      runPCA
```

Description

runs a Principal Component Analysis

Usage

```
runPCA(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  reduction = c("cells", "genes"),
  name = "pca",
  genes_to_use = NULL,
  return_gobject = TRUE,
  scale_unit = F,
  ncp = 200,
  ...
)
```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	expression values to use
<code>reduction</code>	cells or genes
<code>name</code>	arbitrary name for PCA run
<code>genes_to_use</code>	subset of genes to use for PCA
<code>return_gobject</code>	boolean: return giotto object (default = TRUE)
<code>scale_unit</code>	scale features before PCA
<code>ncp</code>	number of principal components to calculate
<code>...</code>	additional parameters for PCA (see details)

Details

See [PCA](#) for more information about other parameters.

Value

giotto object with updated PCA dimension reduction

Examples

```
runPCA(gobject)
```

<code>runtSNE</code>	<i>runtSNE</i>
----------------------	----------------

Description

run tSNE

Usage

```
runtSNE(  
  gobject,  
  expression_values = c("normalized", "scaled", "custom"),  
  reduction = c("cells", "genes"),  
  dim_reduction_to_use = "pca",  
  dim_reduction_name = "pca",  
  dimensions_to_use = 1:10,  
  name = "tsne",  
  genes_to_use = NULL,  
  return_gobject = TRUE,  
  dims = 2,  
  perplexity = 30,  
  theta = 0.5,  
  do_PCA_first = F,  
  set_seed = T,  
  seed_number = 1234,  
  ...  
)
```


Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	expression values to use
<code>reduction</code>	cells or genes
<code>dim_reduction_to_use</code>	use another dimension reduction set as input
<code>dim_reduction_name</code>	name of dimension reduction set to use
<code>dimensions_to_use</code>	number of dimensions to use as input
<code>name</code>	arbitrary name for tSNE run
<code>genes_to_use</code>	if <code>dim_reduction_to_use = NULL</code> , which genes to use
<code>return_gobject</code>	boolean: return giotto object (default = TRUE)
<code>dims</code>	tSNE param: number of dimensions to return
<code>perplexity</code>	tSNE param: perplexity
<code>theta</code>	tSNE param: theta
<code>do_PCA_first</code>	tSNE param: do PCA before tSNE (default = FALSE)
<code>set_seed</code>	use of seed
<code>seed_number</code>	seed number to use
<code>...</code>	additional tSNE parameters

Details

See [Rtsne](#) for more information about these and other parameters.

- Input for tSNE dimension reduction can be another dimension reduction (default = 'pca')
- To use gene expression as input set `dim_reduction_to_use = NULL`
- multiple tSNE results can be stored by changing the *name* of the analysis

Value

giotto object with updated tSNE dimension reduction

Examples

```
runtSNE(gobject)
```

runUMAP

*runUMAP***Description**

run UMAP

Usage

```
runUMAP(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  reduction = c("cells", "genes"),
  dim_reduction_to_use = "pca",
  dim_reduction_name = "pca",
  dimensions_to_use = 1:10,
  name = "umap",
  genes_to_use = NULL,
  return_gobject = TRUE,
  n_neighbors = 40,
  n_components = 2,
  n_epochs = 400,
  min_dist = 0.01,
  n_threads = 1,
  spread = 5,
  set_seed = T,
  seed_number = 1234,
  ...
)
```

Arguments

gobject	giotto object
expression_values	expression values to use
reduction	cells or genes
dim_reduction_to_use	use another dimension reduction set as input
dim_reduction_name	name of dimension reduction set to use
dimensions_to_use	number of dimensions to use as input
name	arbitrary name for UMAP run
genes_to_use	if dim_reduction_to_use = NULL, which genes to use
return_gobject	boolean: return giotto object (default = TRUE)
n_neighbors	UMAP param: number of neighbors
n_components	UMAP param: number of components
n_epochs	UMAP param: number of epochs

min_dist	UMAP param: minimum distance
n_threads	UMAP param: threads to use
spread	UMAP param: spread
set_seed	use of seed
seed_number	seed number to use
...	additional UMAP parameters

Details

See [umap](#) for more information about these and other parameters.

- Input for UMAP dimension reduction can be another dimension reduction (default = 'pca')
- To use gene expression as input set `dim_reduction_to_use = NULL`
- multiple UMAP results can be stored by changing the *name* of the analysis

Value

giotto object with updated UMAP dimension reduction

Examples

```
runUMAP(gobject)
```

selectPatternGenes	<i>selectPatternGenes</i>
--------------------	---------------------------

Description

Select genes correlated with spatial patterns

Usage

```
selectPatternGenes(
  spatPatObj,
  dimensions = 1:5,
  top_pos_genes = 10,
  top_neg_genes = 10,
  min_pos_cor = 0.5,
  min_neg_cor = -0.5,
  return_top_selection = FALSE
)
```

Arguments

spatPatObj	Output from detectSpatialPatterns
dimensions	dimensions to identify correlated genes for.
top_pos_genes	Top positively correlated genes.
top_neg_genes	Top negatively correlated genes.
min_pos_cor	Minimum positive correlation score to include a gene.
min_neg_cor	Minimum negative correlation score to include a gene.

Details

Description.

Value

Data.table with genes associated with selected dimension (PC).

Examples

```
selectPatternGenes(gobject)
```

```
select_expression_values  
      select_expression_values
```

Description

helper function to select expression values

Usage

```
select_expression_values(gobject, values)
```

Arguments

gobject	giotto object
values	expression values to extract

Value

expression matrix

```
show,giotto-method      show method for giotto class
```

Description

show method for giotto class

Usage

```
## S4 method for signature 'giotto'  
show(object)
```

showClusterDendrogram *showClusterDendrogram*

Description

Creates dendrogram for selected clusters.

Usage

```
showClusterDendrogram(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  cluster_column,
  cor = c("pearson", "spearman"),
  distance = "ward.D",
  h = NULL,
  h_color = "red",
  rotate = FALSE,
  show_plot = NA,
  return_plot = NA,
  save_plot = NA,
  save_param = list(),
  default_save_name = "showClusterDendrogram",
  ...
)
```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	expression values to use
<code>cluster_column</code>	name of column to use for clusters
<code>cor</code>	correlation score to calculate distance
<code>distance</code>	distance method to use for hierarchical clustering
<code>h</code>	height of horizontal lines to plot
<code>h_color</code>	color of horizontal lines
<code>rotate</code>	rotate dendrogram 90 degrees
<code>show_plot</code>	show plot
<code>return_plot</code>	return ggplot object
<code>save_plot</code>	directly save the plot [boolean]
<code>save_param</code>	list of saving parameters from all_plots_save_function
<code>default_save_name</code>	default save name for saving, don't change, change <code>save_name</code> in <code>save_param</code>
<code>...</code>	additional parameters for <code>ggdendrogram()</code>

Details

Expression correlation dendrogram for selected clusters.

Value

ggplot

Examples

```
showClusterDendrogram(gobject)
```

showClusterHeatmap	<i>showClusterHeatmap</i>
--------------------	---------------------------

Description

Creates heatmap based on identified clusters

Usage

```
showClusterHeatmap(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  genes = "all",
  cluster_column,
  cor = c("pearson", "spearman"),
  distance = "ward.D",
  show_plot = NA,
  return_plot = NA,
  save_plot = NA,
  save_param = list(),
  default_save_name = "showClusterHeatmap",
  ...
)
```

Arguments

gobject	giotto object
expression_values	expression values to use
genes	vector of genes to use, default to 'all'
cluster_column	name of column to use for clusters
cor	correlation score to calculate distance
distance	distance method to use for hierarchical clustering
show_plot	show plot
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function
default_save_name	default save name for saving, don't change, change save_name in save_param
...	additional parameters for the Heatmap function from ComplexHeatmap

Details

Correlation heatmap of selected clusters.

Value

ggplot

Examples

```
showClusterHeatmap(gobject)
```

showCPGscores	<i>showCPGscores</i>
---------------	----------------------

Description

visualize Cell Proximity Gene enrichment scores

Usage

```
showCPGscores(  
  gobject,  
  CPGscore,  
  method = c("volcano", "cell_barplot", "cell-cell", "cell_sankey"),  
  min_cells = 5,  
  min_fdr = 0.05,  
  min_spat_diff = 0.2,  
  min_log2_fc = 0.5,  
  keep_int_duplicates = TRUE,  
  direction = c("both", "up", "down"),  
  cell_color_code = NULL,  
  show_plot = NA,  
  return_plot = NA,  
  save_plot = NA,  
  save_param = list(),  
  default_save_name = "showCPGscores"  
)
```

Arguments

CPGscore	CPGscore, output from getCellProximityGeneScores()
method	visualization method
min_cells	min number of cells threshold
min_fdr	fdr threshold
min_spat_diff	spatial difference threshold
min_log2_fc	min log2 fold-change
keep_int_duplicates	keep both cell_A-cell_B and cell_B-cell_A
direction	up or downregulation or both

cell_color_code	color code for cell types
show_plot	show plot
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function
default_save_name	default save name for saving, don't change, change save_name in save_param

Details

Give more details ...

Value

Gene to gene scores in data.table format

Examples

```
showCPGscores(CPGscore)
```

showGeneExpressionProximityScore
<i>showGeneExpressionProximityScore</i>

Description

Create heatmap from cell-cell proximity scores

Usage

```
showGeneExpressionProximityScore(  
  scores,  
  selected_gene,  
  sort_column = "diff_spat"  
)
```

Arguments

scores	CPscore, output from getAverageCellProximityGeneScores()
selected_gene	gene to show
sort_column	column name to use for sorting

Details

Give more details ...

Value

ggplot barplot

Examples

```
showGeneExpressionProximityScore(scores)
```

```
showGiottoInstructions
      showGiottoInstructions
```

Description

Function to display all instructions from giotto object

Usage

```
showGiottoInstructions(gobject)
```

Arguments

gobject giotto object

Value

named vector with giotto instructions

Examples

```
showGiottoInstructions()
```

```
showGTGscores                  showGTGscores
```

Description

visualize Cell Proximity Gene enrichment scores

Usage

```
showGTGscores(
  GTGscore,
  method = c("cell_barplot", "cell-cell", "cell_sankey"),
  min_cells = 5,
  min_pval = 0.05,
  min_spat_diff = 0.2,
  min_log2_fc = 0.5,
  direction = c("both", "up", "down"),
  cell_color_code = NULL,
  show_plot = T,
  specific_genes_1 = NULL,
  specific_genes_2 = NULL,
  first_cell_name = "ligand cell",
  second_cell_name = "receptor cell",
  return_DT = F
)
```

Arguments

method	visualization method
min_cells	min number of cells threshold
min_pval	p-value threshold
min_spat_diff	spatial difference threshold
min_log2_fc	log2 fold-change threshold
direction	up or downregulation or both
cell_color_code	color code for cell types
show_plot	print plot
specific_genes_1	subset of genes, matched with specific_genes_2
specific_genes_2	subset of genes, matched with specific_genes_1
first_cell_name	name for first cells
second_cell_name	name for second cells
CPGscore	CPGscore, output from getCellProximityGeneScores()

Details

Give more details ...

Value

ggplot

Examples

```
showGTGscores(CPGscore)
```

```
showIntExpressionProximityScore
```

```
showIntExpressionProximityScore
```

Description

Create heatmap from cell-cell proximity scores

Usage

```
showIntExpressionProximityScore(
  scores,
  selected_interaction,
  sort_column = "diff_spat",
  show_enriched_n = 5,
  show_depleted_n = 5
)
```

Arguments

- scores scores, output from getAverageCellProximityGeneScores()
- selected_interaction interaction to show
- sort_column column name to use for sorting
- show_enriched_n show top enriched interactions
- show_depleted_n show top depleted interactions

Details

Give more details ...

Value

ggplot barplot

Examples

showIntExpressionProximityScore(scores)

showPattern	<i>showPattern</i>
-------------	--------------------

Description

show patterns for 2D spatial data

Usage

showPattern(gobject, spatPatObj, ...)

Arguments

- gobject giotto object
- spatPatObj Output from detectSpatialPatterns
- dimension dimension to plot
- trim Trim ends of the PC values.
- background_color background color for plot
- grid_border_color color for grid
- show_legend show legend of ggplot
- show_plot show plot
- return_plot return ggplot object
- save_plot directly save the plot [boolean]
- save_param list of saving parameters from [all_plots_save_function](#)
- default_save_name default save name for saving, don't change, change save_name in save_param

Value

ggplot

See Also

[showPattern2D](#)

Examples

```
showPattern(gobject)
```

showPattern2D	<i>showPattern2D</i>
---------------	----------------------

Description

show patterns for 2D spatial data

Usage

```
showPattern2D(  
  gobject,  
  spatPatObj,  
  dimension = 1,  
  trim = c(0.02, 0.98),  
  background_color = "white",  
  grid_border_color = "grey",  
  show_legend = T,  
  point_size = 1,  
  show_plot = NA,  
  return_plot = NA,  
  save_plot = NA,  
  save_param = list(),  
  default_save_name = "showPattern2D"  
)
```

Arguments

gobject	giotto object
spatPatObj	Output from detectSpatialPatterns
dimension	dimension to plot
trim	Trim ends of the PC values.
background_color	background color for plot
grid_border_color	color for grid
show_legend	show legend of ggplot
show_plot	show plot
return_plot	return ggplot object

save_plot directly save the plot [boolean]
 save_param list of saving parameters from [all_plots_save_function](#)
 default_save_name default save name for saving, don't change, change save_name in save_param

Value

ggplot

Examples

```
showPattern2D(gobject)
```

showPattern3D	<i>showPattern3D</i>
---------------	----------------------

Description

show patterns for 3D spatial data

Usage

```
showPattern3D(
  gobject,
  spatPatObj,
  dimension = 1,
  trim = c(0.02, 0.98),
  background_color = "white",
  grid_border_color = "grey",
  show_legend = T,
  point_size = 1,
  axis_scale = c("cube", "real", "custom"),
  custom_ratio = NULL,
  x_ticks = NULL,
  y_ticks = NULL,
  z_ticks = NULL,
  show_plot = NA,
  return_plot = NA,
  save_plot = NA,
  save_param = list(),
  default_save_name = "showPattern3D"
)
```

Arguments

gobject giotto object
 spatPatObj Output from detectSpatialPatterns
 dimension dimension to plot
 trim Trim ends of the PC values.
 background_color background color for plot

grid_border_color	color for grid
show_legend	show legend of plot
point_size	adjust the point size
axis_scale	scale the axis
custom_ratio	customize the scale of the axis
x_ticks	the tick number of x_axis
y_ticks	the tick number of y_axis
z_ticks	the tick number of z_axis
show_plot	show plot
return_plot	return plot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function
default_save_name	default save name for saving, don't change, change save_name in save_param

Value

plotly

Examples

showPattern3D(gobject)

showPatternGenes	<i>showPatternGenes</i>
------------------	-------------------------

Description

show genes correlated with spatial patterns

Usage

```
showPatternGenes(  
  gobject,  
  spatPatObj,  
  dimension = 1,  
  top_pos_genes = 5,  
  top_neg_genes = 5,  
  point_size = 1,  
  return_DT = FALSE,  
  show_plot = NA,  
  return_plot = NA,  
  save_plot = NA,  
  save_param = list(),  
  default_save_name = "showPatternGenes"  
)
```

Arguments

<code>gobject</code>	giotto object
<code>spatPatObj</code>	Output from <code>detectSpatialPatterns</code>
<code>dimension</code>	dimension to plot genes for.
<code>top_pos_genes</code>	Top positively correlated genes.
<code>top_neg_genes</code>	Top negatively correlated genes.
<code>point_size</code>	size of points
<code>return_DT</code>	if TRUE, it will return the data.table used to generate the plots
<code>show_plot</code>	show plot
<code>return_plot</code>	return ggplot object
<code>save_plot</code>	directly save the plot [boolean]
<code>save_param</code>	list of saving parameters from <code>all_plots_save_function()</code>
<code>default_save_name</code>	default save name for saving, don't change, change <code>save_name</code> in <code>save_param</code>

Value

ggplot

Examples

```
showPatternGenes(gobject)
```

<code>showProcessingSteps</code>	<i>showProcessingSteps</i>
----------------------------------	----------------------------

Description

shows the sequential processing steps that were performed in a summarized format

Usage

```
showProcessingSteps(gobject)
```

Arguments

<code>gobject</code>	giotto object
----------------------	---------------

Value

list of processing steps and names

Examples

```
showProcessingSteps(gobject)
```

showSpatialCorGenes	<i>showSpatialCorGenes</i>
---------------------	----------------------------

Description

Shows and filters spatially correlated genes

Usage

```
showSpatialCorGenes(
  spatCorObject,
  use_clus_name = NULL,
  selected_clusters = NULL,
  genes = NULL,
  min_spat_cor = 0.5,
  min_expr_cor = NULL,
  min_cor_diff = NULL,
  min_rank_diff = NULL,
  show_top_genes = NULL
)
```

Arguments

spatCorObject	spatial correlation object
use_clus_name	cluster information to show
selected_clusters	subset of clusters to show
genes	subset of genes to show
min_spat_cor	filter on minimum spatial correlation
min_expr_cor	filter on minimum single-cell expression correlation
min_cor_diff	filter on minimum correlation difference (spatial vs expression)
min_rank_diff	filter on minimum correlation rank difference (spatial vs expression)
show_top_genes	show top genes per gene

Value

data.table with filtered information

Examples

```
showSpatialCorGenes(gobject)
```

showTopGeneToGene	<i>showTopGeneToGene</i>
-------------------	--------------------------

Description

Show enriched/depleted gene-gene enrichments

Usage

```
showTopGeneToGene(  
  GTGscore,  
  top_interactions = 10,  
  direction = c("increased", "decreased"),  
  complement_data = T,  
  subset_cell_ints = NULL,  
  subset_genes = NULL  
)
```

Arguments

- GTGscore GTGscore, output from getGeneToGeneScores()
- top_interactions number of top gene-gene enrichments to show
- direction show top increased or decreased gene-gene enrichments
- complement_data include non-enriched gene-gene scores from other cell-cell interactions
- subset_cell_ints subset cell-cell interactions to show
- subset_genes subset genes to show

Details

Give more details ...

Value

ggplot barplot

Examples

```
showTopGeneToGene(scores)
```

signPCA

*signPCA***Description**

identify significant principal components (PCs)

Usage

```
signPCA(
  gobject,
  method = c("screeplot", "jackstraw"),
  expression_values = c("normalized", "scaled", "custom"),
  reduction = c("cells", "genes"),
  genes_to_use = NULL,
  scale_unit = T,
  ncp = 50,
  scree_labels = T,
  scree_ylim = c(0, 10),
  jack_iter = 10,
  jack_threshold = 0.01,
  jack_verbose = T,
  show_plot = NA,
  return_plot = NA,
  save_plot = NA,
  save_param = list(),
  default_save_name = "signPCA",
  ...
)
```

Arguments

<code>gobject</code>	giotto object
<code>method</code>	method to use to identify significant PCs
<code>expression_values</code>	expression values to use
<code>reduction</code>	cells or genes
<code>genes_to_use</code>	subset of genes to use for PCA
<code>scale_unit</code>	scale features before PCA
<code>ncp</code>	number of principal components to calculate
<code>scree_labels</code>	show labels on scree plot
<code>scree_ylim</code>	y-axis limits on scree plot
<code>jack_iter</code>	number of iterations for jackstraw
<code>jack_threshold</code>	p-value threshold to call a PC significant
<code>jack_verbose</code>	show progress of jackstraw method
<code>show_plot</code>	show plot
<code>return_plot</code>	return ggplot object

save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function()
default_save_name	default save name for saving, don't change, change save_name in save_param
...	additional parameters for PCA

Details

Two different methods can be used to assess the number of relevant or significant principal components (PC's).

1. Screeplot works by plotting the explained variance of each individual PC in a barplot allowing you to identify which PC does not show a significant contribution anymore (= 'elbow method').
2. The Jackstraw method uses the [permutationPA](#) function. By systematically permuting genes it identifies robust, and thus significant, PCs.

multiple PCA results can be stored by changing the *name* parameter

Value

ggplot object for scree method and maxtrix of p-values for jackstraw

Examples

```
signPCA(gobject)
```

spatCellPlot	<i>spatCellPlot</i>
--------------	---------------------

Description

Visualize cells according to spatial coordinates

Usage

```
spatCellPlot(
  gobject,
  sdimx = "sdimx",
  sdimy = "sdimy",
  spat_enr_names = NULL,
  cell_annotation_values,
  cell_color_gradient = c("blue", "white", "red"),
  gradient_midpoint = NULL,
  gradient_limits = NULL,
  select_cell_groups = NULL,
  select_cells = NULL,
  point_size = 3,
  point_border_col = "black",
  point_border_stroke = 0.1,
  show_cluster_center = F,
  show_center_label = F,
  center_point_size = 4,
  center_point_border_col = "black",
```

```

center_point_border_stroke = 0.1,
label_size = 4,
label_fontface = "bold",
show_network = F,
spatial_network_name = "spatial_network",
network_color = NULL,
network_alpha = 1,
show_grid = F,
spatial_grid_name = "spatial_grid",
grid_color = NULL,
show_other_cells = T,
other_cell_color = "lightgrey",
other_point_size = 1,
other_cells_alpha = 0.1,
coord_fix_ratio = NULL,
show_legend = T,
legend_text = 8,
axis_text = 8,
axis_title = 8,
cow_n_col = 2,
cow_rel_h = 1,
cow_rel_w = 1,
cow_align = "h",
show_plot = NA,
return_plot = NA,
save_plot = NA,
save_param = list(),
default_save_name = "spatCellPlot"
)

```

Arguments

<code>gobject</code>	giotto object
<code>sdimx</code>	x-axis dimension name (default = 'sdimx')
<code>sdimy</code>	y-axis dimension name (default = 'sdimy')
<code>spat_enr_names</code>	names of spatial enrichment results to include
<code>cell_annotation_values</code>	numeric cell annotation columns
<code>cell_color_gradient</code>	vector with 3 colors for numeric data
<code>gradient_midpoint</code>	midpoint for color gradient
<code>gradient_limits</code>	vector with lower and upper limits
<code>select_cell_groups</code>	select subset of cells/clusters based on <code>cell_color</code> parameter
<code>select_cells</code>	select subset of cells based on cell IDs
<code>point_size</code>	size of point (cell)
<code>point_border_col</code>	color of border around points

point_border_stroke	stroke size of border around points
show_cluster_center	plot center of selected clusters
show_center_label	plot label of selected clusters
center_point_size	size of center points
label_size	size of labels
label_fontface	font of labels
show_network	show underlying spatial network
spatial_network_name	name of spatial network to use
network_color	color of spatial network
network_alpha	alpha of spatial network
show_grid	show spatial grid
spatial_grid_name	name of spatial grid to use
grid_color	color of spatial grid
show_other_cells	display not selected cells
other_cell_color	color of not selected cells
other_point_size	point size of not selected cells
other_cells_alpha	alpha of not selected cells
coord_fix_ratio	fix ratio between x and y-axis
show_legend	show legend
legend_text	size of legend text
axis_text	size of axis text
axis_title	size of axis title
show_plot	show plot
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function
default_save_name	default save name for saving, don't change, change save_name in save_param

Details

Description of parameters.

Value

ggplot

Examples

```
spatCellPlot(gobject)
```

spatCellPlot2D

spatCellPlot2D

Description

Visualize cells according to spatial coordinates

Usage

```
spatCellPlot2D(
  gobject,
  sdimx = "sdimx",
  sdimy = "sdimy",
  spat_enr_names = NULL,
  cell_annotation_values,
  cell_color_gradient = c("blue", "white", "red"),
  gradient_midpoint = NULL,
  gradient_limits = NULL,
  select_cell_groups = NULL,
  select_cells = NULL,
  point_size = 3,
  point_border_col = "black",
  point_border_stroke = 0.1,
  show_cluster_center = F,
  show_center_label = F,
  center_point_size = 4,
  center_point_border_col = "black",
  center_point_border_stroke = 0.1,
  label_size = 4,
  label_fontface = "bold",
  show_network = F,
  spatial_network_name = "spatial_network",
  network_color = NULL,
  network_alpha = 1,
  show_grid = F,
  spatial_grid_name = "spatial_grid",
  grid_color = NULL,
  show_other_cells = T,
  other_cell_color = "lightgrey",
  other_point_size = 1,
  other_cells_alpha = 0.1,
  coord_fix_ratio = NULL,
  show_legend = T,
  legend_text = 8,
  axis_text = 8,
  axis_title = 8,
  cow_n_col = 2,
```

```

cow_rel_h = 1,
cow_rel_w = 1,
cow_align = "h",
show_plot = NA,
return_plot = NA,
save_plot = NA,
save_param = list(),
default_save_name = "spatCellPlot2D"
)

```

Arguments

<code>gobject</code>	giotto object
<code>sdimx</code>	x-axis dimension name (default = 'sdimx')
<code>sdimy</code>	y-axis dimension name (default = 'sdimy')
<code>spat_enr_names</code>	names of spatial enrichment results to include
<code>cell_annotation_values</code>	numeric cell annotation columns
<code>cell_color_gradient</code>	vector with 3 colors for numeric data
<code>gradient_midpoint</code>	midpoint for color gradient
<code>gradient_limits</code>	vector with lower and upper limits
<code>select_cell_groups</code>	select subset of cells/clusters based on <code>cell_color</code> parameter
<code>select_cells</code>	select subset of cells based on cell IDs
<code>point_size</code>	size of point (cell)
<code>point_border_col</code>	color of border around points
<code>point_border_stroke</code>	stroke size of border around points
<code>show_cluster_center</code>	plot center of selected clusters
<code>show_center_label</code>	plot label of selected clusters
<code>center_point_size</code>	size of center points
<code>label_size</code>	size of labels
<code>label_fontface</code>	font of labels
<code>show_network</code>	show underlying spatial network
<code>spatial_network_name</code>	name of spatial network to use
<code>network_color</code>	color of spatial network
<code>network_alpha</code>	alpha of spatial network
<code>show_grid</code>	show spatial grid
<code>spatial_grid_name</code>	name of spatial grid to use

grid_color	color of spatial grid
show_other_cells	display not selected cells
other_cell_color	color of not selected cells
other_point_size	point size of not selected cells
other_cells_alpha	alpha of not selected cells
coord_fix_ratio	fix ratio between x and y-axis
show_legend	show legend
legend_text	size of legend text
axis_text	size of axis text
axis_title	size of axis title
show_plot	show plot
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function
default_save_name	default save name for saving, don't change, change save_name in save_param

Details

Description of parameters.

Value

ggplot

Examples

spatCellPlot2D(gobject)

spatDimCellPlot	<i>spatDimCellPlot</i>
-----------------	------------------------

Description

Visualize numerical features of cells according to spatial AND dimension reduction coordinates in 2D

Usage

```
spatDimCellPlot(  
  gobject,  
  plot_alignment = c("vertical", "horizontal"),  
  spat_enr_names = NULL,  
  cell_annotation_values,  
  dim_reduction_to_use = "umap",  
  dim_reduction_name = "umap",  
  dim1_to_use = 1,  
  dim2_to_use = 2,  
  sdimx = "sdimx",  
  sdimy = "sdimy",  
  cell_color_gradient = c("blue", "white", "red"),  
  gradient_midpoint = NULL,  
  gradient_limits = NULL,  
  select_cell_groups = NULL,  
  select_cells = NULL,  
  dim_point_size = 1,  
  dim_point_border_col = "black",  
  dim_point_border_stroke = 0.1,  
  spat_point_size = 1,  
  spat_point_border_col = "black",  
  spat_point_border_stroke = 0.1,  
  dim_show_cluster_center = F,  
  dim_show_center_label = T,  
  dim_center_point_size = 4,  
  dim_center_point_border_col = "black",  
  dim_center_point_border_stroke = 0.1,  
  dim_label_size = 4,  
  dim_label_fontface = "bold",  
  spat_show_cluster_center = F,  
  spat_show_center_label = F,  
  spat_center_point_size = 4,  
  spat_center_point_border_col = "black",  
  spat_center_point_border_stroke = 0.1,  
  spat_label_size = 4,  
  spat_label_fontface = "bold",  
  show_NN_network = F,  
  nn_network_to_use = "sNN",  
  nn_network_name = "sNN.pca",  
  dim_edge_alpha = 0.5,  
  spat_show_network = F,  
  spatial_network_name = "spatial_network",  
  spat_network_color = "red",  
  spat_network_alpha = 0.5,  
  spat_show_grid = F,  
  spatial_grid_name = "spatial_grid",  
  spat_grid_color = "green",  
  show_other_cells = TRUE,  
  other_cell_color = "grey",  
  dim_other_point_size = 0.5,  
  spat_other_point_size = 0.5,
```

```

    spat_other_cells_alpha = 0.5,
    coord_fix_ratio = NULL,
    cow_n_col = 2,
    cow_rel_h = 1,
    cow_rel_w = 1,
    cow_align = "h",
    show_legend = T,
    legend_text = 8,
    axis_text = 8,
    axis_title = 8,
    show_plot = NA,
    return_plot = NA,
    save_plot = NA,
    save_param = list(),
    default_save_name = "spatDimCellPlot"
)

```

Arguments

<code>gobject</code>	giotto object
<code>plot_alignment</code>	direction to align plot
<code>spat_enr_names</code>	names of spatial enrichment results to include
<code>cell_annotation_values</code>	numeric cell annotation columns
<code>dim_reduction_to_use</code>	dimension reduction to use
<code>dim_reduction_name</code>	dimension reduction name
<code>dim1_to_use</code>	dimension to use on x-axis
<code>dim2_to_use</code>	dimension to use on y-axis
<code>sdimx</code>	= spatial dimension to use on x-axis
<code>sdimy</code>	= spatial dimension to use on y-axis
<code>cell_color_gradient</code>	vector with 3 colors for numeric data
<code>gradient_midpoint</code>	midpoint for color gradient
<code>gradient_limits</code>	vector with lower and upper limits
<code>select_cell_groups</code>	select subset of cells/clusters based on <code>cell_color</code> parameter
<code>select_cells</code>	select subset of cells based on cell IDs
<code>dim_point_size</code>	size of points in dim. reduction space
<code>dim_point_border_col</code>	border color of points in dim. reduction space
<code>dim_point_border_stroke</code>	border stroke of points in dim. reduction space
<code>spat_point_size</code>	size of spatial points

```

    spat_point_border_col
        border color of spatial points
    spat_point_border_stroke
        border stroke of spatial points
    dim_show_cluster_center
        show the center of each cluster
    dim_show_center_label
        provide a label for each cluster
    dim_center_point_size
        size of the center point
    dim_center_point_border_col
        border color of center point
    dim_center_point_border_stroke
        stroke size of center point
    dim_label_size
        size of the center label
    dim_label_fontface
        font of the center label
    spat_show_cluster_center
        show the center of each cluster
    spat_show_center_label
        provide a label for each cluster
    spat_center_point_size
        size of the center point
    spat_label_size
        size of the center label
    spat_label_fontface
        font of the center label
    show_NN_network
        show underlying NN network
    nn_network_to_use
        type of NN network to use (kNN vs sNN)
    nn_network_name
        name of NN network to use, if show_NN_network = TRUE
    dim_edge_alpha
        column to use for alpha of the edges
    spat_show_network
        show spatial network
    spatial_network_name
        name of spatial network to use
    spat_network_color
        color of spatial network
    spat_show_grid
        show spatial grid
    spatial_grid_name
        name of spatial grid to use
    spat_grid_color
        color of spatial grid
    show_other_cells
        display not selected cells
    other_cell_color
        color of not selected cells

```

dim_other_point_size	size of not selected dim cells
spat_other_point_size	size of not selected spat cells
spat_other_cells_alpha	alpha of not selected spat cells
coord_fix_ratio	ratio for coordinates
cow_n_col	cowplot param: how many columns
cow_rel_h	cowplot param: relative height
cow_rel_w	cowplot param: relative width
cow_align	cowplot param: how to align
show_legend	show legend
legend_text	size of legend text
axis_text	size of axis text
axis_title	size of axis title
show_plot	show plot
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function
default_save_name	default save name for saving, don't change, change save_name in save_param

Details

Description of parameters.

Value

ggplot

Examples

```
spatDimCellPlot(gobject)
```

spatDimCellPlot2D	<i>spatDimCellPlot2D</i>
-------------------	--------------------------

Description

Visualize numerical features of cells according to spatial AND dimension reduction coordinates in 2D

Usage

```

spatDimCellPlot2D(
  gobject,
  plot_alignment = c("vertical", "horizontal"),
  spat_enr_names = NULL,
  cell_annotation_values,
  dim_reduction_to_use = "umap",
  dim_reduction_name = "umap",
  dim1_to_use = 1,
  dim2_to_use = 2,
  sdimx = "sdimx",
  sdimy = "sdimy",
  cell_color_gradient = c("blue", "white", "red"),
  gradient_midpoint = NULL,
  gradient_limits = NULL,
  select_cell_groups = NULL,
  select_cells = NULL,
  dim_point_size = 1,
  dim_point_border_col = "black",
  dim_point_border_stroke = 0.1,
  spat_point_size = 1,
  spat_point_border_col = "black",
  spat_point_border_stroke = 0.1,
  dim_show_cluster_center = F,
  dim_show_center_label = T,
  dim_center_point_size = 4,
  dim_center_point_border_col = "black",
  dim_center_point_border_stroke = 0.1,
  dim_label_size = 4,
  dim_label_fontface = "bold",
  spat_show_cluster_center = F,
  spat_show_center_label = F,
  spat_center_point_size = 4,
  spat_center_point_border_col = "black",
  spat_center_point_border_stroke = 0.1,
  spat_label_size = 4,
  spat_label_fontface = "bold",
  show_NN_network = F,
  nn_network_to_use = "sNN",
  nn_network_name = "sNN.pca",
  dim_edge_alpha = 0.5,
  spat_show_network = F,
  spatial_network_name = "spatial_network",
  spat_network_color = "red",
  spat_network_alpha = 0.5,
  spat_show_grid = F,
  spatial_grid_name = "spatial_grid",
  spat_grid_color = "green",
  show_other_cells = TRUE,
  other_cell_color = "grey",
  dim_other_point_size = 0.5,
  spat_other_point_size = 0.5,

```

```

    spat_other_cells_alpha = 0.5,
    coord_fix_ratio = NULL,
    cow_n_col = 2,
    cow_rel_h = 1,
    cow_rel_w = 1,
    cow_align = "h",
    show_legend = T,
    legend_text = 8,
    axis_text = 8,
    axis_title = 8,
    show_plot = NA,
    return_plot = NA,
    save_plot = NA,
    save_param = list(),
    default_save_name = "spatDimCellPlot2D"
)

```

Arguments

<code>gobject</code>	giotto object
<code>plot_alignment</code>	direction to align plot
<code>spat_enr_names</code>	names of spatial enrichment results to include
<code>cell_annotation_values</code>	numeric cell annotation columns
<code>dim_reduction_to_use</code>	dimension reduction to use
<code>dim_reduction_name</code>	dimension reduction name
<code>dim1_to_use</code>	dimension to use on x-axis
<code>dim2_to_use</code>	dimension to use on y-axis
<code>sdimx</code>	= spatial dimension to use on x-axis
<code>sdimy</code>	= spatial dimension to use on y-axis
<code>cell_color_gradient</code>	vector with 3 colors for numeric data
<code>gradient_midpoint</code>	midpoint for color gradient
<code>gradient_limits</code>	vector with lower and upper limits
<code>select_cell_groups</code>	select subset of cells/clusters based on <code>cell_color</code> parameter
<code>select_cells</code>	select subset of cells based on cell IDs
<code>dim_point_size</code>	size of points in dim. reduction space
<code>dim_point_border_col</code>	border color of points in dim. reduction space
<code>dim_point_border_stroke</code>	border stroke of points in dim. reduction space
<code>spat_point_size</code>	size of spatial points

```

    spat_point_border_col
        border color of spatial points
    spat_point_border_stroke
        border stroke of spatial points
    dim_show_cluster_center
        show the center of each cluster
    dim_show_center_label
        provide a label for each cluster
    dim_center_point_size
        size of the center point
    dim_center_point_border_col
        border color of center point
    dim_center_point_border_stroke
        stroke size of center point
    dim_label_size
        size of the center label
    dim_label_fontface
        font of the center label
    spat_show_cluster_center
        show the center of each cluster
    spat_show_center_label
        provide a label for each cluster
    spat_center_point_size
        size of the center point
    spat_label_size
        size of the center label
    spat_label_fontface
        font of the center label
    show_NN_network
        show underlying NN network
    nn_network_to_use
        type of NN network to use (kNN vs sNN)
    nn_network_name
        name of NN network to use, if show_NN_network = TRUE
    dim_edge_alpha
        column to use for alpha of the edges
    spat_show_network
        show spatial network
    spatial_network_name
        name of spatial network to use
    spat_network_color
        color of spatial network
    spat_show_grid
        show spatial grid
    spatial_grid_name
        name of spatial grid to use
    spat_grid_color
        color of spatial grid
    show_other_cells
        display not selected cells
    other_cell_color
        color of not selected cells

```

dim_other_point_size	size of not selected dim cells
spat_other_point_size	size of not selected spat cells
spat_other_cells_alpha	alpha of not selected spat cells
coord_fix_ratio	ratio for coordinates
cow_n_col	cowplot param: how many columns
cow_rel_h	cowplot param: relative height
cow_rel_w	cowplot param: relative width
cow_align	cowplot param: how to align
show_legend	show legend
legend_text	size of legend text
axis_text	size of axis text
axis_title	size of axis title
show_plot	show plot
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function
default_save_name	default save name for saving, don't change, change save_name in save_param

Details

Description of parameters.

Value

ggplot

Examples

spatDimCellPlot2D(gobject)

spatDimGenePlot	<i>spatDimGenePlot</i>
-----------------	------------------------

Description

Visualize cells according to spatial AND dimension reduction coordinates in ggplot mode

Usage

```

spatDimGenePlot(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  plot_alignment = c("vertical", "horizontal"),
  genes,
  dim_reduction_to_use = "umap",
  dim_reduction_name = "umap",
  dim1_to_use = 1,
  dim2_to_use = 2,
  point_size = 1,
  dim_point_border_col = "black",
  dim_point_border_stroke = 0.1,
  show_NN_network = F,
  show_spatial_network = F,
  show_spatial_grid = F,
  nn_network_to_use = "sNN",
  network_name = "sNN.pca",
  edge_alpha_dim = NULL,
  scale_alpha_with_expression = FALSE,
  spatial_network_name = "spatial_network",
  spatial_grid_name = "spatial_grid",
  spat_point_size = 1,
  spat_point_border_col = "black",
  spat_point_border_stroke = 0.1,
  midpoint = 0,
  genes_high_color = "red",
  genes_mid_color = "white",
  genes_low_color = "blue",
  cow_n_col = 2,
  cow_rel_h = 1,
  cow_rel_w = 1,
  cow_align = "h",
  show_legend = T,
  show_plot = NA,
  return_plot = NA,
  save_plot = NA,
  save_param = list(),
  default_save_name = "spatDimGenePlot"
)

```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	gene expression values to use
<code>plot_alignment</code>	direction to align plot
<code>genes</code>	genes to show
<code>dim_reduction_to_use</code>	dimension reduction to use
<code>dim_reduction_name</code>	dimension reduction name

dim1_to_use	dimension to use on x-axis
dim2_to_use	dimension to use on y-axis
point_size	size of point (cell)
dim_point_border_col	color of border around points
dim_point_border_stroke	stroke size of border around points
show_NN_network	show underlying NN network
nn_network_to_use	type of NN network to use (kNN vs sNN)
network_name	name of NN network to use, if show_NN_network = TRUE
edge_alpha_dim	dim reduction plot: column to use for alpha of the edges
scale_alpha_with_expression	scale expression with ggplot alpha parameter
spatial_network_name	name of spatial network to use
spatial_grid_name	name of spatial grid to use
spat_point_size	spatial plot: point size
spat_point_border_col	color of border around points
spat_point_border_stroke	stroke size of border around points
midpoint	size of point (cell)
cow_n_col	cowplot param: how many columns
cow_rel_h	cowplot param: relative height
cow_rel_w	cowplot param: relative width
cow_align	cowplot param: how to align
show_legend	show legend
show_plot	show plots
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function
default_save_name	default save name for saving, don't change, change save_name in save_param
dim_point_size	dim reduction plot: point size

Details

Description of parameters.

Value

ggplot

See Also[spatDimGenePlot3D](#)**Examples**

```
spatDimGenePlot(gobject)
```

spatDimGenePlot2D	<i>spatDimGenePlot2D</i>
-------------------	--------------------------

Description

Visualize cells according to spatial AND dimension reduction coordinates in ggplot mode

Usage

```
spatDimGenePlot2D(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  plot_alignment = c("vertical", "horizontal"),
  genes,
  dim_reduction_to_use = "umap",
  dim_reduction_name = "umap",
  dim1_to_use = 1,
  dim2_to_use = 2,
  point_size = 1,
  dim_point_border_col = "black",
  dim_point_border_stroke = 0.1,
  show_NN_network = F,
  show_spatial_network = F,
  show_spatial_grid = F,
  nn_network_to_use = "sNN",
  network_name = "sNN.pca",
  edge_alpha_dim = NULL,
  scale_alpha_with_expression = FALSE,
  spatial_network_name = "spatial_network",
  spatial_grid_name = "spatial_grid",
  spat_point_size = 1,
  spat_point_border_col = "black",
  spat_point_border_stroke = 0.1,
  midpoint = 0,
  genes_high_color = "red",
  genes_mid_color = "white",
  genes_low_color = "blue",
  cow_n_col = 2,
  cow_rel_h = 1,
  cow_rel_w = 1,
  cow_align = "h",
  show_legend = T,
  show_plot = NA,
  return_plot = NA,
```

```

    save_plot = NA,
    save_param = list(),
    default_save_name = "spatDimGenePlot2D"
)

```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	gene expression values to use
<code>plot_alignment</code>	direction to align plot
<code>genes</code>	genes to show
<code>dim_reduction_to_use</code>	dimension reduction to use
<code>dim_reduction_name</code>	dimension reduction name
<code>dim1_to_use</code>	dimension to use on x-axis
<code>dim2_to_use</code>	dimension to use on y-axis
<code>point_size</code>	size of point (cell)
<code>dim_point_border_col</code>	color of border around points
<code>dim_point_border_stroke</code>	stroke size of border around points
<code>show_NN_network</code>	show underlying NN network
<code>nn_network_to_use</code>	type of NN network to use (kNN vs sNN)
<code>network_name</code>	name of NN network to use, if <code>show_NN_network = TRUE</code>
<code>edge_alpha_dim</code>	dim reduction plot: column to use for alpha of the edges
<code>scale_alpha_with_expression</code>	scale expression with ggplot alpha parameter
<code>spatial_network_name</code>	name of spatial network to use
<code>spatial_grid_name</code>	name of spatial grid to use
<code>spat_point_size</code>	spatial plot: point size
<code>spat_point_border_col</code>	color of border around points
<code>spat_point_border_stroke</code>	stroke size of border around points
<code>midpoint</code>	size of point (cell)
<code>cow_n_col</code>	cowplot param: how many columns
<code>cow_rel_h</code>	cowplot param: relative height
<code>cow_rel_w</code>	cowplot param: relative width
<code>cow_align</code>	cowplot param: how to align

show_legend	show legend
show_plot	show plots
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function
default_save_name	default save name for saving, don't change, change save_name in save_param
dim_point_size	dim reduction plot: point size

Details

Description of parameters.

Value

ggplot

See Also

[spatDimGenePlot3D](#)

Examples

spatDimGenePlot2D(gobject)

spatDimGenePlot3D	<i>spatDimGenePlot3D</i>
-------------------	--------------------------

Description

Visualize cells according to spatial AND dimension reduction coordinates in ggplot mode

Usage

```
spatDimGenePlot3D(  
  gobject,  
  expression_values = c("normalized", "scaled", "custom"),  
  plot_alignment = c("horizontal", "vertical"),  
  dim_reduction_to_use = "umap",  
  dim_reduction_name = "umap",  
  dim1_to_use = 1,  
  dim2_to_use = 2,  
  dim3_to_use = NULL,  
  sdimx = "sdimx",  
  sdimy = "sdimy",  
  sdimz = "sdimz",  
  genes,  
  cluster_column = NULL,  
  select_cell_groups = NULL,  
  select_cells = NULL,
```

```

show_other_cells = T,
other_cell_color = "lightgrey",
other_point_size = 1.5,
show_NN_network = F,
nn_network_to_use = "sNN",
network_name = "sNN.pca",
label_size = 16,
genes_low_color = "blue",
genes_mid_color = "white",
genes_high_color = "red",
dim_point_size = 3,
nn_network_alpha = 0.5,
show_spatial_network = F,
spatial_network_name = "spatial_network",
network_color = "lightgray",
spatial_network_alpha = 0.5,
show_spatial_grid = F,
spatial_grid_name = "spatial_grid",
spatial_grid_color = NULL,
spatial_grid_alpha = 0.5,
spatial_point_size = 3,
legend_text_size = 12,
axis_scale = c("cube", "real", "custom"),
custom_ratio = NULL,
x_ticks = NULL,
y_ticks = NULL,
z_ticks = NULL,
show_plot = NA,
return_plot = NA,
save_plot = NA,
save_param = list(),
default_save_name = "spatDimGenePlot3D"
)

```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	gene expression values to use
<code>plot_alignment</code>	direction to align plot
<code>dim_reduction_to_use</code>	dimension reduction to use
<code>dim_reduction_name</code>	dimension reduction name
<code>dim1_to_use</code>	dimension to use on x-axis
<code>dim2_to_use</code>	dimension to use on y-axis
<code>dim3_to_use</code>	dimension to use on z-axis
<code>genes</code>	genes to show
<code>show_NN_network</code>	show underlying NN network

nn_network_to_use	type of NN network to use (kNN vs sNN)
network_name	name of NN network to use, if show_NN_network = TRUE
dim_point_size	dim reduction plot: point size
spatial_network_name	name of spatial network to use
spatial_grid_name	name of spatial grid to use
spatial_point_size	spatial plot: point size
show_plot	show plots
return_plot	return plotly object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function
default_save_name	default save name for saving, don't change, change save_name in save_param
edge_alpha_dim	dim reduction plot: column to use for alpha of the edges
scale_alpha_with_expression	scale expression with ggplot alpha parameter
point_size	size of point (cell)
show_legend	show legend

Details

Description of parameters.

Value

plotly

Examples

```
spatDimGenePlot3D(gobject)
```

spatDimPlot	<i>spatDimPlot</i>
-------------	--------------------

Description

Visualize cells according to spatial AND dimension reduction coordinates 2D

Usage

```

spatDimPlot(
  gobject,
  plot_alignment = c("vertical", "horizontal"),
  dim_reduction_to_use = "umap",
  dim_reduction_name = "umap",
  dim1_to_use = 1,
  dim2_to_use = 2,
  sdimx = "sdimx",
  sdimy = "sdimy",
  spat_enr_names = NULL,
  cell_color = NULL,
  color_as_factor = T,
  cell_color_code = NULL,
  cell_color_gradient = c("blue", "white", "red"),
  gradient_midpoint = NULL,
  gradient_limits = NULL,
  select_cell_groups = NULL,
  select_cells = NULL,
  dim_point_size = 1,
  dim_point_border_col = "black",
  dim_point_border_stroke = 0.1,
  spat_point_size = 1,
  spat_point_border_col = "black",
  spat_point_border_stroke = 0.1,
  dim_show_cluster_center = F,
  dim_show_center_label = T,
  dim_center_point_size = 4,
  dim_center_point_border_col = "black",
  dim_center_point_border_stroke = 0.1,
  dim_label_size = 4,
  dim_label_fontface = "bold",
  spat_show_cluster_center = F,
  spat_show_center_label = F,
  spat_center_point_size = 4,
  spat_label_size = 4,
  spat_label_fontface = "bold",
  show_NN_network = F,
  nn_network_to_use = "sNN",
  network_name = "sNN.pca",
  nn_network_alpha = 0.05,
  show_spatial_network = F,
  spat_network_name = "spatial_network",
  spat_network_color = "blue",
  spat_network_alpha = 0.5,
  show_spatial_grid = F,
  spat_grid_name = "spatial_grid",
  spat_grid_color = "blue",
  show_other_cells = T,
  other_cell_color = "lightgrey",
  dim_other_point_size = 1,
  spat_other_point_size = 1,

```



```

    spat_other_cells_alpha = 0.5,
    dim_show_legend = F,
    spat_show_legend = F,
    legend_text = 8,
    axis_text = 8,
    axis_title = 8,
    show_plot = NA,
    return_plot = NA,
    save_plot = NA,
    save_param = list(),
    default_save_name = "spatDimPlot"
)

```

Arguments

<code>gobject</code>	giotto object
<code>plot_alignment</code>	direction to align plot
<code>dim_reduction_to_use</code>	dimension reduction to use
<code>dim_reduction_name</code>	dimension reduction name
<code>dim1_to_use</code>	dimension to use on x-axis
<code>dim2_to_use</code>	dimension to use on y-axis
<code>sdimx</code>	= spatial dimension to use on x-axis
<code>sdimy</code>	= spatial dimension to use on y-axis
<code>spat_enr_names</code>	names of spatial enrichment results to include
<code>cell_color</code>	color for cells (see details)
<code>color_as_factor</code>	convert color column to factor
<code>cell_color_code</code>	named vector with colors
<code>cell_color_gradient</code>	vector with 3 colors for numeric data
<code>gradient_midpoint</code>	midpoint for color gradient
<code>gradient_limits</code>	vector with lower and upper limits
<code>select_cell_groups</code>	select subset of cells/clusters based on <code>cell_color</code> parameter
<code>select_cells</code>	select subset of cells based on cell IDs
<code>dim_point_size</code>	size of points in dim. reduction space
<code>dim_point_border_col</code>	border color of points in dim. reduction space
<code>dim_point_border_stroke</code>	border stroke of points in dim. reduction space
<code>spat_point_size</code>	size of spatial points
<code>spat_point_border_col</code>	border color of spatial points

```

spat_point_border_stroke
    border stroke of spatial points
dim_show_cluster_center
    show the center of each cluster
dim_show_center_label
    provide a label for each cluster
dim_center_point_size
    size of the center point
dim_center_point_border_col
    border color of center point
dim_center_point_border_stroke
    stroke size of center point
dim_label_size size of the center label
dim_label_fontface
    font of the center label
spat_show_cluster_center
    show the center of each cluster
spat_show_center_label
    provide a label for each cluster
spat_center_point_size
    size of the center point
spat_label_size
    size of the center label
spat_label_fontface
    font of the center label
show_NN_network
    show underlying NN network
nn_network_to_use
    type of NN network to use (kNN vs sNN)
network_name name of NN network to use, if show_NN_network = TRUE
nn_network_alpha
    column to use for alpha of the edges
show_spatial_network
    show spatial network
spat_network_name
    name of spatial network to use
spat_network_color
    color of spatial network
show_spatial_grid
    show spatial grid
spat_grid_name name of spatial grid to use
spat_grid_color
    color of spatial grid
show_other_cells
    display not selected cells
other_cell_color
    color of not selected cells
dim_other_point_size
    size of not selected dim cells

```

spat_other_point_size	size of not selected spat cells
spat_other_cells_alpha	alpha of not selected spat cells
dim_show_legend	show legend of dimension reduction plot
spat_show_legend	show legend of spatial plot
legend_text	size of legend text
axis_text	size of axis text
axis_title	size of axis title
show_plot	show plot
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function
default_save_name	default save name for saving, don't change, change save_name in save_param

Details

Description of parameters.

Value

ggplot

See Also

[spatDimPlot2D](#) and [spatDimPlot3D](#) for 3D visualization.

Examples

spatDimPlot(gobject)

spatDimPlot2D	<i>spatDimPlot2D</i>
---------------	----------------------

Description

Visualize cells according to spatial AND dimension reduction coordinates 2D

Usage

```

spatDimPlot2D(
  gobject,
  plot_alignment = c("vertical", "horizontal"),
  dim_reduction_to_use = "umap",
  dim_reduction_name = "umap",
  dim1_to_use = 1,
  dim2_to_use = 2,
  sdimx = "sdimx",
  sdimy = "sdimy",
  spat_enr_names = NULL,
  cell_color = NULL,
  color_as_factor = T,
  cell_color_code = NULL,
  cell_color_gradient = c("blue", "white", "red"),
  gradient_midpoint = NULL,
  gradient_limits = NULL,
  select_cell_groups = NULL,
  select_cells = NULL,
  dim_point_size = 1,
  dim_point_border_col = "black",
  dim_point_border_stroke = 0.1,
  spat_point_size = 1,
  spat_point_border_col = "black",
  spat_point_border_stroke = 0.1,
  dim_show_cluster_center = F,
  dim_show_center_label = T,
  dim_center_point_size = 4,
  dim_center_point_border_col = "black",
  dim_center_point_border_stroke = 0.1,
  dim_label_size = 4,
  dim_label_fontface = "bold",
  spat_show_cluster_center = F,
  spat_show_center_label = F,
  spat_center_point_size = 4,
  spat_label_size = 4,
  spat_label_fontface = "bold",
  show_NN_network = F,
  nn_network_to_use = "sNN",
  network_name = "sNN.pca",
  nn_network_alpha = 0.05,
  show_spatial_network = F,
  spat_network_name = "spatial_network",
  spat_network_color = "blue",
  spat_network_alpha = 0.5,
  show_spatial_grid = F,
  spat_grid_name = "spatial_grid",
  spat_grid_color = "blue",
  show_other_cells = T,
  other_cell_color = "lightgrey",
  dim_other_point_size = 1,
  spat_other_point_size = 1,

```

```

    spat_other_cells_alpha = 0.5,
    dim_show_legend = F,
    spat_show_legend = F,
    legend_text = 8,
    axis_text = 8,
    axis_title = 8,
    show_plot = NA,
    return_plot = NA,
    save_plot = NA,
    save_param = list(),
    default_save_name = "spatDimPlot2D"
)

```

Arguments

<code>gobject</code>	giotto object
<code>plot_alignment</code>	direction to align plot
<code>dim_reduction_to_use</code>	dimension reduction to use
<code>dim_reduction_name</code>	dimension reduction name
<code>dim1_to_use</code>	dimension to use on x-axis
<code>dim2_to_use</code>	dimension to use on y-axis
<code>sdimx</code>	= spatial dimension to use on x-axis
<code>sdimy</code>	= spatial dimension to use on y-axis
<code>spat_enr_names</code>	names of spatial enrichment results to include
<code>cell_color</code>	color for cells (see details)
<code>color_as_factor</code>	convert color column to factor
<code>cell_color_code</code>	named vector with colors
<code>cell_color_gradient</code>	vector with 3 colors for numeric data
<code>gradient_midpoint</code>	midpoint for color gradient
<code>gradient_limits</code>	vector with lower and upper limits
<code>select_cell_groups</code>	select subset of cells/clusters based on <code>cell_color</code> parameter
<code>select_cells</code>	select subset of cells based on cell IDs
<code>dim_point_size</code>	size of points in dim. reduction space
<code>dim_point_border_col</code>	border color of points in dim. reduction space
<code>dim_point_border_stroke</code>	border stroke of points in dim. reduction space
<code>spat_point_size</code>	size of spatial points
<code>spat_point_border_col</code>	border color of spatial points

```

spat_point_border_stroke
    border stroke of spatial points
dim_show_cluster_center
    show the center of each cluster
dim_show_center_label
    provide a label for each cluster
dim_center_point_size
    size of the center point
dim_center_point_border_col
    border color of center point
dim_center_point_border_stroke
    stroke size of center point
dim_label_size
    size of the center label
dim_label_fontface
    font of the center label
spat_show_cluster_center
    show the center of each cluster
spat_show_center_label
    provide a label for each cluster
spat_center_point_size
    size of the center point
spat_label_size
    size of the center label
spat_label_fontface
    font of the center label
show_NN_network
    show underlying NN network
nn_network_to_use
    type of NN network to use (kNN vs sNN)
network_name
    name of NN network to use, if show_NN_network = TRUE
nn_network_alpha
    column to use for alpha of the edges
show_spatial_network
    show spatial network
spat_network_name
    name of spatial network to use
spat_network_color
    color of spatial network
show_spatial_grid
    show spatial grid
spat_grid_name
    name of spatial grid to use
spat_grid_color
    color of spatial grid
show_other_cells
    display not selected cells
other_cell_color
    color of not selected cells
dim_other_point_size
    size of not selected dim cells

```

spat_other_point_size	size of not selected spat cells
spat_other_cells_alpha	alpha of not selected spat cells
dim_show_legend	show legend of dimension reduction plot
spat_show_legend	show legend of spatial plot
legend_text	size of legend text
axis_text	size of axis text
axis_title	size of axis title
show_plot	show plot
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function
default_save_name	default save name for saving, don't change, change save_name in save_param

Details

Description of parameters.

Value

ggplot

See Also

[spatDimPlot3D](#)

Examples

spatDimPlot2D(gobject)

spatDimPlot3D	<i>spatDimPlot3D</i>
---------------	----------------------

Description

Visualize cells according to spatial AND dimension reduction coordinates in plotly mode

Usage

```

spatDimPlot3D(
  gobject,
  plot_alignment = c("horizontal", "vertical"),
  dim_reduction_to_use = "umap",
  dim_reduction_name = "umap",
  dim1_to_use = 1,
  dim2_to_use = 2,
  dim3_to_use = 3,
  sdimx = "sdimx",
  sdimy = "sdimy",
  sdimz = "sdimz",
  show_NN_network = F,
  nn_network_to_use = "sNN",
  network_name = "sNN.pca",
  show_cluster_center = F,
  show_center_label = T,
  center_point_size = 4,
  label_size = 16,
  select_cell_groups = NULL,
  select_cells = NULL,
  show_other_cells = T,
  other_cell_color = "lightgrey",
  other_point_size = 1.5,
  cell_color = NULL,
  color_as_factor = T,
  cell_color_code = NULL,
  dim_point_size = 3,
  nn_network_alpha = 0.5,
  show_spatial_network = F,
  spatial_network_name = "spatial_network",
  network_color = "lightgray",
  spatial_network_alpha = 0.5,
  show_spatial_grid = F,
  spatial_grid_name = "spatial_grid",
  spatial_grid_color = NULL,
  spatial_grid_alpha = 0.5,
  spatial_point_size = 3,
  axis_scale = c("cube", "real", "custom"),
  custom_ratio = NULL,
  x_ticks = NULL,
  y_ticks = NULL,
  z_ticks = NULL,
  legend_text_size = 12,
  show_plot = NA,
  return_plot = NA,
  save_plot = NA,
  save_param = list(),
  default_save_name = "spatDimPlot3D"
)

```


Arguments

<code>gobject</code>	giotto object
<code>plot_alignment</code>	direction to align plot
<code>dim_reduction_to_use</code>	dimension reduction to use
<code>dim_reduction_name</code>	dimension reduction name
<code>dim1_to_use</code>	dimension to use on x-axis
<code>dim2_to_use</code>	dimension to use on y-axis
<code>dim3_to_use</code>	dimension to use on z-axis
<code>sdimx</code>	= spatial dimension to use on x-axis
<code>sdimy</code>	= spatial dimension to use on y-axis
<code>sdimz</code>	= spatial dimension to use on z-axis
<code>show_NN_network</code>	show underlying NN network
<code>nn_network_to_use</code>	type of NN network to use (kNN vs sNN)
<code>network_name</code>	name of NN network to use, if <code>show_NN_network = TRUE</code>
<code>show_cluster_center</code>	show the center of each cluster
<code>show_center_label</code>	provide a label for each cluster
<code>center_point_size</code>	size of the center point
<code>label_size</code>	size of the center label
<code>select_cell_groups</code>	select subset of cells/clusters based on <code>cell_color</code> parameter
<code>select_cells</code>	select subset of cells based on cell IDs
<code>show_other_cells</code>	display not selected cells
<code>other_cell_color</code>	color of not selected cells
<code>other_point_size</code>	size of not selected cells
<code>cell_color</code>	color for cells (see details)
<code>color_as_factor</code>	convert color column to factor
<code>cell_color_code</code>	named vector with colors
<code>dim_point_size</code>	size of points in dim. reduction space
<code>nn_network_alpha</code>	column to use for alpha of the edges
<code>show_spatial_network</code>	show spatial network
<code>spatial_network_name</code>	name of spatial network to use

spatial_network_alpha	alpha of spatial network
show_spatial_grid	show spatial grid
spatial_grid_name	name of spatial grid to use
spatial_grid_color	color of spatial grid
spatial_point_size	size of spatial points
show_plot	show plot
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function
default_save_name	default save name for saving, don't change, change save_name in save_param
dim_point_border_col	border color of points in dim. reduction space
dim_point_border_stroke	border stroke of points in dim. reduction space
spatial_network_color	color of spatial network
spatial_other_point_size	size of not selected spatial points
spatial_other_cells_alpha	alpha of not selected spatial points
dim_other_point_size	size of not selected dim. reduction points
show_legend	show legend

Details

Description of parameters.

Value

plotly

Examples

```
spatDimPlot3D(gobject)
```

spatGenePlot

*spatGenePlot***Description**

Visualize cells and gene expression according to spatial coordinates

Usage

```
spatGenePlot(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  genes,
  genes_high_color = "darkred",
  genes_mid_color = "white",
  genes_low_color = "darkblue",
  show_network = F,
  network_color = NULL,
  spatial_network_name = "spatial_network",
  edge_alpha = NULL,
  show_grid = F,
  grid_color = NULL,
  spatial_grid_name = "spatial_grid",
  midpoint = 0,
  scale_alpha_with_expression = FALSE,
  point_size = 1,
  point_border_col = "black",
  point_border_stroke = 0.1,
  show_legend = T,
  cow_n_col = 2,
  cow_rel_h = 1,
  cow_rel_w = 1,
  cow_align = "h",
  show_plot = NA,
  return_plot = NA,
  save_plot = NA,
  save_param = list(),
  default_save_name = "spatGenePlot"
)
```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	gene expression values to use
<code>genes</code>	genes to show
<code>genes_high_color</code>	color represents high gene expression
<code>genes_mid_color</code>	color represents middle gene expression

<code>genes_low_color</code>	color represents low gene expression
<code>show_network</code>	show underlying spatial network
<code>network_color</code>	color of spatial network
<code>spatial_network_name</code>	name of spatial network to use
<code>show_grid</code>	show spatial grid
<code>grid_color</code>	color of spatial grid
<code>spatial_grid_name</code>	name of spatial grid to use
<code>midpoint</code>	expression midpoint
<code>scale_alpha_with_expression</code>	scale expression with ggplot alpha parameter
<code>point_size</code>	size of point (cell)
<code>point_border_col</code>	color of border around points
<code>point_border_stroke</code>	stroke size of border around points
<code>show_legend</code>	show legend
<code>cow_n_col</code>	cowplot param: how many columns
<code>cow_rel_h</code>	cowplot param: relative height
<code>cow_rel_w</code>	cowplot param: relative width
<code>cow_align</code>	cowplot param: how to align
<code>show_plot</code>	show plots
<code>return_plot</code>	return ggplot object
<code>save_plot</code>	directly save the plot [boolean]
<code>save_param</code>	list of saving parameters from all_plots_save_function
<code>default_save_name</code>	default save name for saving, don't change, change save_name in save_param
<code>...</code>	parameters for <code>cowplot::save_plot()</code>

Details

Description of parameters.

Value

ggplot

See Also

[spatGenePlot3D](#) and [spatGenePlot2D](#)

Examples

```
spatGenePlot(gobject)
```

spatGenePlot2D

*spatGenePlot2D***Description**

Visualize cells and gene expression according to spatial coordinates

Usage

```
spatGenePlot2D(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  genes,
  genes_high_color = "darkred",
  genes_mid_color = "white",
  genes_low_color = "darkblue",
  show_network = F,
  network_color = NULL,
  spatial_network_name = "spatial_network",
  edge_alpha = NULL,
  show_grid = F,
  grid_color = NULL,
  spatial_grid_name = "spatial_grid",
  midpoint = 0,
  scale_alpha_with_expression = FALSE,
  point_size = 1,
  point_border_col = "black",
  point_border_stroke = 0.1,
  show_legend = T,
  cow_n_col = 2,
  cow_rel_h = 1,
  cow_rel_w = 1,
  cow_align = "h",
  show_plot = NA,
  return_plot = NA,
  save_plot = NA,
  save_param = list(),
  default_save_name = "spatGenePlot2D"
)
```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	gene expression values to use
<code>genes</code>	genes to show
<code>genes_high_color</code>	color represents high gene expression
<code>genes_mid_color</code>	color represents middle gene expression

genes_low_color	color represents low gene expression
show_network	show underlying spatial network
network_color	color of spatial network
spatial_network_name	name of spatial network to use
show_grid	show spatial grid
grid_color	color of spatial grid
spatial_grid_name	name of spatial grid to use
midpoint	expression midpoint
scale_alpha_with_expression	scale expression with ggplot alpha parameter
point_size	size of point (cell)
point_border_col	color of border around points
point_border_stroke	stroke size of border around points
show_legend	show legend
cow_n_col	cowplot param: how many columns
cow_rel_h	cowplot param: relative height
cow_rel_w	cowplot param: relative width
cow_align	cowplot param: how to align
show_plot	show plots
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function
default_save_name	default save name for saving, don't change, change save_name in save_param
...	parameters for cowplot::save_plot()

Details

Description of parameters.

Value

ggplot

See Also

[spatGenePlot3D](#)

Examples

```
spatGenePlot2D(gobject)
```

spatGenePlot3D	<i>spatGenePlot3D</i>
----------------	-----------------------

Description

Visualize cells and gene expression according to spatial coordinates

Usage

```
spatGenePlot3D(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  genes,
  show_network = F,
  network_color = NULL,
  spatial_network_name = "spatial_network",
  edge_alpha = NULL,
  show_grid = F,
  cluster_column = NULL,
  select_cell_groups = NULL,
  select_cells = NULL,
  show_other_cells = T,
  other_cell_color = "lightgrey",
  other_point_size = 1,
  genes_high_color = NULL,
  genes_mid_color = "white",
  genes_low_color = "blue",
  spatial_grid_name = "spatial_grid",
  point_size = 2,
  show_legend = T,
  axis_scale = c("cube", "real", "custom"),
  custom_ratio = NULL,
  x_ticks = NULL,
  y_ticks = NULL,
  z_ticks = NULL,
  show_plot = NA,
  return_plot = NA,
  save_plot = NA,
  save_param = list(),
  default_save_name = "spatGenePlot3D"
)
```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	gene expression values to use
<code>genes</code>	genes to show
<code>show_network</code>	show underlying spatial network
<code>network_color</code>	color of spatial network

spatial_network_name	name of spatial network to use
show_grid	show spatial grid
genes_high_color	color represents high gene expression
genes_mid_color	color represents middle gene expression
genes_low_color	color represents low gene expression
spatial_grid_name	name of spatial grid to use
point_size	size of point (cell)
show_legend	show legend
show_plot	show plots
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function
default_save_name	default save name for saving, don't change, change save_name in save_param
grid_color	color of spatial grid
midpoint	expression midpoint
scale_alpha_with_expression	scale expression with ggplot alpha parameter
...	parameters for cowplot::save_plot()

Details

Description of parameters.

Value

ggplot

Examples

spatGenePlot3D(gobject)

Spatial_AEH	<i>Spatial_AEH</i>
-------------	--------------------

Description

calculate automatic expression histology with spatialDE method

Usage

```
Spatial_AEH(  
  gobject = NULL,  
  results = NULL,  
  pattern_num = 5,  
  l = 1.05,  
  show_AEH = T,  
  sdimx = NULL,  
  sdimy = NULL,  
  point_size = 3,  
  point_alpha = 1,  
  low_color = "blue",  
  mid_color = "white",  
  high_color = "red",  
  midpoint = 0,  
  python_path = NULL  
)
```

Arguments

gobject	Giotto object
results	output from spatial_DE
pattern_num	the number of gene expression patterns
show_AEH	show AEH plot
python_path	specify specific path to python if required

Details

Description.

Value

a list or a dataframe of SVs

Examples

```
Spatial_AEH(gobject)
```

Spatial_DE	<i>Spatial_DE</i>
------------	-------------------

Description

calculate spatial variable genes with spatialDE method

Usage

```
Spatial_DE(  
  gobject = NULL,  
  show_plot = T,  
  size = c(4, 2, 1),  
  color = c("blue", "green", "red"),  
  sig_alpha = 0.5,  
  unsig_alpha = 0.5,  
  python_path = NULL  
)
```

Arguments

- gobject Giotto object
- show_plot show FSV plot
- python_path specify specific path to python if required

Details

Description.

Value

a list or a dataframe of SVs

Examples

```
Spatial_DE(gobject)
```

spatPlot	<i>spatPlot</i>
----------	-----------------

Description

Visualize cells according to spatial coordinates

Usage

```
spatPlot(  
  gobject,  
  group_by = NULL,  
  group_by_subset = NULL,  
  sdimx = "sdimx",  
  sdimy = "sdimy",  
  spat_enr_names = NULL,  
  cell_color = NULL,  
  color_as_factor = T,  
  cell_color_code = NULL,  
  cell_color_gradient = c("blue", "white", "red"),  
  gradient_midpoint = NULL,  
  gradient_limits = NULL,
```

```

select_cell_groups = NULL,
select_cells = NULL,
point_size = 3,
point_border_col = "black",
point_border_stroke = 0.1,
show_cluster_center = F,
show_center_label = F,
center_point_size = 4,
center_point_border_col = "black",
center_point_border_stroke = 0.1,
label_size = 4,
label_fontface = "bold",
show_network = F,
spatial_network_name = "spatial_network",
network_color = NULL,
network_alpha = 1,
show_grid = F,
spatial_grid_name = "spatial_grid",
grid_color = NULL,
show_other_cells = T,
other_cell_color = "lightgrey",
other_point_size = 1,
other_cells_alpha = 0.1,
coord_fix_ratio = NULL,
title = NULL,
show_legend = T,
legend_text = 8,
axis_text = 8,
axis_title = 8,
cow_n_col = 2,
cow_rel_h = 1,
cow_rel_w = 1,
cow_align = "h",
show_plot = NA,
return_plot = NA,
save_plot = NA,
save_param = list(),
default_save_name = "spatPlot"
)

```

Arguments

<code>gobject</code>	giotto object
<code>group_by_subset</code>	subset the <code>group_by</code> factor column
<code>sdimx</code>	x-axis dimension name (default = 'sdimx')
<code>sdimy</code>	y-axis dimension name (default = 'sdimy')
<code>spat_enr_names</code>	names of spatial enrichment results to include
<code>cell_color</code>	color for cells (see details)
<code>color_as_factor</code>	convert color column to factor

cell_color_code	named vector with colors
cell_color_gradient	vector with 3 colors for numeric data
gradient_midpoint	midpoint for color gradient
gradient_limits	vector with lower and upper limits
select_cell_groups	select subset of cells/clusters based on cell_color parameter
select_cells	select subset of cells based on cell IDs
point_size	size of point (cell)
point_border_col	color of border around points
point_border_stroke	stroke size of border around points
show_cluster_center	plot center of selected clusters
show_center_label	plot label of selected clusters
center_point_size	size of center points
label_size	size of labels
label_fontface	font of labels
show_network	show underlying spatial network
spatial_network_name	name of spatial network to use
network_color	color of spatial network
network_alpha	alpha of spatial network
show_grid	show spatial grid
spatial_grid_name	name of spatial grid to use
grid_color	color of spatial grid
show_other_cells	display not selected cells
other_cell_color	color of not selected cells
other_point_size	point size of not selected cells
other_cells_alpha	alpha of not selected cells
coord_fix_ratio	fix ratio between x and y-axis
title	title of plot
show_legend	show legend
legend_text	size of legend text

axis_text	size of axis text
axis_title	size of axis title
cow_n_col	cowplot param: how many columns
cow_rel_h	cowplot param: relative height
cow_rel_w	cowplot param: relative width
cow_align	cowplot param: how to align
show_plot	show plot
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function
default_save_name	default save name for saving, don't change, change save_name in save_param
groub_by	create multiple plots based on cell annotation column

Details

Description of parameters.

Value

ggplot

See Also

[spatPlot3D](#)

Examples

```
spatPlot(gobject)
```

spatPlot2D	<i>spatPlot2D</i>
------------	-------------------

Description

Visualize cells according to spatial coordinates

Usage

```
spatPlot2D(  
  gobject,  
  group_by = NULL,  
  group_by_subset = NULL,  
  sdimx = "sdimx",  
  sdimy = "sdimy",  
  spat_enr_names = NULL,  
  cell_color = NULL,  
  color_as_factor = T,  
  cell_color_code = NULL,  
)
```

```

cell_color_gradient = c("blue", "white", "red"),
gradient_midpoint = NULL,
gradient_limits = NULL,
select_cell_groups = NULL,
select_cells = NULL,
point_size = 3,
point_border_col = "black",
point_border_stroke = 0.1,
show_cluster_center = F,
show_center_label = F,
center_point_size = 4,
center_point_border_col = "black",
center_point_border_stroke = 0.1,
label_size = 4,
label_fontface = "bold",
show_network = F,
spatial_network_name = "spatial_network",
network_color = NULL,
network_alpha = 1,
show_grid = F,
spatial_grid_name = "spatial_grid",
grid_color = NULL,
show_other_cells = T,
other_cell_color = "lightgrey",
other_point_size = 1,
other_cells_alpha = 0.1,
coord_fix_ratio = NULL,
title = NULL,
show_legend = T,
legend_text = 8,
axis_text = 8,
axis_title = 8,
cow_n_col = 2,
cow_rel_h = 1,
cow_rel_w = 1,
cow_align = "h",
show_plot = NA,
return_plot = NA,
save_plot = NA,
save_param = list(),
default_save_name = "spatPlot2D"
)

```

Arguments

<code>gobject</code>	giotto object
<code>group_by_subset</code>	subset the <code>group_by</code> factor column
<code>sdimx</code>	x-axis dimension name (default = 'sdimx')
<code>sdimy</code>	y-axis dimension name (default = 'sdimy')
<code>spat_enr_names</code>	names of spatial enrichment results to include
<code>cell_color</code>	color for cells (see details)

color_as_factor	convert color column to factor
cell_color_code	named vector with colors
cell_color_gradient	vector with 3 colors for numeric data
gradient_midpoint	midpoint for color gradient
gradient_limits	vector with lower and upper limits
select_cell_groups	select subset of cells/clusters based on cell_color parameter
select_cells	select subset of cells based on cell IDs
point_size	size of point (cell)
point_border_col	color of border around points
point_border_stroke	stroke size of border around points
show_cluster_center	plot center of selected clusters
show_center_label	plot label of selected clusters
center_point_size	size of center points
label_size	size of labels
label_fontface	font of labels
show_network	show underlying spatial network
spatial_network_name	name of spatial network to use
network_color	color of spatial network
network_alpha	alpha of spatial network
show_grid	show spatial grid
spatial_grid_name	name of spatial grid to use
grid_color	color of spatial grid
show_other_cells	display not selected cells
other_cell_color	color of not selected cells
other_point_size	point size of not selected cells
other_cells_alpha	alpha of not selected cells
coord_fix_ratio	fix ratio between x and y-axis
title	title of plot

show_legend	show legend
legend_text	size of legend text
axis_text	size of axis text
axis_title	size of axis title
cow_n_col	cowplot param: how many columns
cow_rel_h	cowplot param: relative height
cow_rel_w	cowplot param: relative width
cow_align	cowplot param: how to align
show_plot	show plot
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function
default_save_name	default save name for saving, don't change, change save_name in save_param
groub_by	create multiple plots based on cell annotation column

Details

Description of parameters.

Value

ggplot

See Also

[spatPlot3D](#)

Examples

spatPlot2D(gobject)

spatPlot2D_single	<i>spatPlot2D_single</i>
-------------------	--------------------------

Description

Visualize cells according to spatial coordinates

Usage

```

spatPlot2D_single(
  gobject,
  sdimx = "sdimx",
  sdimy = "sdimy",
  spat_enr_names = NULL,
  cell_color = NULL,
  color_as_factor = T,
  cell_color_code = NULL,
  cell_color_gradient = c("blue", "white", "red"),
  gradient_midpoint = NULL,
  gradient_limits = NULL,
  select_cell_groups = NULL,
  select_cells = NULL,
  point_size = 3,
  point_border_col = "black",
  point_border_stroke = 0.1,
  show_cluster_center = F,
  show_center_label = F,
  center_point_size = 4,
  center_point_border_col = "black",
  center_point_border_stroke = 0.1,
  label_size = 4,
  label_fontface = "bold",
  show_network = F,
  spatial_network_name = "spatial_network",
  network_color = NULL,
  network_alpha = 1,
  show_grid = F,
  spatial_grid_name = "spatial_grid",
  grid_color = NULL,
  show_other_cells = T,
  other_cell_color = "lightgrey",
  other_point_size = 1,
  other_cells_alpha = 0.1,
  coord_fix_ratio = NULL,
  title = NULL,
  show_legend = T,
  legend_text = 8,
  axis_text = 8,
  axis_title = 8,
  show_plot = NA,
  return_plot = NA,
  save_plot = NA,
  save_param = list(),
  default_save_name = "spatPlot2D_single"
)

```

Arguments

<code>gobject</code>	giotto object
<code>sdimx</code>	x-axis dimension name (default = 'sdimx')

<code>sdimy</code>	y-axis dimension name (default = 'sdimy')
<code>spat_enr_names</code>	names of spatial enrichment results to include
<code>cell_color</code>	color for cells (see details)
<code>color_as_factor</code>	convert color column to factor
<code>cell_color_code</code>	named vector with colors
<code>cell_color_gradient</code>	vector with 3 colors for numeric data
<code>gradient_midpoint</code>	midpoint for color gradient
<code>gradient_limits</code>	vector with lower and upper limits
<code>select_cell_groups</code>	select subset of cells/clusters based on <code>cell_color</code> parameter
<code>select_cells</code>	select subset of cells based on cell IDs
<code>point_size</code>	size of point (cell)
<code>point_border_col</code>	color of border around points
<code>point_border_stroke</code>	stroke size of border around points
<code>show_cluster_center</code>	plot center of selected clusters
<code>show_center_label</code>	plot label of selected clusters
<code>center_point_size</code>	size of center points
<code>label_size</code>	size of labels
<code>label_fontface</code>	font of labels
<code>show_network</code>	show underlying spatial network
<code>spatial_network_name</code>	name of spatial network to use
<code>network_color</code>	color of spatial network
<code>network_alpha</code>	alpha of spatial network
<code>show_grid</code>	show spatial grid
<code>spatial_grid_name</code>	name of spatial grid to use
<code>grid_color</code>	color of spatial grid
<code>show_other_cells</code>	display not selected cells
<code>other_cell_color</code>	color of not selected cells
<code>other_point_size</code>	point size of not selected cells
<code>other_cells_alpha</code>	alpha of not selected cells

coord_fix_ratio	fix ratio between x and y-axis
title	title of plot
show_legend	show legend
legend_text	size of legend text
axis_text	size of axis text
axis_title	size of axis title
show_plot	show plot
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function
default_save_name	default save name for saving, don't change, change save_name in save_param

Details

Description of parameters.

Value

ggplot

See Also

[spatPlot3D](#)

Examples

```
spatPlot2D_single(gobject)
```

spatPlot3D	<i>spatPlot3D</i>
------------	-------------------

Description

Visualize cells according to spatial coordinates

Usage

```
spatPlot3D(  
  gobject,  
  sdimx = "sdimx",  
  sdimy = "sdimy",  
  sdimz = "sdimz",  
  point_size = 3,  
  cell_color = NULL,  
  cell_color_code = NULL,  
  select_cell_groups = NULL,  
  select_cells = NULL,
```

```

show_other_cells = T,
other_cell_color = "lightgrey",
other_point_size = 0.5,
show_network = F,
network_color = NULL,
network_alpha = 1,
other_cell_alpha = 0.5,
spatial_network_name = "spatial_network",
show_grid = F,
grid_color = NULL,
spatial_grid_name = "spatial_grid",
title = "",
show_legend = T,
axis_scale = c("cube", "real", "custom"),
custom_ratio = NULL,
x_ticks = NULL,
y_ticks = NULL,
z_ticks = NULL,
show_plot = NA,
return_plot = NA,
save_plot = NA,
save_param = list(),
default_save_name = "spat3D"
)

```

Arguments

<code>gobject</code>	giotto object
<code>sdimx</code>	x-axis dimension name (default = 'sdimx')
<code>sdimy</code>	y-axis dimension name (default = 'sdimy')
<code>sdimz</code>	z-axis dimension name (default = 'sdimy')
<code>point_size</code>	size of point (cell)
<code>cell_color</code>	color for cells (see details)
<code>cell_color_code</code>	named vector with colors
<code>select_cell_groups</code>	select subset of cells/clusters based on <code>cell_color</code> parameter
<code>select_cells</code>	select subset of cells based on cell IDs
<code>show_other_cells</code>	display not selected cells
<code>other_cell_color</code>	color of not selected cells
<code>show_network</code>	show underlying spatial network
<code>network_color</code>	color of spatial network
<code>spatial_network_name</code>	name of spatial network to use
<code>show_grid</code>	show spatial grid
<code>grid_color</code>	color of spatial grid

spatial_grid_name	name of spatial grid to use
title	title of plot
show_legend	show legend
axis_scale	the way to scale the axis
custom_ratio	customize the scale of the plot
x_ticks	set the number of ticks on the x-axis
y_ticks	set the number of ticks on the y-axis
z_ticks	set the number of ticks on the z-axis
show_plot	show plot
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function
default_save_name	default save name for saving, don't change, change save_name in save_param

Details

Description of parameters.

Value

ggplot

Examples

spatPlot3D(gobject)

specificCellCellcommunicationScores

specificCellCellcommunicationScores

Description

Specific Cell-Cell communication scores based on spatial expression of interacting cells

Usage

```
specificCellCellcommunicationScores(  
  gobject,  
  spatial_network_name = "spatial_network",  
  cluster_column = "cell_types",  
  random_iter = 100,  
  cell_type_1 = "astrocyte",  
  cell_type_2 = "endothelial",  
  gene_set_1,  
  gene_set_2,
```

```

    log2FC_addendum = 0.1,
    min_observations = 2,
    verbose = T
)

```

Arguments

<code>gobject</code>	giotto object to use
<code>spatial_network_name</code>	spatial network to use for identifying interacting cells
<code>cluster_column</code>	cluster column with cell type information
<code>random_iter</code>	number of iterations
<code>cell_type_1</code>	first cell type
<code>cell_type_2</code>	second cell type
<code>gene_set_1</code>	first specific gene set from gene pairs
<code>gene_set_2</code>	second specific gene set from gene pairs
<code>log2FC_addendum</code>	addendum to add when calculating log2FC
<code>min_observations</code>	minimum number of interactions needed to be considered
<code>verbose</code>	verbose

Details

Statistical framework to identify if pairs of genes (such as ligand-receptor combinations) are expressed at higher levels than expected based on a reshuffled null distribution of gene expression values in cells that are spatially in proximity to eachother.. More details will follow soon.

Value

Cell-Cell communication scores for gene pairs based on spatial interaction

Examples

```
specificCellCellcommunicationScores(gobject)
```

```
split_dendrogram_in_two
```

```
split_dendrogram_in_two
```

Description

Merge selected clusters based on pairwise correlation scores and size of cluster.

Usage

```
split_dendrogram_in_two(dend)
```

Arguments

dend dendrogram object

Value

list of two dendrograms and height of node

Examples

```
split_dendrogram_in_two(dend)
```

stitchFieldCoordinates

stitchFieldCoordinates

Description

Helper function to stitch field coordinates together to form one complete picture

Usage

```
stitchFieldCoordinates(
  location_file,
  offset_file,
  cumulate_offset_x = F,
  cumulate_offset_y = F,
  field_col = "Field of View",
  X_coord_col = "X",
  Y_coord_col = "Y",
  reverse_final_x = F,
  reverse_final_y = T
)
```

Arguments

location_file location dataframe with X and Y coordinates

offset_file dataframe that describes the offset for each field (see details)

cumulate_offset_x
 (boolean) Do the x-axis offset values need to be cumulated?

cumulate_offset_y
 (boolean) Do the y-axis offset values need to be cumulated?

field_col column that indicates the field within the location_file

X_coord_col column that indicates the x coordinates

Y_coord_col column that indicates the x coordinates

reverse_final_x
 (boolean) Do the final x coordinates need to be reversed?

reverse_final_y
 (boolean) Do the final y coordinates need to be reversed?

Details

Stitching of fields:

- 1. have cell locations: at least 3 columns: field, X, Y
- 2. create offset file: offset file has 3 columns: field, x_offset, y_offset
- 3. create new cell location file by stitching original cell locations with stitchFieldCoordinates
- 4. provide new cell location file to [createGiottoObject](#)

Value

Updated location dataframe with new X ['X_final'] and Y ['Y_final'] coordinates

Examples

```
stitchFieldCoordinates(gobject)
```

subClusterCells	<i>subClusterCells</i>
-----------------	------------------------

Description

subcluster cells

Usage

```
subClusterCells(  
  gobject,  
  name = "sub_clus",  
  cluster_method = c("leiden", "louvain_community", "louvain_multinet"),  
  cluster_column = NULL,  
  selected_clusters = NULL,  
  hvg_param = list(reverse_log_scale = T, difference_in_variance = 1, expression_values  
    = "normalized"),  
  hvg_min_perc_cells = 5,  
  hvg_mean_expr_det = 1,  
  use_all_genes_as_hvg = FALSE,  
  min_nr_of_hvg = 5,  
  pca_param = list(expression_values = "normalized", scale_unit = T),  
  nn_param = list(dimensions_to_use = 1:20),  
  k_neighbors = 10,  
  resolution = 1,  
  gamma = 1,  
  omega = 1,  
  python_path = NULL,  
  nn_network_to_use = "sNN",  
  network_name = "sNN.pca",  
  return_gobject = TRUE,  
  verbose = T  
)
```


Arguments

<code>gobject</code>	giotto object
<code>name</code>	name for new clustering result
<code>cluster_method</code>	clustering method to use
<code>cluster_column</code>	cluster column to subcluster
<code>selected_clusters</code>	only do subclustering on these clusters
<code>hvg_param</code>	parameters for calculateHVG
<code>hvg_min_perc_cells</code>	threshold for detection in min percentage of cells
<code>hvg_mean_expr_det</code>	threshold for mean expression level in cells with detection
<code>use_all_genes_as_hvg</code>	forces all genes to be HVG and to be used as input for PCA
<code>min_nr_of_hvg</code>	minimum number of HVG, or all genes will be used as input for PCA
<code>pca_param</code>	parameters for runPCA
<code>nn_param</code>	parameters for parameters for createNearestNetwork
<code>k_neighbors</code>	number of k for createNearestNetwork
<code>resolution</code>	resolution
<code>gamma</code>	gamma
<code>omega</code>	omega
<code>python_path</code>	specify specific path to python if required
<code>nn_network_to_use</code>	type of NN network to use (kNN vs sNN)
<code>network_name</code>	name of NN network to use
<code>return_gobject</code>	boolean: return giotto object (default = TRUE)
<code>verbose</code>	verbose

Details

This function performs subclustering on selected clusters. The systematic steps are:

- 1. subset Giotto object
- 2. identify highly variable genes
- 3. run PCA
- 4. create nearest neighbouring network
- 5. do clustering

Value

giotto object with new subclusters appended to cell metadata

See Also

[doLouvainCluster_multinet](#), [doLouvainCluster_community](#) and @seealso [doLeidenCluster](#)

Examples

```
subClusterCells(gobject)
```

subsetGiotto

subsetGiotto

Description

subsets Giotto object including previous analyses.

Usage

```
subsetGiotto(gobject, cell_ids = NULL, gene_ids = NULL, verbose = FALSE)
```

Arguments

gobject	giotto object
cell_ids	cell IDs to keep
gene_ids	gene IDs to keep
verbose	be verbose

Value

giotto object

Examples

```
subsetGiotto(gobject)
```

subsetGiottoLocs

subsetGiottoLocs

Description

subsets Giotto object based on spatial locations

Usage

```
subsetGiottoLocs(
  gobject,
  x_max = NULL,
  x_min = NULL,
  y_max = NULL,
  y_min = NULL,
  z_max = NULL,
  z_min = NULL,
  return_gobject = T,
  verbose = FALSE
)
```

Arguments

<code>gobject</code>	giotto object
<code>x_max</code>	maximum x-coordinate
<code>x_min</code>	minimum x-coordinate
<code>y_max</code>	maximum y-coordinate
<code>y_min</code>	minimum y-coordinate
<code>z_max</code>	maximum z-coordinate
<code>z_min</code>	minimum z-coordinate
<code>return_gobject</code>	return Giotto object

Details

if `return_gobject = FALSE`, then a filtered combined metadata `data.table` will be returned

Value

giotto object

Examples

```
subsetGiottoLocs(gobject)
```

<code>viewHMRFresults</code>	<i><code>viewHMRFresults</code></i>
------------------------------	-------------------------------------

Description

View results from doHMRF.

Usage

```
viewHMRFresults(
  gobject,
  HMRFoutput,
  k = NULL,
  betas_to_view = NULL,
  third_dim = NULL,
  ...
)
```

Arguments

<code>gobject</code>	giotto object
<code>HMRFoutput</code>	HMRF output from doHMRF
<code>k</code>	number of HMRF domains
<code>betas_to_view</code>	results from different betas that you want to view
<code>...</code>	paramters to <code>visPlot()</code>

Details

Description ...

Value

spatial plots with HMRF domains

See Also

[visPlot](#)

Examples

`viewHMRFresults(gobject)`

<code>viewHMRFresults2D</code>	<i><code>viewHMRFresults2D</code></i>
--------------------------------	---------------------------------------

Description

View results from doHMRF.

Usage

```
viewHMRFresults2D(  
  gobject,  
  HMRFoutput,  
  k = NULL,  
  betas_to_view = NULL,  
  third_dim = NULL,  
  ...  
)
```

Arguments

<code>gobject</code>	giotto object
<code>HMRFoutput</code>	HMRF output from doHMRF
<code>k</code>	number of HMRF domains
<code>betas_to_view</code>	results from different betas that you want to view
<code>...</code>	paramters to <code>visPlot()</code>

Details

Description ...

Value

spatial plots with HMRF domains

See Also

[spatPlot2D](#)

Examples

```
viewHMRResults2D(gobject)
```

viewHMRResults3D	<i>viewHMRResults3D</i>
------------------	-------------------------

Description

View results from doHMRF.

Usage

```
viewHMRResults3D(  
  gobject,  
  HMRFoutput,  
  k = NULL,  
  betas_to_view = NULL,  
  third_dim = NULL,  
  ...  
)
```

Arguments

gobject	giotto object
HMRFoutput	HMRF output from doHMRF
k	number of HMRF domains
betas_to_view	results from different betas that you want to view
...	paramters to visPlot()

Details

Description ...

Value

spatial plots with HMRF domains

See Also

[spatPlot3D](#)

Examples

```
viewHMRResults3D(gobject)
```

violinPlot

violinPlot

Description

Creates violinplot for selected clusters

Usage

```
violinPlot(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  genes,
  cluster_column,
  cluster_custom_order = NULL,
  color_violin = c("genes", "cluster"),
  cluster_color_code = NULL,
  strip_position = c("top", "right", "left", "bottom"),
  strip_text = 7,
  axis_text_x_size = 10,
  axis_text_y_size = 6,
  show_plot = NA,
  return_plot = NA,
  save_plot = NA,
  save_param = list(),
  default_save_name = "violinPlot"
)
```

Arguments

gobject	giotto object
expression_values	expression values to use
genes	genes to plot
cluster_column	name of column to use for clusters
cluster_custom_order	custom order of clusters
color_violin	color violin according to genes or clusters
cluster_color_code	color code for clusters
strip_position	position of gene labels
strip_text	size of strip text
axis_text_x_size	size of x-axis text
axis_text_y_size	size of y-axis text
show_plot	show plot
return_plot	return ggplot object

save_plot	directly save the plot [boolean]
save_param	list of saving parameters from all_plots_save_function
default_save_name	default save name for saving, don't change, change save_name in save_param

Value

ggplot

Examples

```
violinPlot(gobject)
```

visDimGenePlot	<i>visDimGenePlot</i>
----------------	-----------------------

Description

Visualize cells and gene expression according to dimension reduction coordinates

Usage

```
visDimGenePlot(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  genes = NULL,
  dim_reduction_to_use = "umap",
  dim_reduction_name = "umap",
  dim1_to_use = 1,
  dim2_to_use = 2,
  dim3_to_use = NULL,
  show_NN_network = F,
  nn_network_to_use = "sNN",
  network_name = "sNN.pca",
  network_color = "lightgray",
  edge_alpha = NULL,
  scale_alpha_with_expression = FALSE,
  point_size = 1,
  genes_high_color = NULL,
  genes_mid_color = "white",
  genes_low_color = "blue",
  point_border_col = "black",
  point_border_stroke = 0.1,
  midpoint = 0,
  cow_n_col = 2,
  cow_rel_h = 1,
  cow_rel_w = 1,
  cow_align = "h",
  show_legend = T,
  plot_method = c("ggplot", "plotly"),
  show_plots = F
)
```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	gene expression values to use
<code>genes</code>	genes to show
<code>dim_reduction_to_use</code>	dimension reduction to use
<code>dim_reduction_name</code>	dimension reduction name
<code>dim1_to_use</code>	dimension to use on x-axis
<code>dim2_to_use</code>	dimension to use on y-axis
<code>dim3_to_use</code>	dimension to use on z-axis
<code>show_NN_network</code>	show underlying NN network
<code>nn_network_to_use</code>	type of NN network to use (kNN vs sNN)
<code>network_name</code>	name of NN network to use, if <code>show_NN_network = TRUE</code>
<code>edge_alpha</code>	column to use for alpha of the edges
<code>scale_alpha_with_expression</code>	scale expression with ggplot alpha parameter
<code>point_size</code>	size of point (cell)
<code>point_border_col</code>	color of border around points
<code>point_border_stroke</code>	stroke size of border around points
<code>midpoint</code>	size of point (cell)
<code>cow_n_col</code>	cowplot param: how many columns
<code>cow_rel_h</code>	cowplot param: relative height
<code>cow_rel_w</code>	cowplot param: relative width
<code>cow_align</code>	cowplot param: how to align
<code>show_legend</code>	show legend
<code>show_plots</code>	show plots

Details

Description of parameters.

Value

ggplot

Examples

```
visDimGenePlot(gobject)
```

```
visDimGenePlot_2D_ggplot
      visDimGenePlot_2D_ggplot
```

Description

Visualize cells and gene expression according to dimension reduction coordinates

Usage

```
visDimGenePlot_2D_ggplot(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  genes = NULL,
  dim_reduction_to_use = "umap",
  dim_reduction_name = "umap",
  dim1_to_use = 1,
  dim2_to_use = 2,
  show_NN_network = F,
  nn_network_to_use = "sNN",
  network_name = "sNN.pca",
  network_color = "lightgray",
  edge_alpha = NULL,
  scale_alpha_with_expression = FALSE,
  point_size = 1,
  genes_high_color = "red",
  genes_mid_color = "white",
  genes_low_color = "blue",
  point_border_col = "black",
  point_border_stroke = 0.1,
  midpoint = 0,
  cow_n_col = 2,
  cow_rel_h = 1,
  cow_rel_w = 1,
  cow_align = "h",
  show_legend = T,
  show_plots = F
)
```

Arguments

gobject	giotto object
expression_values	gene expression values to use
genes	genes to show
dim_reduction_to_use	dimension reduction to use
dim_reduction_name	dimension reduction name
dim1_to_use	dimension to use on x-axis

dim2_to_use	dimension to use on y-axis
show_NN_network	show underlying NN network
nn_network_to_use	type of NN network to use (kNN vs sNN)
network_name	name of NN network to use, if show_NN_network = TRUE
edge_alpha	column to use for alpha of the edges
scale_alpha_with_expression	scale expression with ggplot alpha parameter
point_size	size of point (cell)
point_border_col	color of border around points
point_border_stroke	stroke size of border around points
midpoint	size of point (cell)
cow_n_col	cowplot param: how many columns
cow_rel_h	cowplot param: relative height
cow_rel_w	cowplot param: relative width
cow_align	cowplot param: how to align
show_legend	show legend
show_plots	show plots

Details

Description of parameters.

Value

ggplot

Examples

```
visDimGenePlot_2D_ggplot(gobject)
```

```
visDimGenePlot_3D_plotly
visDimGenePlot_3D_plotly
```

Description

Visualize cells and gene expression according to dimension reduction coordinates

Usage

```
visDimGenePlot_3D_plotly(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  genes = NULL,
  dim_reduction_to_use = "umap",
  dim_reduction_name = "umap",
  dim1_to_use = 1,
  dim2_to_use = 2,
  dim3_to_use = 3,
  show_NN_network = F,
  nn_network_to_use = "sNN",
  network_name = "sNN.pca",
  network_color = "lightgray",
  edge_alpha = NULL,
  point_size = 1,
  genes_high_color = NULL,
  genes_mid_color = "white",
  genes_low_color = "blue",
  show_legend = T,
  show_plots = F
)
```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	gene expression values to use
<code>genes</code>	genes to show
<code>dim_reduction_to_use</code>	dimension reduction to use
<code>dim_reduction_name</code>	dimension reduction name
<code>dim1_to_use</code>	dimension to use on x-axis
<code>dim2_to_use</code>	dimension to use on y-axis
<code>dim3_to_use</code>	dimension to use on z-axis
<code>show_NN_network</code>	show underlying NN network
<code>nn_network_to_use</code>	type of NN network to use (kNN vs sNN)
<code>network_name</code>	name of NN network to use, if <code>show_NN_network = TRUE</code>
<code>edge_alpha</code>	column to use for alpha of the edges
<code>point_size</code>	size of point (cell)
<code>show_legend</code>	show legend
<code>show_plots</code>	show plots

Details

Description of parameters.

Value

ggplot

Examples

```
visDimGenePlot_3D_plotly(gobject)
```

visDimPlot	<i>visDimPlot</i>
------------	-------------------

Description

Visualize cells according to dimension reduction coordinates

Usage

```
visDimPlot(  
  gobject,  
  dim_reduction_to_use = "umap",  
  dim_reduction_name = "umap",  
  dim1_to_use = 1,  
  dim2_to_use = 2,  
  dim3_to_use = NULL,  
  show_NN_network = F,  
  nn_network_to_use = "sNN",  
  network_name = "sNN.pca",  
  cell_color = NULL,  
  color_as_factor = T,  
  cell_color_code = NULL,  
  select_cell_groups = NULL,  
  select_cells = NULL,  
  show_other_cells = T,  
  other_cell_color = "lightgrey",  
  other_point_size = 0.5,  
  show_cluster_center = F,  
  show_center_label = T,  
  center_point_size = 4,  
  center_point_border_col = "black",  
  center_point_border_stroke = 0.1,  
  label_size = 4,  
  label_fontface = "bold",  
  edge_alpha = NULL,  
  point_size = 3,  
  point_border_col = "black",  
  point_border_stroke = 0.1,  
  plot_method = c("ggplot", "plotly"),  
  show_legend = T,  
  show_plot = F,  
  return_plot = TRUE,  
  save_plot = F,  
  save_dir = NULL,
```

```

    save_folder = NULL,
    save_name = NULL,
    save_format = NULL,
    show_saved_plot = F,
    ...
)

```

Arguments

<code>gobject</code>	giotto object
<code>dim_reduction_to_use</code>	dimension reduction to use
<code>dim_reduction_name</code>	dimension reduction name
<code>dim1_to_use</code>	dimension to use on x-axis
<code>dim2_to_use</code>	dimension to use on y-axis
<code>dim3_to_use</code>	dimension to use on z-axis
<code>show_NN_network</code>	show underlying NN network
<code>nn_network_to_use</code>	type of NN network to use (kNN vs sNN)
<code>network_name</code>	name of NN network to use, if <code>show_NN_network = TRUE</code>
<code>cell_color</code>	color for cells (see details)
<code>color_as_factor</code>	convert color column to factor
<code>cell_color_code</code>	named vector with colors
<code>show_cluster_center</code>	plot center of selected clusters
<code>show_center_label</code>	plot label of selected clusters
<code>center_point_size</code>	size of center points
<code>label_size</code>	size of labels
<code>label_fontface</code>	font of labels
<code>edge_alpha</code>	column to use for alpha of the edges
<code>point_size</code>	size of point (cell)
<code>point_border_col</code>	color of border around points
<code>point_border_stroke</code>	stroke size of border around points
<code>show_legend</code>	show legend
<code>show_plot</code>	show plot
<code>return_plot</code>	return ggplot object
<code>save_plot</code>	directly save the plot [boolean]
<code>save_dir</code>	directory to save the plot

save_folder	(optional) folder in directory to save the plot
save_name	name of plot
save_format	format of plot (e.g. tiff, png, pdf, ...)
show_saved_plot	load & display the saved plot

Details

Description of parameters.

Value

ggplot or plotly

Examples

```
visDimPlot(gobject)
```

visDimPlot_2D_ggplot	<i>visDimPlot_2D_ggplot</i>
----------------------	-----------------------------

Description

Visualize cells according to dimension reduction coordinates

Usage

```
visDimPlot_2D_ggplot(
  gobject,
  dim_reduction_to_use = "umap",
  dim_reduction_name = "umap",
  dim1_to_use = 1,
  dim2_to_use = 2,
  show_NN_network = F,
  nn_network_to_use = "sNN",
  network_name = "sNN.pca",
  cell_color = NULL,
  color_as_factor = T,
  cell_color_code = NULL,
  select_cell_groups = NULL,
  select_cells = NULL,
  show_other_cells = T,
  other_cell_color = "lightgrey",
  other_point_size = 0.5,
  show_cluster_center = F,
  show_center_label = T,
  center_point_size = 4,
  center_point_border_col = "black",
  center_point_border_stroke = 0.1,
  label_size = 4,
  label_fontface = "bold",
```

```

    edge_alpha = NULL,
    point_size = 1,
    point_border_col = "black",
    point_border_stroke = 0.1,
    show_legend = T,
    show_plot = F,
    return_plot = TRUE,
    save_plot = F,
    save_dir = NULL,
    save_folder = NULL,
    save_name = NULL,
    save_format = NULL,
    show_saved_plot = F,
    ...
)

```

Arguments

<code>gobject</code>	giotto object
<code>dim_reduction_to_use</code>	dimension reduction to use
<code>dim_reduction_name</code>	dimension reduction name
<code>dim1_to_use</code>	dimension to use on x-axis
<code>dim2_to_use</code>	dimension to use on y-axis
<code>show_NN_network</code>	show underlying NN network
<code>nn_network_to_use</code>	type of NN network to use (kNN vs sNN)
<code>network_name</code>	name of NN network to use, if <code>show_NN_network = TRUE</code>
<code>cell_color</code>	color for cells (see details)
<code>color_as_factor</code>	convert color column to factor
<code>cell_color_code</code>	named vector with colors
<code>select_cell_groups</code>	select subset of cells/clusters based on <code>cell_color</code> parameter
<code>select_cells</code>	select subset of cells based on cell IDs
<code>show_other_cells</code>	display not selected cells
<code>other_cell_color</code>	color of not selected cells
<code>other_point_size</code>	size of not selected cells
<code>show_cluster_center</code>	plot center of selected clusters
<code>show_center_label</code>	plot label of selected clusters
<code>center_point_size</code>	size of center points

label_size	size of labels
label_fontface	font of labels
edge_alpha	column to use for alpha of the edges
point_size	size of point (cell)
point_border_col	color of border around points
point_border_stroke	stroke size of border around points
show_legend	show legend

Details

Description of parameters.

Value

ggplot

Examples

```
visDimPlot_2D_ggplot(gobject)
```

visDimPlot_2D_plotly *visDimPlot_2D_plotly*

Description

Visualize cells according to dimension reduction coordinates

Usage

```
visDimPlot_2D_plotly(
  gobject,
  dim_reduction_to_use = "umap",
  dim_reduction_name = "umap",
  dim1_to_use = 1,
  dim2_to_use = 2,
  select_cell_groups = NULL,
  select_cells = NULL,
  show_other_cells = T,
  other_cell_color = "lightgrey",
  other_point_size = 0.5,
  show_NN_network = F,
  nn_network_to_use = "sNN",
  network_name = "sNN.pca",
  color_as_factor = T,
  cell_color = NULL,
  cell_color_code = NULL,
  show_cluster_center = F,
  show_center_label = T,
```



```

    center_point_size = 4,
    label_size = 4,
    edge_alpha = NULL,
    point_size = 5
  )

```

Arguments

<code>gobject</code>	giotto object
<code>dim_reduction_to_use</code>	dimension reduction to use
<code>dim_reduction_name</code>	dimension reduction name
<code>dim1_to_use</code>	dimension to use on x-axis
<code>dim2_to_use</code>	dimension to use on y-axis
<code>show_NN_network</code>	show underlying NN network
<code>nn_network_to_use</code>	type of NN network to use (kNN vs sNN)
<code>network_name</code>	name of NN network to use, if <code>show_NN_network = TRUE</code>
<code>color_as_factor</code>	convert color column to factor
<code>cell_color</code>	color for cells (see details)
<code>cell_color_code</code>	named vector with colors
<code>show_cluster_center</code>	plot center of selected clusters
<code>show_center_label</code>	plot label of selected clusters
<code>center_point_size</code>	size of center points
<code>label_size</code>	size of labels
<code>edge_alpha</code>	column to use for alpha of the edges
<code>point_size</code>	size of point (cell)

Details

Description of parameters.

Value

plotly

Examples

```
visDimPlot_2D_plotly(gobject)
```

visDimPlot_3D_plotly *visDimPlot_3D_plotly*

Description

Visualize cells according to dimension reduction coordinates

Usage

```
visDimPlot_3D_plotly(
  gobject,
  dim_reduction_to_use = "umap",
  dim_reduction_name = "umap",
  dim1_to_use = 1,
  dim2_to_use = 2,
  dim3_to_use = 3,
  select_cell_groups = NULL,
  select_cells = NULL,
  show_other_cells = T,
  other_cell_color = "lightgrey",
  other_point_size = 0.5,
  show_NN_network = F,
  nn_network_to_use = "sNN",
  network_name = "sNN.pca",
  color_as_factor = T,
  cell_color = NULL,
  cell_color_code = NULL,
  show_cluster_center = F,
  show_center_label = T,
  center_point_size = 4,
  label_size = 4,
  edge_alpha = NULL,
  point_size = 1
)
```

Arguments

<code>gobject</code>	giotto object
<code>dim_reduction_to_use</code>	dimension reduction to use
<code>dim_reduction_name</code>	dimension reduction name
<code>dim1_to_use</code>	dimension to use on x-axis
<code>dim2_to_use</code>	dimension to use on y-axis
<code>dim3_to_use</code>	dimension to use on z-axis
<code>show_NN_network</code>	show underlying NN network
<code>nn_network_to_use</code>	type of NN network to use (kNN vs sNN)

network_name	name of NN network to use, if show_NN_network = TRUE
color_as_factor	convert color column to factor
cell_color	color for cells (see details)
cell_color_code	named vector with colors
show_cluster_center	plot center of selected clusters
show_center_label	plot label of selected clusters
center_point_size	size of center points
label_size	size of labels
edge_alpha	column to use for alpha of the edges
point_size	size of point (cell)

Details

Description of parameters.

Value

plotly

Examples

```
visDimPlot_3D_plotly(gobject)
```

visForceLayoutPlot	<i>visForceLayoutPlot</i>
--------------------	---------------------------

Description

Visualize cells according to forced layout algorithm coordinates

Usage

```
visForceLayoutPlot(
  gobject,
  nn_network_to_use = "sNN",
  network_name = "sNN.pca",
  layout_name = "layout",
  dim1_to_use = 1,
  dim2_to_use = 2,
  show_NN_network = T,
  cell_color = NULL,
  color_as_factor = TRUE,
  cell_color_code = NULL,
  edge_alpha = NULL,
  point_size = 1,
```

```

    point_border_col = "black",
    point_border_stroke = 0.1,
    show_legend = T,
    show_plot = F,
    return_plot = TRUE,
    save_plot = F,
    save_dir = NULL,
    save_folder = NULL,
    save_name = NULL,
    save_format = NULL,
    show_saved_plot = F,
    ...
)

```

Arguments

<code>gobject</code>	giotto object
<code>nn_network_to_use</code>	type of NN network to use (kNN vs sNN)
<code>network_name</code>	NN network to use
<code>layout_name</code>	name of layout to use
<code>dim1_to_use</code>	dimension to use on x-axis
<code>dim2_to_use</code>	dimension to use on y-axis
<code>show_NN_network</code>	show underlying NN network
<code>cell_color</code>	color for cells (see details)
<code>color_as_factor</code>	convert color column to factor
<code>cell_color_code</code>	named vector with colors
<code>edge_alpha</code>	column to use for alpha of the edges
<code>point_size</code>	size of point (cell)
<code>point_border_col</code>	color of border around points
<code>point_border_stroke</code>	stroke size of border around points
<code>show_legend</code>	show legend
<code>show_plot</code>	show plot
<code>return_plot</code>	return ggplot object
<code>save_plot</code>	directly save the plot [boolean]
<code>save_dir</code>	directory to save the plot
<code>save_folder</code>	(optional) folder in directory to save the plot
<code>save_name</code>	name of plot
<code>save_format</code>	format of plot (e.g. tiff, png, pdf, ...)
<code>show_saved_plot</code>	load & display the saved plot

Details

Description of parameters.

Value

ggplot

Examples

```
visForceLayoutPlot(gobject)
```

visGenePlot	<i>visGenePlot</i>
-------------	--------------------

Description

Visualize cells and gene expression according to spatial coordinates

Usage

```
visGenePlot(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  genes,
  genes_high_color = NULL,
  genes_mid_color = "white",
  genes_low_color = "blue",
  show_network = F,
  network_color = NULL,
  spatial_network_name = "spatial_network",
  edge_alpha = NULL,
  show_grid = F,
  grid_color = NULL,
  spatial_grid_name = "spatial_grid",
  midpoint = 0,
  scale_alpha_with_expression = FALSE,
  point_size = 1,
  point_border_col = "black",
  point_border_stroke = 0.1,
  show_legend = T,
  cow_n_col = 2,
  cow_rel_h = 1,
  cow_rel_w = 1,
  cow_align = "h",
  axis_scale = c("cube", "real", "custom"),
  custom_ratio = NULL,
  x_ticks = NULL,
  y_ticks = NULL,
  z_ticks = NULL,
  plot_method = c("ggplot", "plotly"),
  show_plots = F
)
```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	gene expression values to use
<code>genes</code>	genes to show
<code>genes_high_color</code>	color represents high gene expression
<code>genes_mid_color</code>	color represents middle gene expression
<code>genes_low_color</code>	color represents low gene expression
<code>show_network</code>	show underlying spatial network
<code>network_color</code>	color of spatial network
<code>spatial_network_name</code>	name of spatial network to use
<code>show_grid</code>	show spatial grid
<code>grid_color</code>	color of spatial grid
<code>spatial_grid_name</code>	name of spatial grid to use
<code>midpoint</code>	expression midpoint
<code>scale_alpha_with_expression</code>	scale expression with ggplot alpha parameter
<code>point_size</code>	size of point (cell)
<code>point_border_col</code>	color of border around points
<code>point_border_stroke</code>	stroke size of border around points
<code>show_legend</code>	show legend
<code>cow_n_col</code>	cowplot param: how many columns
<code>cow_rel_h</code>	cowplot param: relative height
<code>cow_rel_w</code>	cowplot param: relative width
<code>cow_align</code>	cowplot param: how to align
<code>axis_scale</code>	three mode to adjust axis scale
<code>x_ticks</code>	number of ticks on x axis
<code>y_ticks</code>	number of ticks on y axis
<code>z_ticks</code>	number of ticks on z axis
<code>plot_method</code>	two methods of plot
<code>show_plots</code>	show plots

Details

Description of parameters.

Value

ggplot or plotly

Examples

```
visGenePlot(gobject)
```

```
visGenePlot_2D_ggplot  visGenePlot_2D_ggplot
```

Description

Visualize cells and gene expression according to spatial coordinates

Usage

```
visGenePlot_2D_ggplot(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  genes,
  genes_high_color = "darkred",
  genes_mid_color = "white",
  genes_low_color = "darkblue",
  show_network = F,
  network_color = NULL,
  spatial_network_name = "spatial_network",
  edge_alpha = NULL,
  show_grid = F,
  grid_color = NULL,
  spatial_grid_name = "spatial_grid",
  midpoint = 0,
  scale_alpha_with_expression = FALSE,
  point_size = 1,
  point_border_col = "black",
  point_border_stroke = 0.1,
  show_legend = T,
  cow_n_col = 2,
  cow_rel_h = 1,
  cow_rel_w = 1,
  cow_align = "h",
  show_plots = F
)
```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	gene expression values to use
<code>genes</code>	genes to show
<code>genes_high_color</code>	color represents high gene expression
<code>genes_mid_color</code>	color represents middle gene expression

genes_low_color	color represents low gene expression
show_network	show underlying spatial network
network_color	color of spatial network
spatial_network_name	name of spatial network to use
show_grid	show spatial grid
grid_color	color of spatial grid
spatial_grid_name	name of spatial grid to use
midpoint	expression midpoint
scale_alpha_with_expression	scale expression with ggplot alpha parameter
point_size	size of point (cell)
point_border_col	color of border around points
point_border_stroke	stroke size of border around points
show_legend	show legend
cow_n_col	cowplot param: how many columns
cow_rel_h	cowplot param: relative height
cow_rel_w	cowplot param: relative width
cow_align	cowplot param: how to align
show_plots	show plots

Details

Description of parameters.

Value

ggplot

Examples

```
visGenePlot_2D_ggplot(gobject)
```

visGenePlot_3D_plotly *visGenePlot_3D_plotly*

Description

Visualize cells and gene expression according to spatial coordinates

Usage

```
visGenePlot_3D_plotly(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  genes,
  show_network = F,
  network_color = NULL,
  spatial_network_name = "spatial_network",
  edge_alpha = NULL,
  show_grid = F,
  genes_high_color = NULL,
  genes_mid_color = "white",
  genes_low_color = "blue",
  spatial_grid_name = "spatial_grid",
  point_size = 1,
  show_legend = T,
  axis_scale = c("cube", "real", "custom"),
  custom_ratio = NULL,
  x_ticks = NULL,
  y_ticks = NULL,
  z_ticks = NULL,
  show_plots = F
)
```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	gene expression values to use
<code>genes</code>	genes to show
<code>show_network</code>	show underlying spatial network
<code>network_color</code>	color of spatial network
<code>spatial_network_name</code>	name of spatial network to use
<code>show_grid</code>	show spatial grid
<code>genes_high_color</code>	color represents high gene expression
<code>genes_mid_color</code>	color represents middle gene expression
<code>genes_low_color</code>	color represents low gene expression
<code>spatial_grid_name</code>	name of spatial grid to use
<code>point_size</code>	size of point (cell)
<code>show_legend</code>	show legend
<code>axis_scale</code>	three mode to adjust axis scale
<code>x_ticks</code>	number of ticks on x axis
<code>y_ticks</code>	number of ticks on y axis

z_ticks	number of ticks on z axis
show_plots	show plots
grid_color	color of spatial grid
cow_n_col	cowplot param: how many columns
cow_rel_h	cowplot param: relative height
cow_rel_w	cowplot param: relative width
cow_align	cowplot param: how to align

Details

Description of parameters.

Value

plotly

Examples

```
visGenePlot_3D_plotly(gobject)
```

visPlot	<i>visPlot</i>
---------	----------------

Description

Visualize cells according to spatial coordinates

Usage

```
visPlot(  
  gobject,  
  sdimx = NULL,  
  sdimy = NULL,  
  sdimz = NULL,  
  point_size = 3,  
  point_border_col = "black",  
  point_border_stroke = 0.1,  
  cell_color = NULL,  
  cell_color_code = NULL,  
  color_as_factor = T,  
  select_cell_groups = NULL,  
  select_cells = NULL,  
  show_other_cells = T,  
  other_cell_color = "lightgrey",  
  show_network = F,  
  network_color = NULL,  
  network_alpha = 1,  
  other_cell_alpha = 0.1,  
  spatial_network_name = "spatial_network",  
  show_grid = F,  
)
```

```

    grid_color = NULL,
    grid_alpha = 1,
    spatial_grid_name = "spatial_grid",
    coord_fix_ratio = 0.6,
    title = "",
    show_legend = T,
    axis_scale = c("cube", "real", "custom"),
    custom_ratio = NULL,
    x_ticks = NULL,
    y_ticks = NULL,
    z_ticks = NULL,
    plot_method = c("ggplot", "plotly"),
    show_plot = F,
    return_plot = TRUE,
    save_plot = F,
    save_dir = NULL,
    save_folder = NULL,
    save_name = NULL,
    save_format = NULL,
    show_saved_plot = F,
    ...
)

```

Arguments

<code>gobject</code>	giotto object
<code>sdimx</code>	x-axis dimension name (default = 'sdimx')
<code>sdimy</code>	y-axis dimension name (default = 'sdimy')
<code>sdimz</code>	z-axis dimension name (default = 'sdimz')
<code>point_size</code>	size of point (cell)
<code>point_border_col</code>	color of border around points
<code>point_border_stroke</code>	stroke size of border around points
<code>cell_color</code>	color for cells (see details)
<code>cell_color_code</code>	named vector with colors
<code>color_as_factor</code>	convert color column to factor
<code>select_cell_groups</code>	select subset of cells/clusters based on <code>cell_color</code> parameter
<code>select_cells</code>	select subset of cells based on cell IDs
<code>show_other_cells</code>	display not selected cells
<code>other_cell_color</code>	color of not selected cells
<code>show_network</code>	show underlying spatial network
<code>network_color</code>	color of spatial network
<code>spatial_network_name</code>	name of spatial network to use

show_grid	show spatial grid
grid_color	color of spatial grid
spatial_grid_name	name of spatial grid to use
coord_fix_ratio	fix ratio between x and y-axis
title	title of plot
show_legend	show legend
show_plot	show plot
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_dir	directory to save the plot
save_folder	(optional) folder in directory to save the plot
save_name	name of plot
save_format	format of plot (e.g. tiff, png, pdf, ...)
show_saved_plot	load & display the saved plot

Details

Description of parameters.

Value

ggplot

Examples

visPlot(gobject)

visPlot_2D_ggplot	<i>visPlot_2D_ggplot</i>
-------------------	--------------------------

Description

Visualize cells according to spatial coordinates

Usage

```
visPlot_2D_ggplot(  
  gobject,  
  sdimx = NULL,  
  sdimy = NULL,  
  point_size = 3,  
  point_border_col = "black",  
  point_border_stroke = 0.1,  
  cell_color = NULL,  
  cell_color_code = NULL,
```

```

    color_as_factor = T,
    select_cell_groups = NULL,
    select_cells = NULL,
    show_other_cells = T,
    other_cell_color = "lightgrey",
    show_network = F,
    network_color = NULL,
    network_alpha = 1,
    other_cells_alpha = 0.1,
    spatial_network_name = "spatial_network",
    show_grid = F,
    grid_color = NULL,
    spatial_grid_name = "spatial_grid",
    coord_fix_ratio = 0.6,
    title = "",
    show_legend = T,
    axis_scale = c("cube", "real", "custom"),
    custom_ratio = NULL,
    x_ticks = NULL,
    y_ticks = NULL,
    z_ticks = NULL,
    show_plot = F,
    return_plot = TRUE,
    save_plot = F,
    save_dir = NULL,
    save_folder = NULL,
    save_name = NULL,
    save_format = NULL,
    show_saved_plot = F,
    ...
  )

```

Arguments

<code>gobject</code>	giotto object
<code>sdimx</code>	x-axis dimension name (default = 'sdimx')
<code>sdimy</code>	y-axis dimension name (default = 'sdimy')
<code>point_size</code>	size of point (cell)
<code>point_border_col</code>	color of border around points
<code>point_border_stroke</code>	stroke size of border around points
<code>cell_color</code>	color for cells (see details)
<code>cell_color_code</code>	named vector with colors
<code>color_as_factor</code>	convert color column to factor
<code>select_cell_groups</code>	select subset of cells/clusters based on <code>cell_color</code> parameter
<code>select_cells</code>	select subset of cells based on cell IDs

show_other_cells	display not selected cells
other_cell_color	color of not selected cells
show_network	show underlying spatial network
network_color	color of spatial network
spatial_network_name	name of spatial network to use
show_grid	show spatial grid
grid_color	color of spatial grid
spatial_grid_name	name of spatial grid to use
coord_fix_ratio	fix ratio between x and y-axis
title	title of plot
show_legend	show legend
show_plot	show plot
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_dir	directory to save the plot
save_folder	(optional) folder in directory to save the plot
save_name	name of plot
save_format	format of plot (e.g. tiff, png, pdf, ...)
show_saved_plot	load & display the saved plot

Details

Description of parameters.

Value

ggplot

Examples

```
visPlot_2D_ggplot(gobject)
```

visPlot_2D_plotly	<i>visPlot_2D_plotly</i>
-------------------	--------------------------

Description

Visualize cells according to spatial coordinates

Usage

```
visPlot_2D_plotly(
  gobject,
  sdimx = NULL,
  sdimy = NULL,
  point_size = 3,
  cell_color = NULL,
  cell_color_code = NULL,
  color_as_factor = T,
  select_cell_groups = NULL,
  select_cells = NULL,
  show_other_cells = T,
  other_cell_color = "lightgrey",
  other_point_size = 0.5,
  show_network = F,
  network_color = "lightgray",
  network_alpha = 1,
  other_cell_alpha = 0.5,
  spatial_network_name = "spatial_network",
  show_grid = F,
  grid_color = NULL,
  grid_alpha = 1,
  spatial_grid_name = "spatial_grid",
  show_legend = T,
  axis_scale = c("cube", "real", "custom"),
  custom_ratio = NULL,
  x_ticks = NULL,
  y_ticks = NULL,
  show_plot = F
)
```

Arguments

<code>gobject</code>	giotto object
<code>sdimx</code>	x-axis dimension name (default = 'sdimx')
<code>sdimy</code>	y-axis dimension name (default = 'sdimy')
<code>point_size</code>	size of point (cell)
<code>cell_color</code>	color for cells (see details)
<code>cell_color_code</code>	named vector with colors
<code>color_as_factor</code>	convert color column to factor

select_cell_groups	select a subset of the groups from cell_color
show_network	show underlying spatial network
network_color	color of spatial network
spatial_network_name	name of spatial network to use
show_grid	show spatial grid
grid_color	color of spatial grid
grid_alpha	alpha of spatial grid
spatial_grid_name	name of spatial grid to use
show_legend	show legend
show_plot	show plot

Details

Description of parameters.

Value

plotly

Examples

visPlot_2D_plotly(gobject)

visPlot_3D_plotly	<i>visPlot_3D_plotly</i>
-------------------	--------------------------

Description

Visualize cells according to spatial coordinates

Usage

```
visPlot_3D_plotly(  
  gobject,  
  sdimx = NULL,  
  sdimy = NULL,  
  sdimz = NULL,  
  point_size = 3,  
  cell_color = NULL,  
  cell_color_code = NULL,  
  select_cell_groups = NULL,  
  select_cells = NULL,  
  show_other_cells = T,  
  other_cell_color = "lightgrey",  
  other_point_size = 0.5,  
  show_network = F,
```



```

    network_color = NULL,
    network_alpha = 1,
    other_cell_alpha = 0.5,
    spatial_network_name = "spatial_network",
    spatial_grid_name = "spatial_grid",
    title = "",
    show_legend = T,
    axis_scale = c("cube", "real", "custom"),
    custom_ratio = NULL,
    x_ticks = NULL,
    y_ticks = NULL,
    z_ticks = NULL,
    show_plot = F
)

```

Arguments

<code>gobject</code>	giotto object
<code>sdimx</code>	x-axis dimension name (default = 'sdimx')
<code>sdimy</code>	y-axis dimension name (default = 'sdimy')
<code>sdimz</code>	z-axis dimension name (default = 'sdimz')
<code>point_size</code>	size of point (cell)
<code>cell_color</code>	color for cells (see details)
<code>cell_color_code</code>	named vector with colors
<code>select_cell_groups</code>	select a subset of the groups from <code>cell_color</code>
<code>show_network</code>	show underlying spatial network
<code>network_color</code>	color of spatial network
<code>spatial_network_name</code>	name of spatial network to use
<code>spatial_grid_name</code>	name of spatial grid to use
<code>title</code>	title of plot
<code>show_legend</code>	show legend
<code>show_plot</code>	show plot
<code>point_border_col</code>	color of border around points
<code>point_border_stroke</code>	stroke size of border around points
<code>color_as_factor</code>	convert color column to factor
<code>show_grid</code>	show spatial grid
<code>grid_color</code>	color of spatial grid
<code>coord_fix_ratio</code>	fix ratio between x and y-axis

Details

Description of parameters.

Value

ggplot

Examples

```
visPlot_3D_plotly(gobject)
```

visSpatDimGenePlot	<i>visSpatDimGenePlot</i>
--------------------	---------------------------

Description

integration of visSpatDimGenePlot_2D(ggplot) and visSpatDimGenePlot_3D(plotly)

Usage

```
visSpatDimGenePlot(
  gobject,
  plot_method = c("ggplot", "plotly"),
  expression_values = c("normalized", "scaled", "custom"),
  plot_alignment = c("horizontal", "vertical"),
  dim_reduction_to_use = "umap",
  dim_reduction_name = "umap",
  dim1_to_use = 1,
  dim2_to_use = 2,
  dim3_to_use = NULL,
  sdimx = NULL,
  sdimy = NULL,
  sdimz = NULL,
  genes,
  dim_point_border_col = "black",
  dim_point_border_stroke = 0.1,
  show_NN_network = F,
  nn_network_to_use = "sNN",
  network_name = "sNN.pca",
  edge_alpha_dim = NULL,
  scale_alpha_with_expression = FALSE,
  label_size = 16,
  genes_low_color = "blue",
  genes_mid_color = "white",
  genes_high_color = "red",
  dim_point_size = 3,
  nn_network_alpha = 0.5,
  show_spatial_network = F,
  spatial_network_name = "spatial_network",
  network_color = "lightgray",
  spatial_network_alpha = 0.5,
```

```

show_spatial_grid = F,
spatial_grid_name = "spatial_grid",
spatial_grid_color = NULL,
spatial_grid_alpha = 0.5,
spatial_point_size = 3,
spatial_point_border_col = "black",
spatial_point_border_stroke = 0.1,
legend_text_size = 12,
axis_scale = c("cube", "real", "custom"),
custom_ratio = NULL,
x_ticks = NULL,
y_ticks = NULL,
z_ticks = NULL,
midpoint = 0,
point_size = 1,
cow_n_col = 2,
cow_rel_h = 1,
cow_rel_w = 1,
cow_align = "h",
show_legend = T,
show_plots = F
)

```

Arguments

<code>gobject</code>	giotto object
<code>expression_values</code>	gene expression values to use
<code>plot_alignment</code>	direction to align plot
<code>dim_reduction_to_use</code>	dimension reduction to use
<code>dim_reduction_name</code>	dimension reduction name
<code>dim1_to_use</code>	dimension to use on x-axis
<code>dim2_to_use</code>	dimension to use on y-axis
<code>dim3_to_use</code>	dimension to use on z-axis
<code>sdimx</code>	x-axis dimension name (default = 'sdimx')
<code>sdimy</code>	y-axis dimension name (default = 'sdimy')
<code>sdimz</code>	z-axis dimension name (default = 'sdimz')
<code>genes</code>	genes to show
<code>dim_point_border_col</code>	color of border around points
<code>dim_point_border_stroke</code>	stroke size of border around points
<code>show_NN_network</code>	show underlying NN network
<code>nn_network_to_use</code>	type of NN network to use (kNN vs sNN)
<code>network_name</code>	name of NN network to use, if <code>show_NN_network = TRUE</code>

edge_alpha_dim	dim reduction plot: column to use for alpha of the edges
scale_alpha_with_expression	scale expression with ggplot alpha parameter
label_size	size for the label
genes_low_color	color to represent low expression of gene
genes_high_color	color to represent high expression of gene
dim_point_size	dim reduction plot: point size
spatial_network_name	name of spatial network to use
spatial_grid_name	name of spatial grid to use
spatial_point_size	spatial plot: point size
spatial_point_border_col	color of border around points
spatial_point_border_stroke	stroke size of border around points
legend_text_size	the size of the text in legend
axis_scale	three modes to adjust axis scale ratio
custom_ratio	set the axis scale ratio on custom
x_ticks	number of ticks on x axis
y_ticks	number of ticks on y axis
z_ticks	number of ticks on z axis
midpoint	size of point (cell)
point_size	size of point (cell)
cow_n_col	cowplot param: how many columns
cow_rel_h	cowplot param: relative height
cow_rel_w	cowplot param: relative width
cow_align	cowplot param: how to align
show_legend	show legend
show_plot	show plot

Details

Description of parameters.

Value

ggplot or plotly

Examples

```
visSpatDimGenePlot(gobject)
```

visSpatDimGenePlot_2D *visSpatDimGenePlot_2D*

Description

Visualize cells according to spatial AND dimension reduction coordinates in ggplot mode

Usage

```
visSpatDimGenePlot_2D(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  plot_alignment = c("horizontal", "vertical"),
  genes,
  dim_reduction_to_use = "umap",
  dim_reduction_name = "umap",
  dim1_to_use = 1,
  dim2_to_use = 2,
  point_size = 1,
  dim_point_border_col = "black",
  dim_point_border_stroke = 0.1,
  show_NN_network = F,
  show_spatial_network = F,
  show_spatial_grid = F,
  nn_network_to_use = "sNN",
  network_name = "sNN.pca",
  edge_alpha_dim = NULL,
  scale_alpha_with_expression = FALSE,
  spatial_network_name = "spatial_network",
  spatial_grid_name = "spatial_grid",
  spatial_point_size = 1,
  spatial_point_border_col = "black",
  spatial_point_border_stroke = 0.1,
  midpoint = 0,
  genes_high_color = "red",
  genes_mid_color = "white",
  genes_low_color = "blue",
  cow_n_col = 2,
  cow_rel_h = 1,
  cow_rel_w = 1,
  cow_align = "h",
  axis_scale = c("cube", "real", "custom"),
  custom_ratio = NULL,
  x_ticks = NULL,
  y_ticks = NULL,
  show_legend = T,
  show_plots = F
)
```

Arguments

gobject giotto object

expression_values	gene expression values to use
plot_alignment	direction to align plot
genes	genes to show
dim_reduction_to_use	dimension reduction to use
dim_reduction_name	dimension reduction name
dim1_to_use	dimension to use on x-axis
dim2_to_use	dimension to use on y-axis
point_size	size of point (cell)
dim_point_border_col	color of border around points
dim_point_border_stroke	stroke size of border around points
show_NN_network	show underlying NN network
nn_network_to_use	type of NN network to use (kNN vs sNN)
network_name	name of NN network to use, if show_NN_network = TRUE
edge_alpha_dim	dim reduction plot: column to use for alpha of the edges
scale_alpha_with_expression	scale expression with ggplot alpha parameter
spatial_network_name	name of spatial network to use
spatial_grid_name	name of spatial grid to use
spatial_point_size	spatial plot: point size
spatial_point_border_col	color of border around points
spatial_point_border_stroke	stroke size of border around points
midpoint	size of point (cell)
cow_n_col	cowplot param: how many columns
cow_rel_h	cowplot param: relative height
cow_rel_w	cowplot param: relative width
cow_align	cowplot param: how to align
show_legend	show legend
dim_point_size	dim reduction plot: point size
show_plot	show plot

Details

Description of parameters.

Value

ggplot

Examples

```
visSpatDimGenePlot_2D(gobject)
```

```
visSpatDimGenePlot_3D  visSpatDimGenePlot_3D
```

Description

Visualize cells according to spatial AND dimension reduction coordinates in plotly mode

Usage

```
visSpatDimGenePlot_3D(
  gobject,
  expression_values = c("normalized", "scaled", "custom"),
  plot_alignment = c("horizontal", "vertical"),
  dim_reduction_to_use = "umap",
  dim_reduction_name = "umap",
  dim1_to_use = 1,
  dim2_to_use = 2,
  dim3_to_use = NULL,
  sdimx = NULL,
  sdimy = NULL,
  sdimz = NULL,
  genes,
  show_NN_network = F,
  nn_network_to_use = "sNN",
  network_name = "sNN.pca",
  label_size = 16,
  genes_low_color = "blue",
  genes_mid_color = "white",
  genes_high_color = "red",
  dim_point_size = 3,
  nn_network_alpha = 0.5,
  show_spatial_network = F,
  spatial_network_name = "spatial_network",
  network_color = "lightgray",
  spatial_network_alpha = 0.5,
  show_spatial_grid = F,
  spatial_grid_name = "spatial_grid",
  spatial_grid_color = NULL,
  spatial_grid_alpha = 0.5,
  spatial_point_size = 3,
  legend_text_size = 12,
  axis_scale = c("cube", "real", "custom"),
  custom_ratio = NULL,
  x_ticks = NULL,
```

```

    y_ticks = NULL,
    z_ticks = NULL
  )

```

Arguments

<code>gobject</code>	giotto object
<code>plot_alignment</code>	direction to align plot
<code>dim_reduction_to_use</code>	dimension reduction to use
<code>dim_reduction_name</code>	dimension reduction name
<code>dim1_to_use</code>	dimension to use on x-axis
<code>dim2_to_use</code>	dimension to use on y-axis
<code>dim3_to_use</code>	dimension to use on z-axis
<code>show_NN_network</code>	show underlying NN network
<code>nn_network_to_use</code>	type of NN network to use (kNN vs sNN)
<code>network_name</code>	name of NN network to use, if <code>show_NN_network = TRUE</code>
<code>genes_low_color</code>	color represent high gene expression (see details)
<code>genes_high_color</code>	color represent high gene expression (see details)
<code>nn_network_alpha</code>	column to use for alpha of the edges
<code>show_spatial_network</code>	show spatial network
<code>spatial_network_name</code>	name of spatial network to use
<code>network_color</code>	color of spatial/nn network
<code>spatial_network_alpha</code>	alpha of spatial network
<code>show_spatial_grid</code>	show spatial grid
<code>spatial_grid_name</code>	name of spatial grid to use
<code>spatial_grid_color</code>	color of spatial grid
<code>spatial_grid_alpha</code>	alpha of spatial grid
<code>legend_text_size</code>	text size of legend
<code>show_legend</code>	show legend
<code>show_plot</code>	show plot

Details

Description of parameters.

Value

plotly

Examples

```
visSpatDimPlot_3D(gobject)
```

visSpatDimPlot

visSpatDimPlot

Description

integration of visSpatDimPlot_2D and visSpatDimPlot_3D

Usage

```
visSpatDimPlot(
  gobject,
  plot_method = c("ggplot", "plotly"),
  plot_alignment = NULL,
  dim_reduction_to_use = "umap",
  dim_reduction_name = "umap",
  dim1_to_use = 1,
  dim2_to_use = 2,
  dim3_to_use = NULL,
  sdims = NULL,
  sdims = NULL,
  sdims = NULL,
  show_NN_network = F,
  nn_network_to_use = "sNN",
  network_name = "sNN.pca",
  show_cluster_center = F,
  show_center_label = T,
  center_point_size = 4,
  label_size = NULL,
  label_fontface = "bold",
  cell_color = NULL,
  color_as_factor = T,
  cell_color_code = NULL,
  select_cell_groups = NULL,
  select_cells = NULL,
  show_other_cells = T,
  other_cell_color = "lightgrey",
  dim_point_size = 3,
  dim_point_border_col = "black",
  dim_point_border_stroke = 0.1,
  nn_network_alpha = NULL,
  show_spatial_network = F,
  spatial_network_name = "spatial_network",
  network_color = "lightgray",
  spatial_network_alpha = 0.5,
```

```

show_spatial_grid = F,
spatial_grid_name = "spatial_grid",
spatial_grid_color = NULL,
spatial_grid_alpha = 0.5,
spatial_point_size = 3,
legend_text_size = 12,
spatial_point_border_col = "black",
spatial_point_border_stroke = 0.1,
show_legend = T,
axis_scale = c("cube", "real", "custom"),
custom_ratio = NULL,
x_ticks = NULL,
y_ticks = NULL,
z_ticks = NULL,
show_plot = F
)

```

Arguments

<code>gobject</code>	giotto object
<code>plot_alignment</code>	direction to align plot
<code>dim_reduction_to_use</code>	dimension reduction to use
<code>dim_reduction_name</code>	dimension reduction name
<code>dim1_to_use</code>	dimension to use on x-axis
<code>dim2_to_use</code>	dimension to use on y-axis
<code>dim3_to_use</code>	dimension to use on z-axis
<code>show_NN_network</code>	show underlying NN network
<code>nn_network_to_use</code>	type of NN network to use (kNN vs sNN)
<code>network_name</code>	name of NN network to use, if <code>show_NN_network = TRUE</code>
<code>cell_color</code>	color for cells (see details)
<code>color_as_factor</code>	convert color column to factor
<code>cell_color_code</code>	named vector with colors
<code>select_cell_groups</code>	select subset of cells/clusters based on <code>cell_color</code> parameter
<code>select_cells</code>	select subset of cells based on cell IDs
<code>show_other_cells</code>	display not selected cells
<code>other_cell_color</code>	color of not selected cells
<code>nn_network_alpha</code>	column to use for alpha of the edges
<code>show_spatial_network</code>	show spatial network

```

spatial_network_name
    name of spatial network to use
spatial_network_alpha
    alpha of spatial network
show_spatial_grid
    show spatial grid
spatial_grid_name
    name of spatial grid to use
spatial_grid_color
    color of spatial grid
spatial_grid_alpha
    alpha of spatial grid
legend_text_size
    text size of legend
show_legend
    show legend
show_plot
    show plot
plot_mode
    choose the mode to draw plot : ggplot or plotly
spatial_network_color
    color of spatial network

```

Details

Description of parameters.

Value

ggplot or plotly

Examples

```
visSpatDimPlot(gobject)
```

visSpatDimPlot_2D	<i>visSpatDimPlot_2D</i>
-------------------	--------------------------

Description

Visualize cells according to spatial AND dimension reduction coordinates in ggplot2 mode

Usage

```

visSpatDimPlot_2D(
  gobject,
  plot_alignment = c("vertical", "horizontal"),
  dim_reduction_to_use = "umap",
  dim_reduction_name = "umap",
  dim1_to_use = 1,
  dim2_to_use = 2,
  sdimx = NULL,
  sdimy = NULL,

```

```

show_NN_network = F,
nn_network_to_use = "sNN",
network_name = "sNN.pca",
show_cluster_center = F,
show_center_label = T,
center_point_size = 4,
label_size = 4,
label_fontface = "bold",
cell_color = NULL,
color_as_factor = T,
cell_color_code = NULL,
select_cell_groups = NULL,
select_cells = NULL,
show_other_cells = T,
other_cell_color = "lightgrey",
dim_plot_mode = NULL,
dim_point_size = 1,
dim_point_border_col = "black",
dim_point_border_stroke = 0.1,
nn_network_alpha = 0.05,
show_spatial_network = F,
spatial_network_name = "spatial_network",
spatial_network_color = NULL,
show_spatial_grid = F,
spatial_grid_name = "spatial_grid",
spatial_grid_color = NULL,
spatial_point_size = 1,
spatial_point_border_col = "black",
spatial_point_border_stroke = 0.1,
show_legend = T,
show_plot = F,
plot_method = "ggplot"
)

```

Arguments

<code>gobject</code>	giotto object
<code>plot_alignment</code>	direction to align plot
<code>dim_reduction_to_use</code>	dimension reduction to use
<code>dim_reduction_name</code>	dimension reduction name
<code>dim1_to_use</code>	dimension to use on x-axis
<code>dim2_to_use</code>	dimension to use on y-axis
<code>show_NN_network</code>	show underlying NN network
<code>nn_network_to_use</code>	type of NN network to use (kNN vs sNN)
<code>network_name</code>	name of NN network to use, if <code>show_NN_network = TRUE</code>
<code>cell_color</code>	color for cells (see details)

color_as_factor	convert color column to factor
cell_color_code	named vector with colors
select_cell_groups	select subset of cells/clusters based on cell_color parameter
select_cells	select subset of cells based on cell IDs
show_other_cells	display not selected cells
other_cell_color	color of not selected cells
nn_network_alpha	column to use for alpha of the edges
show_spatial_network	show spatial network
spatial_network_name	name of spatial network to use
spatial_network_color	color of spatial network
show_spatial_grid	show spatial grid
spatial_grid_name	name of spatial grid to use
spatial_grid_color	color of spatial grid
show_legend	show legend
show_plot	show plot
return_plot	return ggplot object
save_plot	directly save the plot [boolean]
save_dir	directory to save the plot
save_folder	(optional) folder in directory to save the plot
save_name	name of plot
save_format	format of plot (e.g. tiff, png, pdf, ...)
show_saved_plot	load & display the saved plot

Details

Description of parameters.

Value

ggplot

Examples

```
visSpatDimPlot_2D(gobject)
```

visSpatDimPlot_3D	<i>visSpatDimPlot_3D</i>
-------------------	--------------------------

Description

Visualize cells according to spatial AND dimension reduction coordinates in plotly mode

Usage

```
visSpatDimPlot_3D(
  gobject,
  plot_alignment = c("horizontal", "vertical"),
  dim_reduction_to_use = "umap",
  dim_reduction_name = "umap",
  dim1_to_use = 1,
  dim2_to_use = 2,
  dim3_to_use = NULL,
  sdimx = NULL,
  sdimy = NULL,
  sdimz = NULL,
  show_NN_network = F,
  nn_network_to_use = "sNN",
  network_name = "sNN.pca",
  show_cluster_center = F,
  show_center_label = T,
  center_point_size = 4,
  label_size = 16,
  cell_color = NULL,
  color_as_factor = T,
  cell_color_code = NULL,
  dim_point_size = 3,
  nn_network_alpha = 0.5,
  show_spatial_network = F,
  spatial_network_name = "spatial_network",
  network_color = "lightgray",
  spatial_network_alpha = 0.5,
  show_spatial_grid = F,
  spatial_grid_name = "spatial_grid",
  spatial_grid_color = NULL,
  spatial_grid_alpha = 0.5,
  spatial_point_size = 3,
  axis_scale = c("cube", "real", "custom"),
  custom_ratio = NULL,
  x_ticks = NULL,
  y_ticks = NULL,
  z_ticks = NULL,
  legend_text_size = 12
)
```

Arguments

gobject giotto object

plot_alignment	direction to align plot
dim_reduction_to_use	dimension reduction to use
dim_reduction_name	dimension reduction name
dim1_to_use	dimension to use on x-axis
dim2_to_use	dimension to use on y-axis
dim3_to_use	dimension to use on z-axis
show_NN_network	show underlying NN network
nn_network_to_use	type of NN network to use (kNN vs sNN)
network_name	name of NN network to use, if show_NN_network = TRUE
cell_color	color for cells (see details)
color_as_factor	convert color column to factor
cell_color_code	named vector with colors
nn_network_alpha	column to use for alpha of the edges
show_spatial_network	show spatial network
spatial_network_name	name of spatial network to use
spatial_network_alpha	alpha of spatial network
show_spatial_grid	show spatial grid
spatial_grid_name	name of spatial grid to use
spatial_grid_color	color of spatial grid
spatial_grid_alpha	alpha of spatial grid
legend_text_size	text size of legend
spatial_network_color	color of spatial network
show_legend	show legend
show_plot	show plot

Details

Description of parameters.

Value

plotly

Examples

```
visSpatDimPlot_3D(gobject)
```

writeHMRResults	<i>writeHMRResults</i>
-----------------	------------------------

Description

write results from doHMRF to a data.table.

Usage

```
writeHMRResults(
  gobject,
  HMRFoutput,
  k = NULL,
  betas_to_view = NULL,
  print_command = F
)
```

Arguments

gobject	giotto object
HMRFoutput	HMRF output from doHMRF
k	k to write results for
betas_to_view	results from different betas that you want to view
print_command	see the python command

Value

data.table with HMRF results for each b and the selected k

Examples

```
writeHMRResults(gobject)
```

write_giotto_viewer_annotation	<i>write_giotto_viewer_annotation</i>
--------------------------------	---------------------------------------

Description

write out factor-like annotation data from a giotto object for the Viewer

Usage

```
write_giotto_viewer_annotation(
  annotation,
  annot_name = "test",
  output_directory = getwd()
)
```


Arguments

annotation	annotation from the data.table from giotto object
annot_name	name of the annotation
output_directory	directory where to save the files

Value

write a .txt and .annot file for the selection annotation

```
write_giotto_viewer_dim_reduction
      write_giotto_viewer_dim_reduction
```

Description

write out dimensional reduction data from a giotto object for the Viewer

Usage

```
write_giotto_viewer_dim_reduction(
  dim_reduction_cell,
  dim_red = NULL,
  dim_red_name = NULL,
  dim_red_rounding = NULL,
  dim_red_rescale = c(-20, 20),
  output_directory = getwd()
)
```

Arguments

dim_reduction_cell	dimension reduction slot from giotto object
dim_red	high level name of dimension reduction
dim_red_name	specific name of dimension reduction to use
dim_red_rounding	numerical indicating how to round the coordinates
dim_red_rescale	numericals to rescale the coordinates
output_directory	directory where to save the files

Value

write a .txt and .annot file for the selection annotation

```
write_giotto_viewer_numeric_annotation  
    write_giotto_viewer_numeric_annotation
```

Description

write out numeric annotation data from a giotto object for the Viewer

Usage

```
write_giotto_viewer_numeric_annotation(  
  annotation,  
  annot_name = "test",  
  output_directory = getwd()  
)
```

Arguments

annotation	annotation from the data.table from giotto object
annot_name	name of the annotation
output_directory	directory where to save the files

Value

write a .txt and .annot file for the selection annotation

Index

- *Topic **giotto**,
 - giotto-class, [136](#)
 - print.giotto, [179](#)
 - show,giotto-method, [188](#)
- *Topic **giotto**
 - createGiottoObject, [47](#)
- *Topic **object**
 - giotto-class, [136](#)
 - print.giotto, [179](#)
 - show,giotto-method, [188](#)
- [addCellMetadata, 7, 49](#)
- [addCellStatistics, 7, 12](#)
- [addGeneMetadata, 8, 49](#)
- [addGeneStatistics, 9, 12](#)
- [addHMRF, 10](#)
- [addNetworkLayout, 11](#)
- [addStatistics, 12](#)
- [adjustGiottoMatrix, 12](#)
- [aes_string2, 13](#)
- [all_plots_save_function, 15, 21, 25, 27, 28, 30, 32, 34, 66, 69, 71, 73, 74, 77, 80, 83, 85, 138, 149, 151, 155, 157, 159, 161, 163, 165, 167, 168, 170, 172, 174, 181, 189, 190, 192, 195, 197, 198, 205, 208, 212, 216, 218, 221, 223, 227, 231, 234, 236, 238, 240, 245, 248, 251, 253, 263](#)
- [allCellCellcommunicationsScores, 14](#)
- [annotate_spatlocs_with_spatgrid_2D, 17](#)
- [annotate_spatlocs_with_spatgrid_3D, 18](#)
- [annotateGiotto, 16](#)
- [annotateSpatialNetwork, 17](#)
- [average_gene_gene_expression_in_groups, 18](#)
- [binGetSpatialGenes, 19](#)
- [calculate_spatial_genes_python, 23](#)
- [calculateHVG, 20](#)
- [calculateMetaTable, 22](#)
- [calculateMetaTableCells, 23](#)
- [cellProximityBarplot, 24](#)
- [cellProximityEnrichment, 25](#)
- [cellProximityHeatmap, 26](#)
- [cellProximityNetwork, 27](#)
- [cellProximitySpatPlot, 29](#)
- [cellProximitySpatPlot2D, 30, 30](#)
- [cellProximitySpatPlot3D, 30, 32](#)
- [cellProximityVisPlot, 34](#)
- [cellProximityVisPlot_2D_ggplot, 36](#)
- [cellProximityVisPlot_2D_plotly, 38](#)
- [cellProximityVisPlot_3D_plotly, 40](#)
- [changeGiottoInstructions, 41](#)
- [cluster_walktrap, 102](#)
- [clusterCells, 42](#)
- [clusterSpatialCorGenes, 45](#)
- [combineMetadata, 45](#)
- [convertEnsemblToGeneSymbol, 46](#)
- [cowplot::save_plot, 136](#)
- [create_average_detection_DT, 58](#)
- [create_average_DT, 58](#)
- [create_cell_type_random_cell_IDs, 59](#)
- [create_cluster_matrix, 60](#)
- [create_dimObject, 60](#)
- [createGiottoInstructions, 46, 48](#)
- [createGiottoObject, 47, 256](#)
- [createHeatmap_DT, 49](#)
- [createMetagenes, 50](#)
- [createNearestNetwork, 51](#)
- [createSpatialEnrich, 53, 107](#)
- [createSpatialGrid, 54](#)
- [createSpatialGrid_2D, 55](#)
- [createSpatialGrid_3D, 56](#)
- [createSpatialNetwork, 57, 62](#)
- [decide_cluster_order, 61](#)
- [detectSpatialCorGenes, 62](#)
- [detectSpatialPatterns, 63](#)
- [dimCellPlot, 64](#)
- [dimCellPlot2D, 66, 67](#)
- [dimGenePlot, 69](#)
- [dimGenePlot2D, 71](#)
- [dimGenePlot3D, 71, 73, 73](#)
- [dimPlot, 75](#)
- [dimPlot2D, 77, 78, 159, 161, 165, 167, 170, 172](#)
- [dimPlot2D_single, 81](#)

- dimPlot3D, [69](#), [77](#), [80](#), [83](#), [83](#)
- direction_test(direction_test_CPG), [85](#)
- direction_test_CPG, [85](#)
- do_spatial_grid_averaging, [104](#)
- do_spatial_knn_smoothing, [105](#)
- doHclust, [44](#), [86](#)
- doHMRF, [87](#)
- doKmeans, [44](#), [88](#)
- doLeidenCluster, [44](#), [90](#), [93](#), [257](#)
- doLeidenSubCluster, [91](#)
- doLouvainCluster, [44](#), [93](#)
- doLouvainCluster_community, [44](#), [94](#), [94](#), [98](#), [99](#), [257](#)
- doLouvainCluster_multinet, [44](#), [94](#), [95](#), [98](#), [101](#), [257](#)
- doLouvainSubCluster, [96](#)
- doLouvainSubCluster_community, [98](#)
- doLouvainSubCluster_multinet, [100](#)
- doRandomWalkCluster, [44](#), [101](#)
- doSNNCluster, [44](#), [103](#)
- dt_to_matrix, [106](#)
- exportGiottoViewer, [106](#)
- exprOnlyCellCellcommunicationScores, [107](#)
- extended_gini_fun, [108](#)
- extractNearestNetwork, [109](#)
- fDataDT, [109](#)
- filterCombinations, [110](#), [113](#)
- filterCPGscores, [111](#)
- filterDistributions, [112](#)
- filterGiotto, [113](#)
- find_grid_2D, [123](#)
- find_grid_3D, [123](#)
- find_grid_x, [123](#)
- find_grid_y, [124](#)
- find_grid_z, [124](#)
- findGiniMarkers, [114](#), [116](#), [117](#)
- findGiniMarkers_one_vs_all, [115](#), [119](#)
- findMarkers, [116](#), [122](#)
- findMarkers_one_vs_all, [118](#)
- findMastMarkers, [117](#), [119](#), [121](#)
- findMastMarkers_one_vs_all, [119](#), [120](#)
- findScranMarkers, [117](#), [121](#), [123](#)
- findScranMarkers_one_vs_all, [119](#), [122](#)
- fish_function, [124](#)
- fish_function2, [124](#)
- FSV_show, [125](#)
- GenePattern_show, [126](#)
- general_save_function, [16](#), [127](#)
- get10Xmatrix, [128](#)
- get_cell_to_cell_sorted_name_conversion, [133](#)
- get_interaction_gene_enrichment, [134](#)
- get_specific_interaction_gene_enrichment, [134](#)
- getCellProximityGeneScores, [128](#)
- getClusterSimilarity, [130](#)
- getDendrogramSplits, [131](#)
- getDistinctColors, [132](#)
- getGeneToGeneScores, [132](#)
- ggplot_save_function, [135](#)
- giotto (giotto-class), [136](#)
- giotto-class, [136](#)
- glouvain_ml, [96](#)
- hclust, [87](#)
- Heatmap, [138](#)
- heatmSpatialCorGenes, [137](#)
- hyperGeometricEnrich, [53](#), [138](#)
- kmeans, [89](#)
- kmeans_binarize, [139](#)
- kNN, [52](#)
- layout_with_drl, [11](#)
- loadHMRF, [139](#)
- make_simulated_network, [141](#)
- makeSignMatrixPAGE, [140](#), [146](#)
- makeSignMatrixRank, [140](#), [180](#)
- mergeClusters, [141](#)
- mygini_fun, [143](#)
- nnDT_to_kNN, [143](#)
- node_clusters, [143](#)
- normalizeGiotto, [144](#)
- OR_function2, [145](#)
- PAGEEnrich, [53](#), [140](#), [146](#)
- PCA, [184](#)
- pDataDT, [147](#)
- permutationPA, [203](#)
- plot_network_layer_ggplot, [174](#)
- plot_point_layer_ggplot, [175](#)
- plot_spat_point_layer_ggplot, [177](#)
- plotCPGscores, [147](#)
- plotGTGScores, [148](#)
- plotHeatmap, [150](#)
- plotly_axis_scale_2D, [152](#)
- plotly_axis_scale_3D, [152](#)
- plotly_grid, [153](#)
- plotly_network, [154](#)
- plotMetaDataCellsHeatmap, [154](#), [158](#)

- plotMetaDataHeatmap, [156](#), [156](#)
- plotPCA, [158](#)
- plotPCA_2D, [160](#)
- plotPCA_3D, [159](#), [161](#), [162](#)
- plotTSNE, [163](#)
- plotTSNE_2D, [165](#)
- plotTSNE_3D, [165](#), [167](#), [167](#)
- plotUMAP, [169](#)
- plotUMAP_2D, [171](#)
- plotUMAP_3D, [170](#), [172](#), [173](#)
- print.giotto, [179](#)
- rank_binarize, [181](#)
- rankEnrich, [53](#), [141](#), [179](#)
- rankSpatialCorGroups, [180](#)
- readGiottoInstructions, [181](#)
- removeCellAnnotation, [182](#)
- removeGeneAnnotation, [182](#)
- replaceGiottoInstructions, [183](#)
- Rtsne, [185](#)
- runPCA, [183](#)
- runTSNE, [184](#)
- runUMAP, [186](#)
- select_expression_values, [188](#)
- selectPatternGenes, [187](#)
- show,giotto-method, [188](#)
- showClusterDendrogram, [189](#)
- showClusterHeatmap, [190](#)
- showCPGscores, [191](#)
- showGeneExpressionProximityScore, [192](#)
- showGiottoInstructions, [193](#)
- showGTGscores, [193](#)
- showIntExpressionProximityScore, [194](#)
- showPattern, [195](#)
- showPattern2D, [196](#), [196](#)
- showPattern3D, [197](#)
- showPatternGenes, [198](#)
- showProcessingSteps, [199](#)
- showSpatialCorGenes, [63](#), [200](#)
- showTopGeneToGene, [201](#)
- signPCA, [202](#)
- sNN, [52](#)
- sNNclust, [103](#)
- spatCellPlot, [203](#)
- spatCellPlot2D, [206](#)
- spatDimCellPlot, [208](#)
- spatDimCellPlot2D, [212](#)
- spatDimGenePlot, [216](#)
- spatDimGenePlot2D, [219](#)
- spatDimGenePlot3D, [219](#), [221](#), [221](#)
- spatDimPlot, [223](#)
- spatDimPlot2D, [227](#), [227](#)
- spatDimPlot3D, [227](#), [231](#), [231](#)
- spatGenePlot, [235](#)
- spatGenePlot2D, [236](#), [237](#)
- spatGenePlot3D, [236](#), [238](#), [239](#)
- Spatial_AEH, [240](#)
- Spatial_DE, [241](#)
- spatPlot, [242](#)
- spatPlot2D, [245](#), [260](#)
- spatPlot2D_single, [248](#)
- spatPlot3D, [245](#), [248](#), [251](#), [251](#), [261](#)
- specificCellCellcommunicationScores, [253](#)
- split_dendrogram_in_two, [254](#)
- stitchFieldCoordinates, [49](#), [255](#)
- subClusterCells, [256](#)
- subsetGiotto, [258](#)
- subsetGiottoLocs, [258](#)
- umap, [187](#)
- viewHMRResults, [259](#)
- viewHMRResults2D, [260](#)
- viewHMRResults3D, [261](#)
- violinPlot, [262](#)
- visDimGenePlot, [263](#)
- visDimGenePlot_2D_ggplot, [265](#)
- visDimGenePlot_3D_plotly, [266](#)
- visDimPlot, [268](#)
- visDimPlot_2D_ggplot, [270](#)
- visDimPlot_2D_plotly, [272](#)
- visDimPlot_3D_plotly, [274](#)
- visForceLayoutPlot, [275](#)
- visGenePlot, [277](#)
- visGenePlot_2D_ggplot, [279](#)
- visGenePlot_3D_plotly, [280](#)
- visPlot, [260](#), [282](#)
- visPlot_2D_ggplot, [284](#)
- visPlot_2D_plotly, [287](#)
- visPlot_3D_plotly, [288](#)
- visSpatDimGenePlot, [290](#)
- visSpatDimGenePlot_2D, [293](#)
- visSpatDimGenePlot_3D, [295](#)
- visSpatDimPlot, [297](#)
- visSpatDimPlot_2D, [299](#)
- visSpatDimPlot_3D, [302](#)
- write_giotto_viewer_annotation, [304](#)
- write_giotto_viewer_dim_reduction, [305](#)
- write_giotto_viewer_numeric_annotation, [306](#)
- writeHMRResults, [304](#)
- zlm, [120](#)