# **Lab: Strings and Text Processing**

You can check your solutions here: <a href="https://judge.softuni.bg/Contests/3178/Additional-Exercises">https://judge.softuni.bg/Contests/3178/Additional-Exercises</a>.

# 1. Reverse Strings

You will be given series of strings until you receive an "end" command. Write a program that reverses strings and prints each pair on separate line in format "{word} = {reversed word}".

### **Examples**

Input	Output
helLo Softuni bottle end	helLo = oLleh Softuni = inutfoS bottle = elttob
Dog caT chAir end	Dog = goD caT = Tac chAir = riAhc

#### **Solution**

Use while loop and read strings until you receive "end".

```
string line = Console.ReadLine();
while (line != "end")
    line = Console.ReadLine();
```

Reverse the string with for loop. Start from the last index and append each symbol to the new string.

```
string reversed = "";
for (int i = line.Length - 1; i >= 0; i--)
{
    reversed += line[i];
```

Print the reversed string in the specified format.

```
Console.WriteLine($"{line} = {reversed}");
```

## 2. Repeat Strings

Write a Program That Reads an Array of Strings. Each String is Repeated N Times, Where N is the Length of the String. Print the Concatenated String.

### **Examples**















hi abc add	hihiabcabcabcaddaddadd
work	workworkwork
ball	ballballball

#### Solution

• Read a string array.

```
string[] words = Console.ReadLine().Split();
```

Initialize StringBuilder.

```
StringBuilder resutl = new StringBuilder();
```

Iterate through elements in the array.

```
foreach (string word in words)
{
}
```

Find the length of the current word and append it.

```
int count = word.Length;
for (int i = 0; i < count; i++)</pre>
{
    result.Append(word);
```

Print the StringBuilder.

## 3. Substring

On the first line you will receive a string. On the second line you will receive a second string. Write a program that removes all of the occurrences of the first string in the second until there is no match. At the end print the remaining string.

## **Examples**

Input	Output	Comment
Ice	kgb	We remove ice once and we get "kgiciceeb"
kicegiciceeb		We match "ice" one more time and we get "kgiceb"
		There is one more match. The finam result is "kgb"

#### Hints

- Read the input.
- Find the first index where the key appears.
  - Use the built-in method IndexOf()
- Remove the match.
  - Use the built-in method Remove(index, length)
- Repeat it until the text doesn't contain the key anymore.

















#### 4. Text Filter

Write a program that takes a text and a string of banned words. All words included in the ban list should be replaced with asterisks "\*", equal to the word's length. The entries in the ban list will be separated by a comma and space ", ".

The ban list should be entered on the first input line and the text on the second input line.

### **Examples**

Input	Output
Linux, Windows It is not Linux, it is GNU/Linux. Linux is merely the kernel, while GNU adds the functionality. Therefore we owe it to them by calling the OS GNU/Linux! Sincerely, a Windows client	

#### Hints

- Read the input.
- Replace all ban words in the text with asterisk (\*).
  - Use the built-in method **Replace**(banWord, replacement).
  - Use **new string**(char ch, int repeatCount) to create the replacement

# 5. Digits, Letters and Other

Write a program that receives a single string and on the first line prints all the digits, on the second – all the letters, and on the third - all the other characters. There will always be at least one digit, one letter and one other characters.

### **Examples**

Input	Output
Agd#53Dfg^&4F53	53453
	AgdDfgF
	#^&

#### Hints

- Read the input.
- Use loop to iterate through all characters in the text. If the char is digit print it, otherwise ignore it.
  - Use char.IsDigit(char symbol)
- Do the same for the letters and other chars
  - Find something like IsDigit method for the letters.















