


Methods

Defining and Using Methods, Overloads



SoftUni Team
Technical Trainers



SoftUni


Software University

<https://softuni.bg>

Table of Contents

1. What Is a Method?
2. Declaring and Invoking Methods
3. Methods with Parameters
4. Value vs Reference Types
5. Returning values from Methods
6. Overloading Methods
7. Program Execution Flow
8. Naming and Best Practices





Void Method

Simple Methods

- **Named block of code**, that can be invoked later

- Sample method **definition**:


```
static void PrintHelloWorld()  
{  
    Console.WriteLine("Hello World");  
}
```

Method named
PrintHelloWorld

Method **body**
is always
surrounded
by **{ }**

- **Invoking** (calling) the method several times:

```
PrintHelloWorld();  
PrintHelloWorld();
```



Why Use Methods?

- Methods make code **maintainable**
 - Splits large problems into small pieces
 - Better organization of the program
 - Improves code **readability**
 - Improves code **understandability**
- Avoiding **repeating code**
 - Improves code maintainability
- Code **reusability**
 - Using existing methods several times



Void Type Method

- Executes the code between the brackets
- Does not return result

```
static void PrintHello()  
{  
    Console.WriteLine("Hello");  
}
```

Prints "Hello"
on the console

```
static void Main()  
{  
    PrintHello();  
}
```

Main() is also
a method



Declaring and Invoking Methods

Declaring Methods

Return type

Method name

Parameters

```
static void PrintText(string text)
{
    Console.WriteLine(text);
}
```

Method
body

- 
- Methods are declared **inside a class**
 - Variables inside a method are **local**

Invoking a Method (1)

- Methods are first **declared**, then **invoked** (many times)

```
static void PrintHeader()  
{  
    Console.WriteLine("-----");  
}
```

Method
declaration

- Methods** can be **invoked** (called) by their **name + ()**:

```
static void Main()  
{  
    PrintHeader();  
}
```

Method
invocation

Invoking a Method (2)

- A method can be invoked:

- From the **main method**


```
static void Main()  
{  
    PrintHeader();  
}
```

- From **its own body** – recursion

```
static void Crash()  
{ Crash(); }
```

- From some **other method**

```
static void PrintHeader()  
{  
    PrintHeaderTop();  
    PrintHeaderBottom();  
}
```



Methods with Parameters

- Method **parameters** can be of **any data type**

```
static void PrintNumbers(int start, int end)  
{  
    for (int i = start; i <= end; i++)  
        Console.Write("{0} ", i);  
}
```

Multiple parameters
separated by comma

- Call the method with certain values (**arguments**)

```
static void Main()  
{  
    PrintNumbers(5, 10);  
}
```

Passing arguments
at invocation

Method Parameters (2)

- You can pass **zero** or **several** parameters
- You can pass parameters of **different types**
- Each parameter has **name** and **type**

Multiple parameters
of different types

Parameter
type

Parameter
name

```
static void PrintStudent(string name, int age, double grade)  
{  
    Console.WriteLine("Student: {0}; Age: {1}, Grade: {2}",  
        name, age, grade);  
}
```

Short Syntax for Defining Methods

- Methods with short body can be defined using the `=>` operator:

```
static int Sum(int a, int b) => a + b;
```

- This is the same as:


```
static int Sum(int a, int b)
{
    return a + b;
}
```

- Another example:

```
static void Print(int x) => Console.WriteLine(x);
```

Problem: Grades

- Write a method that receives a **grade** between 2.00 and 6.00 and prints the corresponding **grade in words**
 - 2.00 - 2.99 - "Fail"
 - 3.00 - 3.49 - "Poor"
 - 3.50 - 4.49 - "Good"
 - 4.50 - 5.49 - "Very good"
 - 5.50 - 6.00 - "Excellent"




```
static void Main() =>
    PrintInWords(double.Parse(Console.ReadLine()));

private static void PrintInWords(double grade)
{
    string gradeInWords = string.Empty;
    if (grade >= 2 && grade <= 2.99)
        gradeInWords = "Fail";
    // TODO: continue with the rest
    Console.WriteLine(gradeInWords);
}
```


Problem: Sign of Integer Number

- Create a method that prints the **sign** of an integer number **n**:



Solution: Sign of Integer Number

```
static void Main() =>
    PrintSign(int.Parse(Console.ReadLine()));

static void PrintSign(int number)
{
    if (number > 0)
        Console.WriteLine("The number {0} is positive", number);
    else if (number < 0)
        Console.WriteLine("The number {0} is negative.", number);
    else
        Console.WriteLine("The number {0} is zero.", number);
}
```

Check your solution here: <https://judge.softuni.bg/Contests/Practice/Index/3160#1>

- Parameters can accept **default values**:

```
static void PrintNumbers(int start = 0, int end = 100)
{
    for (int i = start; i <= end; i++)
    {
        Console.Write("{0} ", i);
    }
}
```

Default values

- The above method can be called in several ways:

```
PrintNumbers(5, 10);
```

```
PrintNumbers(end: 40, start: 35);
```

```
PrintNumbers(15);
```

```
PrintNumbers();
```

Can be **skipped** at method invocation

Problem: Printing Triangle

- Create a method for printing triangles as shown below:

3



```
1
1 2
1 2 3
1 2
1
```

4



```
1
1 2
1 2 3
1 2 3 4
1 2 3
1 2
1
```

Solution: Printing Triangle (1)

- Create a method that **prints a single line**, consisting of numbers from a **given start** to a **given end**:

```
static void PrintLine(int start, int end)
{
    for (int i = start; i <= end; i++)
    {
        Console.Write(i + " ");
    }
    Console.WriteLine();
}
```

**Solution continues
on next slide**

Solution: Printing Triangle (2)

- Create a method that prints the **first half (1..n)** and then the **second half (n-1...1)** of the triangle:

```
static void PrintTriangle(int n)
{
    for (int line = 1; line <= n; line++)
        PrintLine(1, line);


    for (int line = n - 1; line >= 1; line--)
        PrintLine(1, line);
}
```

Method with
parameter **n**

Lines 1...n

Lines n-1...1

Check your solution here: <https://judge.softuni.bg/Contests/Practice/Index/3160#3>




Memory Stack and Heap

Value Types

- **Value type** variables hold directly their value
 - `int`, `float`, `double`, `bool`, `char`, `BigInteger`, ...
- Each variable has its own **copy** of the **value**

```
int i = 42;  
char ch = 'A';  
bool result = true;
```




Reference Types

- **Reference type** variables hold a reference (pointer / memory address) of the value itself
 - **string, int[], char[], string[], Random**
- Two reference type variables can **reference** the **same object**
 - Operations on both variables access/modify **the same data**



Value Types vs. Reference Types

```
int i = 42;  
char ch = 'A';  
bool result = true;  
object obj = 42;  
string str = "Hello";  
byte[] bytes = { 1, 2, 3 };
```



Example: Value Types

```
public static void Main() {  
    int number = 5;  
    Increment(number, 15);  
    Console.WriteLine(number);  
}
```

number == 5

```
public static void Increment(int num, int value)  
{  
    num += value;  
}
```

num == 20

Example: Reference Types

```
public static void Main() {  
    int[] nums = { 5 };  
    Increment(nums, 15);  
    Console.WriteLine(nums[0]);  
}
```


nums[0] == 20

```
public static void Increment(int[] nums, int value)  
{  
    nums[0] += value;  
}
```

nums[0] == 20


Value vs. Reference Types

pass by reference

cup = 

fillCup()

pass by value

cup = 


fillCup()



Returning Values from Methods

The Return Statement

- The **return** keyword immediately stops the method's execution
- Returns the specified value



```
static string ReadFullName()  
{  
    string firstName = Console.ReadLine();  
    string lastName = Console.ReadLine();  
    return firstName + " " + lastName;  
}
```

Returns a
string

- Void methods can be **terminated** by just using **return**

Using the Return Values

- Return value can be:
 - Assigned** to a variable:


```
int max = GetMax(5, 10);
```

- Used** in expression:

```
decimal total = GetPrice() * quantity * 1.20m;
```

- Passed** to another method:


```
int age = int.Parse(Console.ReadLine());
```



Problem: Calculate Rectangle Area

- Create a method which returns **rectangle area** by given **width** and **height**

3
4




12

6
8



48

5
10



50

7
8



56

Solution: Calculate Rectangle Area

```
static void Main()
{
    double width = double.Parse(Console.ReadLine());
    double height = double.Parse(Console.ReadLine());
    double area = CalcRectangleArea(width, height);
    Console.WriteLine(area);
}
```

```
static double CalcRectangleArea(double width, double height)
{
    return width * height;
}
```

Check your solution here: <https://judge.softuni.bg/Contests/Practice/Index/3160#4>

Problem: Repeat String

- Write a method that receives a **string** and a repeat count **n**
 - The method should return a **new string**, holding the **input string**, repeated **n times**

abc
3



abcabcabc

String
2



StringString

Solution: Repeat String (1)

```
static void Main()
{
    string inputStr = Console.ReadLine();
    int count = int.Parse(Console.ReadLine());

    string result = RepeatString(inputStr, count);
    Console.WriteLine(result);
}
```

Check your solution here: <https://judge.softuni.bg/Contests/Practice/Index/3160#5>


Solution: Repeat String (2)

```
private static string RepeatString(string str, int count)
{
    StringBuilder result = new StringBuilder();
    for (int i = 0; i < count; i++)
    {
        result.Append(str);
    }
    return result.ToString();
}
```

Check your solution here: <https://judge.softuni.bg/Contests/Practice/Index/3160#5>

Problem: Math Power

- Create a method that calculates and returns the value of a **number raised to a given power**



A diagram showing a box containing 2^8 followed by a right-pointing arrow and another box containing 256.



A diagram showing a box containing 3^4 followed by a right-pointing arrow and another box containing 81.

```
static double MathPower(double number, int power)
{
    double result = 1;
    for (int i = 0; i < power; i++)
        result *= number;
    return result;
}
```

Check your solution here: <https://judge.softuni.bg/Contests/Practice/Index/3160#6>



Overloading Methods

- The combination of method's **name** and **parameters** is called **signature**

```
static void Print(string text)
{
    Console.WriteLine(text);
}
```

Method's
signature

- Signature **differentiates** between methods with same names
- When methods with the **same name** have **different signature**, this is called method "**overloading**"

- Using same name for multiple methods with different **signatures** (method **name** and **parameters**)

```
static void Print(string text)
{
    Console.WriteLine(text);
}
```

```
static void Print(int number)
{
    Console.WriteLine(number);
}
```

```
static void Print(string text, int number)
{
    Console.WriteLine(text + ' ' + number);
}
```

Different
method
signatures


- Method's return type **is not part** of its signature

```
static void Print(string text)
{
    Console.WriteLine(text);
}

static string Print(string text)
{
    return text;
}
```

Compile-time
error!

- How would the compiler know **which method to call?**




Program Execution Flow

- The program **continues**, after a method **execution completes**:

```
static void Main()  
{  
    Console.WriteLine("before method executes");  
    PrintLogo();  
    Console.WriteLine("after method executes");  
}
```

```
static void PrintLogo()  
{  
    Console.WriteLine("Company Logo");  
    Console.WriteLine("http://www.companywebsite.com");  
}
```

- "The stack" **stores information** about the **active subroutines** (methods) of a computer program
- Keeps track of **the point** to which each active subroutine should **return control** when it **finishes executing**



Problem: Multiply Evens by Odds

- Create a program that **multiplies the sum of all even digits** of a number **by the sum of all odd digits** of the same number:



- Create a method **GetSumOfEvenDigits()**
- Create a method **GetSumOfOddDigits()**
- Create a method called **GetMultipleOfEvensAndOdds()**
- You may need to use **Math.Abs()** for negative numbers

Solution: Multiply Evens by Odds (1)

```
static int GetSumOfEvenDigits(int number)
{
    int evenSum = 0;
    while (number >= 1)
    {
        int digit = number % 10;
        if (digit % 2 == 0)
            evenSum += digit;
        number /= 10;
    }
    return evenSum;
}
```

```
static int GetSumOfOddDigits(int number)
{
    // Use the same logic ...
}
```

Check your solution here: <https://judge.softuni.bg/Contests/Practice/Index/3160#8>

Solution: Multiply Evens by Odds (2)

```
static int GetMultipliedEvensAndOdds(int number)
{
    int evenSum = GetSumOfEvenDigits(number);
    int oddSum = GetSumOfOddDigits(number);
    int result = evenSum * oddSum;
    return result;
}
```

```
static void Main(string[] args)
{
    int num = int.Parse(Console.ReadLine());
    int number = Math.Abs(num);
    int result = GetMultipliedEvensAndOdds(number);
    Console.WriteLine(result);
}
```

Check your solution here: <https://judge.softuni.bg/Contests/Practice/Index/3160#8>



Naming and Best Practices

Naming Methods

- Methods naming guidelines
 - Use **meaningful** method names, use [**Verb**]
 - Method names should answer the question:
 - **What does this method do?**



FindStudent, LoadReport, Sine

- If you cannot find a good name for a method, think about whether it has a **clear intent**




Method1, DoSomething, HandleStuff, SampleMethod, DirtyHack



Naming Method Parameters

- Method parameters names
 - Preferred form: [**Noun**] or [**Adjective**] + [**Noun**]
 - Should be in **camelCase**
 - Should be **meaningful**



```
firstName, report, speedKmH,  
usersList, fontSizeInPixels, font
```

- Unit of measure should be obvious

```
p, p1, p2, populate, LastName, last_name, convertImage
```


- Each method should perform a **single**, well-defined task
 - A Method's name should **describe that task** in a clear and non-ambiguous way
- **Avoid** methods **longer than one screen**
 - **Split them** to several shorter methods

```
private static void PrintReceipt()  
{  
    PrintHeader();  
    PrintBody();  
    PrintFooter();  
}
```


**Self documenting
and easy to test**

- Make sure to use correct **indentation**

```
static void Main()  
{  
    ➡ // some code...  
    ➡ // some more code...  
}
```




```
static void Main()  
    ➡ {  
        ➡ // some code...  
➡ // some more code...  
}
```



- Leave a **blank line** between **methods**, after **loops** and after **if** statements
- Always use **curly brackets** for loops and if statements bodies
- Avoid long lines** and **complex expressions**

- Break large programs into simple **methods** that solve small sub-problems
- Methods consist of **declaration** and **body**
- Methods are invoked by their **name** + **()**
- Methods can accept **parameters**
- Methods can **return** a value or nothing (**void**)

Questions?



- This course (slides, examples, demos, exercises, homework, documents, videos and other assets) is **copyrighted content**
- Unauthorized copy, reproduction or use is illegal
- © SoftUni – <https://softuni.org>
- © Software University – <https://softuni.bg>

