

# Zabbix 7 Monitoring

---

**Enterprise Monitoring With Zabbix**

*Patrik Uytterhoeven*

*Creative Commons Attribution-NonCommercial-ShareAlike 4.0 International License*

# Table of contents

---


|  |    |
|--|----|
| 1. What is this book about ?                     | 4  |
| 2. Who am I ?                                    | 4  |
| 3. What OS do I need ?                           | 4  |
| 4. What version of Zabbix is used in this book ? | 5  |
| 5. How to use this book ?                        | 5  |
| 6. Getting started                               | 7  |
| 6.1 Requirements                                 | 7  |
| 6.2 Installing Zabbix DB Server                  | 10 |
| 6.3 Installing Zabbix                            | 21 |
| 7. The basics                                    | 35 |
| 7.1 Zabbix Interface                             | 35 |
| 7.2 Zabbix Users                                 | 42 |
| 7.3 Zabbix hosts                                 | 50 |
| 7.4 Interfaces                                   | 53 |
| 7.5 Host groups                                  | 54 |
| 7.6 templates                                    | 55 |
| 7.7 Items  | 56 |
| 7.8 Zabbix triggers                              | 57 |
| 7.9 Macros                                       | 58 |
| 7.10 Data Flow                                   | 59 |
| 7.11 Zabbix Agent                                | 60 |
| 8. Problem detection                             | 61 |
| 8.1 Triggers                                     | 61 |
| 9. Taking action when problems come              | 62 |
| 9.1 Event based Actions                          | 62 |
| 10. Managing permissions                         | 63 |
| 10.1 Managing Permissions                        | 63 |
| 11. Visualising Problems                         | 64 |
| 11.1 Visualising our problems                    | 64 |
| 12. Automating configuration                     | 65 |
| 12.1 Automating configuration                    | 65 |
| 13. VMWare monitoring                            | 66 |
| 13.1 VMWare monitoring                           | 66 |
| 14. Monitoring websites                          | 67 |
| 14.1 Monitoring websites                         | 67 |

|                                    |    |
|------------------------------------|----|
| 15. Monitoring SNMP, IPMI and JAVA | 68 |
| 15.1 Monitoring SNMP,IPMI and JAVA | 68 |
| 15.2 JAVA monitoring               | 69 |
| 15.3 IPMI monitoring               | 70 |
| 16. Monitoring with Proxies        | 71 |
| 16.1 Monitoring with Proxies       | 71 |
| 17. Securing Zabbix                | 72 |
| 17.1 Securing Zabbix               | 72 |
| 18. Maintaining Zabbix             | 73 |
| 18.1 Maintaining Zabbix            | 73 |
| 19. Monitoring Windows             | 74 |
| 19.1 Monitoring Windows            | 74 |
| 20. Zabbix API                     | 75 |
| 20.1 Zabbix API                    | 75 |

## 1. What is this book about ?

---

Hi, welcome and thank you for your interest in my Zabbix book. I wrote the [Zabbix cookbook](#) and co wrote with Richards [Zabbix 4 Network Monitoring](#) a few years ago for PackPub.



The cookbook the first of it's kind probably outdated and will be replaced by the [Zabbix 7 IT Infrastructure Monitoring Cookbook](#), written by Brian and Nathan, 2 people I like a lot to work with and can highly recommend. There are many more books available from Packt about Zabbix a complete overview can be found here [Zabbix books at packt](#). Or if you like to find some non English books Amazon has some books from Packt and other Publishers in Chinese, Spanish and maybe some other languages as well. [Other books](#)

As Zabbix is an opensource product and making money out of the books was never my intention, it got me thinking how to do things different. How to make a new book without using a publisher like I had done before. After a while, I came up with the idea to make a book that would be free and that would be updated when new versions came out. Since I am a huge fan of documentation in markdown or asciidoc I came up with the idea to share the book in git and use markdown. The only problem left was how to make those markdown files readable in an easy way like a book ? After some searching trying to look for a good solution I found [MkDocs](#). MkDocs is a Python-Markdown library that can convert everything to HTML and can be templated. So the problem was solved and a new book was born.

## 2. Who am I ?

---

My name is Patrik Uytterhoeven and I work for a Belgium company named Open-Future. I started at this company at Januari 2013 and that's when my journey started with Zabbix as well. They gave me the opportunity to build my experience and to get certified as Zabbix trainer. Since this year I am officially 10y Zabbix trainer. If you would like to follow one of my trainings feel free to register for a training at our website [www.open-future.be](http://www.open-future.be). Why would you follow a training if you can read this book for free are you now thinking? Because trainings just like the book explain you all the details on how to set up and do things but also give you valueable tips and feedback that you never get from a book. Books just can't cover everything.

## 3. What OS do I need ?

---

Since I work mostly with RHEL based systems and since I am convinced that RHEL is the better choice in Production environments I have chosen to focus on using one of the forks that is available for free. Zabbix is supported on Ubuntu, Debian, Suse, Raspberry .... and it can be compiled on any OS that is Unix based so it's almost impossible to cover them all. However the book is Opensource and in GIT so feel free to contribute the code for your favorite flavour :). I will use [Rocky Linux 9](#) in this book, but it should work for most of the other installations as well.

## 4. What version of Zabbix is used in this book ?

---

Since we are almost at the release of Zabbix 7, I will focus on version 7 since it will be the new LTS. It should also apply to most other versions but of course there will be minor changes. In the future, if there is enough support from the community to update this book together, it would be great if we could build a book for every LTS version available.

## 5. How to use this book ?

---

The book will try to cover all the topics, feel free to let me know if something is missing or feel free to make a pull request. There is no need to start from page 1 and read the book till the end. Some people will be looking for basic knowledge others might want to skip to the fun part, so I want the book to be useful for everyone. Therefor I will try to explain as best as possible in every topic the exact steps needed to reproduce.

There will be moments in the book where you need to type some code, I will show the commands you need to type in a box just like here.

```
# some command
```

Notes to some useful documentation will be added at the bottom of the page.

Here is a simple footnote<sup>1</sup>. With some additional text after it.

In case there is some important information to share I will add notes in the documentation like can be seen here :



### Note

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Nulla et euismod nulla. Curabitur feugiat, tortor non consequat finibus, justo purus auctor massa, nec semper lorem quam in massa.



### Info

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Nulla et euismod nulla. Curabitur feugiat, tortor non consequat finibus, justo purus auctor massa, nec semper lorem quam in massa.



### Tip

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Nulla et euismod nulla. Curabitur feugiat, tortor non consequat finibus, justo purus auctor massa, nec semper lorem quam in massa.



### Question

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Nulla et euismod nulla. Curabitur feugiat, tortor non consequat finibus, justo purus auctor massa, nec semper lorem quam in massa.



### Warning

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Nulla et euismod nulla. Curabitur feugiat, tortor non consequat finibus, justo purus auctor massa, nec semper lorem quam in massa.



Lorem ipsum dolor sit amet, consectetur adipiscing elit. Nulla et euismod nulla. Curabitur feugiat, tortor non consequat finibus, justo purus auctor massa, nec semper lorem quam in massa.



#### Example

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Nulla et euismod nulla. Curabitur feugiat, tortor non consequat finibus, justo purus auctor massa, nec semper lorem quam in massa.

---

<sup>1</sup>. My reference. ←

## 6. Getting started

### 6.1 Requirements

Zabbix has a set of requirements that need to be met on the hardware level and software level. These requirements can change over time and also depends on the size of your setup and the software you choose. So before you start buying metal or installing a random database version have a look at the Zabbix documentation and check the latest requirements for the version you want to install. The latest requirements can be found [here](#). Don't forget to select your correct *Zabbix* version from the list.

#### 6.1.1 Basic OS configuration

##### firewall

It's important for our Zabbix server to have an OS that is well prepared before we start to install our monitoring tool. First we need to make sure our firewall is installed.

```
# dnf install firewalld --now
```

Our firewall is installed now, and we are ready to configure the needed ports. For our Zabbix server, we need to allow access to port 10051/tcp this is the port where our Zabbix trapper listens on for incoming data. So we need to open this port in our firewall to allow access to our Zabbix trapper.

```
# firewall-cmd --add-service=Zabbix-server --permanent
```

or if the service is not known

```
# firewall-cmd --add-port=10051/tcp --permanent
```



##### firewalld

"Firewalld is the replacement of iptables in Redhat and allows us to make changes available immediately without the need to restart a service. It's possible that your distribution is not using [Firewalld](#) in this case you have to look to the documentation of your OS."

##### timeserver

Another thing we need to configure is the setup of timeserver and sync our Zabbix server to the timeserver by making use of an ntp client. This needs to be done for the Zabbix server but also for the devices we will monitor as time is very important for Zabbix. Imagine one of our hosts having a time zone that is wrong we could end up looking for a problem in Zabbix that happened 6h ago while it had happened maybe only 2h ago.

```
# dnf install chronyd --now
```

Chrony should be installed now and enabled and running. This can be verified with the command:

```
# systemctl status chronyd
```



##### dnf

"dnf is a packagemanager from RedHat you need to replace dnf with your correct packagemanager like zypper, apt, yum, ... chrony is a replacement for ntpd and does a better job being faster and more accurate. If your OS does not support [chrony](#) then maybe ntpd is still available."

Once Chrony is installed we also need to setup our correct time zone. We can have a look first with 'timedatectl' to see how our time is configured

```
# timedatectl
Local time: Thu 2023-11-16 15:09:14 UTC
Universal time: Thu 2023-11-16 15:09:14 UTC
RTC time: Thu 2023-11-16 15:09:15
Time zone: UTC (UTC, +0000)
System clock synchronized: yes
```

```
NTP service: active
RTC in local TZ: no
```

Make sure that the service `crond` is active, see above on how to do if you missed it. We can choose the correct time zone from a list that we can lookup with the following command:

```
# timedatectl list-time zones
```

This will give us a list with all available time zones. Choose the one closest to you.

```
Africa/Abidjan
Africa/Accra
...
Pacific/Tongatapu
Pacific/Wake
Pacific/Wallis
UTC
```

We can now configure our correct time zone with the following command:

```
timedatectl set-time zone Europe/Brussels
```

When we look again we should see our time zone properly configured.

```
# timedatectl
          Local time: Thu 2023-11-16 16:13:35 CET
          Universal time: Thu 2023-11-16 15:13:35 UTC
            RTC time: Thu 2023-11-16 15:13:36
          Time zone: Europe/Brussels (CET, +0100)
System clock synchronized: yes
              NTP service: active
          RTC in local TZ: no
```



#### Note

"Some people like to install all servers in the UTC time zone so that all server logs are in the same time zone when having servers all over the world. Zabbix supports user based time zone settings so it's possible to keep the time zone in UTC on the server and then add the correct time zone in the user interface if you like."

We can test if Chrony is synchronizing with the correct timeservers as well by running the command `chronyc`

```
# chronyc
chrony version 4.2
Copyright (C) 1997-2003, 2007, 2009-2021 Richard P. Curnow and others
chrony comes with ABSOLUTELY NO WARRANTY. This is free software, and
you are welcome to redistribute it under certain conditions. See the
GNU General Public License version 2 for details.

chronyc>
```

Then we type `sources`

```
chronyc> sources
MS Name/IP address         Stratum Poll Reach LastRx Last sample
=====
^~ 51-15-20-83.rev.poneytel> 2  9  377  354  +429us[ +429us] +/-  342ms
^~ 5.255.99.180             2 10  377  620  +7424us[+7424us] +/-   37ms
^~ hachi.paina.net          2 10  377  412  +445us[ +445us] +/-   39ms
^* leontpl.office.panq.nl   1 10  377  904  +6806ns[ +171us] +/- 2336us
```

Here we can see that we are using a bunch of ntp servers that are not in our own country so we better switch to some timeservers in our local country or if we have a timeserver in our company we could use this one. We can find some local timeservers here : <https://www.ntppool.org/>

To change this we have to edit our config file `"/etc/chrony.conf"` and replace the existing ntp server with our local one

```
# Use public servers from the pool.ntp.org project.
# Please consider joining the pool (http://www.pool.ntp.org/join.html).
pool 2.centos.pool.ntp.org iburst
```



And change it to a local server:

```
# Use public servers from the pool.ntp.org project.
# Please consider joining the pool (http://www.pool.ntp.org/join.html).
pool be.pool.ntp.org iburst
```

Don't forget to restart the ntpd client of course.

```
# systemctl restart chronyd
```

When we look again we will see that we are now using our local timeservers.

```
chronyc> sources

MS Name/IP address         Stratum Poll Reach LastRx Last sample
=====
^- ntp1.unix-solutions.be   2      6    17    43   -375us[ -676us] +/-  28ms
^* ntp.devrandom.be        2      6    17    43   -579us[ -880us] +/- 2877us
^+ time.cloudflare.com     3      6    17    43   +328us[ +27us]  +/- 2620us
^+ time.cloudflare.com     3      6    17    43   +218us[ -83us]  +/- 2815us
```

## 6.2 Installing Zabbix DB Server

### 6.2.1 Installing Zabbix with MariaDB

Let us start with the installation of the MariaDB server, you need to create a MariaDB repository configuration file `mariadb.repo` manually in the following path `/etc/yum.repos.d/`. To create a MariaDB repository file, you can use the following command.

#### Add the MariaDB repo

```
# vi /etc/yum.repos.d/mariadb.repo
```

The above command will create a new repository file, Once it is created, you need to add the following configuration into the file. Make sure your version, in this case 10.11, is supported by Zabbix by looking at the latest [requirements](#) for your version.

```
# MariaDB 10.11 RedHatEnterpriseLinux repository list - created 2023-11-01 14:20 UTC
# https://mariadb.org/download/
[mariadb]
name = MariaDB
# rpm.mariadb.org is a dynamic mirror if your preferred mirror goes offline. See https://mariadb.org/mirrorbits/ for details.
# baseurl = https://rpm.mariadb.org/10.11/rhel/$releasever/$basearch
baseurl = https://mirror.23m.com/mariadb/yum/10.11/rhel/$releasever/$basearch
# gpgkey = https://rpm.mariadb.org/RPM-GPG-KEY-MariaDB
gpgkey = https://mirror.23m.com/mariadb/yum/RPM-GPG-KEY-MariaDB
gpgcheck = 1
```

Lets update our OS first with the latest patches

```
# dnf update -y
```

#### Install the MariaDB database

Now we are ready to install our MariaDB database.

```
# dnf install MariaDB-server MariaDB-client
```

We are now ready to enable and start or MariaDB database.

```
# systemctl enable mariadb --now
```

Once the installation is complete, you can verify the version of the MariaDB server by using the following command:

```
# mysql -V
```

The output should look like this:

```
mysql Ver 15.1 Distrib 10.11.6-MariaDB, for Linux (x86_64) using EditLine wrapper
```

And when we ask the status of our MariaDB server we should get an output like this:

```
# systemctl status mariadb

● mariadb.service - MariaDB 10.11.6 database server
   Loaded: loaded (/usr/lib/systemd/system/mariadb.service; enabled; preset: disabled)
   Drop-In: /etc/systemd/system/mariadb.service.d
            └─migrated-from-my.cnf-settings.conf
   Active: active (running) since Sat 2023-11-18 19:19:36 CET; 2min 13s ago
     Docs: man:mariadb(8)
           https://mariadb.com/kb/en/library/systemd/
   Process: 41986 ExecStartPre=/bin/sh -c systemctl unset-environment _WSREP_START_POSITION (code=exited, status=0/SUCCESS)
   Process: 41987 ExecStartPre=/bin/sh -c [ ! -e /usr/bin/galera_recovery ] && VAR= || VAR=`cd /usr/bin/..; /usr/bin/galera_recovery`; [ $? -eq 0 ] &&
   Process: 42006 ExecStartPost=/bin/sh -c systemctl unset-environment _WSREP_START_POSITION (code=exited, status=0/SUCCESS)
   Main PID: 41995 (mariabdb)
   Status: "Taking your SQL requests now..."
   Tasks: 9 (limit: 12344)
   Memory: 206.8M
   CPU: 187ms
```

## Securing the MariaDB database

It's time to secure our database by removing the test database and user and set our own root password. Run the command `mariadb-secure-installation`, you should get the following output.

```
# mariadb-secure-installation

NOTE: RUNNING ALL PARTS OF THIS SCRIPT IS RECOMMENDED FOR ALL MariaDB
      SERVERS IN PRODUCTION USE!  PLEASE READ EACH STEP CAREFULLY!

In order to log into MariaDB to secure it, we'll need the current
password for the root user. If you've just installed MariaDB, and
haven't set the root password yet, you should just press enter here.

Enter current password for root (enter for none):
OK, successfully used password, moving on...

Setting the root password or using the unix_socket ensures that nobody
can log into the MariaDB root user without the proper authorisation.

You already have your root account protected, so you can safely answer 'n'.

Switch to unix_socket authentication [Y/n] n
... skipping.

You already have your root account protected, so you can safely answer 'n'.

Change the root password? [Y/n] y
New password:
Re-enter new password:
Password updated successfully!
Reloading privilege tables..
... Success!

By default, a MariaDB installation has an anonymous user, allowing anyone
to log into MariaDB without having to have a user account created for
them. This is intended only for testing, and to make the installation
go a bit smoother. You should remove them before moving into a
production environment.

Remove anonymous users? [Y/n] y
... Success!

Normally, root should only be allowed to connect from 'localhost'. This
ensures that someone cannot guess at the root password from the network.

Disallow root login remotely? [Y/n] y
... Success!

By default, MariaDB comes with a database named 'test' that anyone can
access. This is also intended only for testing, and should be removed
before moving into a production environment.

Remove test database and access to it? [Y/n] y
- Dropping test database...
... Success!
- Removing privileges on test database...
... Success!

Reloading the privilege tables will ensure that all changes made so far
will take effect immediately.

Reload privilege tables now? [Y/n] y
... Success!

Cleaning up...

All done! If you've completed all of the above steps, your MariaDB
installation should now be secure.

Thanks for using MariaDB!
```

## Create the Zabbix database

```
# mysql -uroot -p
password

MariaDB [(none)]> CREATE DATABASE zabbix CHARACTER SET utf8mb4 COLLATE utf8mb4_bin;
MariaDB [(none)]> CREATE USER 'zabbix-web'@'<zabbix server ip>' IDENTIFIED BY '<password>';
MariaDB [(none)]> CREATE USER 'zabbix-srv'@'<zabbix server ip>' IDENTIFIED BY '<password>';
MariaDB [(none)]> GRANT ALL PRIVILEGES ON zabbix.* TO 'zabbix-srv'@'<zabbix server ip>';
```

```
MariaDB [(none)]> GRANT SELECT, UPDATE, DELETE, INSERT ON zabbix.* TO 'zabbix-web'@'<zabbix server ip>';
MariaDB [(none)]> SET GLOBAL log_bin_trust_function_creators = 1;
MariaDB [(none)]> QUIT
```

### Warning

"The Zabbix documentation explicitly mentions that deterministic triggers need to be created during the import of schema. On MySQL and MariaDB, this requires GLOBAL log\_bin\_trust\_function\_creators = 1 to be set if binary logging is enabled and there is no superuser privileges and log\_bin\_trust\_function\_creators = 1 is not set in MySQL configuration file."

## Add the Zabbix repository and populate the DB

```
# rpm -Uvh https://repo.zabbix.com/zabbix/6.5/rocky/9/x86_64/zabbix-release-6.5-2.el9.noarch.rpm
# dnf clean all
# dnf install zabbix-sql-scripts
```

Upload the data from zabbix (db structure, images, user, ... )

```
# zcat /usr/share/zabbix-sql-scripts/mysql/server.sql.gz | mysql --default-character-set=utf8mb4 -uroot -p zabbix
```

### Warning

"Depending on the speed of your hardware or VM this can take a few seconds upto a few minutes so please don't cancel just sit and wait for the prompt."

Log back into your MariaDB Database as root

```
# mysql -uroot -p
```

Remove the global parameter again as its not needed anymore and also for security reasons.

```
MariaDB [(none)]> SET GLOBAL log_bin_trust_function_creators = 0;
Query OK, 0 rows affected (0.001 sec)
```

## Configure the firewall

One last thing we need to do is open the firewall and allow incoming connections for the MariaDB database from our Zabbix server because at the moment we dont accept any connections yet.

```
# firewall-cmd --list-all
public (active)
  target: default
  icmp-block-inversion: no
  interfaces: enp0s3 enp0s8
  sources:
  services: cockpit dhcpv6-client ssh
  ports:
  protocols:
  forward: yes
  masquerade: no
  forward-ports:
  source-ports:
  icmp-blocks:
  rich rules:
```

First we will create an appropriate zone for our MariaDB and open port 3306/tcp but only for the ip from our Zabbix server.

```
# firewall-cmd --new-zone=mariadb-access --permanent
success

# firewall-cmd --reload
success

# firewall-cmd --get-zones
block dmz drop external home internal mariadb-access nm-shared public trusted work

# firewall-cmd --zone=mariadb-access --add-source=<zabbix-serverip> --permanent
success
```

```
# firewall-cmd --zone=mariadb-access --add-port=3306/tcp --permanent
success
# firewall-cmd --reload
```

Now let's have a look to our firewall rules to see if they are what we expected:

```
# firewall-cmd --zone=mariadb-access --list-all
```

```
mariadb-access (active)
target: default
icmp-block-inversion: no
interfaces:
sources: <ip from zabbix-server>
services:
ports: 3306/tcp
protocols:
forward: no
masquerade: no
forward-ports:
source-ports:
icmp-blocks:
rich rules:
```

Our database server is ready now to accept connections from our Zabbix server :). You can continue with the next task [Installing the Zabbix Server](#)

## 6.2.2 Installing Zabbix with MySQL

Let us start with the installation of the MySQL server, you need to create a MySQL repository first so that we can install the proper files for our MySQL server. It's always best to check the Zabbix [documentation](#) to see what version is supported so you don't install a version that is not supported or is not supported anymore.

### Add the MySQL repo

Run the following command to install the MySQL repo for version 8.0

```
# dnf -y install https://dev.mysql.com/get/mysql80-community-release-el9-1.noarch.rpm
```



"If you install this on RedHat 8 and higher or alternatives like CentOS, Rocky or Alma 8 then you need to disable the mysql module by running 'module disable mysql'."

Let's update our OS first with the latest patches

```
# dnf update -y
```

### INSTALLING THE MYSQL DATABASE

```
# dnf -y install mysql-community-server
```

We are now ready to enable and start our MySQL database.

```
# systemctl enable mysqld --now
```

Once the installation is complete, you can verify the version of the MySQL server by using the following command:

```
# mysql -V
```

The output should look like this:

```
mysql Ver 8.0.35 for Linux on x86_64 (MySQL Community Server - GPL)
```

And when we ask the status of our MariaDB server we should get an output like this:

```
# systemctl status mysqld

● mysqld.service - MySQL Server
   Loaded: loaded (/usr/lib/systemd/system/mysqld.service; enabled; preset: disabled)
   Active: active (running) since Mon 2023-11-20 22:15:51 CET; 1min 15s ago
     Docs: man:mysqld(8)
           http://dev.mysql.com/doc/refman/en/using-systemd.html
```

```

Process: 44947 ExecStartPre=/usr/bin/mysqld_pre_systemd (code=exited, status=0/SUCCESS)
Main PID: 45012 (mysqld)
Status: "Server is operational"
Tasks: 37 (limit: 12344)
Memory: 448.3M
CPU: 4.073s
CGroup: /system.slice/mysqld.service
        └─45012 /usr/sbin/mysqld

Nov 20 22:15:43 mysql-db systemd[1]: Starting MySQL Server...
Nov 20 22:15:51 mysql-db systemd[1]: Started MySQL Server.

```

## Securing the MySQL database

MySQL will secure our database with a random root password that is generated when we install the database. First thing we need to do is replace it with our own password. To find what the password is we need to read the log file with the following command:

```
# grep 'temporary password' /var/log/mysqld.log
```

Change the root password as soon as possible by logging in with the generated, temporary password and set a custom password for the superuser account:

```
# mysql -uroot -p
```

```
mysql> ALTER USER 'root'@'localhost' IDENTIFIED BY '<my mysql password>';
mysql> quit
```

Next we can run the command `mysql_secure_installation`, you should get the following output:



**Note**

"There is no need to reset the root password for MySQL again as we have reset it already. The next step is optional but recommended."

```

# mysql_secure_installation

Securing the MySQL server deployment.

Enter password for user root:
The 'validate_password' component is installed on the server.
The subsequent steps will run with the existing configuration
of the component.
Using existing password for root.

Estimated strength of the password: 100
Change the password for root ? ((Press y|Y for Yes, any other key for No) : n

... skipping.
By default, a MySQL installation has an anonymous user,
allowing anyone to log into MySQL without having to have
a user account created for them. This is intended only for
testing, and to make the installation go a bit smoother.
You should remove them before moving into a production
environment.

Remove anonymous users? (Press y|Y for Yes, any other key for No) : y
Success.

Normally, root should only be allowed to connect from
'localhost'. This ensures that someone cannot guess at
the root password from the network.

Disallow root login remotely? (Press y|Y for Yes, any other key for No) : y
Success.

By default, MySQL comes with a database named 'test' that
anyone can access. This is also intended only for testing,
and should be removed before moving into a production
environment.

Remove test database and access to it? (Press y|Y for Yes, any other key for No) : y
- Dropping test database...
Success.

- Removing privileges on test database...
Success.

Reloading the privilege tables will ensure that all changes
made so far will take effect immediately.

Reload privilege tables now? (Press y|Y for Yes, any other key for No) : y

```

Success.

All done!

Let's create our DB users and the correct permissions in the database:

```
mysql -uroot -p
```

```
mysql> CREATE DATABASE zabbix CHARACTER SET utf8mb4 COLLATE utf8mb4_bin;
mysql> CREATE USER 'zabbix-web'@'<zabbix server ip>' IDENTIFIED BY '<password>';
mysql> CREATE USER 'zabbix-srv'@'<zabbix server ip>' IDENTIFIED BY '<password>';
mysql> GRANT ALL PRIVILEGES ON zabbix.* TO 'zabbix-srv'@'<zabbix server ip>';
mysql> GRANT SELECT, UPDATE, DELETE, INSERT ON zabbix.* TO 'zabbix-web'@'<zabbix server ip>';
mysql> SET GLOBAL log_bin_trust_function_creators = 1;
mysql> QUIT
```

### warning

"The Zabbix documentation explicitly mentions that deterministic triggers need to be created during the import of schema. On MySQL and MariaDB, this requires GLOBAL log\_bin\_trust\_function\_creators = 1 to be set if binary logging is enabled and there is no superuser privileges and log\_bin\_trust\_function\_creators = 1 is not set in MySQL configuration file."

## Add the Zabbix repository and populate the DB

```
# rpm -Uvh https://repo.zabbix.com/zabbix/6.5/rocky/9/x86_64/zabbix-release-6.5-2.el9.noarch.rpm
# dnf clean all
# dnf install zabbix-sql-scripts
```

Now let's upload the data from zabbix (db structure, images, user, ... )

```
# zcat /usr/share/zabbix-sql-scripts/mysql/server.sql.gz | mysql --default-character-set=utf8mb4 -uroot -p zabbix
Enter password:
```

### warning

"Depending on the speed of your hardware or VM this can take a few seconds upto a few minutes so please don't cancel just sit and wait for the prompt."

Log back into your MySQL Database as root

```
# mysql -uroot -p
```

Remove the global parameter again as its not needed anymore and also for security reasons.

```
mysql> SET GLOBAL log_bin_trust_function_creators = 0;
Query OK, 0 rows affected, 1 warning (0.00 sec)
```

## Configure the firewall

One last thing we need to do is open the firewall and allow incoming connections from our Zabbix server to our MySQL database because at the moment we don't accept any connections yet.

```
# firewall-cmd --list-all
public (active)
  target: default
  icmp-block-inversion: no
  interfaces: enp0s3 enp0s8
  sources:
  services: cockpit dhcpv6-client ssh
  ports:
  protocols:
  forward: yes
  masquerade: no
  forward-ports:
  source-ports:
  icmp-blocks:
  rich rules:
```

First we will create an appropriate zone for our MySQL Database and open port 3306/tcp but only for the IP from our Zabbix server. This way no one unallowed is able to connect.

```
# firewall-cmd --new-zone=mysql-access --permanent
success

# firewall-cmd --reload
success

# firewall-cmd --get-zones
block dmz drop external home internal mysql-access nm-shared public trusted work

# firewall-cmd --zone=mysql-access --add-source=<zabbix-serverip> --permanent

success
# firewall-cmd --zone=mysql-access --add-port=3306/tcp --permanent

success
# firewall-cmd --reload
```

Now lets have a look to our firewall rules to see if they are what we expected:

```
# firewall-cmd --list-all --zone=mysql-access
```

```
mysql-access (active)
  target: default
  icmp-block-inversion: no
  interfaces:
  sources: <ip from the zabbix-server>
  services:
  ports: 3306/tcp
  protocols:
  forward: no
  masquerade: no
  forward-ports:
  source-ports:
  icmp-blocks:
  rich rules:
```

Our database server is ready now to accept connections from our Zabbix server :). You can continue with the next task [Installing the Zabbix Server](#)

## 6.2.3 Installing Zabbix with PostgreSQL

For our DB setup with PostgreSQL we need to add our PostgreSQL repository first to the system. As of writing PostgreSQL 13-16 are supported but best is to have a look before you install it as new versions may be supported and older maybe unsupported both by Zabbix and PostgreSQL. Usually it's a good idea to go with the latest version that is supported by Zabbix. Zabbix also supports the extension TimescaleDB this is something we will talk later about. As you will see the setup from PostgreSQL is very different from MySQL not only the installation but also securing the DB.

The table of compatibility can be found [here](#).

### Add the PostgreSQL repo

So let us start first setting up our PostgreSQL repository with the folowing commands.

```
# Install the repository RPM:
sudo dnf install -y https://download.postgresql.org/pub/repos/yum/reporpms/EL-9-x86_64/pgdg-redhat-repo-latest.noarch.rpm

# Disable the built-in PostgreSQL module:
sudo dnf -qy module disable postgresql

# Install PostgreSQL:
sudo dnf install -y postgresql16-server

# Initialize the database and enable automatic start:
sudo /usr/pgsql-16/bin/postgresql-16-setup initdb
sudo systemctl enable postgresql-16 --now
```

### Securing the PostgreSQL database

As i told you PostgreSQL works a bit different then MySQL or MariaDB and this applies aswell to how we manage access permissions. Postgres works with a file with the name `pg_hba.conf` where we have to tell who can access our database from where and what encryption is used for the password. So let's edit this file to allow our frontend and zabbix server to access the database.





"Client authentication is configured by a configuration file with the name `pg_hba.conf`. HBA here stands for host based authentication. For more information feel free to check the [PostgreSQL documentation](#)."

Add the following lines, the order here is important.

```
# vi /var/lib/pgsql/16/data/pg_hba.conf

# "local" is for Unix domain socket connections only
local   zabbix      zabbix-srv           scram-sha-256
local   all         all                 peer
# IPv4 local connections:
host    zabbix      zabbix-srv           <ip from zabbix server/24>  scram-sha-256
host    zabbix      zabbix-web        <ip from zabbix server/24>  scram-sha-256
host    all         all             127.0.0.1/32              scram-sha-256
```

After we changed the `pg_hba` file don't forget to restart postgres else the settings will not be applied. But before we restart let us also edit the file `postgresql.conf` and allow our database to listen on our network interface for incoming connections from the zabbix server. PostgreSQL will standard only allow connections from the socket.

```
# vi /var/lib/pgsql/16/data/postgresql.conf
```

and replace the line with `listen_addresses` so that PostgreSQL will listen on all interfaces and not only on our localhost.

```
#listen_addresses = 'localhost' with listen_addresses = '*'
```

When done restart the PostgreSQL cluster and see if it comes back online in case of an error check the `pg_hba.conf` file you just edited for typos.

```
# systemctl restart postgresql-16
```

For our Zabbix server we need to create tables in the database for this we need to install the Zabbix repository like we did for our Zabbix server and install the Zabbix package containing all the database tables images icons, ....

### Add the Zabbix repository and populate the DB

```
# dnf install https://repo.zabbix.com/zabbix/6.0/rhel/9/x86_64/zabbix-release-6.0-4.el9.noarch.rpm -y
# dnf install zabbix-sql-scripts -y
```

Now we are ready to create our Zabbix users for the server and the frontend:

```
# su - postgres
# createuser --pwprompt zabbix-srv
Enter password for new role: <server-password>
Enter it again: <server-password>
```

Let's do the same for our frontend let's create a user to connect to the database:

```
# createuser --pwprompt zabbix-web
Enter password for new role: <frontend-password>
Enter it again: <frontend-password>
```

Next we have to unzip the database schema files. Run as user root followin command::

```
# gzip -d /usr/share/zabbix-sql-scripts/postgresql/server.sql.gz
```

We are now ready to create our database zabbix. Become user postgres again and run next command to create the database as our user zabbix-srv:

```
# su - postgres
# createdb -E Unicode -O zabbix-srv zabbix
```

Let's verify that we are really connected to the database with the correct session. Login from the Postgres shell on the zabbix database

```
# psql -d zabbix -U zabbix-srv
```

Make sure we are logged in with our correct user `zabbix-srv`.

```
zabbix=> SELECT session_user, current_user;
 session_user | current_user
-----+-----
 zabbix-srv   | zabbix-srv
(1 row)
```

PostgreSQL works a bit different then MySQL or MariaDB when it comes to almost everything :) One of the things that it has that MySQL not has are for example shemas. If you like to know more about it i can recommend [this](#) URI. It explains in detail what it is and why we need it. But in short ... In PostgreSQL schema enables a multi-user environment that allows multiple users to access the same database without interference. Schemas are important when several users use the application and access the database in their way or when various applications utilize the same database. There is a standard schema that you can use but the better way is to create our own schema.



"There is a standard schema `public` that you can use but the better way is to create our own schema this was if later something else is installed next to the Zabbix database it will be easier to create users with only access to the newly created database tables."

```
zabbix=> CREATE SCHEMA zabbix_server AUTHORIZATION "zabbix-srv";
CREATE SCHEMA
zabbix=> set search_path to "zabbix_server";
zabbix=> \dn
      List of schemas
   Name      | Owner
-----+-----
 public      | pg_database_owner
 zabbix_server | zabbix-srv
(2 rows)
```

Now we have our DB ready with correct permissions for user `zabbix-srv` but not yet for our user `zabbix-web`. Let's fix this first and give the rights to connect to our schema.

```
zabbix=# GRANT USAGE ON SCHEMA zabbix_server TO "zabbix-web";
GRANT
```

The user `zabbix-web` has now the rights to connect to our schema but cannot to anything yet lets fix this but also don't give too many rights.

```
zabbix=# GRANT SELECT, INSERT, UPDATE, DELETE ON ALL TABLES IN SCHEMA zabbix_server TO "zabbix-web";
GRANT
zabbix=# GRANT SELECT, UPDATE ON ALL SEQUENCES IN SCHEMA zabbix_server TO "zabbix-web";
GRANT
```

There we go both users are created with the correct permissons. We are now ready to populate the database with the Zabbix table structures etc ... log back in as user postgres and run the following commands

Let's upload the Zabbix SQL file we extracted earlier to populate our database with the needed schemas images users etc ...



"Depending on the speed of your hardware or VM this can take a few seconds upto a few minutes so please don't cancel just sit and wait for the prompt."

```
zabbix=# \i /usr/share/zabbix-sql-scripts/postgresql/server.sql
CREATE TABLE
CREATE INDEX
...
...
INSERT 0 1
INSERT 0 1
INSERT 0 1
INSERT 0 1
COMMIT
zabbix=#
```



"If the import fails with `psql:/usr/share/zabbix-sql-scripts/postgresql/server.sql:7: ERROR: no schema has been selected to create in` then you probably made an error in the line where you set the search path."

Lets verify that our tables are properly created with the correct permissions

```
zabbix=# \dt
          List of relations
Schema | Name | Type | Owner
-----+-----+-----+-----
zabbix_server | acknowledges | table | zabbix-srv
zabbix_server | actions | table | zabbix-srv
zabbix_server | alerts | table | zabbix-srv
zabbix_server | auditlog | table | zabbix-srv
zabbix_server | autoreg_host | table | zabbix-srv
...
zabbix_server | usrgroup | table | zabbix-srv
zabbix_server | valuemap | table | zabbix-srv
zabbix_server | valuemap_mapping | table | zabbix-srv
zabbix_server | widget | table | zabbix-srv
zabbix_server | widget_field | table | zabbix-srv
(173 rows)
```



"If you are like me and don't like to set the search path every time you logon with the user zabbix-srv to the correct search path you can run the following SQL.

```
zabbix=> alter role "zabbix-srv" set search_path = "$user", public, zabbix_server ;"
```

If you are ready you can exit the database and return as user root.

```
zabbix=> \q
# exit
```

## Configure the firewall

One last thing we need to do is open the firewall and allow incoming connections for the PostgreSQL database from our Zabbix server because at the moment we dont accept any connections yet.

```
# firewall-cmd --list-all
public (active)
  target: default
  icmp-block-inversion: no
  interfaces: enp0s3 enp0s8
  sources:
  services: cockpit dhcpv6-client ssh
  ports:
  protocols:
  forward: yes
  masquerade: no
  forward-ports:
  source-ports:
  icmp-blocks:
  rich rules:
```

First we will create an appropriate zone for our PostgreSQL DB and open port 5432/tcp but only for the ip from our Zabbix server.

```
# firewall-cmd --new-zone=postgresql-access --permanent
success

# firewall-cmd --reload
success

# firewall-cmd --get-zones
block dmz drop external home internal nm-shared postgresql-access public trusted work

# firewall-cmd --zone=postgresql-access--add-source=<zabbix-serverip> --permanent
success

# firewall-cmd --zone=postgresql-access --add-port=5432/tcp --permanent
success

# firewall-cmd --reload
```

Now lets have a look to our firewall rules to see if they are what we expected:

```
# firewall-cmd --zone=postgresql-access --list-all
```


```
postgresql-access (active)
  target: default
  icmp-block-inversion: no
  interfaces:
  sources: 192.168.56.18
  services:
  ports: 5432/tcp
  protocols:
  forward: no
  masquerade: no
  forward-ports:
  source-ports:
  icmp-blocks:
  rich rules:
```

Our database server is ready now to accept connections from our Zabbix server :). You can continue with the next task [Installing the Zabbix Server](#)

## 6.3 Installing Zabbix

Before we can install Zabbix we first have to know how the design is. The Zabbix server has been build op modular based on 3 components.

- The Zabbix server
- The Zabbix web server
- The Zabbix database



All these components can be installed on 1 server or can be split over 3 different servers. The Zabbix server itself is the brain this part is doing all the trigger calculations and sending all the alert. The database is where the Zabbix server stores its config and all the data that we have gathered. The web server provides us with a front-end. Note that Zabbix has a API and that this is also located on the front-end and not on the Zabbix server side.

All these parts have to work together so as you can see in our image above. The Zabbix server needs to read the config and store the data in our database and the Zabbix front-end needs to be able to write the configuration in the database as well. The Zabbix front-end also needs to check the online status of our Zabbix server and needs to read some other information as well.

For our setup, we will use 2 VM's, 1 VM with a Zabbix server and our Zabbix web server and another VM with our Zabbix database.

### 6.3.1 Installing the Zabbix Server

Before you start to install your Zabbix server make sure the server is properly configure as we explained in our topic [Basic OS configuration before we start](#). Something else that is important in this case is that we need to disable SELinux. We will see later in chapter [Securing Zabbix](#) how to do this properly. We can check the status of SELinux with the command `sestatus` :

```
# sestatus
SELinux status:                enabled
SELinuxfs mount:              /sys/fs/selinux
SELinux root directory:      /etc/selinux
Loaded policy name:          targeted
Current mode:                enforcing
Mode from config file:      enforcing
Policy MLS status:          enabled
Policy deny_unknown status: allowed
Memory protection checking:  actual (secure)
Max kernel policy version:   33
```

As you can see we are now in enforcing mode. To disable SELinux just run `setenforce 0` to disable it.

```
# setenforce 0
# sestatus

SELinux status:                enabled
SELinuxfs mount:              /sys/fs/selinux
SELinux root directory:      /etc/selinux
Loaded policy name:          targeted
Current mode:                permissive
Mode from config file:      enforcing
Policy MLS status:          enabled
Policy deny_unknown status: allowed
Memory protection checking:  actual (secure)
Max kernel policy version:   33
```

As you can see our current mode is now permissive. However this is not persistent so we also need to alter our SELinux configuration file. This can be done by altering the file `/etc/config/selinux` and replacing enforcing by permissive. A more easy way is to run the following command :

```
sed -i 's/SELINUX=enforcing/SELINUX=permissive/g' /etc/selinux/config
```

This line will alter the config file for you. So when we run `sestatus` again we will see that we are in `permissive` mode and that our config file is also in `permissive` mode.

We can verify this with our `cat` commando.

```
# cat /etc/selinux/config

# This file controls the state of SELinux on the system.
# SELINUX= can take one of these three values:
#   enforcing - SELinux security policy is enforced.
#   permissive - SELinux prints warnings instead of enforcing.
#   disabled - No SELinux policy is loaded.
# See also:
# https://docs.fedoraproject.org/en-US/quick-docs/getting-started-with-selinux/#getting-started-with-selinux-selinux-states-and-modes
#
# NOTE: In earlier Fedora kernel builds, SELINUX=disabled would also
# fully disable SELinux during boot. If you need a system with SELinux
# fully disabled instead of SELinux running with no policy loaded, you
# need to pass selinux=0 to the kernel command line. You can use grubby
# to persistently set the bootloader to boot with selinux=0:
#
#   grubby --update-kernel ALL --args selinux=0
#
# To revert back to SELinux enabled:
#
#   grubby --update-kernel ALL --remove-args selinux
#
SELINUX=permissive
# SELINUXTYPE= can take one of these three values:
#   targeted - Targeted processes are protected,
#   minimum - Modification of targeted policy. Only selected processes are protected.
#   mls - Multi Level Security protection.
SELINUXTYPE=targeted
```

And we can also verify it with our commando `setstatus`

```
# sestatus

SELinux status:                enabled
SELinuxfs mount:              /sys/fs/selinux
SELinux root directory:      /etc/selinux
Loaded policy name:          targeted
```

```
Current mode:                permissive
Mode from config file:      permissive
Policy MLS status:         enabled
Policy deny_unknown status: allowed
Memory protection checking: actual (secure)
Max kernel policy version:  33
```

ADDING THE ZABBIX REPOSITORY

From the [Zabbix Download page](#) select the correct Zabbix version you would like to install. In our case it will be 7.0 LTS. Select the correct OS distribution as well. This will be Rocky Linux 9 in our case. We are going to install the Server and will be using NGINX.

ZABBIX VERSION

6.4

6.0 LTS

5.0 LTS

4.0 LTS

7.0 PRE-RELEASE

OS DISTRIBUTION

Alma Linux

CentOS

Debian

Debian (arm64)

OpenSUSE Leap

Oracle Linux

Raspberry Pi OS

Red Hat Enterprise Linux

Rocky Linux

SUSE Linux Enterprise Server

Ubuntu

Ubuntu (arm64)

OS VERSION

9

8

ZABBIX COMPONENT

Server, Frontend, Agent

Proxy

Agent

Agent 2

Java Gateway

Web Service

DATABASE

MySQL

PostgreSQL


WEB SERVER

Apache

Nginx

Our first step is to disable Zabbix packages provided by EPEL, if you have it installed. Edit file /etc/yum.repos.d/epel.repo and add the following statement.


```
[epel]
...
excludepkgs=zabbix*
```



Having the EPEL repository enabled is a bad practice and could be dangerous if you use EPEL it's best to disable the repo and use dnf install --enablerepo=epel. This way you will never overwrite or install unwanted packages by accident.

Our next task is to install the Zabbix repository on our OS and do a dnf cleanup so that old cache files from our repository metadata is cleaned up.

```
rpm -Uvh https://repo.zabbix.com/zabbix/6.5/rocky/9/x86_64/zabbix-release-6.5-2.el9.noarch.rpm
dnf clean all
```



A repository is a config in Linux that you can add to make packages available for you OS to install. The best way to look at it is maybe to think of it like an APP store that you add where you can find the software of your vendor. In this case the repository from Zabbix. There are many repositories you can add but you should be sure that they can be trusted. So it's always a good idea to stick to the repositories of your OS and only add extra repositories when you are sure they are to be trusted and needed. In our case the repository is from our vendor Zabbix so it should be safe to add. Epeel is another popular repository for RedHat systems that is considered to be safe.

INSTALLING THE ZABBIX SERVER FOR MYSQL/MARIADB

Now that we have our repository with software added to our system we are ready to install our Zabbix server and webserver. Remember the webserver could be installed on another system. There is no need to install both on the same server.

```
dnf install zabbix-server-mysql zabbix-web-mysql
```

Now that we have installed our packages for the Zabbix server and our frontend we still need to change the configuration of our Zabbix server so that we can connect to our database. Open the file `/etc/zabbix/zabbix_server.conf` and replace the following lines:

```
DBHost=<ip or dns of your MariaDB server>
DBName=<the name of your database>
DBUser=<the user that will connect to the database>
DBPassword=<your super secret password>
```

Make sure you don't have a '#' in front of the config parameter else Zabbix will see this as text and not as a parameter. Also make sure that there are not extra duplicate lines Zabbix will always take the last config parameter if there is more than 1 line with the same parameter

In our case the config will look like this:

```
# vi /etc/zabbix/zabbix_server.conf

DBHost=<ip or dns of your MariaDB server>
DBName=zabbix
DBUser=zabbix-srv
DBPassword=<your super secret password>
DBPort=3306
```



The Zabbix server configuration file has the option to include an extra config file with parameters you like to alter or add. In production it's probably better to not touch the configuration file but to add a new file and include the parameters you like to change. This way you never have to edit your original configuration file after an upgrade it will also make your life more easy when working with configuration tools like Ansible, Puppet, SaltStack, .... The only thing that needs to be done is remove the # in front of the line '# Include=/usr/local/etc/zabbix\_server.conf.d/\*.conf' and make sure the path exists with a customized config file of your won that is readable by the user zabbix.

Ok now that we have changed the configuration of you Zabbix server so that it is able to connect to our DB we are ready to start. Run the following command to enable the Zabbix server and make it active on boot next time.

```
systemctl enable zabbix-server --now
```

Our Zabbix server service will start and if everything goes well you should see in the Zabbix server log file the following output

```
tail /var/log/zabbix/zabbix_server.log
```

```
1123:20231120:110604.440 Starting Zabbix Server. Zabbix 7.0.0alpha7 (revision 60de6a81aca).
1123:20231120:110604.440 ***** Enabled features *****
1123:20231120:110604.440 SNMP monitoring:      YES
1123:20231120:110604.440 IPMI monitoring:       YES
1123:20231120:110604.440 Web monitoring:        YES
1123:20231120:110604.440 VMware monitoring:     YES
1123:20231120:110604.440 SMTP authentication:   YES
1123:20231120:110604.440 ODBC:                  YES
1123:20231120:110604.440 SSH support:           YES
1123:20231120:110604.440 IPv6 support:          YES
1123:20231120:110604.440 TLS support:           YES
1123:20231120:110604.440 *****
1123:20231120:110604.440 using configuration file: /etc/zabbix/zabbix_server.conf
1123:20231120:110604.470 current database version (mandatory/optional): 06050143/06050143
1123:20231120:110604.470 required mandatory version: 06050143
1124:20231120:110604.490 starting HA manager
1124:20231120:110604.507 HA manager started in active mode
1123:20231120:110604.508 server #0 started [main process]
1126:20231120:110604.509 server #2 started [configuration syncer #1]
1125:20231120:110604.510 server #1 started [service manager #1]
1133:20231120:110604.841 server #9 started [lld worker #1]
1132:20231120:110604.841 server #8 started [lld manager #1]
1134:20231120:110604.841 server #10 started [lld worker #2]
```

If there was an error and the server was not able to connect to the database you would see something like this in the server log file :

```
10773:20231118:213248.570 Starting Zabbix Server. Zabbix 7.0.0alpha7 (revision 60de6a81aca).
10773:20231118:213248.570 ***** Enabled features *****
10773:20231118:213248.570 SNMP monitoring:      YES
10773:20231118:213248.570 IPMI monitoring:       YES
10773:20231118:213248.570 Web monitoring:        YES
10773:20231118:213248.570 VMware monitoring:     YES
10773:20231118:213248.570 SMTP authentication:   YES
10773:20231118:213248.570 ODBC:                  YES
10773:20231118:213248.570 SSH support:           YES
```



```

10773:20231118:213248.570 IPv6 support: YES
10773:20231118:213248.570 TLS support: YES
10773:20231118:213248.570 *****
10773:20231118:213248.570 using configuration file: /etc/zabbix/zabbix_server.conf
10773:20231118:213248.574 [Z3001] connection to database 'zabbix' failed: [2002] Can't connect to server on 'xxx.xxx.xxx.xxx' (115)
10773:20231118:213248.574 database is down: reconnecting in 10 seconds
10773:20231118:213258.579 [Z3001] connection to database 'zabbix' failed: [2002] Can't connect to server on 'xxx.xxx.xxx.xxx' (115)
10773:20231118:213258.579 database is down: reconnecting in 10 seconds

```

Let's check the Zabbix server service to see if it's enabled so that it survives a reboot

```

# systemctl status zabbix-server

● zabbix-server.service - Zabbix Server
   Loaded: loaded (/usr/lib/systemd/system/zabbix-server.service; enabled; preset: disabled)
   Active: active (running) since Mon 2023-11-20 11:06:04 CET; 1h 2min ago
   Main PID: 1123 (zabbix_server)
     Tasks: 59 (limit: 12344)
    Memory: 52.6M
       CPU: 20.399s
   CGroup: /system.slice/zabbix-server.service
           └─1123 /usr/sbin/zabbix_server -c /etc/zabbix/zabbix_server.conf
           └─1124 "/usr/sbin/zabbix_server: ha manager"
           └─1125 "/usr/sbin/zabbix_server: service manager #1 [processed 0 events, updated 0 event tags, deleted 0 problems, synced 0 service updates, idle
5.008686 sec during 5.016382 sec]"
           └─1126 "/usr/sbin/zabbix_server: configuration syncer [synced configuration in 0.092797 sec, idle 10 sec]"
           └─1127 "/usr/sbin/zabbix_server: alert manager #1 [sent 0, failed 0 alerts, idle 5.027620 sec during 5.027828 sec]"
           └─1128 "/usr/sbin/zabbix_server: alerter #1 started"
           └─1129 "/usr/sbin/zabbix_server: alerter #2 started"
           └─1130 "/usr/sbin/zabbix_server: alerter #3 started"
           └─1131 "/usr/sbin/zabbix_server: preprocessing manager #1 [queued 1, processed 2 values, idle 5.490312 sec during 5.490555 sec]"
           └─1132 "/usr/sbin/zabbix_server: lld manager #1 [processed 1 LLD rules, idle 5.028973sec during 5.029123 sec]"
           └─1133 "/usr/sbin/zabbix_server: lld worker #1 [processed 1 LLD rules, idle 60.060180 sec during 60.085009 sec]"
           └─1134 "/usr/sbin/zabbix_server: lld worker #2 [processed 1 LLD rules, idle 60.065526 sec during 60.095165 sec]"
           └─1135 "/usr/sbin/zabbix_server: housekeeper [deleted 0 hist/trends, 0 items/triggers, 0 events, 0 sessions, 0 alarms, 0 audit items, 0
autoreg_host, 0 records in 0.019108 sec, idle for 1 hour(s)]"
           └─1136 "/usr/sbin/zabbix_server: timer #1 [updated 0 hosts, suppressed 0 events in 0.002856 sec, idle 59 sec]"
           └─1137 "/usr/sbin/zabbix_server: http poller #1 [got 0 values in 0.000059 sec, idle 5 sec]"
           └─1138 "/usr/sbin/zabbix_server: discovery manager #1 [processing 0 rules, 0.000000% of queue used, 0 unsaved checks]"
           └─1139 "/usr/sbin/zabbix_server: history syncer #1 [processed 0 values, 0 triggers in 0.000036 sec, idle 1 sec]"
           └─1140 "/usr/sbin/zabbix_server: history syncer #2 [processed 1 values, 0 triggers in 0.005016 sec, idle 1 sec]"
           └─1141 "/usr/sbin/zabbix_server: history syncer #3 [processed 0 values, 0 triggers in 0.000031 sec, idle 1 sec]"
           └─1142 "/usr/sbin/zabbix_server: history syncer #4 [processed 0 values, 0 triggers in 0.000014 sec, idle 1 sec]"
           └─1143 "/usr/sbin/zabbix_server: escalator #1 [processed 0 escalations in 0.005587 sec, idle 3 sec]"
           └─1144 "/usr/sbin/zabbix_server: proxy poller #1 [exchanged data with 0 proxies in 0.000010 sec, idle 5 sec]"
           └─1145 "/usr/sbin/zabbix_server: self-monitoring [processed data in 0.000016 sec, idle 1 sec]"
           └─1146 "/usr/sbin/zabbix_server: task manager [processed 0 task(s) in 0.002511 sec, idle 5 sec]"
           └─1147 "/usr/sbin/zabbix_server: poller #1 [got 0 values in 0.000009 sec, idle 1 sec]"
           └─1148 "/usr/sbin/zabbix_server: poller #2 [got 1 values in 0.000232 sec, idle 1 sec]"
           └─1149 "/usr/sbin/zabbix_server: poller #3 [got 0 values in 0.000015 sec, idle 1 sec]"
           └─1150 "/usr/sbin/zabbix_server: poller #4 [got 0 values in 0.000010 sec, idle 1 sec]"

```

This concludes our chapter on installing and configuring our Zabbix server. Next we have to configure our frontend. You can have a look at [Installing Zabbix frontend with Nginx](#) or [Installing Zabbix frontend with Apache](#)

## INSTALLING THE ZABBIX SERVER FOR POSTGRESQL

Now that we have our repository with software added to our system we are ready to install our Zabbix server and webserver. Remember the webserver could be installed on another system. There is no need to install both on the same server.

```
dnf install zabbix-server-pgsql zabbix-web-pgsql
```

Now that we have installed our packages for the Zabbix server and our frontend we still need to change the configuration of our Zabbix server so that we can connect to our database. Open the file `/etc/zabbix/zabbix_server.conf` and replace the following lines:

```

DBHost=<ip or dns of your PostgreSQL server>
DBName=<the name of your database>
DBSchema=<our PostgreSQL schema name>
DBUser=<the user that will connect to the database>
DBPassword=<your super secret password>

```

Make sure you don't have a '#' in front of the config parameter else Zabbix will see this as text and not as a parameter. Also make sure that there are not extra duplicate lines Zabbix will always take the last config parameter if there is more then 1 line with the same parameter

In our case the config will look like this:

```

# vi /etc/zabbix/zabbix_server.conf

DBHost=<ip or dns of your MariaDB server>
DBName=zabbix
DBSchema=zabbix_server
DBUser=zabbix-srv

```

```
DBPassword=<your super secret password>
DBPort=5432
```



The Zabbix server configuration file has the option to include an extra config file with parameters you like to alter or add. In production it's probably better to not touch the configuration file but to add a new file and include the parameters you like to change. This way you never have to edit your original configuration file after an upgrade it will also make your life more easy when working with configuration tools like Ansible, Puppet, SaltStack, .... The only thing that needs to be done is remove the # in front of the line '# Include=/usr/local/etc/zabbix\_server.conf.d/\*.conf' and make sure the path exists with a customized config file of your won that is readable by the user zabbix.

Ok now that we have changed the configuration of you Zabbix server so that it is able to connect to our DB we are ready to start. Run the following command to enable the Zabbix server and make it active on boot next time.

```
systemctl enable zabbix-server --now
```

Our Zabbix server service will start and if everything goes well you should see in the Zabbix server log file the following output

```
tail /var/log/zabbix/zabbix_server.log
```

```
1123:20231120:110604.440 Starting Zabbix Server. Zabbix 7.0.0alpha7 (revision 60de6a81aca).
1123:20231120:110604.440 ***** Enabled features *****
1123:20231120:110604.440 SNMP monitoring:      YES
1123:20231120:110604.440 IPMI monitoring:      YES
1123:20231120:110604.440 Web monitoring:      YES
1123:20231120:110604.440 VMware monitoring:    YES
1123:20231120:110604.440 SMTP authentication:  YES
1123:20231120:110604.440 ODBC:                YES
1123:20231120:110604.440 SSH support:         YES
1123:20231120:110604.440 IPv6 support:        YES
1123:20231120:110604.440 TLS support:         YES
1123:20231120:110604.440 *****
1123:20231120:110604.440 using configuration file: /etc/zabbix/zabbix_server.conf
1123:20231120:110604.470 current database version (mandatory/optional): 06050143/06050143
1123:20231120:110604.470 required mandatory version: 06050143
1124:20231120:110604.490 starting HA manager
1124:20231120:110604.507 HA manager started in active mode
1123:20231120:110604.508 server #0 started [main process]
1126:20231120:110604.509 server #2 started [configuration syncer #1]
1125:20231120:110604.510 server #1 started [service manager #1]
1133:20231120:110604.841 server #9 started [lld worker #1]
1132:20231120:110604.841 server #8 started [lld manager #1]
1134:20231120:110604.841 server #10 started [lld worker #2]
```

If there was an error and the server was not able to connect to the database you would see something like this in the server log file :

```
10773:20231118:213248.570 Starting Zabbix Server. Zabbix 7.0.0alpha7 (revision 60de6a81aca).
10773:20231118:213248.570 ***** Enabled features *****
10773:20231118:213248.570 SNMP monitoring:      YES
10773:20231118:213248.570 IPMI monitoring:      YES
10773:20231118:213248.570 Web monitoring:      YES
10773:20231118:213248.570 VMware monitoring:    YES
10773:20231118:213248.570 SMTP authentication:  YES
10773:20231118:213248.570 ODBC:                YES
10773:20231118:213248.570 SSH support:         YES
10773:20231118:213248.570 IPv6 support:        YES
10773:20231118:213248.570 TLS support:         YES
10773:20231118:213248.570 *****
10773:20231118:213248.570 using configuration file: /etc/zabbix/zabbix_server.conf
10773:20231118:213248.574 [Z3001] connection to database 'zabbix' failed: [2002] Can't connect to server on 'xxx.xxx.xxx.xxx' (115)
10773:20231118:213248.574 database is down: reconnecting in 10 seconds
10773:20231118:213258.579 [Z3001] connection to database 'zabbix' failed: [2002] Can't connect to server on 'xxx.xxx.xxx.xxx' (115)
10773:20231118:213258.579 database is down: reconnecting in 10 seconds
```

Let's check the Zabbix server service to see if it's enabled so that it survives a reboot

```
# systemctl status zabbix-server
```

```
• zabbix-server.service - Zabbix Server
   Loaded: loaded (/usr/lib/systemd/system/zabbix-server.service; enabled; preset: disabled)
   Active: active (running) since Mon 2023-11-20 11:06:04 CET; 1h 2min ago
   Main PID: 1123 (zabbix_server)
     Tasks: 59 (limit: 12344)
    Memory: 52.6M
      CPU: 20.399s
   CGroup: /system.slice/zabbix-server.service
           └─1123 /usr/sbin/zabbix_server -c /etc/zabbix/zabbix_server.conf
           └─1124 "/usr/sbin/zabbix_server: ha manager"
```

```

|1125 "/usr/sbin/zabbix_server: service manager #1 [processed 0 events, updated 0 event tags, deleted 0 problems, synced 0 service updates, idle
5.008686 sec during 5.016382 sec]"
|1126 "/usr/sbin/zabbix_server: configuration syncer [synced configuration in 0.092797 sec, idle 10 sec]"
|1127 "/usr/sbin/zabbix_server: alert manager #1 [sent 0, failed 0 alerts, idle 5.027620 sec during 5.027828 sec]"
|1128 "/usr/sbin/zabbix_server: alerter #1 started"
|1129 "/usr/sbin/zabbix_server: alerter #2 started"
|1130 "/usr/sbin/zabbix_server: alerter #3 started"
|1131 "/usr/sbin/zabbix_server: preprocessing manager #1 [queued 1, processed 2 values, idle 5.490312 sec during 5.490555 sec]"
|1132 "/usr/sbin/zabbix_server: lld manager #1 [processed 1 LLD rules, idle 5.028973sec during 5.029123 sec]"
|1133 "/usr/sbin/zabbix_server: lld worker #1 [processed 1 LLD rules, idle 60.060180 sec during 60.085009 sec]"
|1134 "/usr/sbin/zabbix_server: lld worker #2 [processed 1 LLD rules, idle 60.065526 sec during 60.095165 sec]"
|1135 "/usr/sbin/zabbix_server: housekeeper [deleted 0 hist/trends, 0 items/triggers, 0 events, 0 sessions, 0 alarms, 0 audit items, 0
autoreg_host, 0 records in 0.019108 sec, idle for 1 hour(s)]"
|1136 "/usr/sbin/zabbix_server: timer #1 [updated 0 hosts, suppressed 0 events in 0.002856 sec, idle 59 sec]"
|1137 "/usr/sbin/zabbix_server: http poller #1 [got 0 values in 0.000059 sec, idle 5 sec]"
|1138 "/usr/sbin/zabbix_server: discovery manager #1 [processing 0 rules, 0.000000% of queue used, 0 unsaved checks]"
|1139 "/usr/sbin/zabbix_server: history syncer #1 [processed 0 values, 0 triggers in 0.000036 sec, idle 1 sec]"
|1140 "/usr/sbin/zabbix_server: history syncer #2 [processed 1 values, 0 triggers in 0.005016 sec, idle 1 sec]"
|1141 "/usr/sbin/zabbix_server: history syncer #3 [processed 0 values, 0 triggers in 0.000031 sec, idle 1 sec]"
|1142 "/usr/sbin/zabbix_server: history syncer #4 [processed 0 values, 0 triggers in 0.000014 sec, idle 1 sec]"
|1143 "/usr/sbin/zabbix_server: escalator #1 [processed 0 escalations in 0.005587 sec, idle 3 sec]"
|1144 "/usr/sbin/zabbix_server: proxy poller #1 [exchanged data with 0 proxies in 0.000010 sec, idle 5 sec]"
|1145 "/usr/sbin/zabbix_server: self-monitoring [processed data in 0.000016 sec, idle 1 sec]"
|1146 "/usr/sbin/zabbix_server: task manager [processed 0 task(s) in 0.002511 sec, idle 5 sec]"
|1147 "/usr/sbin/zabbix_server: poller #1 [got 0 values in 0.000009 sec, idle 1 sec]"
|1148 "/usr/sbin/zabbix_server: poller #2 [got 1 values in 0.000232 sec, idle 1 sec]"
|1149 "/usr/sbin/zabbix_server: poller #3 [got 0 values in 0.000015 sec, idle 1 sec]"
|1150 "/usr/sbin/zabbix_server: poller #4 [got 0 values in 0.000010 sec, idle 1 sec]"

```

This concludes our chapter on installing and configuring our Zabbix server. Next we have to configure our frontend. You can have a look at [Installing Zabbix frontend with Nginx](#) or [Installing Zabbix frontend with Apache](#)

## Installing Zabbix frontend with Nginx

Before we can configure our frontend we need to install our package first. If you run the frontend on the same server as the Zabbix server then there is nothing else you have to do you can just run the following command on your server to install the packages needed for our frontend to install:

```
dnf install zabbix-nginx-conf and zabbix-web-mysql or if you used Postgres dnf install zabbix-web-pgsql
```

In case the frontend is on another server installed you need to add the Zabbix repository first like we did on our Zabbix server. In case you forgot or just skipped to this topic and don't know how to do this have a look at [Adding the Zabbix repository](#)

First thing we have to do is alter the Nginx configuration file so that we don't use the standard config.

```
vi /etc/nginx/nginx.conf
```

In this config look for the followin block that starts with :

```

server {
    listen      80;
    listen      [::]:80;
    server_name _;
    root        /usr/share/nginx/html;

    # Load configuration files for the default server block.
    include /etc/nginx/default.d/*.conf;

```

And place the following lines in comment:

```

#     server {
#         listen      80;
#         listen      [::]:80;
#         server_name _;
#         root        /usr/share/nginx/html;

```

We now have to alter the Zabbix configuration file so that it matches our setup. Edit the following file:

```
vi /etc/nginx/conf.d/zabbix.conf
```

```

server {
    listen      8080;
    server_name example.com;

    root        /usr/share/zabbix;

    index       index.php;

```

Replace the first 2 lines with the correct port and domain for your frontend in case you don't have a domain you can replace `server_name` with `_`; like in the example below:

```
server {
#       listen            8080;
#       server_name       example.com;
    listen 80;
    server_name _;

    root    /usr/share/zabbix;

    index  index.php;
}
```

We are now ready to start our webserver and enable it so that it comes online after a reboot.

```
systemctl enable php-fpm --now
systemctl enable nginx --now
```

Let's verify if the service is properly started and enabled so that it survives our reboot next time.

```
# systemctl status nginx

● nginx.service - The nginx HTTP and reverse proxy server
   Loaded: loaded (/usr/lib/systemd/system/nginx.service; enabled; preset: disabled)
   Drop-In: /usr/lib/systemd/system/nginx.service.d
            └─php-fpm.conf
   Active: active (running) since Mon 2023-11-20 11:42:18 CET; 30min ago
   Main PID: 1206 (nginx)
     Tasks: 2 (limit: 12344)
    Memory: 4.8M
       CPU: 38ms
   CGroup: /system.slice/nginx.service
            └─1206 "nginx: master process /usr/sbin/nginx"
              └─1207 "nginx: worker process"

Nov 20 11:42:18 zabbix-srv systemd[1]: Starting The nginx HTTP and reverse proxy server...
Nov 20 11:42:18 zabbix-srv nginx[1204]: nginx: the configuration file /etc/nginx/nginx.conf syntax is ok
Nov 20 11:42:18 zabbix-srv nginx[1204]: nginx: configuration file /etc/nginx/nginx.conf test is successful
Nov 20 11:42:18 zabbix-srv systemd[1]: Started The nginx HTTP and reverse proxy server.
```

The service is running and enabled so there is only 1 thing left to do before we can start the configuration in the GUI and that is to configure our firewall to allow incoming communication to the webserver.

```
firewall-cmd --add-service=http --permanent
firewall-cmd --reload
```

Open your browser and go to the url or ip of your frontend :

```
http://<ip or dns of the zabbix frontend server>/
```

If all goes well you should be greeted with a Zabbix welcome page. In case you have an error check the configuration again or have a look at the nginx log file :

```
/var/log/nginx/error.log
```

or run


```
journalctl -xe
```

This should help you in locating the errors you made.

When you point your browser to the correct URL you should be greeted with a page like here :



As you see there is only a limited list of local translations available on our Zabbix frontend to choose from



What if we want to install Chinese as language or another language from the list ? Run the next command to get a list of all locales available for your OS.

```
dnf list glibc-langpack-*
```

This will give you a list like

```
Installed Packages
glibc-langpack-en.x86_64
Available Packages
glibc-langpack-aa.x86_64
...
```

```
glibc-langpack-zu.x86_64
```


Let's search for our Chinese locale to see if it is available. As you can see the code starts with zh

```
# dnf list glibc-langpack-* | grep zh
glibc-langpack-zh.x86_64
glibc-langpack-lzh.x86_64
```

The command returns us 2 lines but as we have seen that the code was zh\_CN we only have to install the first package.

```
# dnf install glibc-langpack-zh.x86_64 -y
```


When we return now to our frontend we are able to select the Chinese language.



#### Note

If your language is not available in the frontend don't panic it just means that there is no translation or that the translation was not 100% complete. Zabbix is free and relies on the community for its translations so you can help in creating the translation. Go to the page <https://translate.zabbix.com/> and help us to make Zabbix get better. Once the translation is complete the next Zabbix minor patch version should have your language included.

Click next when you are satisfied with the translations available. You will arrive at a screen to verify if all pre-requisites are met. If not fix them first but normally it should be fine and you should be just able to click Next



- Welcome
- Check of pre-requisites
- Configure DB connection
- Settings
- Pre-installation summary
- Install

## Check of pre-requisites

|                                     | Current value | Required |    |
|-------------------------------------|---------------|----------|----|
| PHP version                         | 8.0.30        | 7.4.0    | OK |
| PHP option "memory_limit"           | 128M          | 128M     | OK |
| PHP option "post_max_size"          | 16M           | 16M      | OK |
| PHP option "upload_max_filesize"    | 2M            | 2M       | OK |
| PHP option "max_execution_time"     | 300           | 300      | OK |
| PHP option "max_input_time"         | 300           | 300      | OK |
| PHP databases support               | MySQL         |          | OK |
| PHP bcmath                          | on            |          | OK |
| PHP mbstring                        | on            |          | OK |
| PHP option "mbstring.func_overload" | off           | off      | OK |

[Back](#)
[Next step](#)

Licensed under [GPL v2](#)

The next page will show you a page with the connection parameters for our database.

First you select your DB type 'MySQL' or 'PostgreSQL' and fill in the IP or DNS name of the location of your database server. Use port 3306 for MariaDB/MySQL or 5432 if you used PostgreSQL.

Fill in the correct database name, in our case it was `zabbix`. If you used PostgreSQL then you also need to fill in the correct schema name in our case it was `zabbix_server`

Next line will ask you for the DB users here we created a user `zabbix-web`. Enter it in the correct field and fill in the password that you used for this user.

Make sure the option `Database TLS encryption` is not selected and press `Next step`.

**ZABBIX**

Welcome

Check of pre-requisites

Configure DB connection

Settings

Pre-installation summary

Install

## Configure DB connection

Please create database manually, and set the configuration parameters for connection to this database.  
Press "Next step" button when done.

Database type

MySQL

Database host

xxx.xxx.xxx.xxx

Database port

3306

0 - use default port

Database name

zabbix

Store credentials in

Plain text

HashiCorp Vault

CyberArk Vault

User

zabbix-web

Password

\*\*\*\*\*

Database TLS encryption

☐


Back

Next step

Licensed under [GPL v2](#)

We are almost there. The only thing that rests us to do is give our instance a name, select our timezone and select a default time we like to use.





The screenshot shows the ZABBIX Settings configuration page. On the left is a sidebar with the ZABBIX logo and a list of steps: Welcome, Check of pre-requisites, Configure DB connection, Settings (highlighted), Pre-installation summary, and Install. The main content area is titled 'Settings' and contains three configuration fields: 'Zabbix server name' with a text input containing 'Zabbix Server', 'Default time zone' with a dropdown menu showing '(UTC+01:00) Europe/Brussels', and 'Default theme' with a dropdown menu showing 'Blue'. At the bottom right are 'Back' and 'Next step' buttons. The footer states 'Licensed under GPL v2'.

**ZABBIX**

**Settings**

Zabbix server name


Default time zone

Default theme

[Back](#) [Next step](#)


Licensed under [GPL v2](#)

Press [Next step](#) again you will see a page that tells you that the configuration is successful. Press [Finish](#) to end the configuration.



The screenshot shows the ZABBIX Install completion screen. The sidebar is identical to the previous screen, with 'Install' highlighted. The main content area is titled 'Install' and features a large green message: 'Congratulations! You have successfully installed Zabbix frontend.' Below this, it states 'Configuration file "/>

We are now ready to login :

The image shows the Zabbix login interface. At the top, the ZABBIX logo is displayed in white text on a red rectangular background. Below the logo, the word 'Username' is followed by a text input field. Underneath that, the word 'Password' is followed by another text input field. Below the password field, there is a checkbox that is checked, followed by the text 'Remember me for 30 days'. At the bottom of the form is a blue rectangular button with the text 'Sign in' in white. Below the entire form area, there are two links: 'Help' and 'Support', separated by a small dot.

Login : Admin Password : zabbix

### Installing Zabbix frontend with Apache

ToDo

## 6.3.2 Setting up Zabbix HA

ToDo

## 7. The basics

### 7.1 Zabbix Interface

This chapter is going to cover the basics we need to know when it comes to the Zabbix userinterface and the thing we need to know before we can start to fully dive into our monitoring tool. We will see how the userinterface works how to add a host, groups users, items ... so that we have a good understanding of the basics. This is something that is sometimes missed and can lead to frustrations not knowing why things don't work like we had expected them to work. So even if you are an advanced user it may be usefull to have a look into this chapter.

#### Overview of the interface

With Zabbix 7 the user interface after logging in is a bit changed. Our menu on the left side of the screen has has a small overhaul. Let's dive into it. When we login into our Zabbix setup the first time with our Admin user we see a page like this where we have our `main window` in green our `main menu` marked in red and our `links` marked in yellow.

The main menu can be hidden by collapsing it completely or to reduce it to a set of small icons.

When we click on the button with the 2 arrows to the left:



You will see that the menu collapses to a set of small icons. Pressing ">>" will bring the `main menu` back to it's original state. Pressing the box with the arrow sticking out next to the "<<" button will hide the `main menu` completely.



To get the main menu back it's not too difficult we just look for the button on the left with three horizontal lines and click it. This will bring the menu back and clicking on the box with the arrow again will bring the `main menu` back.

Yet another way to make the screen bigger that is quite useful for monitors in NOK teams for example is the kiosk mode button. This one is however located on the left side of your screen and looks like 4 arrows pointing to every corner of the screen. Pressing this button will remove all the menus and leave only main window to focus on.



When wanting to leave the kiosk mode the button will be changed to 2 arrows pointing to the inside of the screen. Pressing this button will revert us back to the original state.




We can also enter and exit kiosk mode by making use of parameters in our Zabbix url: `/zabbix.php?action=dashboard.view&kiosk=1` - activate kiosk mode or `/zabbix.php?action=dashboard.view&kiosk=0` - activate normal mode



There are many other page parameters we can use. A full list can be found [here](#)

Zabbix also has a global search menu that we can use to find hosts, host groups and templates.



If we look in the search box for `server` you will see that we get an overview of all templates, host groups and hosts with the name `server` in it.

Search: server?

Hosts

| Host          | IP        | DNS | Monitoring   | Configuration  |
|---------------|-----------|-----|--|--|
| Zabbix server | 127.0.0.1 |     | <a href="#">Latest data</a> <a href="#">Problems</a> <a href="#">Graphs</a> <a href="#">Dashboards</a> <a href="#">Web</a> | <a href="#">Items 99</a> <a href="#">Triggers 56</a> <a href="#">Graphs 19</a> <a href="#">Discovery 4</a> <a href="#">Web</a> |

Displaying 1 of 1 found

Host groups

| Host group     | Monitoring   | Configuration           |
|----------------|--|-------------------------|
| Linux servers  | <a href="#">Latest data</a> <a href="#">Problems</a> <a href="#">Web</a> | <a href="#">Hosts</a>   |
| Zabbix servers | <a href="#">Latest data</a> <a href="#">Problems</a> <a href="#">Web</a> | <a href="#">Hosts 1</a> |

Displaying 2 of 2 found

Templates

| Template  | Configuration   |
|---|---|
| AWS ECS Serverless Cluster by HTTP                    | <a href="#">Items 15</a> <a href="#">Triggers 4</a> <a href="#">Graphs 4</a> <a href="#">Dashboards 1</a> <a href="#">Discovery 2</a> <a href="#">Web</a>   |
| Azure Microsoft SQL Serverless Database by HTTP       | <a href="#">Items 27</a> <a href="#">Triggers 7</a> <a href="#">Graphs 3</a> <a href="#">Dashboards</a> <a href="#">Discovery</a> <a href="#">Web</a>       |
| Azure MySQL Flexible Server by HTTP                   | <a href="#">Items 20</a> <a href="#">Triggers 8</a> <a href="#">Graphs 3</a> <a href="#">Dashboards</a> <a href="#">Discovery</a> <a href="#">Web</a>       |
| Azure MySQL Single Server by HTTP                     | <a href="#">Items 19</a> <a href="#">Triggers 9</a> <a href="#">Graphs 4</a> <a href="#">Dashboards</a> <a href="#">Discovery</a> <a href="#">Web</a>       |
| Azure PostgreSQL Flexible Server by HTTP              | <a href="#">Items 25</a> <a href="#">Triggers 8</a> <a href="#">Graphs 3</a> <a href="#">Dashboards</a> <a href="#">Discovery</a> <a href="#">Web</a>       |
| Azure PostgreSQL Single Server by HTTP                | <a href="#">Items 20</a> <a href="#">Triggers 8</a> <a href="#">Graphs 4</a> <a href="#">Dashboards</a> <a href="#">Discovery</a> <a href="#">Web</a>       |
| Control-M server by HTTP                              | <a href="#">Items 9</a> <a href="#">Triggers 4</a> <a href="#">Graphs 2</a> <a href="#">Dashboards 1</a> <a href="#">Discovery 2</a> <a href="#">Web</a>    |
| HashiCorp Nomad Server by HTTP                        | <a href="#">Items 128</a> <a href="#">Triggers 11</a> <a href="#">Graphs 4</a> <a href="#">Dashboards 3</a> <a href="#">Discovery</a> <a href="#">Web</a>   |
| Kubernetes API server by HTTP                         | <a href="#">Items 23</a> <a href="#">Triggers 2</a> <a href="#">Graphs 1</a> <a href="#">Dashboards 1</a> <a href="#">Discovery 10</a> <a href="#">Web</a>  |
| Microsoft Exchange Server 2016 by Zabbix agent        | <a href="#">Items 9</a> <a href="#">Triggers</a> <a href="#">Graphs 1</a> <a href="#">Dashboards</a> <a href="#">Discovery 3</a> <a href="#">Web</a>        |
| Microsoft Exchange Server 2016 by Zabbix agent active | <a href="#">Items 9</a> <a href="#">Triggers</a> <a href="#">Graphs 1</a> <a href="#">Dashboards</a> <a href="#">Discovery 3</a> <a href="#">Web</a>        |
| Remote Zabbix server health                           | <a href="#">Items 57</a> <a href="#">Triggers 43</a> <a href="#">Graphs 11</a> <a href="#">Dashboards 2</a> <a href="#">Discovery 1</a> <a href="#">Web</a> |
| WildFly Server by JMX                                 | <a href="#">Items 17</a> <a href="#">Triggers 5</a> <a href="#">Graphs 1</a> <a href="#">Dashboards</a> <a href="#">Discovery 4</a> <a href="#">Web</a>     |
| Zabbix server health                                  | <a href="#">Items 57</a> <a href="#">Triggers 42</a> <a href="#">Graphs 11</a> <a href="#">Dashboards 2</a> <a href="#">Discovery 1</a> <a href="#">Web</a> |

Displaying 14 of 14 found

Template groups

| Template group            | Configuration                |
|---------------------------|------------------------------|
| Templates/Server hardware | <a href="#">Templates 22</a> |

Displaying 1 of 1 found

7.1.1 Main menu

Our main menu on the left consists of a few sections, 9 to be exact:


| Menu Name       | Details   |
|-----------------|---|
| Dashboards      | Contains an overview of all the dashboards we have access to.                                     |
| Monitoring      | Shows us the hosts, problems, latest data, maps, ...  |
| Services        | An overview of all the Services and SLA settings.   |
| Inventory       | An overview of our collected inventory data.  |
| Reports         | Shows us the system information, scheduled reports, audit logs, action logs, etc .                |
| Data collection | Contains all things related to collecting data like hosts, templates, maintenance, discovery, ... |
| Alert           | The configuration of our media types, scripts and actions   |
| Users           | User configuration like user roles, user groups, authentication, API tokens, ...                  |
| Administration  | The administration part containing all global settings, housekeeper, proxies, queue, ...          |

## 7.1.2 Links menu

Our last part the `links` part contain a set of useful links that we can use:

| Menu name     | Details   |
|---------------|---|
| Support       | This brings us to the technical support page that you can buy from Zabbix. Remember that your local partner is also able to sell these contracts and can help you in your own language. <a href="#">Your local distributors</a> |
| Integrations  | The official zabbix <a href="#">integration page</a>  |
| Help          | The link to the documentation of your <a href="#">Zabbix version</a>  |
| User settings | The user profile settings.  |
| Sign out      | Log out of the current session.   |

There are still a few buttons that we need to cover on the right side of our screen



The edit button allows us to change our dashboard. This is something we will cover later. On the far left side there is a "?" this will bring you to the Zabbix documentation page that explains everything about the dashboard. The button on the right side with the 3 horizontal lines is the one to share, rename, delete, ... our dashboards.

| System information <span>⚙️ ...</span>             |             |                 |
|--|-------------|-----------------|
| Parameter  | Value       | Details         |
| Zabbix server is running                           | Yes         | localhost:10051 |
| Zabbix server version                              | 7.0.0alpha8 |                 |
| Zabbix frontend version                            | 7.0.0alpha8 |                 |
| Number of hosts (enabled/disabled)                 | 1           | 1 / 0           |
| Number of templates                                | 352         |                 |
| Number of items (enabled/disabled/not supported)   | 99          | 90 / 0 / 9      |
| Number of triggers (enabled/disabled [problem/ok]) | 56          | 56 / 0 [1 / 55] |
| Number of users (online)                           | 2           | 1               |
| Required server performance, new values per second | 1.46        |                 |
| High availability cluster                          | Disabled    |                 |

### 7.1.3 System Information

There is also a box on the dashboard called `System Information`. This widget will show you the current System status of your Zabbix setup. Let's go over the different lines of information as they are important to understand.

| Parameter   | Value   | Details  |
|---|---|--|
| Zabbix server is running                          | This gives us the status of our zabbix server if it is running yes or no and if it is running on our localhost or another IP and on what port the zabbix server is listening. If no trapper is listening the rest of the information can not be displayed | IP and port of the Zabbix server   |
| Zabbix server version                             | This shows us the version of the <code>zabbix_server</code> so the version you see at the bottom of your screen is the one from the Zabbix frontend and can be different but should be in the same major version.   | Version Number   |
| Zabbix frontend version                           | This is the version of the frontend and should match with what you see at the bottom of your screen.  | Version Number   |
| Number of hosts (enabled/disabled)                | The total number of hosts configured on our system  | How many of those are enabled and disabled   |
| Number of templates                               | The number of templates installed on our Zabbix server.   |  |
| Number of items (enabled/disabled/not supported)  | This line shows us the number of items we have configured in total in this case 99  | 90 are enabled and 0 are disabled but 9 of them are unsupported. This last number is important as those are items not working. We will look into this later why it happens and how to fix it. For now remember that a high number of unsupported items is not a good idea.                 |
| Number of triggers (Enabled/disabled[problem/ok]) | The number of triggers configured   | Number of enabled and disabled triggers. Just as with items we also see if there are triggers that are in a problem state or ok state. A trigger in a problem state is a non working trigger something we need to monitor and fix. We will cover this also later.                          |
| Number of users (online)                          | Here we see the number of users that are configured on our system   | The number of users currently online.  |
| Required server performance, nvps                 | The number of new values per second that Zabbix will process per second.  | This is just an estimated number as some values we get are unknown so the real value is probably higher. So we can have some indication about how many IOPS we need and how busy our database is. A better indication is probably the internal item <code>zabbix[wcache,values,all]</code> |
| High availability cluster                         | It will show us if we are running on a Zabbix HA cluster or not   | Failover delay once HA is activated  |



System information may display some additional warnings like when your database doesn't have the correct character set or collation UTF-8. Also when the database you used is lower or higher than the recommended version or when there are misconfigurations on housekeeper or TimescaleDB. Another warning you can see is about database history tables that aren't upgraded or primary keys that have not been set. This is possible if you are coming from an older version before Zabbix 6 and never did the upgrade.

## 7.1.4 The main menu explained

It's important to know that we have so far seen our dashboard with the Admin user and that this user is a `Zabbix Super Admin` user. This means that the user has no restrictions. Zabbix works with 3 different levels of users we have the regular users, Zabbix Admin and Zabbix Super Admin users. Let's have a look

- A `Zabbix User` will only see the red part of our `main menu` and will only be able to see our collected data.
- A `Zabbix Admin` will see the red part and the yellow part of the `main menu` and is able to change our configuration.
- A `Zabbix Super Admin` will see the complete `main menu` and so is able to change the configuration and all the global settings.
- Problems: This page will give us an overview of all the problems. With filter we can look at recent problems past problems and problems that are active now. There are many more filters for drill down more.
- Hosts: This will give us a quick overview page with whats happening on our hosts and allows us to quickly go to the latest data, graphs and dashboards.
- Latest data: This page I probably use the most, it shows us all the information collected from all our hosts.
- Maps: The location where we can create map that are an overview of our IT infrastructure very useful to get a high level overview of the network.
- Discovery: When we run a network discovery this is the place where we can find the results.




- Services: This page will give us a high level overview of all services configured in Zabbix.
- SLA: An overview of all the SLAs configured in Zabbix.
- SLA Report: Here we can watch all SLA reports based on filters.

- Overview: A place where we can watch all our inventory data that we have retrieved from our hosts.
- Hosts: Here we can filter by host and watch all inventory data for the hosts we have selected.

- System information: System information is a summary of key Zabbix server and system data.
- Scheduled reports: The place where we can schedule our reports, a pdf of the dashboard that will be sent at a specified time and date.
- Availability report: Another page I visit a lot here we have our top list with triggers that have been in a nok state.
- Top 100 triggers: Another page I visit a lot here we have our top list with triggers that have been in a nok state.
- Audit log: An overview of the user activity that happened on our system. Useful if we want to know who did what and when.
- Action log: A detailed overview of our actions can be found here. What mail was sent to who and when ...?
- Notifications: A detailed overview of the number of notifications sent to each user.

- Hosts:
- Maintenance:
- Event correlation:
- Discovery:






More information can be found in the online Zabbix documentation [here](#)

## 7.2 Zabbix Users

Now that we know how the Zabbix dashboard is build up our first task will be to create a user. In case you missed it the standard Zabbix (yes the capital Z here is eeded to login.) user is Admin and has the password zabbix so we need to change this ASAP. The most confusing part is probably that the user Admin in zabbix is actually a 'super admin' but more about that later.

### 7.2.1 Changing the Zabbix super admin password

In our menu on the right side of the screen click the 'Users' section and then choose "users". As you see here in the screenshot.



You will now see a list of all the users that are created on the system when installing a new Zabbix instance. Here you will always see a list of all users that are configured on the system.

The screenshot shows the Zabbix Users management page. The left sidebar contains the navigation menu with 'Users' selected. The main area has a form to create or edit a user, with fields for Username, Name, Last name, User roles, and User groups. Below the form is a table listing existing users: Admin, Zabbix, and guest. The Admin user is highlighted.

| Username | Name   | Last name     | User role        | Groups                | Is online?                   | Login | Frontend access | API access | Debug mode | Status   | Provisioned | Info |
|----------|--------|---------------|------------------|-----------------------|------------------------------|-------|-----------------|------------|------------|----------|-------------|------|
| Admin    | Zabbix | Administrator | Super admin role | Zabbix administrators | Yes (2024-02-03 12:54:17 PM) | Ok    | System default  | Enabled    | Disabled   | Enabled  |             |      |
| guest    |        |               | Guest role       | Disabled, Guests      | No                           | Ok    | Internal        | Disabled   | Disabled   | Disabled |             |      |

To change the password do the following steps - Click user "Admin" - Click on the button "Change password" - Fill in the current password "zabbix" - Fill in the new password twice and press "Update" at the bottom of the page.

## 7.2.2 Zabbix User types

Before we create new users it's important to know that Zabbix has 3 user types that are built-in.

- Zabbix user -> This is a normal user that only has read only permissions if given. So there are no permissions assigned by default.
- Zabbix admin -> A user with read/write permissions. Just like the Zabbix user there are not permissions by default
- Zabbix super admin -> A user with read/write permissions that can't be revoked

Besides these differences these users also have different accesses rights in our menu. Let's have a closer look.

- A normal user will only see a part of our menu on the left. Also some sub sections of the menu will not be visible. An `Admin` user will have more rights than a regular user and will be able to make some configuration changes in Zabbix. A `Super Admin` user will have unlimited right and see every part of the menu. The only way to limit a `Super Admin` will be by making use of roles. Something we cover later.
- An `Admin` user will have more rights than a regular user and will be able to make some configuration changes in Zabbix.
- A `Super Admin` can access all parts of the menu. The user will have read/write access to all host and template groups. Access can't be revoked by denying access to groups like with a normal admin.

This table gives an overview of all the permissions a Zabbix user, admin and super admin have:

|                            | Zabbix User | Zabbix Admin | Zabbix Super Admin |
|----------------------------|-------------|--------------|--------------------|
| Dashboards                 | ✓           | ✓            | ✓                  |
| Monitoring                 | ✓           | ✓            | ✓                  |
| - Problems                 | ✓           | ✓            | ✓                  |
| - Hosts                    | ✓           | ✓            | ✓                  |
| - Latest data              | ✓           | ✓            | ✓                  |
| - Maps                     | ✓           | ✓            | ✓                  |
| - Discovery                | ✗           | ✓            | ✓                  |
| Services                   | ✓           | ✓            | ✓                  |
| - Services                 | ✓           | ✓            | ✓                  |
| - SLA                      | ✗           | ✓            | ✓                  |
| - SLA Report               | ✓           | ✓            | ✓                  |
| Inventory                  | ✓           | ✓            | ✓                  |
| - Overview                 | ✓           | ✓            | ✓                  |
| - Hosts                    | ✓           | ✓            | ✓                  |
| Reports                    | ✓           | ✓            | ✓                  |
| - System information       | ✗           | ✗            | ✓                  |
| - Scheduled reports        | ✗           | ✓            | ✓                  |
| - Availability report      | ✓           | ✓            | ✓                  |
| - Triggers top 100         | ✓           | ✓            | ✓                  |
| - Audit log                | ✗           | ✗            | ✓                  |
| - Action log               | ✗           | ✗            | ✓                  |
| - Notifications            | ✗           | ✓            | ✓                  |
| Data Collection            | ✗           | ✓            | ✓                  |
| - Template groups          | ✗           | ✓            | ✓                  |
| - Host groups              | ✗           | ✓            | ✓                  |
| - Templates                | ✗           | ✓            | ✓                  |
| - Hosts                    | ✗           | ✓            | ✓                  |
| - Maintenance              | ✗           | ✓            | ✓                  |
| - Event correlation        | ✗           | ✗            | ✓                  |
| - Discovery                | ✗           | ✓            | ✓                  |
| Alerts                     | ✗           | ✓            | ✓                  |
| - Trigger actions          | ✗           | ✓            | ✓                  |
| - Service actions          | ✗           | ✓            | ✓                  |
| - Autoregistration actions | ✗           | ✓            | ✓                  |
| - Internal actions         | ✗           | ✓            | ✓                  |
| - Media types              | ✗           | ✗            | ✓                  |

|                  | Zabbix User | Zabbix Admin | Zabbix Super Admin |
|------------------|-------------|--------------|--------------------|
| - Scripts        | ✗           | ✗            | ✓                  |
| Users            | ✗           | ✗            | ✓                  |
| - User groups    | ✗           | ✗            | ✓                  |
| - User roles     | ✗           | ✗            | ✓                  |
| - Users          | ✗           | ✗            | ✓                  |
| - Api tokens     | ✗           | ✗            | ✓                  |
| - Authentication | ✗           | ✗            | ✓                  |
| Administration   | ✗           | ✗            | ✓                  |
| - General        | ✗           | ✗            | ✓                  |
| - Audit log      | ✗           | ✗            | ✓                  |
| - Housekeeping   | ✗           | ✗            | ✓                  |
| - Proxies        | ✗           | ✗            | ✓                  |
| - Macros         | ✗           | ✗            | ✓                  |
| - Queue          | ✗           | ✗            | ✓                  |

- An `Admin` user will have more rights than a regular user and will be able to make some configuration changes in Zabbix.
- A `Super Admin` can access all parts of the menu. The user will have read/write access to all host and template groups. Access can't be revoked by denying access to groups like with a normal admin.

## 7.2.3 User Roles

User roles have been in Zabbix since version 5.2 and make our live more easy by allowing us to make some custom adjustments to the standard defined user types in Zabbix.



### Warning

Be aware the no permissions can be added to user roles only permissions can be revoked.

## 7.2.4 Creating a new User in Zabbix

So now that we are in the users section of Zabbix it's probably a good time to create a new user for our system. If you skipped previous step go to the menu `Users` -> `Users`.

Click on the top right on `Create user` and fill in the details of your new users. You will see that some fields have red asterisks in front of them like Username and Password, ... this means that those fields are mandatory to fill in.

## Users

User Media Permissions

\* Username

Name

Last name

Groups  Select

\* Password 

\* Password (once again)

Password is not mandatory for non internal authentication type.

Language  

Time zone

Theme

Auto-login ☐

Auto-logout ☐

\* Refresh

\* Rows per page

URL (after login)

Add

Cancel

| Parameter         | Description   |
|-------------------|---|
| Username          | A unique name that will be used as username when we login   |
| Name              | The users firstname this field is optional visible in acknowledgment information and notification recipient information if set.   |
| Last name         | Users last name. Optional, this field is optional visible in acknowledgment information and notification recipient information if set.  |
| Groups            | Select what group the user will belong to. Atleast 1 group needs to be selected. This feeld will auto complete or you can press the "Select" button at the end of the field.  |
| Passowrd          | There are 2 password fields they can only be used for internal authentication but more about this later. If the user has the Super admin role then clicking on the Change password button opens an additional field to entering the current (old) password. On a successful password change, the user for which the password was changed will be logged out of all active sessions. |
| Language          | Language of the frontend. The php gettext extension is required for the translations to work. And the language needs to be configured on the system. See the chapter "Installing Zabbix" in case you forgot.  |
| Time zone         | Select the time zone per user or use the default timezone that is configured on the Zabbix server.  |
| Theme             | Here users can select their own look and feel by choosing one of the 4 themes provided by Zabbix or another custom made theme. Default will switch to the default theme chosen by the admin.  |
| Auto-login        | Check this box so that the user will be remembered for 30 days. The browser must accept cookies for this to work.   |
| Auto-logout       | Checking this box makes sure the user gets logged out automatically, after the set amount of seconds (minimum 90 seconds, maximum 1 day).   |
|                   | Time suffixes are supported, e.g. 90s, 5m, 2h, 1d.  |
|                   | Note that this option will not work if :  |
|                   | * If the "Show warning if Zabbix server is down" global configuration option is enabled and Zabbix frontend is kept open.   |
|                   | * When Monitoring menu pages perform background information refreshes.  |
|                   | * If logging in with the Remember me for 30 days option checked.  |
| Refresh           | Set the refresh rate used for graphs, plain text data, etc. Can be set to 0 to disable. Time suffixes are supported. Ex: 90s, 5m, 1h.   |
| Rows per page     | Define how many rows per page will be displayed in lists.   |
| URL (after login) | You can make Zabbix transfer the user to a specific URL after successful login. This can be useful for monitors in NOC team for example so you arrive on a specific dashboard that is maximised.  |
|                   | The URL can be the full url or only the relative url like : zabbix.php?action=host.list   |

## User Media

The tab "Media" contains a list of all media that is defined for out user. Media is used for sending notifications to the user. We can click the "Add" button.

## Users

User
Media 2
Permissions

Media

| Type         | Send to                  | When active     | Use if severity | Status  | Action                                      |
|--------------|--------------------------|-----------------|-----------------|---------|---|
| Email        | sales@open-future.be     | 1-5,00:00-24:00 | N I W A H D     | Enabled | <a href="#">Edit</a> <a href="#">Remove</a> |
| Email (HTML) | technical@open-future.be | 1-7,00:00-24:00 | N I W A H D     | Enabled | <a href="#">Edit</a> <a href="#">Remove</a> |

Add

Update
Delete
Cancel



Adding the media here is not enough to receive notification we also need to configure our media properly and we still need to configure Actions as well. When pressing the "Add" button we get a popup where we can select some information.

Media

Type

Email

\* Send to

sales@open-future.be

Remove

Add

\* When active

1-7,00:00-24:00

Use if severity

☒ Not classified
 ☒ Information
 ☒ Warning
 ☒ Average
 ☒ High
 ☒ Disaster

Enabled

☒

Add

Cancel

| Parameter       | Description   |
|-----------------|---|
| Type            | A drop down list with the names of all media types. When a media type is disabled it will be in red.  |
| Send to         | Here we can provide contact information. For an email media type it is possible to add several addresses by clicking on "Add" below the address field. In this case, the notification will be sent to all email addresses provided. It's also possible to specify recipient name in the Send to field of the email recipient in a format 'Recipient name <address1@company.com>'. Note that if a recipient name is provided, an email address should be wrapped in angle brackets (<>). UTF-8 characters in the name are supported, quoted pairs and comments are not. For example: John Doe <manager@open-future.com> and manager@nycdatacenter.com are both valid formats. Incorrect examples: John Doe manager@open-future.com, % "Zabbix\@\"<H(comment)Q\>" zabbix@company.com %%%. |
| when active     | The time when media will be active from monday till sunday, 1-7 and the time from 00:00 till 24:00 for example only in weekends from 6 in the morning till 5 in the evening: 6-7,06-17:00i. This is based on the user his timezone  |
| Use if severity | A list of checkboxes from the severities you would like to receive notifications from. Selected severities will be displayed in color. !! Read the warning below!!  |
| Status          | Status of the media we have selected either enabled or disabled ( in use or not )   |

### Warning

When selecting the different severities be aware that you have to select "Not classified" if you want to receive notifications about non trigger events like internal events. For more info check out : [Event sources](#). This is something that is not obvious and Zabbix documentation could be better in explaining this imho.

## 7.3 Zabbix hosts

To understand how Zabbix works it's important to know that **Host** in Zabbix are a reference to anything we would like to monitor it can be a physical host, a virtual machine, an application a device or even just a dummy host used to calculate data from existing other hosts into something new.

It's probably one of the first tasks that we will do as an Admin when we first login to Zabbix because we need a host if we would like to monitor some metrics. It's however important to know that hosts cannot be created without them being in a hostgroup.

With this said let's create our first host.

Let's go to the menu on our **Left** and select Data Collection -> Hosts. We see that there is already a host configured and that the availability icon is "RED" don't worry about it this is normal we have no Zabbix agent installed or configured.

To Add a new host to our system we press **Create host** this button can be found in the upper right corner of our screen.

The screenshot displays the Zabbix web interface for managing hosts. On the left, the sidebar menu has 'Data collection' and 'Hosts' selected. The main content area is titled 'Hosts' and features a 'Create host' button in the top right corner, indicated by a red arrow. Below the header, there are search and filter options for host groups, templates, and status. A form allows adding a new host with fields for Name, DNS, IP, and Port. Below the form is a table of existing hosts. The table has columns for Name, Items, Triggers, Graphs, Discovery, Web, Interface, Proxy, Templates, Status, Availability, Agent encryption, Info, and Tags. One host is listed: 'Zabbix server' with 99 items, 56 triggers, 19 graphs, 4 discovery items, and a 'Web' interface at 127.0.0.1:10050. Its status is 'Enabled' and its availability is 'zBX' (indicated by a red icon). The bottom of the table shows '0 selected' and buttons for 'Enable', 'Disable', 'Export', 'Mass update', and 'Delete'.

We now get a modal form where we need to fill in some information about our host. The fields marked with a **red** asterisk "\*" are the fields that are mandatory.

New host

Host

IPMI

Tags

Macros

Inventory

Encryption

Value mapping

\* Host name

Visible name

Templates

type here to search

Select

\* Host groups

type here to search

Select

Interfaces

No interfaces are defined.

Add

Description

Monitored by proxy

(no proxy)

Enabled

☒

Add

Cancel

| Parameter                 | Description  |
|---------------------------|--|
| <b>Host name</b>          | Here we need to enter the <b>Host name</b> of our machine we like to add. The name can contain alphanumeric, spaces, dots, dashes and underscores. HOWEVER you are not allowed to use leading and trailing spaces. The <b>Host name</b> in the frontend is what we need later for the configuration of our Zabbix agent so make sure you remember it.  |
| <b>Visible name</b>       | The <b>host name</b> as we have seen is needed to configure our <b>Zabbix agent</b> . So in case you like to give it a unique name that is random generated etc you can add a visible name here. This name will then be used in the frontend instead of what we call the technical name <b>host name</b> . This name has support for UTF-8 so special characters are supported. This name will be used in all the places like maps, latest data, inventory , ... |
| <b>Templates</b>          | Templates are like blueprints that we can use on our hosts to add items, triggers , .... We explain more about it in the topic <b>Zabbix templates</b> . You can start typing the name of the template and Zabbix will start to show a list with matches or you can press the ``Select`` box and choose one from the list.   |
| <b>Host groups</b>        | Every host needs to be in at least 1 ``host group``. This is because permissions are set on host groups. You can type the name of the <b>host group</b> and a list of matching groups will start to appear. Another way is to select a host group from an existing list by pressing the <b>Select</b> button. Or you can create a new group by just typing the name and pressing on the box that shows the name of the group you typed with (new) behind it      |
| <b>Interfaces</b>         | Zabbix supports several host interfaces like Zabbix agent, SNMP, JMX and IPMI. By default when we create a host no interface is added. To add an interface press <b>Add</b> and fill in the needed info like IP or DNS depending on the host interface chosen. When an interface is in use (items created that use the interface) then the interface cannot be removed.  |
| <b>Description</b>        | A place to enter a short description about our host.   |
| <b>Monitored by proxy</b> | If we have proxies configured we can select here if we like to monitor our host by a proxy.  |
| <b>Enabled</b>            | Mark the checkbox to enable the host. This will make it monitored by Zabbix. When unchecked the host will not be monitored.  |

### 7.3.1 Host menu details

Before we add a host ourselves there are a few things we need to know first. When we click on a host that we already configured before there are a few things that we notice. First of all we see a **blue** line under **Host**. This means that we are on the current **tab** of the host page. As you can see there are multiple tabs that we can click on like IPMI, Tags, Macros, ...

## Host

Host IPMI Tags **Macros 2** Inventory Encryption ● Value mapping

The next thing we see is that next to the tab `Macros` there is a number 2. This is because there are 2 macros configured in the macro tab. So when we add information in tabs like macros or tags ... Zabbix will show how many items we have added on these tabs by showing next to the tab name the number.

When looking at the `encryption` tab we notice the green dot. This shows us that an option on the tab has been activated. Now that we know this lets get a quick overview of every tab and see what it does.

### IPMI

So looking at the tab `IPMI` there are a few thing we need to fill in when working with an IPMI interface. IPMI stands for Intelligent Platform Management Interface and is basically a set of standards to manage hardware platforms. In short it allows us to monitor and manage ours servers hardware even if the server is not turned on yet. IPMI is better known as ILO on HP servers and DRAC on Dell servers.

| Parameter                       | Description  |
|---------------------------------|--|
| <b>Authentication algorithm</b> | Select the authentication algorithm that we have configured on our IPMI server this can be Default, none, MD2, MD5, Straight, OEM, RMCP+ |
| <b>Privelege level</b>          | Here we select the privelege level: Callback, User, Operator, Admin or OEM.  |
| <b>Username</b>                 | The user for authentication that was created on the host. User Macros can be used  |
| <b>Password</b>                 | The password for our user on the host. User macros can be used.  |

??? Note+ We will cover IPMI in more detail later in the Chapter [IPMI Monitoring](#)

### Tags

## 7.4 Interfaces

---

## 7.5 Host groups

---

## 7.6 templates

---

## 7.7 Items

---



## 7.8 Zabbix triggers

---

## 7.9 Macros

---

## 7.10 Data Flow

---

### 7.10.1 Data Collection

---

### 7.10.2 Simple Checks

---

## 7.11 Zabbix Agent

---

### 7.11.1 Zabbix agent Linux

---

### 7.11.2 Zabbix agent windows

---

## 8. Problem detection

---

### 8.1 Triggers

---

## 9. Taking action when problems come

---

### 9.1 Event based Actions

---

## 10. Managing permissions

---

### 10.1 Managing Permissions

---

## 11. Visualising Problems

---

### 11.1 Visualising our problems

---



## 12. Automating configuration

---

### 12.1 Automating configuration

---

## 13. VMWare monitoring

---

### 13.1 VMWare monitoring

---

## 14. Monitoring websites

---

### 14.1 Monitoring websites

---

## 15. Monitoring SNMP, IPMI and JAVA

---

### 15.1 Monitoring SNMP,IPMI and JAVA

---

## 15.2 JAVA monitoring

---

## 15.3 IPMI monitoring

---

## 16. Monitoring with Proxies

---

### 16.1 Monitoring with Proxies

---

## 17. Securing Zabbix

---

### 17.1 Securing Zabbix

---



## 18. Maintaining Zabbix

---

### 18.1 Maintaining Zabbix

---

## 19. Monitoring Windows

---

### 19.1 Monitoring Windows

---

## 20. Zabbix API

---

### 20.1 Zabbix API

---