

```
#include <stdio.h>
```

```
int main() {
```

```
    FILE *fp;
```

```
    int mark, count, i;
```

```
    printf("BHARGAV GUJJAR \n");
```

```
    fp = fopen("marks.dat", "wb");
```

```
    if (fp == NULL) {
```

```
        printf("Error opening file for writing.\n");
```

```
        return 1;
```

```
    }
```

```
    printf("Enter the number of students: ");
```

```
    scanf("%d", &count);
```

```
    printf("Enter marks for %d students:\n", count);
```

```
    for (i = 0; i < count; i++) {
```

```
        printf("Mark %d: ", i + 1);
```

```
        scanf("%d", &mark);
```

```
        putw(mark, fp);
```

```
    }
```

```
    fclose(fp);
```

```
    printf("\nMarks stored successfully.\n");
```

```
    fp = fopen("marks.dat", "rb");
```

```
    if (fp == NULL) {
```

```
        printf("Error opening file for reading.\n");
```

```
        return 1;
```

```
    }
```

```
printf("\nRetrieved marks:\n");  
while (1) {  
    mark = getw(fp);  
    if (feof(fp)) {  
        break;  
    }  
    printf("%d\n", mark);  
}  
  
fclose(fp);  
return 0;  
}
```