

**Web Basics –
HTML 5**

Lesson 4. List

Lesson Objectives

- In this lesson, you will learn about:
 - Numbered List
 - Bulleted List



HTML provides support for ordered, unordered and other types of lists

4.1: Numbered List

Numbered List

- List of items can be numbered or ordered is called numbered/ordered List
- Tags can be used for creating ordered list are:
 - ``
 - ``
- `` tag
 - Defines a list item.
 - Should be used as a child tag of either `` or `` tag.
- `` tag
 - `` defines an ordered list.
 - An ordered list can be numerical or alphabetical.
 - Attributes in `` tag are
 - start
 - type



Copyright © Capgemini 2015. All Rights Reserved 3

Numbered List:

HTML enables you to create a numbered, or ordered list that will automatically generate numbers in front of each item in the list.

The number placed in front of an item depends on the location of the item in the list.

At the beginning of the list, place the `` (for ordered list) tag. At the end of the list, place the `` tag and in front of each item in the list, place the `` (for list item) tag.

End tag for `` is optional.

4.1: Numbered List

Example

■ Example (Code)

```
<!DOCTYPE html>
<html>
  <body>
    <h2>My favorite cricket
teams</h2>
        <ol>
          <li>INDIA</li>
          <li>SRILANKA</li>
        </ol>
      </body>
</html>
```

Output

My favorite cricket teams

1. INDIA
2. SRILANKA

4.1: Numbered List

Attributes in tag

- Type Attribute:
 - Specifies the kind of marked to use in the list
 - Valid values for the Type Attribute
 - A-Uppercase letters
 - a-Lowercase letters
 - I-Uppercase Roman letters
 - i-Lowercase Roman letters
 - 1-Standard numbers, default
- Start Attribute
 - Specifies the start value of an ordered list



Copyright © Capgemini 2015. All Rights Reserved 5

You can even select the type of numbering system to be used with the type attribute. For example:

A-Uppercase letters: `<ol type=A>`

a-Lowercase letters: `<ol type=a>`

I-Uppercase Roman letters: `<ol type=I>`

i-Lowercase Roman letters: `<ol type=i>`

1-Standard numbers: `<ol type=1>`

Type attribute enables you to alter the style of numbers used in the lists, whereas start attribute sets the starting number of the list.

To start an ordered list at a number other than 1, place the start attribute on the `` tag at the beginning of the list.

You can also use the VALUE attribute within `` tag to change the numbering sequence within a list.

4.1: Numbered List

Example

Example:

```
<!DOCTYPE html>
<html>
  <body>
    <h2>My favorite cricket teams</h2>
    <ol start="2" type="a">
      <li>INDIA
      <li>SRILANKA
      <li>PAKISTAN
      <li>AUSTRALIA
      <li>SOUTH AFRICA
    </ol>
  </body>
</html>
```

Output

My favorite cricket teams

- b. INDIA
- c. SRILANKA
- d. PAKISTAN
- e. AUSTRALIA
- f. SOUTH AFRICA

4.1: Numbered List

Demo

▪ NumberedList.html



Capgemini
CONSULTING TECHNOLOGY OUTSOURCING

Copyright © Capgemini 2015. All Rights Reserved 7

4.2: Bulleted List

Bulleted List

- List of items prefixed with bullets is called Bulleted /Unordered List
- `` tag
 - `` defines an unordered list.
 - An unordered list items will be marked with bullets (small black circles).
- Example

```
<!DOCTYPE html>
<html>
  <body>

    <h2>My favorite cricket teams</h2>
    <ul>

      <li>INDIA</li>
      <li>SRILANKA</li>

    </ul>

  </body>
</html>
```

Output

My favorite cricket teams

- INDIA
- SRILANKA

To create a bulleted list use the ``(unordered list) tag at the opening of the list and `` at the end of the list.

4.2: Bulleted List

Attributes in tag

■ Style Attribute:

- Can be used in tag to define the style of the marker.

Style Attribute Value	Description
list-style-type:disc	The list items will be marked with bullets (default)
list-style-type:circle	The list items will be marked with circles
list-style-type:square	The list items will be marked with squares
list-style-type:none	The list items will not be marked
list-style-image: url('logo.gif');	The list items will be marked with an image

■ Example

- <UL style="list-style-type:circle"> will be used to prefix unordered list of items with square.

4.2: Bulleted List

Example (Code):

■ Example

```
<!DOCTYPE html>
<html>
  <body>
    <h2>My favorite cricket teams</h2>
    <ul style="list-style-type:square">
      <li>INDIA</li>
      <li>SRILANKA</li>
    </ul>
  </body>
</html>
```

Output

My favorite cricket teams

- INDIA
- SRILANKA

4.2 Bulleted List


Demo


- BulletedList.html



Lab

■ Lab 3





Capgemini

CONSULTING TECHNOLOGY OUTSOURCING

Copyright © Capgemini 2015. All Rights Reserved

12

Lesson Summary

- In this lesson, you have learnt about:
 - Types of available list items
 - Create bulleted, numbered and glossary listed items



Review Question: Questions

- Question 1: Which tag is used at the beginning of an Ordered List
 - ``
 - ``
 - ``
- Question 2: To create a bulleted list `` tag is used
 - True/ False
- Question 3: _____ attribute is used to modify the appearance of bullets



Review Question: Match the Following

1. <dd>	a. 1-Standard numbers
2. <dt>	b. Square Form
3. <ol type=I>	c. A-Uppercase letters
4. <ol type=A>	d. I-Uppercase Roman letters
5. <ol type=1>	e. Data Definition
6. <ul style="list-style-type:circle">	f. Data Term

