

iOS - MAX方法对照表

一、初始化

MAX	BAG
<pre>ALSdkInitializationConfiguration *initConfig = [ALSdkInitializationConfiguration configurationWithSdkKey:@"«SDK-key»" builderBlock:^(ALSdkInitializationConfigurationBuil der *builder) { builder.mediationProvider = ALMediationProviderMAX; }]; // Initialize the SDK with the configuration [[ALSdk shared] initializeWithConfiguration: initConfig completionHandler:^(ALSdkConfiguration *sdkConfig) { // Start loading ads }];</pre>	<pre>[[BidAggregatorSDK sharedInstance] startWithData:data delegate:self]; #pragma mark - BAGSDKDelegate - (void)allPlatformFinish:(NSError *)error { //所有平台初始化结束 }</pre>

二、开屏广告

	MAX	BAG
创建对象	<pre>self.appOpenAd = [[MAAppOpenAd alloc] initWithAdUnitIdentifier:@"«ad-unit-ID»"]; self.appOpenAd.delegate = self;</pre>	<pre>self.open = [[BAGAppOpen alloc] initWithInfoData:data delegate:self]; self.open.revenueDelegate = self;</pre>
加载	<pre>[self.appOpenAd loadAd];</pre>	<pre>[self.open loadAd];</pre>
Ready	<pre>[self.appOpenAd isReady]</pre>	<pre>[self.open isReady];</pre>
展示	<pre>[self.appOpenAd showAdForPlacement: @"«test-placement-ID»"];</pre>	<pre>[self.open showAd:self];</pre>

- 回调

MAX	BAG
-(void)didLoadAd:(MAAd *)ad	-(void)appOpenDidLoad:(BAGAdObject *)ad
-(void)didFailToLoadAdForAdUnitIdentifier:(NSString *)adUnitIdentifier withError:(MAError *)error	-(void)appOpenLoadFailWithError:(NSError *)error
-(void)didDisplayAd:(MAAd *)ad	-(void)appOpenDidShow:(BAGAdObject *)ad
-(void)didHideAd:(MAAd *)ad	-(void)appOpenDidDismiss:(BAGAdObject *)ad
-(void)didClickAd:(MAAd *)ad	-(void)appOpenDidClick:(BAGAdObject *)ad
-(void)didFailToDisplayAd:(MAAd *)ad withError:(MAError *)error;	-(void)appOpenShowFail:(nullable BAGAdObject *)ad withError:(BAGError *)error

三、插屏广告

	MAX	BAG
创建对象	self.interstitialAd = [[MAInterstitialAd alloc] initWithAdUnitIdentifier:@"«ad-unit-ID»"]; self.interstitialAd.delegate = self;	self.interstitial = [[BAGInterstitial alloc] initWithInfoData:data delegate:self]; self.interstitial.revenueDelegate = self;
加载	[self.self.interstitialAd loadAd];	[self.interstitial loadAd];
Ready	[self.interstitialAd isReady]	[self.interstitial isReady];
展示	[self.interstitialAd showAd];	[self.interstitial showAd:self];

- 回调

MAX	BAG
-(void)didLoadAd:(MAAd *)ad	-(void)interstitialDidLoad:(BAGAdObject *)ad
-(void)didFailToLoadAdForAdUnitIdentifier:(NSString *)adUnitIdentifier withError:(MAError *)error	-(void)interstitialLoadFailWithError:(NSError *)error
-(void)didDisplayAd:(MAAd *)ad	-(void)interstitialDidShow:(BAGAdObject *)ad

-(void)didHideAd:(MAAd *)ad	-(void)interstitialDidDismiss:(BAGAdObject *)ad
-(void)didClickAd:(MAAd *)ad	-(void)interstitialDidClick:(BAGAdObject *)ad
-(void)didFailToDisplayAd:(MAAd *)ad withError:(MAError *)error;	-(void)interstitialShowFail:(nullable BAGAdObject *)ad withError:(BAGError *)error

四、激励视频

	MAX	BAG
创建对象	self.rewardedAd = [MARewardedAd sharedWithAdUnitIdentifier:@"«ad-unit- ID»"]; self.rewardedAd.delegate = self;	self.rewardedVideo = [[BAGRewardedVideo alloc] initWithInfoData:data delegate:self]; self.rewardedVideo.revenueDelegate = self;
加载	[self.rewardedAd loadAd];	[self.rewardedVideo loadAd];
Ready	[self.rewardedAd isReady]	[self.rewardedVideo isReady]
展示	[self.rewardedAd showAd];	[self.rewardedVideo showAd:self];

• 回调

MAX	BAG
-(void)didLoadAd:(MAAd *)ad	-(void)rewardedVideoDidLoad:(BAGAdObject *)ad
-(void)didFailToLoadAdForAdUnitIdentifier:(NSString *)adUnitIdentifier withError:(MAError *)error	-(void)rewardedVideoLoadFailWithError:(NSError *)error
-(void)didDisplayAd:(MAAd *)ad	-(void)rewardedVideoDidShow:(BAGAdObject *)ad
-(void)didHideAd:(MAAd *)ad	-(void)interstitialDidDismiss:(BAGAdObject *)ad
-(void)didClickAd:(MAAd *)ad	-(void)rewardedVideoDidClick:(BAGAdObject *)ad
-(void)didHideAd:(MAAd *)ad	-(void)rewardedVideoDidDismiss:(BAGAdObject *)ad
-(void)didFailToDisplayAd:(MAAd *)ad withError:(MAError *)error;	-(void)rewardedVideoShowFail:(nullable BAGAdObject *)ad withError:(BAGError *)error

-(void)didRewardUserForAd:(MAAd *)ad withReward:(MAReward *)reward	-(void)rewardedVideoDidEarnReward: (BAGAdObject *)ad rewardInfo:(NSDictionary *)rewardInfo
---	---

五、横幅广告

	MAX	BAG
创建对象	self.adView = [[MAAdView alloc] initWithAdUnitIdentifier: @"«ad-unit-ID»"]; self.adView.delegate = self; self.adView.frame = CGRectMake(0, 0, 320, 50);	self.banner = [[BAGBanner alloc] initWithInfoData:data delegate:self]; self.banner.frame = CGRectMake(0, 0, 320, 50); self.banner.rootViewController = self;//可选
加载	[self.adView loadAd];	[self.banner loadAd];
停止刷新	[self.adView stopAutoRefresh];	[self.banner stopAutoRefresh];
开始刷新	[self.adView startAutoRefresh];	[self.banner startAutoRefresh];

• 回调

MAX	BAG
-(void)didLoadAd:(MAAd *)ad	-(void)bannerDidLoad:(BAGAdObject *)ad
-(void)didFailToLoadAdForAdUnitIdentifier: (NSString *)adUnitIdentifier withError:(MAError *)error	-(void)rewardedVideoLoadFailWithError:(NSError *)error
-(void)didDisplayAd:(MAAd *)ad	-(void)bannerDidShow:(BAGAdObject *)ad
-(void)didClickAd:(MAAd *)ad	-(void)bannerDidClick:(BAGAdObject *)ad
-(void)didFailToDisplayAd:(MAAd *)ad withError: (MAError *)error;	-(void)bannerShowFail:(nullable BAGAdObject *)ad withError:(BAGError *)error

六、原生广告

	MAX	BAG
创建对象	self.nativeAdLoader = [[MANativeAdLoader alloc] initWithAdUnitIdentifier: @"«ad-unit-	self.native = [[BAGNative alloc] initWithInfoData:data delegate:self];

	<pre>ID»"]; self.nativeAdLoader.nativeAdDelegate = self; self.nativeAdLoader.revenueDelegate = self;</pre>	<pre>self.native.revenueDelegate = self; self.native.rootViewController = self;//可选</pre>
加载	<pre>[self.nativeAdLoader loadAd];</pre>	<pre>[self.native loadAd];</pre>
创建容器 绑定元素 渲染	<pre>MANativeAdView *nativeAdView = [nativeAdViewNib instantiateWithOwner: nil options: nil].firstObject; MANativeAdViewBinder *binder = [[MANativeAdViewBinder alloc] initWithBuilderBlock:^(MANativeAdViewBi nderBuilder *builder) { builder.titleLabelTag = «title-label-tag»; builder.bodyLabelTag = «body-lable-tag»; builder.callToActionButtonTag = «call-to- action-label-tag»; builder.iconImageViewTag = «icon- image-view-taG»; builder.mediaContentViewTag = «media- view-content-view-tag»; builder.starRatingContentViewTag = «star-rating-content-view-tag»; builder.advertiserLabelTag = «advertiser- label-tag»; builder.optionsContentViewTag = «options-content-view-tag»; }]; [nativeAdView bindViewsWithAdViewBinder: binder]; [self.nativeAdLoader renderNativeAdView:self.nativeAdView withAd:self.ad];</pre>	<pre>self.nativeView = [[BAGNativeView alloc] init]; self.nativeView.frame = self.adView.bounds; self.nativeView.adView = self.nativeTemplate; self.nativeView.mainImageView = self.nativeTemplate.mainImageView; self.nativeView.iconImageView = self.nativeTemplate.iconImageView; self.nativeView.adChoiceImageView = self.nativeTemplate.adChoiceImageView; self.nativeView.titleLabel = self.nativeTemplate.titleLabel; self.nativeView.textLabel = self.nativeTemplate.textLabel; self.nativeView.ctaLabel = self.nativeTemplate.ctaLabel; self.nativeView.ctaButton = self.nativeTemplate.ctaButton; [self.native renderWithNativeView:self.nativeView];</pre>

• 回调

MAX	BAG
-----	-----

<code>-(void)didLoadNativeAd:(nullable MANativeAdView *)nativeAdView forAd:(MAAd *)ad;</code>	<code>-(void)nativeDidLoad:(BAGAdObject *)ad</code>
<code>-(void)didFailToLoadNativeAdForAdUnitIdentifier:(NSString *)adUnitIdentifier withError:(MAError *)error;</code>	<code>-(void)nativeLoadFailWithError:(NSError *)error</code>
<code>-(void)didClickNativeAd:(MAAd *)ad;</code>	<code>-(void)nativeDidClick:(BAGAdObject *)ad</code>

七、其他

	MAX	BAG
DoNotSell	<code>[ALPrivacySettings setDoNotSell: BOOL];</code>	<code>[[BidAggregatorSDK sharedInstance] setDoNotSell:BOOL];</code>
设置 UserID	<code>[ALSdk shared].settings.userIdentifier = @"«user-ID»";</code>	<code>[[BidAggregatorSDK sharedInstance] setUserID:@"YOUR_USER_ID"];</code>