



<http://hl7.org>

Electronic Long-Term Services and Supports (eLTSS) Release 1 - US Realm

2.0.0 - STU2


[searchform.html](#)

<http://hl7.org/fhir>

[Table of Contents \(toc.html\)](#) > [IG Home Page \(index.html\)](#) > [eLTSS Mapping to FHIR \(mapping.html\)](#) > **eLTSS Dataset to FHIR Release 4**

This page is part of the electronic Long-Term Services and Supports Implementation Guide (v2.0.0: STU (<https://confluence.hl7.org/display/HL7/HL7+Balloting>)) based on [FHIR \(HL7® FHIR® Standard\) R4](#) (<http://hl7.org/fhir/R4>). This is the current published version. For a full list of available versions, see the [Directory of published versions](#) (<http://hl7.org/fhir/us/eltss/history.html>)

1.3.1 eLTSS Dataset to FHIR Release 4

This Page contains three tables to aid in FHIR representation and use of eLTSS data.

- The [R4 mapping table \(eLTSS to FHIR R4 element.html#r4-mapping-table\)](#), indicates where eLTSS DAM data elements are to be placed/found in FHIR.
- The [R4 Useful elements table \(eLTSS to FHIR R4 element.html#r4-useful-elements\)](#) details important accessory data elements in meeting the eLTSS use case.
- The [Units table \(eLTSS to FHIR R4 element.html#units\)](#) provides guidance on using units for things such as 'visit/week.'

Contents:

- [R4 mapping table](#)
- [R4 useful elements](#)
- [Units](#)

1.3.1.1 R4 mapping table

eLTSS Grouping	eLTSS Data Element Name	Data Element Definition (includes examples, expected list of values and usage note where applicable)	FHIR R4 Resource Element(s)	FHIR R4 Resource Element Cardinality (with US Core Constraints)	Additional Mapping Details
Beneficiary Demographics	Person Name	The name of the person whom the plan is for.	CarePlan → subject(Patient) Patient → name → family Patient → name → given Patient → name → text	CarePlan ...subject(Patient) 1name 1..*family 1given 1..*text 0..1	1) Will use CarePlan → subject(Patient) as the care plan being developed includes a subject. 2) given is used for both one. 3) family is a string with 4) text is a string that contains 5) Per US Core 1.0.1, each name, and each name may
Beneficiary Demographics	Person Identifier	A string of character(s) used to identify the person whom the plan is for. This may be the Medicaid ID number where applicable.	CarePlan → subject(Patient) Patient → identifier → value	CarePlan ...subject(Patient) 1identifier 1..*value 1system 1	1) Will use CarePlan → subject(Patient) as the care plan being developed includes a subject. 2) identifier is of type Identifier 3) Per US Core 1.0.1, each identifier, and each identifier system. system is the name of the system
Beneficiary Demographics	Person Identifier Type	The type of unique identifier used to identify the person whom the plan is for. Values include: Medicaid Number, State ID, Medical Record Number, Other (free text)	CarePlan → subject(Patient) Patient → identifier → type	CarePlan ...subject(Patient) 1identifier 1..*type 0..1	1) Will use CarePlan → subject(Patient) as the care plan being developed includes a subject. 2) If we have the identifier type, it is required. 3) type is a CodeableConcept with values defined here (identifier-type.html) . Medical Record Number is a LOINC code. LOINC includes Medical Security Number (45396- (Social Beneficiary) code codeset at http://hl7.org , handled with the text element Concept.
Beneficiary Demographics	Person Date of Birth	The birth date of the person whom the plan is for.	CarePlan → subject(Patient) Patient → birthDate	CarePlan ...subject(Patient) 1birthDate 0..1	1) Will use CarePlan → subject(Patient) as the care plan being developed includes a subject. 2) birthDate is in the form YYYY-MM-DD
Beneficiary Demographics	Person Phone Number	The primary phone number of the person whom the plan is for, or his/her legal representative, where applicable.	CarePlan → subject(Patient) Patient → telecom → system Patient → telecom → value	CarePlan ...subject(Patient) 1telecom 0..*value 0..1system 0..1	1) Will use CarePlan → subject(Patient) as the care plan being developed includes a subject. 2) telecom is of type ContactPoint 3) system is required by the phone fax email eLTSS phone number, system 4) Per FHIR, phone # should be E.123, so "(555) 675 574"
Beneficiary Demographics	Person Address	The address of the person whom the plan is for.	CarePlan → subject(Patient) Patient → address → line	CarePlan ...subject(Patient) 1address 0..*	1) Will use CarePlan → subject(Patient) as the care plan being developed includes a subject.

			Patient → address → city Patient → address → state Patient → address → postalCode Patient → address → district Patient → address → text	line 0..*city 0..1state 0..1postalCode 0..1district 0..1text 0..1	2) text is the full (not br 3) line includes street na Main St.). 4) Information such as a into line, generally as a s 5) district covers county.
Beneficiary Demographics	Emergency Contact Name	The name of the individual or entity identified to contact in case of emergency.	CarePlan → subject(Patient) Patient → contact → relationship Patient → contact → name → family Patient → contact → name → given Patient → contact → name → text	CarePlan ...subject(Patient) 1contact 0..*relationship 1..*name 0..1family 0..1given 0..*text 0..1	1) Will use CarePlan → su care plan being develop includes a subject. 2) Emergency contact is i "C". 3) If contact is provided, indicate this is an emerg 4) given is used for both one. 5) family is a string with 6) text is a string with th
Beneficiary Demographics	Emergency Contact Relationship	The relationship (e.g., spouse, neighbor, guardian, daughter) of the individual identified to contact in case of emergency.	CarePlan → subject(Patient) Patient → contact → relationship	CarePlan ...subject(Patient) 1contact 0..*relationship 1..*	1) Will use CarePlan → su care plan being develop includes a subject. 2) Emergency contact is i "C". Other contact codes can l https://www.hl7.org/fhir/ 3) The emergency contac elements, one to indicate one to indicate the relat contact (such as "next-of 4) There are other value more detail, for example value set http://www.hl7.org/implement/relatedperson-relationships
Beneficiary Demographics	Emergency Contact Phone Number	The primary phone number (and extension when applicable) of the individual or entity identified to contact in case of emergency.	CarePlan → subject(Patient) Patient → contact → telecom → system Patient → contact → telecom → value	CarePlan ...subject(Patient) 1contact 0..*telecom 0..*value 0..1system 0..1	1) Will use CarePlan → su care plan being develop includes a subject. 2) telecom is of type Con populate for the phone n 3) system is required if v fax, email, pager, url, sm 4) Per FHIR, phone # sho E.123, so "(555) 675 574
Beneficiary Demographics	Emergency Backup Plan	Description of how to address unforeseen events, emergency health events, emergency events, problems with medical equipment and supplies, and unavailable staffing situations for critical services that put the person's health and safety at risk. This can be included as free text or attachment.	CarePlan [emergency backup plan] → subject(Patient) CarePlan [emergency backup plan] → description CarePlan [emergency backup plan] → partOf(CarePlan) ["main" Care Plan]	CarePlan ...subject(Patient) 1 ...description 0..1 ...part of(CarePlan) 0..*	1) The CarePlan resource plan refers to the "main" other way around, by usi CarePlan → partOf data e CarePlan data element. 2) FHIR requires that Car 3) description contains th Plan if provided as text. 4) type indicates the kind preferred LOINC value se corresponding to an eme can use the Codeable Con "Emergency Backup Plan" but optional in the R4 dra
Goals & Strengths	Goal	A statement of a desired result that the person wants to achieve.	CarePlan → goal(Goal) Goal → description → text	CarePlan ...goal(Goal) 0..*description 1text 1subject(Patient) 1	1) Will use CarePlan → gr plan being developed. 2) description is required CodableConcept whose te include a text description 3) Each goal should go in can potentially reference that addresses the goal. 4) A Goal can be referenc service. For a goal relat extension(pertainsToGoal also use extension(pertai exclusive to each other a both levels. 5) US Core requires the u back to the Patient.
Goals & Strengths	Step or Action	A planned measurable step or action that needs to be taken to accomplish a goal identified by the person.	CarePlan → activity → reference(Resource) → note → text → extension(pertainsToGoal)	CarePlan ...activity 0..*reference(Resource) 0..1note 0..*text 1extension(pertainsToGoal)	1) CarePlan includes activ reference to ServiceRequ 2) ServiceRequest would task under a service. If tl support or an activity bei recipient, the Task Resou the Gravity SDOH IG, car 3) activity → reference(R step or action addresses Extension in the referenc 4) activity → reference(R

					author, participant with to be used to reference who step or action, such as to person is responsible. 5) text is where the Step 6) text is required by FHIR 7) Note that a stated goal not necessarily to an expected person's goal could be to would be achieved through
Goals & Strengths	Strength	A favorable attribute of oneself, his/her support network, environment and/or elements of his/her life.	CarePlan → supportingInfo(Observation) Observation → valueString Observation → code → coding → code Observation → code → coding → system	CarePlan ...supportingInfo(Observation) 0..*valueString 0..1code 1coding 0..*code 0..1system 0..1	1) Will use CarePlan → supportingInfo(Observation) containing the 2) code is required by FHIR coding → code can be set corresponding NEW code "http://hl7.org/us/eLTSS, code". 3) valueString is where the
Person Centered Planning	Assessed Need	The clinical and/or community-based necessity or desire as identified through an assessment that should be addressed by a service.	CarePlan → addresses(Condition) Condition → code → text Condition → category	CarePlan ...addresses(Condition) 0..*code 1text 0..1category 1..*	1) Will use CarePlan → addresses(Condition) for the care 2) code is required by US Core is based on the Set. That value set is based on specific values that do not US Core's documentation the CodeableConcept's text suitable codes exist", so the assessed need. Additional value set of SDOH condition 3) Each assessed need is an element so each can potentially addresses it. 4) Category is required by which per US Core is based on Condition Category Code: (http://hl7.org/fhir/Value values: problem-list-item concern. The additional 'category' relate that the Condition community-based necessity an assessment, that should Consider also using the US categories https://www.hhs.gov/core-screening-assessment) 5) An "assessed need" condition via the condition
Person Centered Planning	Person Setting Choice Indicator	Indicator that reflects the setting in which the person resides is chosen by the individual.	CarePlan → supportingInfo(Questionnaire) Questionnaire → item → linkID Questionnaire → item → text Questionnaire → item → type ----- QuestionnaireResponse → questionnaire(Questionnaire) QuestionnaireResponse → item → linkID QuestionnaireResponse → item → answer → valueBoolean	CarePlan ...supportingInfo(Questionnaire) 0..*item 0..*linkID 1text 0..1type 1 ----- QuestionnaireResponse ...questionnaire(Questionnaire) 0..1 ...item 0..*linkID 1answer 0..*valueBoolean 0..1	1) Will use CarePlan → supportingInfo(Questionnaire) for the care 2) QuestionnaireResponse 3) QuestionnaireResponse or more item elements, value question or answer to a care 4) item includes a mandatory to the question it applies 5) valueBoolean is the actual 6) text is the actual text 7) type is required by FHIR question this is. Values for QuestionnaireItemType value display, boolean, decimal value "boolean" would appear indicate "yes".
Person Centered Planning	Person Setting Choice Options	The alternative home and community-based settings that were considered by the individual.	CarePlan → supportingInfo(Questionnaire) Questionnaire → item → linkID Questionnaire → item → text Questionnaire → item → type ----- QuestionnaireResponse → questionnaire(Questionnaire) QuestionnaireResponse → item → linkID QuestionnaireResponse → item → answer → valueString	CarePlan ...supportingInfo(Questionnaire) 0..*item 0..*linkID 1text 0..1type 1 ----- QuestionnaireResponse ...questionnaire(Questionnaire) 0..1 ...item 0..*linkID 1answer 0..*valueString 0..1	1) Will use CarePlan → supportingInfo(Questionnaire) for the care 2) QuestionnaireResponse 3) QuestionnaireResponse or more item elements, value question or answer to a care 4) item includes a mandatory to the question it applies 5) valueString is the actual 6) text is the actual text 7) type is required by FHIR question this is. Values for QuestionnaireItemType value display, boolean, decimal values "string" (for a few (potentially multi-paragraph
Person Centered Planning	Plan Monitor Name	The name of the person responsible for monitoring the plan.	CarePlan → encounter (Encounter) Encounter → episodeOfCare(EpisodeOfCare) EpisodeOfCare → careManager(Practitioner) Practitioner → name → family Practitioner → name → given Practitioner → name → text	CarePlan ...encounter(Encounter) 0..1episodeOfCare(EpisodeOfCare)0..1careManager(Practitioner) 0..1name 0..*family 0-1given 0-*text 0-1	1) Will use CarePlan → encounter(EpisodeOfCare) that defines for the plan. 2) EpisodeOfCare → care who is monitoring the plan 3) given is used for both one. 4) family is a string with 5) text is a string that contains 6) The values for Plan Monitor

					Name would include the s
Person Centered Planning	Plan Monitor Phone Number	The primary phone number (and extension when applicable) of the plan monitor.	CarePlan → encounter (Encounter) Encounter → episodeOfCare(EpisodeOfCare) EpisodeOfCare → careManager(Practitioner) Practitioner → telecom → system Practitioner → telecom → value	CarePlan ...encounter(Encounter) 0..1 episodeOfCare(EpisodeOfCare)0..1careManager(Practitioner) 0..1telecom 0..*system 0..1value 0..1	1) Will use CarePlan → episodeOfCare that defines the plan. 2) EpisodeOfCare → careManager who is monitoring the plan 3) telecom is of type ContactPoint (https://www.hl7.org/fhir/ContactPoint.html) which contains elements 4) system is required if v fax, email, pager, url, sms, etc. 5) Per FHIR, phone # should be E.123, so "(555) 675 574"
Person Centered Planning	Preference	Presents the person's personal thoughts about something he or she feels is relevant to his or her life experience and may be pertinent when planning.	CarePlan → supportingInfo(Observation) Observation → valueString Observation → code → coding → code Observation → code → coding → system	CarePlan ...supportingInfo(Observation) 0..*valueString 0..1code 1coding 0..*code 0..1system 0..1	1) Will use CarePlan → supportingInfo(Observation) containing the code 2) code is required by FHIR coding → code can be selected corresponding NEW code "http://hl7.org/us/eltss/code". 3) valueString is where the text is provided.
Person Centered Planning	Service Options Given Indicator	States whether or not the person was given a choice of services outlined in the plan.	CarePlan → supportingInfo(Questionnaire) Questionnaire → item → linkID Questionnaire → item → text Questionnaire → item → type ----- QuestionnaireResponse → questionnaire(Questionnaire) QuestionnaireResponse → item → linkID QuestionnaireResponse → item → answer → valueBoolean	CarePlan ...supportingInfo(Questionnaire) 0..*item 0..*linkID 1text 0..1type 1 ----- QuestionnaireResponse ...questionnaire(Questionnaire) 0..1 ...item 0..*linkID 1answer 0..*valueBoolean 0..1	1) Will use CarePlan → supportingInfo(Questionnaire) for the care plan 2) QuestionnaireResponse 3) QuestionnaireResponse or more item elements, value question or answer to a care plan 4) item includes a mandatory to the question it applies 5) valueBoolean is the actual value 6) text is the actual text 7) type is required by FHIR question this is. Values for QuestionnaireItemType value display, boolean, decimal value "boolean" would appear indicate "yes".
Person Centered Planning	Service Selection Indicator	States whether or not the person participated in the selection of the services outlined in the plan.	CarePlan → supportingInfo(Questionnaire) Questionnaire → item → linkID Questionnaire → item → text Questionnaire → item → type ----- QuestionnaireResponse → questionnaire(Questionnaire) QuestionnaireResponse → item → linkID QuestionnaireResponse → item → answer → valueBoolean	CarePlan ...supportingInfo(Questionnaire) 0..*item 0..*linkID 1text 0..1type 1 ----- QuestionnaireResponse ...questionnaire(Questionnaire) 0..1 ...item 0..*linkID 1answer 0..*valueBoolean 0..1	1) Will use CarePlan → supportingInfo(Questionnaire) for the care plan 2) QuestionnaireResponse 3) QuestionnaireResponse or more item elements, value question or answer to a care plan 4) item includes a mandatory to the question it applies 5) valueBoolean is the actual value 6) text is the actual text 7) type is required by FHIR question this is. Values for QuestionnaireItemType value display, boolean, decimal value "boolean" would appear indicate "yes".
Person Centered Planning	Service Plan Agreement Indicator	States whether or not the person agrees to the services outlined in the plan.	CarePlan → supportingInfo(Questionnaire) Questionnaire → item → linkID Questionnaire → item → text Questionnaire → item → type ----- QuestionnaireResponse → questionnaire(Questionnaire) QuestionnaireResponse → item → linkID QuestionnaireResponse → item → answer → valueBoolean	CarePlan ...supportingInfo(Questionnaire) 0..*item 0..*linkID 1text 0..1type 1 ----- QuestionnaireResponse ...questionnaire(Questionnaire) 0..1 ...item 0..*linkID 1answer 0..*valueBoolean 0..1	1) Will use CarePlan → supportingInfo(Questionnaire) for the care plan 2) QuestionnaireResponse 3) QuestionnaireResponse or more item elements, value question or answer to a care plan 4) item includes a mandatory to the question it applies 5) valueBoolean is the actual value 6) text is the actual text 7) type is required by FHIR question this is. Values for QuestionnaireItemType value display, boolean, decimal value "boolean" would appear indicate "yes".
Person Centered Planning	Service Provider Options Given Indicator	States whether or not the person was offered a choice of providers for each service.	CarePlan → supportingInfo(Questionnaire) Questionnaire → item → linkID Questionnaire → item → text Questionnaire → item → type ----- QuestionnaireResponse → questionnaire(Questionnaire) QuestionnaireResponse → item → linkID QuestionnaireResponse → item → answer → valueBoolean	CarePlan ...supportingInfo(Questionnaire) 0..*item 0..*linkID 1text 0..1type 1 ----- QuestionnaireResponse ...questionnaire(Questionnaire) 0..1 ...item 0..*linkID 1answer 0..*valueBoolean 0..1	1) Will use CarePlan → supportingInfo(Questionnaire) for the care plan 2) QuestionnaireResponse 3) QuestionnaireResponse or more item elements, value question or answer to a care plan 4) item includes a mandatory to the question it applies 5) valueBoolean is the actual value 6) text is the actual text 7) type is required by FHIR question this is. Values for QuestionnaireItemType value display, boolean, decimal value "boolean" would appear indicate "yes".

Person Centered Planning	Service Provider Selection Agreement Indicator	States whether or not the person feels he/she made an informed choice in selecting the provider for each service.	CarePlan → supportingInfo(Questionnaire) Questionnaire → item → linkID Questionnaire → item → text Questionnaire → item → type ----- QuestionnaireResponse → questionnaire(Questionnaire) QuestionnaireResponse → item → linkID QuestionnaireResponse → item → answer → valueBoolean	CarePlan ...supportingInfo(Questionnaire) 0..*item 0..*linkID 1text 0..1type 1 ----- QuestionnaireResponse ...questionnaire(Questionnaire) 0..1item 0..*linkID 1answer 0..*valueBoolean 0..1	1) Will use CarePlan → supportingInfo(Questionnaire) for the care plan. 2) QuestionnaireResponse includes a link to the question it applies to. 3) QuestionnaireResponse includes a link to the question or answer to a care plan. 4) item includes a mandatory link to the question it applies to. 5) valueBoolean is the actual text value. 6) text is the actual text value. 7) type is required by FHIR. For this question this is. Values must be Patient, Organization, RelatedPerson or Device. 8) QuestionnaireItemType value must be "boolean" would apply to indicate "yes".
Plan Information	Plan Effective Date	The date upon which the plan goes into effect. Start date is required, end date is optional.	CarePlan → period → start CarePlan → period → end	CarePlan 0..* ...period 0..1start 1end 0..1	1) period includes a start date and time formats which must be valid (e.g. just year or year + month). 2) start is required by eLTSS.
Plan Signatures	Person Signature	The depiction of the person's signature as proof of identity and intent for the plan.	CarePlan → supportingInfo(Contract) Contract → signer → type Contract → signer → signature → data Contract → signer → signature → type Contract → signer → signature → who(Practitioner PractitionerRole RelatedPerson Patient Device Organization)	CarePlan ...supportingInfo(Contract) 0..*signer 0..*type 1signature 1..*data 0..1type 1who(Practitioner PractitionerRole RelatedPerson Patient Device Organization) 1	1) Will use CarePlan → supportingInfo(Contract) containing the signature. 2) Can use a single Contract containing the signature. 3) signer requires the signature of the contract signatory role. 4) FHIR includes a preferred role, which map well to the role for the patient/beneficiary. 5) FHIR implementers may use of the role to realize that type must be the patient, service provider, distinct role types utilized. 6) data is the actual signature (picture, etc.). 7) signature requires it's the entity signed the contract code list. Would probably represents "consent signature". 8) signature requires a value must be a Patient, Organization, RelatedPerson or Device, Patient.
Plan Signatures	Person Printed Name	The printed or typed name of the person.	CarePlan → supportingInfo(Contract) Contract → signer → party(Patient)	CarePlan ...supportingInfo(Contract) 0..*signer 0..*party(Patient) 1	1) Will use CarePlan → supportingInfo(Contract) containing the signature. 2) In this case, party is already documented as Patient.
Plan Signatures	Person Signature Date	The date the person signed the plan.	CarePlan → supportingInfo(Contract) Contract → signer → signature → when	CarePlan ...supportingInfo(Contract) 0..*signer 0..*signature 1..*when 1	1) Will use CarePlan → supportingInfo(Contract) containing the signature. 2) when is required by FHIR when signature was created. 3) when is an instance type least to the second and a date. This is intended for precise logs etc.), and not human date and dateTime. instance.
Plan Signatures	Guardian / Legal Representative Signature	The depiction of the guardian or legally authorized representative's signature as proof of identity and intent for the plan.	CarePlan → supportingInfo(Contract) Contract → signer → type Contract → signer → signature → data Contract → signer → signature → type Contract → signer → signature → who(Practitioner PractitionerRole RelatedPerson Patient Device Organization)	CarePlan ...supportingInfo(Contract) 0..*signer 0..*type 1signature 1..*data 0..1type 1who(Practitioner PractitionerRole RelatedPerson Patient Device Organization) 1	1) Will use CarePlan → supportingInfo(Contract) containing the signature. 2) Can use a single Contract containing the signature. 3) signer requires the signature of the contract signatory role. 4) FHIR includes a preferred role, which map well to the role for the patient/beneficiary. 5) FHIR implementers may use of the role to realize that type must be the patient, service provider, distinct role types utilized. 6) data is the signature (picture, etc.). 7) signature requires it's the entity signed the contract value set. Would probably represents "consent signature". 8) signature requires a value must be a Patient, Organization, RelatedPerson or Device, RelatedPerson.
Plan Signatures	Guardian / Legal Representative Printed Name	The printed or typed name of the guardian or legally authorized	CarePlan → supportingInfo(Contract) Contract → signer → party(RelatedPerson)	CarePlan ...supportingInfo(Contract) 0..*signer 0..*party(RelatedPerson) 1	1) Will use CarePlan → supportingInfo(Contract) containing the signature. 2) In this case, party is a RelatedPerson includes a link to the patient.

		representative.			
Plan Signatures	Guardian / Legal Representative Signature Date	The date the guardian or legally authorized representative signed the plan.	CarePlan → supportingInfo(Contract) Contract → signer → signature → when	CarePlan ...supportingInfo(Contract) 0..*signer 0..*signature 1..*when 1	1) Will use CarePlan → supportingInfo(Contract) 0..* 2) when is required by FHIR signature was created. 3) when is an instance type least to the second and a This is intended for precise logs etc.), and not human date and dateTime. instance
Plan Signatures	Support Planner Signature	The depiction of the support planner's signature as proof of identity and intent for the plan.	CarePlan → supportingInfo(Contract) Contract → signer → type Contract → signer → signature → data Contract → signer → signature → type Contract → signer → signature → who(Practitioner PractitionerRole Organization RelatedPerson Patient Organization)	CarePlan ...supportingInfo(Contract) 0..*signer 0..*type 1signature 1..*data 0..1type 1who(Practitioner PractitionerRole Organization RelatedPerson Patient Organization) 1	1) Will use CarePlan → supportingInfo(Contract) 0..* 2) Can use a single Contract signatures. 3) signer requires the signature contract signatory role. 4) FHIR includes a preferred roles, which map well to multiple values that may want to map. For example which aligns with author eLTSS Dataset elements. appropriate as well such implementers must realize differentiate between the etc. so there need to be (5) data is the actual signature picture, etc.) 6) signature requires it's the entity signed the contract value set, in this case code "Author's Signature". 7) signature requires a value be a Patient, Organization RelatedPerson or Device.
Plan Signatures	Support Planner Printed Name	The printed or typed name of the support planner.	CarePlan → supportingInfo(Contract) Contract → signer → party(Practitioner PractitionerRole Organization)	CarePlan ...supportingInfo(Contract) 0..*signer 0..*party(Practitioner PractitionerRole Organization)	1) Will use CarePlan → supportingInfo(Contract) 0..* 2) In this case, party is a PractitionerRole or Organization of the Support Planner and Organization 3) The values for Support Printed Name would include
Plan Signatures	Support Planner Signature Date	The date the support planner signed the plan.	CarePlan → supportingInfo(Contract) Contract → signer → signature → when	CarePlan ...supportingInfo(Contract) 0..*signer 0..*signature 1..*when 1	1) Will use CarePlan → supportingInfo(Contract) 0..* 2) when is required by FHIR signature was created. 3) when is an instance type least to the second and a This is intended for precise logs etc.), and not human date and dateTime. instance
Plan Signatures	Service Provider Signature	The depiction of the service provider's signature as proof they agree to the services they will provide.	CarePlan → supportingInfo(Contract) Contract → signer → type Contract → signer → signature → data Contract → signer → signature → type Contract → signer → signature → who(Practitioner PractitionerRole RelatedPerson Patient Device Organization)	CarePlan ...supportingInfo(Contract) 0..*signer 0..*type 1signature 1..*data 0..1type 1who(Practitioner PractitionerRole RelatedPerson Patient Device Organization) 1	1) Will use CarePlan → supportingInfo(Contract) 0..* 2) Can use a single Contract signatures. 3) signer requires the signature contract signatory role. 4) FHIR includes a preferred which map well to the eLTSS values that may be used map. The list includes "H" may be the best fit here, However, implementers need differentiate between the etc. so there need to be (5) data is the actual signature picture, etc.) 6) signature requires it's the entity signed the contract value set. In this case code "1.2.840.10065.1.12.1.3" 7) signature requires a value be a Patient, Organization RelatedPerson or Device.
Plan Signatures	Service Provider Printed Name	The printed or typed name of the service provider.	CarePlan → supportingInfo(Contract) Contract → signer → party(Organization Patient Practitioner PractitionerRole RelatedPerson)	CarePlan ...supportingInfo(Contract) 0..*signer 0..*party(Organization Patient Practitioner PractitionerRole RelatedPerson) 1	1) Will use CarePlan → supportingInfo(Contract) 0..* 2) party is a reference to Practitioner, PractitionerRole include a name. (Patient of a service provided by a 3) The values for Service Printed Name would include
Plan Signatures	Service Provider Signature Date	The date the service provider signed the plan.	CarePlan → supportingInfo(Contract) Contract → signer → signature → when	CarePlan ...supportingInfo(Contract) 0..*signer 0..*signature 1..*	1) Will use CarePlan → supportingInfo(Contract) 0..* 2) when is required by FHIR signature was created.

				when 1	3) when is an instance ty least to the second and a This is intended for preci logs etc.), and not human date and dateTime. instai
Risks	Identified Risk	An aspect of a person's life, behavior, environmental exposure, personal characteristic, Social determinants of health, or other barrier that increases the likelihood of disease, condition, injury to self or others, or interaction with the criminal justice system.	CarePlan → supportingInfo(RiskAssessment) RiskAssessment → prediction → outcome → coding → code RiskAssessment → prediction → outcome → coding → system RiskAssessment → prediction → outcome → text	CarePlan ...supportingInfo(RiskAssessment) 0..*prediction 0..*outcome 0..1coding 0..*code 0..1system 0..1text 0..1	1) Will use CarePlan → su RiskAssessment containir 2) outcome is a Codeable element that can be used appropriate coding is ava prior to R4 version 3.3.0. 3) prediction describes th and is the "prediction" of
Risks	Risk Management Plan	Description of planned activities to minimize identified risks that endanger the person's health and safety. This can be included as free text or attachment.	CarePlan → supportingInfo(RiskAssessment) RiskAssessment → mitigation RiskAssessment → extension(RiskAssessment Mitigation Plan)	CarePlan ...supportingInfo(RiskAssessment) 0..*mitigation 0..1 ...RiskAssessment ...extension(RiskAssessment MitigationPlan)	1) Will use CarePlan → su RiskAssessment containir 2) mitigation is a string a Management Plan. 3) The new RiskAssessm Mitigation Plan which is a be used if the Risk Manag attachment rather than a
Service Information	Service Name	Identifies the paid and/or non-paid service provided to a person. Include the code and display name plus any modifiers when a coding system (e.g., Healthcare Common Procedure Coding System (HCPCS), Home Health Revenue Codes) is used.	CarePlan → activity → reference(ServiceRequest) ServiceRequest → code → text ServiceRequest → code → coding → code ServiceRequest → code → coding → system	CarePlan ...activity 0..*reference(ServiceRequest) 0..1code 0..1text 0..1coding 0..1code 0..1system 0..1	1) activity is part of Care to link the two. 2) coding → code is the " in the eLTSS Dataset data identifies the code system HCPCS, the system value "https://www.cms.gov/M 3) text is the "display na data element definition. 4) Note that modifiers for code using a dash. So the single string.
Service Information	Self-Directed Service Indicator	Indicates whether the individual chose to self-direct the service.	CarePlan → activity → reference(ServiceRequest) ServiceRequest → extension → url ServiceRequest → extension → valueCodeableConcept → text	CarePlan ...activity 0..*reference(ServiceRequest) 0..1extension 0..*url 0..1valueCodeableConcept 0..1text 0..1	1) activity is part of Care to link the two. 2) The procedure-directe populating the url data at "http://hl7.org/fhir/Struc directedBy". 3) The text data element "self" to indicate that this values could be provided directing the service. This proper element in the Re CarePlan.activity.reference indicate who is responsib
Service Information	Service Start Date	The start date of the service being provided.	CarePlan → activity → reference(ServiceRequest) ServiceRequest → occurrenceTiming → boundsPeriod → start	CarePlan ...activity 0..*reference(ServiceRequest) 0..1occurrenceTiming 0..1boundsPeriod 0..1start 0..1	1) activity is part of Care to link the two. 2) start is in dateTime for partial date (e.g. just year
Service Information	Service End Date	The end date of the service being provided.	CarePlan → activity → reference(ServiceRequest) ServiceRequest → occurrenceTiming → boundsPeriod → end	CarePlan ...activity 0..*reference(ServiceRequest) 0..1occurrenceTiming 0..1boundsPeriod 0..1end 0..1	1) activity is part of Care to link the two. 2) end is in dateTime for partial date (e.g. just year
Service Information	Service Delivery Address	The address where service delivery will take place if service will not be provided at the person's address.	CarePlan → activity → reference(ServiceRequest) ServiceRequest → locationReference(Location) Location → address → line Location → address → city Location → address → district Location → address → state Location → address → postalCode Location → address → text Location → description	CarePlan ...activity 0..*reference(ServiceRequest) 0..1locationReference(Location) 0..*address 0..*line 0..*city 0..1district 0..1state 0..1postalCode 0..1text 0..1description 0..1	1) activity is part of Care to link the two. 2) text is the full (not br 3 line includes street name St.). 4) Information such as a into line, generally as a s 5) district covers county. 6) description can be use address, such as when s location, such as someone recipient grocery shops.
Service Information	Service Comment	Additional information related to the service being	CarePlan → activity → reference(ServiceRequest)	CarePlan ...activity 0..*reference(ServiceRequest) 0..1	1) activity is part of Care to link the two. 2) text is required by FHI

		provided. This field could capture additional information of the frequency of the service, how the person wants the service delivered and only used when the comment provides additional detail of the service not already handled by another element.	ServiceRequest → note → text	note 0..*text 1	
Service Information	Service Funding Source	The source of payment for the service.	CarePlan → activity → reference(ServiceRequest) ServiceRequest → insurance(Coverage) Coverage → payor(Organization Patient RelatedPerson) Organization Patient RelatedPerson → name	CarePlan ...activity 0..*reference(ServiceRequest) 0..1insurance(Coverage) 0..*payor(Organization Patient RelatedPerson) 1..*name 0..1	1) Will use CarePlan → activity → reference(ServiceRequest), and insurance resource, which must include organization. 2) Coverage resource must include an individual or organization taking responsibility for payment of care cost.
Service Information	Service Unit Quantity	The numerical amount of the service unit being provided for a frequency. This element is slated to be used in conjunction with Service Unit Interval and Unit of Service Type elements to form a full description of how often a service is provided. For example, a service being provided 7 units per week, the Service Unit Quantity = "7". For a service being provided 8 hours a day, the Service Unit Value = "8".	CarePlan → activity → reference(ServiceRequest) ServiceRequest → quantityQuantity → value ServiceRequest → quantityQuantity → unit or ServiceRequest → quantityRatio → numerator → value ServiceRequest → quantityRatio → numerator → unit ServiceRequest → quantityRatio → denominator → value ServiceRequest → quantityRatio → denominator → unit	CarePlan ...activity 0..*reference(ServiceRequest) 0..1quantityQuantity 0..1value 0..1unit 0..1quantityRatio 0..1numerator 0..1value 0..1unit 0..1denominator 0..1value 0..1unit 0..1	1) Will use CarePlan → activity → reference(ServiceRequest). 2) quantityQuantity can be used for quantities such as "1 instance per week" or "7 units per week". quantityRatio can be used for quantities such as "1 instance per hour" or "7 units per day". 3) value is a decimal, and unit is a text. 4) numerator and denominator can be used for quantities with an interval. 5) See the "qty-unit-interval" spreadsheet for additional examples. 6) Please also consider other units of measurement. E.g. if quantity is meant to be per day, start and end date. E.g. if quantity is meant to be per hour, start and end time. 7) Give ServiceRequest.quantity a start and end date if occurrenceTiming is sufficiently complex. The end-date, or one can use occurrenceTiming.bounds. 8) 2023 on occurrenceTiming.bounds. 9) occurrenceTiming.timeOf
Service Information	Unit of Service Type	A named quantity in terms of which services are measured or specified, used as a standard measurement of like services. Values include: minute(s), 8 hour(s), quarter hour(s), hour(s), half day(s), full day(s), day(s), week(s), month(s), dollar(s), meal(s), mile(s), visit(s)/session(s), installation(s), none, other (free text). This element is slated to be used in conjunction with Service Unit Quantity interval and Service Unit Quantity elements to form a full description of how often a service is provided. For example, a service being provided 7 units per week, the Unit of Service Type	see above	see above	see above

		= "units". For a service being provided 8 hours a day, the Unit of Service Type = "hours".			
Service Information	Service Unit Quantity Interval	A period of time corresponding to the quantity of service(s) indicated. Values include: per day, per week, per month, per year, one time only, other (free text). This element is slated to be used in conjunction with Unit of Service Type and Service Unit Quantity elements to form a full description of how often a service is provided. For example, a service being provided 7 units per week, the Service Unit Quantity Interval = "per week". For a service being provided 8 hours a day, the Service Unit Quantity Interval = "per day".	see above	see above	see above
Service Information	Service Rate per Unit	The rate of one unit for a service.	CarePlan → activity → reference(ServiceRequest) ServiceRequest → supportingInfo(Claim) Claim → item → unitPrice	CarePlan ...activity 0..*reference(ServiceRequest) 0..1supportingInfo(Claim) 0..*item 0..*unitPrice 0..1	1) Will use CarePlan → activity 2) item maps to a service 3) unitPrice contains the total cost per one unit of service 4) unitPrice is of type Money, a complex type and inherits from Quantity 5) Workgroup in charge of the Claim workgroup to develop a potential approach is to use unitPrice since that reflects what health plan is being asked for.
Service Information	Total Cost of Service	The total cost of a service for the plan.	CarePlan → activity → reference(ServiceRequest) ServiceRequest → supportingInfo(Claim) Claim → item → net	CarePlan ...activity 0..*reference(ServiceRequest) 0..1supportingInfo(Claim) 0..*item 0..*net 0..1	1) Will use CarePlan → activity 2) item maps to a service 3) net is the total cost of service 4) net is of type Money, a complex type and inherits from Quantity 5) See above.
Service Provider Information	Support Planner Name	The name of the person (e.g., Case Manager, Care Coordinator, Plan Coordinator) who helped develop the plan.	CarePlan → author(Patient Practitioner PractitionerRole RelatedPerson Organization CareTeam) Practitioner Patient RelatedPerson → name → family Practitioner Patient RelatedPerson → name → given Practitioner Patient RelatedPerson → name → text Organization CareTeam → name	CarePlan ...author(Patient Practitioner RelatedPerson) 0..1name 0..*family 0..1given 0..*text 0..1 CarePlan ...author(Organization CareTeam) 0..1name 0..1	1) Will use CarePlan → author 2) Patient (in self-directed plan) and PractitionerRole (in care plan being developed) all include name. 3) PractitionerRole should include name of whom the Practitioner works for 4) given is used for both Patient and PractitionerRole. 5) family is a string with no spaces 6) text is a string that contains elements 7) The values for Support Planner Name would include
Service Provider Information	Support Planner Phone Number	The primary phone number (and extension when applicable) of the support planner.	CarePlan → author(Patient Practitioner PractitionerRole RelatedPerson Organization CareTeam) Patient Practitioner PractitionerRole RelatedPerson Organization CareTeam → telecom → system Patient Practitioner PractitionerRole RelatedPerson Organization CareTeam → telecom → value	CarePlan ...author(Patient Practitioner PractitionerRole RelatedPerson Organization CareTeam) 0..1telecom 0..*system 0..1value 0..1	1) Will use CarePlan → author 2) Patient (in self-directed plan) and PractitionerRole (in care plan being developed) all include name. 3) PractitionerRole should include name of whom the Practitioner works for 4) telecom is of type ContactInfo (https://www.hl7.org/fhir/ContactInfo) which contains elements 5) system is required if value is fax, email, pager, url, sms, etc. 6) Per FHIR, phone # should be in the value

					E.123, so "(555) 675 574"
Service Provider Information	Service Provider Name	The name of the entity or individual providing the service. For paid services use the organization/agency name, for non-paid services use the first and last name of the individual providing the service.	CarePlan → activity → reference(ServiceRequest) ServiceRequest → performer(Practitioner PractitionerRole Organization Patient Device RelatedPerson HealthcareService CareTeam) Practitioner PractitionerRole CareTeam Organization Patient Device RelatedPerson HealthcareService → name	CarePlan ...activity 0..*reference(ServiceRequest) 0..1performer(Practitioner PractitionerRole Patient Device RelatedPerson HealthcareService CareTeam) 0..*name 0..1 -----performer(Organization) 0..*name 1	1) Will use CarePlan → activity reference(ServiceRequest), and perform Organization or HealthcareService available in FHIR, but may use eLTSS Dataset element reference an Organization services, and RelatedPerson 3) Organization → name strings with the organization 4) RelatedPerson → name includes strings for the person 6) name is required by US Core 7) The values for Service Printed Name would include
Service Provider Information	Service Provider Phone Number	The primary phone number (and extension when applicable) of the service provider.	CarePlan → activity → reference(ServiceRequest) ServiceRequest → performer(Practitioner PractitionerRole Organization Patient Device RelatedPerson HealthcareService CareTeam) Practitioner PractitionerRole CareTeam Organization Patient Device RelatedPerson HealthcareService → telecom → system Practitioner PractitionerRole CareTeam Organization Patient Device RelatedPerson HealthcareService → telecom → value	CarePlan ...activity 0..*reference(ServiceRequest) 0..1performer(Practitioner PractitionerRole Patient Device RelatedPerson HealthcareService CareTeam) 0..*telecom 0..*system 0..1value 0..1 -----performer(Organization) 0..*telecom 1..*system 0..1value 1	1) Will use CarePlan → activity reference(ServiceRequest), and perform Organization or HealthcareService available in FHIR, but may use eLTSS Dataset element reference an Organization services, and RelatedPerson 3) telecom is of type Contact (https://www.hl7.org/fhir/Contact which contains elements 4) system is required if value fax, email, pager, url, sms 5) Per FHIR, phone # should be E.123, so "(555) 675 574" 6) US Core requires at least telecom for an Organization
Service Provider Information	Non-Paid Service Provider Relationship	The relationship (e.g., spouse, neighbor, guardian, daughter) of the individual providing a non-paid service or support to the person.	CarePlan → activity → reference(ServiceRequest) ServiceRequest → performer(RelatedPerson) RelatedPerson → relationship	CarePlan ...activity 0..*reference(ServiceRequest) 0..1performer(RelatedPerson) 0..*relationship 0..*	1) Will use CarePlan → activity reference(ServiceRequest), and perform Organization or HealthcareService available in FHIR, but may use eLTSS Dataset element reference a RelatedPerson 3) relationship is a Codeable preferred value set whose PatientRelationshipType is https://www.hl7.org/fhir/long and detailed, for example stepsister, half-sister, twin sister.

1.3.1.2 R4 useful elements

Data Requirements Not Specific to eLTSS Dataset Data Elements This section documents data elements that are mandatory per FHIR XML schemas or US Core requirements, but that do not align with individual eLTSS Dataset data elements.					
FHIR Data Element Name Requirement Source	Data Element Definition	FHIR R4 Resource Element(s)	FHIR R4 Resource Element Cardinality (with US Core Constraints)	Additional Mapping Details	
CarePlan Status FHIR US Core	Indicates whether the plan is currently being acted upon, represents future intentions or is now a historical record.	CarePlan → status	CarePlan ...status 1	1) status is required by both FHIR and US Core, and must use the RequestStatus value set (http://hl7.org/fhir/valueset-request-status.html). Possible values are: draft, active, suspended, completed, entered-in-error, cancelled, and unknown.	
CarePlan Intent FHIR US Core	Indicates the level of authority/intentionality associated with the care plan and where the care plan fits into the workflow chain.	CarePlan → intent	CarePlan ...intent 1	1) intent is required by both FHIR and US Core, and must use the CarePlanIntent value set (http://hl7.org/fhir/valueset-care-plan-intent.html). Possible values are: proposal, plan, order, and option.	
CarePlan Narrative Summary US Core	Text summary of the resource, for human interpretation. The narrative is an XHTML fragment with a flag to indicate its relationship to the data.	CarePlan → text → status CarePlan → text → div	CarePlan ...text 1status 1div 1	1) text is required by US Core. 2) status is required by FHIR and must use the NarrativeStatus value set (http://hl7.org/fhir/us/core/2019Jan/ValueSet-us-core-narrative-status.html). Possible values are: generated, additional. 3) div is required by FHIR and contains limited xhtml content that contains only the basic html formatting elements and attributes.	
CarePlan Category US Core	Identifies what "kind" of plan this is to support differentiation between multiple co-existing plans; e.g. "Home health", "psychiatric", "asthma", "disease management", "wellness plan", etc.	CarePlan → category → coding → system CarePlan → category → coding → code	CarePlan ...category 1..*coding 1..*system 1code 1	1) Per US Core, one category must appear, and must include system with the value "http://hl7.org/fhir/us/core/CodeSystem/careplan-category" and code with the value "assess-plan". 2) US Core does not restrict the number of additional category elements that may appear.	
CarePlan Activity Status FHIR	Identifies what progress is being made for the specific activity.	CarePlan → activity → reference(Resource) → status and CarePlan → activity → progress	CarePlan ...activityreference(Resource)status 1 and CarePlan ...activity	1) status is required by FHIR in Resources Reference by CarePlan.activity.reference. Possible values are: not-started, scheduled, in-progress, on-hold, completed, cancelled, stopped, unknown, and entered-in-error. 2) There is also CarePlan.activity.progress to add	

			progress	a free-text description of the progress, or note. CarePlan.activity.progress is an Annotation data type in FHIR, this means it can be dated and contain the identification of the person who uttered the text. This might be used, for example, when the status stays in the same state, i.e. 'in-progress,' but where there is a evolution of that progress.
CareTeam Status US Core	Indicates the current state of the care team.	CareTeam → status	CareTeam ...status 1	1) status is required by US Core, and must use the CareTeamStatus value set. Possible values are: proposed, active, suspended, inactive, and entered-in-error.
CareTeam Subject US Core	Who care team is for.	CareTeam → subject(Patient)	CareTeam ...subject 1	1) US Core requires one reference to a Patient using subject.
CareTeam Member US Core	Identifies all people and organizations who are expected to be involved in the care team.	CareTeam → participant → member	CareTeam ...participant 1..*member 1	1) US Core requires care team members be listed in CareTeam → participant → member. 2) Note that the Plan Monitor eLTSS Dataset data element utilizes a participant → member as well, and this is documented in the eLTSS element mapping.
CareTeam Participant Role US Core	Indicates specific responsibility of an individual within the care team, such as "Primary care physician", "Trained social worker counselor", "Caregiver", etc.	CareTeam → participant → role	CareTeam ...participant 1..*role 1	1) US Core requires each participant in the CareTeam have a role defined in the "CareTeam Provider Role Value Set" which includes values from NUCC Health Care Provider Taxonomy Code Set for providers and SNOMED-CT for non-clinical and organization roles. 2) Note that the Plan Monitor eLTSS Dataset data element utilizes a participant role as well, and this is documented in the eLTSS element mapping.
Claim Created FHIR	The date this resource was created.	Claim → created	Claim ...created 1	1) created is required by FHIR. Could use date signers signed or agency authorized. Suggest using date/time that signers signed.
Claim Insurance FHIR	Financial instruments for reimbursement for the health care products and services specified on the claim.	Claim → insurance	Claim ...insurance 1	1) insurance is required by FHIR.
Claim Insurance Sequence FHIR	A number to uniquely identify insurance entries and provide a sequence of coverages to convey coordination of benefit order.	Claim → insurance → sequence	Claim ...insurance 1sequence 1	1) sequence is required by FHIR and is a positiveInt. Suggest using "1".
Claim Insurance Focal FHIR	A flag to indicate that this Coverage is to be used for adjudication of this claim when set to true.	Claim → insurance → focal	Claim ...insurance 1focal 1	1) focal is required by FHIR and is a boolean. Suggest using "true".
Claim Insurance Coverage FHIR	Reference to the insurance card level information contained in the Coverage resource. The coverage issuing insurer will use these details to locate the patient's actual coverage within the insurer's information system.	Claim → insurance → coverage	Claim ...insurance 1coverage 1	1) coverage is required by FHIR and references Coverage.
Claim Item ProductOrService FHIR	When the value is a group code then this item collects a set of related claim details, otherwise this contains the product, service, drug or other billing code for the item.	Claim → item → productOrService	Claim ...item 0..*productOrService 1	1) productOrService is required by FHIR and must use the USCLS Codes value set (http://hl7.org/fhir/valueset-service-uscls.html). Suggest using the value "99555" for expense.
Claim Patient FHIR	The party to whom the professional services and/or products have been supplied or are being considered and for whom actual or forecast reimbursement is sought.	Claim → patient	Claim ...patient 1	1) patient is required by FHIR and references Patient.
Claim Priority FHIR	The provider-required urgency of processing the request.	Claim → priority	Claim ...priority 1	1) priority is required by FHIR and must use the Process Priority Codes value set (http://hl7.org/fhir/valueset-process-priority.html). Possible values are: stat, normal, deferred. Suggest using "normal".
Claim Provider FHIR	The provider which is responsible for the claim, predetermination or preauthorization.	Claim → provider	Claim ...provider 1	1) provider is required by FHIR and references Practitioner, PractitionerRole, Organization. Suggest using Practitioner or Organization.
Claim Status FHIR	The status of the resource instance.	Claim → status	Claim ...status 1	1) status is required by FHIR, and must use the Financial Resource Status Codes value set (http://hl7.org/fhir/valueset-fm-status.html). Possible values are: active, cancelled, draft, entered-in-error. Suggest using "active".
Claim Type FHIR	The category of claim, e.g. oral, pharmacy, vision, institutional, professional.	Claim → type	Claim ...type 1	1) type is required by FHIR, and contains the extensible Claim Type Codes value set (http://hl7.org/fhir/valueset-claim-type.html). Possible values are: institutional, oral, pharmacy, professional, vision. Could use "professional", could extend code list, or could use text data element that is part of codeable concept.
Claim Use FHIR	A code to indicate whether the nature of the request is: to request adjudication of products and services previously rendered; or requesting authorization and adjudication for provision in the future; or requesting the non-binding adjudication of the listed products and services which could be provided in the future.	Claim → use	Claim ...use 1	1) use is required by FHIR, and must use the Use value set (http://hl7.org/fhir/valueset-claim-use.html). Possible values are: claim, preauthorization, predetermination. Suggest using "preauthorization"
Claim Item Sequence FHIR	A number to uniquely identify item entries	Claim → item → sequence	Claim ...item 0..*	1) sequence is required by FHIR, and is a positive integer.

			sequence 1	
Condition Verification Status US Core	The verification status to support the clinical status of the condition.	Condition → verificationStatus	Condition ...verificationStatus 1	1) verificationStatus is required by US Core, and must use the ConditionVerificationStatus value set. Possible values are: provisional, differential, confirmed, refuted, entered-in-error, and unknown.
Condition Clinical Status US Core	The clinical status of the condition.	Condition → clinicalStatus	Condition ...clinicalStatus 1	1) clinicalStatus is required by US Core if the value of verificationStatus is not "entered-in-error". FHIR requires that the values come from the Condition Clinical Status Codes value set, which has values: active, recurrence, inactive, remission, and resolved.
Condition Subject US Core	Who has the condition.	Condition → subject(Patient)	Condition ...subject 1	1) subject is required by US Core, and is a reference to a Patient.
Coverage Beneficiary FHIR	The party who benefits from the insurance coverage; the patient when products and/or services are provided.	Coverage → beneficiary	Coverage ...beneficiary 1	1) beneficiary is required by FHIR, and is a reference to a Patient.
Coverage Payor FHIR	The program or plan underwriter or payor including both insurance and non-insurance agreements, such as patient-pay agreements.	Coverage → payor	Coverage ...payor 1	1) payor is required by FHIR, and is a reference to a Organization, Patient, RelatedPerson.
Coverage Status FHIR	The status of the resource instance.	Coverage → status	Coverage ...status 1	1) status is required by FHIR and must use the Financial Resource Status Codes (http://hl7.org/fhir/valueset-fm-status.html). Values include: active, cancelled, draft, entered-in-error. Suggest using active.
DocumentReference Status FHIR	The status of this document reference.	DocumentReference → status	DocumentReference ...status 1	1) status is required by FHIR and must use the DocumentReferenceStatus value set. Possible values are: current, superseded, and entered-in-error.
Encounter Status FHIR	Indicates the status of the encounter.	Encounter → status	Encounter ...status 1	1) status is required by FHIR, and must use the EncounterStatus value set. Possible values are: planned, arrived, triaged, in-progress, onleave, finished, cancelled, entered-in-error, and unknown.
Encounter Class FHIR	Indicates the classification of patient encounter.	Encounter → class → code	Encounter ...class 1code 0..1	1) class is required by FHIR, and is defined to use the extensible V3 Value SetActEncounterCode value set. Possible values are: ambulatory, emergency, field, home health, inpatient encounter, inpatient acute, inpatient non-acute, observation encounter, pre-admission, short stay, and virtual.
Encounter Type FHIR	Specific type of encounter (e.g. e-mail consultation, surgical day-care, skilled nursing, rehabilitation).	Encounter -> type	Encounter ...type 1	1) type is required by US Core and codes SHALL be taken from US Core Encounter Type; other codes may be used where these codes are not suitable.
EpisodeOfCare Status FHIR	Indicates the status of the episode of care.	EpisodeOfCare → status	EpisodeOfCare ...status 0..1	1) status is required by FHIR, and must use the EpisodeOfCareStatus value set. Possible values are: planned, waitlist, active, onhold, finished, and cancelled.
EpisodeOfCare Patient FHIR	The patient who is the focus of this episode of care.	EpisodeOfCare → patient(Patient)	EpisodeOfCare ...patient 0..1	1) patient is required by FHIR, and is a reference to a Patient.
Goal LifecycleStatus FHIR US Core	The state of the goal throughout its lifecycle.	Goal → lifecycleStatus	Goal 0..* ...lifecycleStatus 1	1) lifecycleStatus is required by both FHIR and US Core, and must use the GoalStatus value set which has values: proposed, accepted, in-progress, etc.
Goal Subject FHIR US Core	Identifies the patient, group or organization for whom the goal is being established.	Goal → subject(Patient)	Goal ...subject 1	1) subject is required by both FHIR and US Core, and is a reference to a Patient.
Location Name US Core	Name of the location as used by humans. Does not need to be unique.	Location → name	Location ...name 1	1) US Core requires a name for the Location.
Observation Status FHIR	The status of the result value.	Observation → status	Observation ...status 1	1) status is required by FHIR, and the values are: final, preliminary, registered, cancelled, amended, corrected, entered-in-error, and unknown.
Organization Identifier US Core	Identifier for the organization that is used to identify the organization across multiple disparate systems.	Organization → identifier	Organization ...identifier 1..*	1) At least one identifier is required by US Core. NPI is preferred. Tax id is allowed. Local id is allowed in addition to 'authoritative' identifier.
Organization Active Indicator US Core	Whether the organization's record is still in active use.	Organization → active	Organization ...active 1	1) US Core requires one boolean value in active.
Organization Address US Core	An address for the organization.	Organization → address	Organization ...address 1..*	1) US Core requires at least one address. The contents of address are not specified by US Core.
Patient Administrative Gender US Core	The gender that the patient is considered to have for administration and record keeping purposes.	Patient → gender	Patient ...gender 1	1) gender is required by US Core and must use the AdministrativeGender value set. Possible values are: male, female, other, and unknown.
Practitioner Identifier US Core	An identifier that applies to this person in this role.	Practitioner → identifier	Practitioner ...identifier 1..*	1) At least one identifier is required by US Core. NPI is preferred. Tax id is allowed. Local id is allowed in addition to 'authoritative' identifier.
Practitioner Name US Core	The name(s) associated with the practitioner.	Practitioner → name	Practitioner ...name 1	1) US Core requires one name for a Practitioner.
QuestionnaireResponse	The position of the questionnaire response within its	QuestionnaireResponse	QuestionnaireResponse	1) status is required by FHIR and must use the

Status FHIR	overall lifecycle.	→ status	...status 1	QuestionnaireResponseStatus value set. Possible values are: in-progress, completed, amended, entered-in-error, and stopped.
Questionnaire Status FHIR	The status of this questionnaire. Enables tracking the life-cycle of the content.	Questionnaire → status	Questionnaire ...status 1	1) status is required by FHIR and must use the PublicationStatus value set. Possible values are: draft, active, retired, and unknown.
RelatedPerson Patient FHIR	The patient this person is related to.	RelatedPerson → patient(Patient)	RelatedPerson ...patient 1	1) patient is required by FHIR.
RiskAssessment Status FHIR	The status of the RiskAssessment, using the same statuses as an Observation.	RiskAssessment → status	RiskAssessment ...status 1	1) status is required by FHIR, and must use the ObservationStatus value set. Possible values are: registered, preliminary, final, amended, corrected, cancelled, entered-in-error and unknown.
RiskAssessment Subject FHIR	Identifies the patient, group or organization for whom the goal is being established.	RiskAssessment → subject(Patient)	RiskAssessment ...subject 1	1) subject is required by FHIR, and is a reference to a Patient. (Optional prior to R4 version 3.4.0.)
ServiceRequest Intent FHIR	Whether the request is a proposal, plan, an original order or a reflex order.	ServiceRequest → intent	ServiceRequest ...intent 1	1) intent is required by FHIR, and must use the RequestIntent value set. Possible values are: proposal, plan, order, original-order, reflex-order, filler-order, instance-order and option.
ServiceRequest Status FHIR	The status of the request.	ServiceRequest → status	ServiceRequest ...status 0..1	1) status is required by FHIR, and must use the RequestStatus value set which has values: draft, active, suspended, completed, entered-in-error, and cancelled.
ServiceRequest Subject FHIR	On whom or what the service is to be performed.	ServiceRequest → subject(Patient)	ServiceRequest ...subject 0..1	1) subject is required by FHIR, and is a reference to a Patient.

1.3.1.3 Units

Definitions for Columns of the eLTSS Dataset Element Mapping Spreadsheet	
Column	Definition
eLTSS Grouping	Indicates the top-level group of data elements defined in the eLTSS Dataset.
eLTSS Data Element Name	Name of the data element as defined in the eLTSS Dataset.
FHIR Data Element Name Requirement Source	FHIR resource and data element name. Italics indicates whether mandatory requirement is from FHIR and/or US Core.
Data Element Definition	eLTSS element mapping tab: The definition of the data element as defined in the eLTSS Dataset. Includes examples, potential lists of values, and usage notes where applicable. mandatory FHIR data elements tab: The definition of the data element as defined in FHIR.
eLTSS Datatype / Format	The type of data for the eLTSS Dataset data element, including format where applicable.
FHIR R4 Resource Element(s)	The data elements from FHIR Release 4 that correspond to the eLTSS Dataset data element. The "→" notation indicates the hierarchy. So for example, "Patient → name → family" means that the mapping includes the FHIR "Patient" data element which has the FHIR data element "name" as its child, and "name" has the FHIR data element "family" as its child. For FHIR data elements that are references to other FHIR resources, the type of resource that is being referenced is included in parenthesis. So for example, the notation "Contract → signer → party(Patient)" indicates that "party" data element references a Patient resource. Where the reference can be to different types of resource, the " " is used, for example "CareTeam → participant → member(Practitioner Patient)" indicates that the "member" data element can reference either a Practitioner resource or a Patient resource.
FHIR R4 Resource Element Cardinality (with US Core Constraints)	The cardinality of each data element listed in this column. US Core requires a number of data elements, so cardinality may different between the FHIR specification and US Core requirements. "1" means the data element is mandatory and can appear only once. "0..1" means the data element is optional, and if it occurs can only occur once. "0..*" means the data element is optional, and if it occurs can occur any number of times. "1..*" means the data element is mandatory, and if it occurs can occur any number of times. "0..x" where 'x' is a number means the data element is optional, and if it occurs can occur up to 'x' number of times.
Additional Mapping Details	Provides addition detail regarding the data mapping, including references that are required to link all the data elements, information on data types, notes such as why the additional related data elements may be useful, values available in a referenced code list, etc.

Quantity, Unit and Interval Examples				FHIR quantityQuantity Elements			FHIR quantityRatio Elements		
	eLTSS Dataset Elements			value	unit	unit code and system	numerator value	numerator unit	numerator unit code and system
Example	Svc Unit Qty	Unit of Svc Type	Svc Unit Qty Interval						
8 hours a day	8	hour	per day				8	Hour	hr UCUM (http://unitsofmeasure.org)
adult day care - full day every day	5	full day	per week				5	full day	d UCUM (http://unitsofmeasure.org)
adult day care - half day twice a week	2	half day	per week				2	Half day	d/2 UCUM (http://unitsofmeasure.org)

30 minutes a day	30	minute	per day				30	Minute	min UCUM (http://unitsofmeasure.org)
5 quarter hours weekly	5	quarter hour	per week				1	Quarter hour	hr/4 UCUM (http://unitsofmeasure.org)
1 day a week	1	day	per week				1	Day	d UCUM (http://unitsofmeasure.org)
1 visit a week	1	visit	per week				1	Visit	C25716 NCIT (http://ncicb.nci.nih.gov/xml/owl/EVS/Thesaurus.owl)
10 physical therapy sessions	10	visit	(blank)	10	Visit	C25716 NCIT (http://ncicb.nci.nih.gov/xml/owl/EVS/Thesaurus.owl)			
5 meals a week	5	meal	per week				5	Meal	C80248 NCIT (http://ncicb.nci.nih.gov/xml/owl/EVS/Thesaurus.owl)
50 meals	50	meal	(blank)	50	Meal	C80248 NCIT (http://ncicb.nci.nih.gov/xml/owl/EVS/Thesaurus.owl)			
Hospital bed for the home (delivered)	1	none	one time only	1					
Doorbell installation for a deaf person	1	install	one time only	1	Deploy	C81906 NCIT (http://ncicb.nci.nih.gov/xml/owl/EVS/Thesaurus.owl)			
Transportation to the doctor 10 times	10	other (trips)	(blank)	10	Transportation	C141286 NCIT (http://ncicb.nci.nih.gov/xml/owl/EVS/Thesaurus.owl)			
Transportation to church every week	1	other (trips)	per week				1	Transportation	C141286 NCIT (http://ncicb.nci.nih.gov/xml/owl/EVS/Thesaurus.owl)
Transportation	100	mile	per week				100	Mile	C71183 NCIT (http://ncicb.nci.nih.gov/xml/owl/EVS/Thesaurus.owl)
Medical Alert System Monthly Payment	9.95	dollar	per month				9.95	Dollar	C173108 NCIT (http://ncicb.nci.nih.gov/xml/owl/EVS/Thesaurus.owl)