

NumPy

BILD 62

Before we dive into new content, let's see if we can apply what we've learned to some *real* code documentation

Class

Template for objects

Defines properties for objects
(attributes)

Defines behaviors for objects
(methods)

Object

Instance of a class

Has attributes that are defined
differently in each instance (using
`__init__` method) or that are always
inherited from the Class

```
a      b  
8  
9 class Words(Base):  
10     """A class for collecting and analyzing words data for specified terms list(s).  
11  
12     Attributes  
13     -----  
14     results : list of Articles  
15         Results of 'Words' data for each search term.  
16     labels : list of str  
17  
18     def __init__(self):  
19         """Initialize LISC Words object."""  
20  
21     self.results = list()  
22     self.meta_data = None
```

Possible matches:

1. Method that will execute whenever a class instance is created
2. Inherited class
3. Name of the class we are defining here
4. Attributes that will update when class is initialized

Feature Extraction

The `EphysFeatureExtractor` class calculates electrophysiology features from cell recordings. `extract_cell_features()` can be used to extract the precise feature values available in the Cell Types Database:

```
from allensdk.core.cell_types_cache import CellTypesCache
from allensdk.ephys.extract_cell_features import extract_cell_features
from collections import defaultdict

# initialize the cache
ctc = CellTypesCache(manifest_file='cell_types/manifest.json')

# pick a cell to analyze
specimen_id = 324257146

# download the ephys data and sweep metadata
data_set = ctc.get_ephys_data(specimen_id)
sweeps = ctc.get_ephys_sweeps(specimen_id)
```

b


a

c

Possible matches:

1. Modules we're importing
2. Executing method of class CellTypesCache
3. Instance of class CellTypesCache

From https://alleninstitute.github.io/AllenSDK/cell_types.html



Object-oriented programming

This is how Python containers typically work, but saving all of our data in lists isn't great for performance or memory.

NumPy is a tool for computing with big arrays, and is much more efficient.*

* [for details, see this breakdown](#)

STEP 1.

```
x = np.zeros(3)
```

x




STEP 2.

```
y = x
```


x

y




STEP 3a.

```
y = y+1
```



STEP 3b.

```
y[0] = y[0]+1
```



Objectives for today

- Install and import packages for Python
 - Create NumPy arrays
 - Execute methods & access attributes of arrays
 - Demonstrate how images can be stored in arrays
-

Python supports **modular programming** in multiple ways.

Functions and **classes** are examples of tools for low-level modular programming.

Python **modules** are a higher-level modular programming construct, where we can collect related variables, functions and classes in a module.

Modules are often bundled up into **packages**.

Packages in Python

Python's standard library works for some purposes, but there are many very useful packages for additional purposes:

- **numpy** (<http://numpy.scipy.org>): numerical Python
- **scipy** (<http://www.scipy.org>): scientific Python; built on numpy
- **matplotlib** (<http://www.matplotlib.org>) graphics library



Installing packages & importing modules

To install packages, use

```
$ pip install PACKAGE
```

You can then import modules from the package with

```
>>> from PACKAGE import MODULE
```

to see all of the modules available, use

```
>>> print(dir(MODULE))
```


We typically won't need to do this in the DataHub, because many packages have been installed into our container. However, you *may* need to do this for local notebook operation.

Module	Built-In	Description
csv	Yes	Aids in the reading, writing, and analysis of CSV files.
zipfile	Yes	Aids in the creation and extraction of compressed ZIP archive files.
matplotlib	No	Graphics library for plotting
plotly	No	A graphics library used for creating interactive plots for the web.
seaborn	No	A graphics library built on top of matplotlib with high-quality plots
pandas	No	A data processing library that specializes in data frames, which are analogous to spreadsheets.
scikit-learn	No	Contains basic tools for machine learning (i.e., helping to learn from data and make predictions).
numpy	No	Offers highly efficient data processing.
pygame	No	A game programming library that helps to build interactive, graphical games in Python.
django	No	Web development library that aids in designing websites and web applications.

Common Python modules — ones we'll work with are highlighted


We're learning how to deal with more and more complex data

```
data_point = 8.02
```



single variable
(int, float,
string)

```
data = [8.38, 3.34, 6.35]
```



data structure
(list, tuple,
dictionary)

```
big_data = [data_1, data_2, ...]
```



array
or **dataframe**

NumPy is the fundamental package for scientific computing with Python

- A numpy **array** is a grid of values which are all the same type (they're **homogenous**)
- Useful attributes:
 - **ndim** = # of dimensions
 - **shape** = a tuple of integers giving the size of the array along each dimension
 - **dtype** = type of data

Numpy Arrays

my_array = 1D array

3	2	4	1
---	---	---	---

```
my_array[0] = 3
```

```
my_array.ndim = 1
```

```
my_array.shape = (4,)
```

```
my_array.size = 4
```

2D array

3	2	4	1
1	2	5	3

how to index
2D NumPy
arrays

```
my_array[1,3] = 3
```

```
my_array.ndim = 2
```

```
my_array.shape = (2,4)
```

```
my_array.size = 8
```

The diagram illustrates a 3x3 numpy array with indices 0, 1, and 2. The array is represented as follows:

	0	1	2
[A, B, C]	▼	▼	▼
[D, E, F]			
[G, H, I]			
	0	1	2

Indices 0, 1, and 2 are shown above the array, with arrows pointing to the first element of each row. To the right of the array, the elements are indexed by their position in the flattened array.

`data = [[A, B, C], [D, E, F], [G, H, I]]`

Indices 0, 1, 2 are shown above the array, with arrows pointing to the first element of each row.

`data[0, 0] = A data[0, 1] = B data[0, 2] = C`

`data[1, 0] = D data[1, 1] = E data[1, 2] = F`

`data[2, 0] = G data[2, 1] = H data[2, 2] = I`

Indexing numpy arrays

Image from [Programming with Python: Analyzing Patient Data](#)

Slicing & indexing NumPy arrays works *almost* the same as with Python lists

However, be aware that if you slice an array, it changes the original array.

If you need to copy, you need to explicitly do:

```
v3 = v[2:4].copy()
```

In this case, we would not change original array (v).

```
In [33]: v = np.random.random((5,4))  
v
```

```
Out[33]: array([[0.70782755, 0.1080363 , 0.63931318, 0.30594658],  
[0.23089631, 0.58842692, 0.03879193, 0.56396161],  
[0.92250973, 0.54564224, 0.89690301, 0.76679512],  
[0.83668402, 0.18075749, 0.54652922, 0.03487156],  
[0.48236452, 0.77258043, 0.61857768, 0.66614441]])
```

```
In [35]: v2 = v[2:4]  
v2
```

```
Out[35]: array([[0.92250973, 0.54564224, 0.89690301, 0.76679512],  
[0.83668402, 0.18075749, 0.54652922, 0.03487156]])
```

```
In [37]: v2[1,3] = 2
```

```
In [38]: v
```

```
Out[38]: array([[0.70782755, 0.1080363 , 0.63931318, 0.30594658],  
[0.23089631, 0.58842692, 0.03879193, 0.56396161],  
[0.92250973, 0.54564224, 0.89690301, 0.76679512],  
[0.83668402, 0.18075749, 0.54652922, 2. ],  
[0.48236452, 0.77258043, 0.61857768, 0.66614441]])
```

You can also use **lists** & **booleans** to index NumPy arrays

```
my_array[[1,2,3]]
```

```
my_array[my_array > 1]
```

We can also use this to selectively operate on values in the array that meet our criteria:

```
my_array[my_array > 1] = my_array[my_array > 1] * 2
```

Useful NumPy functions

`np.zeros()`

`np.empty()`

`np.linspace()`

`np.arange()`

`np.reshape()`

`np.random.random()`

`np.vstack()`

`np.hstack()`

`np.save()`

`np.load()`

See [here](#) for a useful Numpy overview.

Key NumPy takeaways

- Import a library into a program using `import libraryname`
- Use the NumPy library to work with arrays in Python.
- The expression `array.shape` gives the shape of an array.
- Use `array[x, y]` to select a single element from a 2D array.
- Array indices start at 0, not 1.
- Use `low:high` to specify a slice that includes the indices from low to high-1.
- Use `np.mean(array)`, `np.max(array)`, and `np.min(array)` to calculate simple statistics.
- Use `np.mean(array, axis=0)` or `np.mean(array, axis=1)` to calculate statistics across the specified axis.

Objectives for today

- Install and import packages for Python
 - Create NumPy arrays
 - Execute methods & access attributes of arrays
 - **Demonstrate how images can be stored in arrays**
-





Figure 18.1 (Plate 5). Examples of a variety of different kinds of images used in biology. Shown from left to right are: a microscope image of a mammalian cell culture (courtesy Dr. Anja Winter, University of Leicester); a red-green fluorescence microscope image of an oocyte and its nucleus (courtesy Dr. Melina Schuh, MRC Laboratory of Molecular Biology); a two-dimensional electrophoresis gel of a plant proteome (courtesy Prof. Paul Dupree, University of Cambridge); an image of a DNA microarray (courtesy Karen Howarth, University of Cambridge); a protein crystal that has been grown for structure determination by X-ray crystallography (courtesy Dr. Aleksandra Watson, University of Cambridge).

We use lots of images in biology
Figure from [Python Programming for Biology](#)

What are images, anyway?


Gray scale images
mean each pixel has
just one value



What are images, anyway?

Images can be represented as 2D NumPy arrays

By convention [0,0] is the top left corner



Resources

Numerical & Scientific Computing with Python: Introduction into NumPy

Lecture-2-Numpy.ipynb

Programming with Python: Analyzing Patient Data

More about the comparison between Numpy arrays & NumPy

<https://webcourses.ucf.edu/courses/1249560/pages/python-lists-vs-numpy-arrays-what-is-the-difference>