

Quality Control Plan

STOCK-QP-025


HSR602L Screwspike 27 x 165mm

Revision	Date	Author	Checked By	Amendments
A	3/09/2025			Initial Issue

Project	STOCK	Part Number	HSR602L
Specification	SPEC-ACC-Ss8	Drawing Number	HSR602L

Quality Control Plan

Sample [] Trial-production [] Mass production [✓]			Main contact/Tel:			Prepared Date: 3/09/2025		Revise Date:	
Core Team:						Approved date about the project (if necessary):			
						Approved date about the quality (if necessary):			
Supplier: SUDELAN			Supplier No.:		Approved date (if necessary):		Approved date about others (if necessary):		

No.	Description	Characteristic			Method					FAT
		Item	Part Name	Content	Criteria/ Nominal Value / Tolerance	Relevant Standard / Document	Measuring Equipment	Min Sample Frequency	Control Method	
1	Material	1	Raw Material	Tensile Strength	$\geq 500 \text{ MPa}$	SPEC-ACC-Ss8 UIC 864-1V	Universal Testing Machine	1 per batch of raw material	Test report	Document review only
				Yield Strength	$\sigma \geq 300 \text{ MPa}$					
				Elongation	$\delta \geq 20\%$					
2	Finished Product	1	HSR602L	Dimensional Accuracy	Inspection dimensions shown in reference document as per example below: 	HSR602L	Various	Single Sampling Plan, General Inspection Level I, AQL 2.5 (ISO 2859-1)	Test report	Document review only
				Identification	As per drawing		Visual Inspection			
							Coating Thickness	Mean $\geq 55 \mu\text{m}$		