

TEST CERTIFICATE

Name:Screw Spike(class 5.6)

Contract No: 9460

Material: 35K

Specification:27×165

Quantity:2000(Pieces)

Inspection date:2025.10.12



Heat No.	Chemical Composition					Mechanical Properties			Dimension															Coating (hot dipgalv anise)	Result
	C%	Si%	Mn%	P%	S%	Tensile Strength N/mm ²	Yield Point N/mm ²	Elong ation %	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O		
	0.32 ~ 0.38	0.10 ~ 0.35	0.60 ~ 0.90	≤ 0.030	≤ 0.035				Φ 49~51	□ 26.5~ 27.5	□ 28.5~ 29.5	21~23	12~14	31~34	R11	Φ 26.7~ 27.7	36~40	160~ 170	15~19	Φ 21.5~ 22.5	Φ 26.5~ 27.5	64.5~ 65.5	2.5		
	≥500	≥300	≥20																				≥55 μ m		
G5311 04423	0.35	0.15	0.72	0.015	0.003	618	381	22	50.1	26.9	29.2	22.1	12.8	32.8	R11	26.9	38.5	167.4	18.4	22.2	27.2	65.3	2.4	88	Pass
	0.35	0.15	0.72	0.015	0.003	610	363	23	50.2	27.1	29.3	22.3	12.9	33.1	R11	27.1	39.1	168.2	18.1	22.0	27.3	65.1	2.5	71	Pass
	0.35	0.15	0.72	0.015	0.003	629	377	22	50.3	26.8	29.0	22.2	13.0	33.0	R11	27.1	39.3	169.0	17.3	22.1	27.2	65.2	2.5	69	Pass
	0.35	0.15	0.72	0.015	0.003	605	389	24	50.2	27.2	28.9	22.4	12.9	32.9	R11	27.0	38.2	166.8	17.9	22.3	27.1	65.1	2.5	97	Pass
	0.35	0.15	0.72	0.015	0.003	597	357	24	50.1	27.0	29.2	22.2	12.9	33.0	R11	27.2	37.8	166.9	18.5	22.0	27.3	65.3	2.4	78	Pass

We hereby certify, that the material described above has been tested and complies with the terms of the order contract.

Inspector:Zhang-QuanHui

Checking:Yang-LiCheng



江苏沙钢集团有限公司
Jiangsu Shagang Group CO., LTD.
高速线材质量证明书
High-speed Wire Rod Quality Certificate

SG03B-1914E

江苏省张家港市锦丰镇 邮编: 215625
Jinfeng, Zhangjiagang, Jiangsu, P. R. CHINA
TEL: (0512) 58568866, 58568829
FAX: (0512) 58550366, 58550818

订货单位CUSTOMER		用户代码CUSTOMER CODE		合同号CONTRACT NO.	X55A0064Q009
牌号STEEL GRADE	SWRCH35K	提货单号DELIVERY	250521177001	发货日期DATE OF DELIVERY	20250521
交货标准 SPECIFICATION	Q/320582 SGY303-2024	质证书号CERTIFICATE NO.	2505211770 015625	1	签发日期DATE OF ISSUE 20250521
		用途USE			精炼方式REFINING MATHOD 炉外精炼

序号 NO	炉号 HEAT NO.	直径 Dia. mm.	盘数 Coils	重量 kg	化学成分CHEMICAL COMPOSITION %										拉伸试验TENSILE TEST				顶锻 试验 H. T.	硬度 试验 HRB	脱碳层 D. of. D	晶粒度 Micro- Grade	索氏体 Sorbite %	备注 REMARKS			
					C	Si	Mn	P	S	Cr	Ni	Cu			Rm	ReL	A11.3	Z									
					2	2	2	3	3	2	2	2															
1= $\times 10^{-1}$ 2= $\times 10^{-2}$ 3= $\times 10^{-3}$ 4= $\times 10^{-4}$ 5= $\times 10^{-5}$										MPa		%															
1	G531104423	28.0	5	10893	35	15	72	15	3	3	1	1			589			46.0	0	81.00	0.01	8					
2	G533004664	24.0	11	24712	36	14	73	15	2	3	1	2			589			46.0	1/3	81.00	0.01	8					
															590			34.0	0	81.00	0.01	8					
															590			34.0	1/3	81.00	0.01	8					
合计 Total			16	35605	说明 NOTES		1. 本质量证明书适用于合金类线材;本产品不含有任何辐射元素。It is guaranteed that the products don't contain radiochemical imparities. 3. We, SHAGANG, hereby certify that the products specified in the present certificate have been fully processed in china. (facility and address information is stated above). *1. H. T. —Head-colding Test; *2 D. of D. —Depth of Decarburization;																				
综合判定 FINAL RESULT		合格 PASS		注意事项 ATTENTIVE ITEMS		1. 质量证明书复印件不作有效证明文件, 除非盖章; The copy of this Certificate is not valid except stamped. 2. 用户验货后使用如有异议应及时告知炉号、牌号, 并保留实物及标志。Please inform us the steel grade and the heat number of under quanlified material(s) found in inspection on time, and keep the material(s) and the marking card																		质检印章 SEAL 质检专用章		签证人 VISA 周多新	

