

TEST CERTIFICATE

Name:Screw Spike(class 5.6)

Contract No: 9502

Material: 55K

Specification: $\varnothing 24 \times 180$

Quantity:4000(Pieces)

Inspection date:2025.12.22



Heat No.	Chemical Composition					Mechanical Properties			Dimension												Coating (hot dipgalv anise) ≥55 μm	Result
	C%	Si%	Mn%	P%	S%	Tensile Strength N/mm²	Yield Point N/mm²	Elong ation %	A	B	C	D	E	F	G	H	I	J	K	L		
	0.32 ~ 0.38	0.10 ~ 0.35	0.60 ~ 0.90	≤ 0.030	≤ 0.035	≥500	≥300	≥20	Φ 50~51	34.8~ 35.9	36.4~ 38.4	22~23	37~41	Φ 23.6~ 24.8	178~ 182	Φ 23.2~ 25.2	5~15	Φ12	Φ 17.2~ 19.2	13		
G533005941	0.35	0.14	0.73	0.011	0.004	595	361	24	50.2	35.1	37.1	22.3	40.4	24.0	178.9	24.0	8.4	12.4	17.9	13.0	77	Pass
	0.35	0.14	0.73	0.011	0.004	608	385	23	50.4	35.2	37.3	22.3	39.5	24.1	181.3	23.9	7.6	12.5	17.7	12.9	96	Pass
	0.35	0.14	0.73	0.011	0.004	611	390	22	50.2	35.2	37.4	22.4	38.7	23.9	180.6	24.1	6.4	12.3	18.0	13.1	75	Pass
	0.35	0.14	0.73	0.011	0.004	602	377	23	50.4	35.3	37.2	22.2	39.7	24.0	181.1	23.9	8.3	12.4	17.9	13.1	83	Pass
	0.35	0.14	0.73	0.011	0.004	626	398	22	50.3	35.3	37.5	22.4	39.3	24.1	179.6	23.8	7.2	12.2	17.8	13.0	68	Pass

We hereby certify, that the material described above has been tested and complies with the terms of the order contract.

Inspector:Zhang-QuanHui

Checking:Yang-LiCheng



沙 钢

江苏沙钢钢铁有限公司
Jiangsu Shagang Steel CO., LTD.
高速线材质量证明书
High-speed Wire Rod Quality Certificate

SG03B-1914E

江苏省张家港市锦丰镇 邮编: 215625
Jinfeng, Zhangjiagang, Jiangsu, P. R. CHINA
TEL: (0512) 58568866, 58568829
FAX: (0512) 58550366, 58550818

订货单位CUSTOMER		用户代码CUSTOMER CODE		合同号CONTRACT NO.	X57A0064Q010
牌号STEEL GRADE	SWRCH35K	提货单号DELIVERY	250721176001	发货日期DATE OF DELIVERY	20250721
交 货 标 准 SPECIFICATION	Q/320582 SGGY303-2024	质证书号CERTIFICATE NO.	2507211760 019765	1	签发日期DATE OF ISSUE 20250721
		用途USE			精炼方式REFINING MATHOD 炉外精炼

序号 NO	炉号 HEAT NO.	直径 Dia. mm.	盘数 Coils	重量 kg	化学成分CHEMICAL COMPOSITTON %										拉伸试验TENSILE TEST				顶锻 试验 H. T.	硬度 试验 HRB	脱碳层 D. of. D	晶粒度 Micro- Grade	索氏体 Sorbite %	备注 REMARKS		
					C	Si	Mn	P	S	Cr	Ni	Cu			Rm	ReL	A11.3	Z								
					2	2	2	3	3	2	2	2														
1= $\times 10^{-1}$ 2= $\times 10^{-2}$ 3= $\times 10^{-3}$ 4= $\times 10^{-4}$ 5= $\times 10^{-5}$										MPa		%														
1	G533005941	26.0	13	29073	35	14	73	11	4	3	1	2			569 569			41.0 41.0	0 1/3	81.00 83.00	0.01 0.01	8 8				
合计 Total			13	29073	说明 NOTES		1. 本质量证明书适用于合金类线材;本产品不含有任何辐射元素。It is guaranteed that the products don't contain radiochemical imparities. 3. We, SHAGANG, hereby certify that the products specified in the present certificate have been fully processed in china. (facility and address information is stated above. *1. H. T. —Head-colding Test; *2 D. of D. —Depth of Decarburization;																			
综合判定 FINAL RESULT	合格 PASS		注意事项 ATTENTIVE ITEMS		1. 质量证明书复印件不作有效证明文件, 除非盖章; The copy of this Certificate is not valid except stamped. 2. 用户验货后使用如有异议应及时告知炉号、牌号, 并保留实物及标志。Please inform us the steel grade and the heat number of under quanlified material(s) found in inspection on time, and keep the material(s) and the marking card																		质检印章 SEAL		签证人 VISA 	