

TEST CERTIFICATE

Name:Screw Spike(class 5.6)

Contract No: 9431

Material: 35K

Specification: Φ24×145

Quantity:4000(Pieces)

Inspection date:2025.07.28



Heat No.	Chemical Composition					Mechanical Properties			Dimension												Coating (hot dipgalv anise)	Result
	C%	Si%	Mn%	P%	S%	Tensile Strength N/mm ²	Yield Point N/mm ²	Elong ation %	A	B	C	D	E	F	G	H	I	J	K	L		
	0.32 ~ 0.38	0.10 ~ 0.35	0.60 ~ 0.90	≤ 0.030	≤ 0.035				Φ 50~51	34.8~ 35.9	36.4~ 38.4	22~23	30~34	Φ 23.6~ 24.8	140~ 150	Φ 23.2~ 25.2	5~15	Φ12	Φ 17.2~ 19.2	13		
						≥500	≥300	≥20												≥55 μm		
G533005940	0.35	0.12	0.71	0.016	0.003	612	376	22	50.3	35.2	37.4	22.3	31.9	24.0	145.3	23.9	6.5	12.5	17.8	12.1	72	Pass
	0.35	0.12	0.71	0.016	0.003	605	363	23	50.4	35.3	37.5	22.2	32.1	24.2	146.7	24.1	8.2	12.5	18.0	13.0	68	Pass
	0.35	0.12	0.71	0.016	0.003	597	379	24	50.3	35.2	37.3	22.3	32.8	23.9	143.8	24.0	7.1	12.3	17.9	12.9	87	Pass
	0.35	0.12	0.71	0.016	0.003	623	384	22	50.4	35.4	37.5	22.2	30.9	24.1	144.6	23.9	7.5	12.3	18.0	13.0	91	Pass
	0.35	0.12	0.71	0.016	0.003	602	392	23	50.5	35.2	37.3	22.4	31.2	24.1	145.9	24.0	8.5	12.4	18.1	13.1	78	Pass

We hereby certify, that the material described above has been tested and complies with the terms of the order contract.

Inspector:Zhang-QuanHui

Checking:Yang-LiCheng



江苏沙钢钢铁有限公司
Jiangsu Shagang Steel CO., LTD.

高速线材质量证明书

沙 钢

High-speed Wire Rod Quality Certificate

SG03B-1914E

江苏省张家港市锦丰镇 邮编: 215625
Jinfeng, Zhangjiagang, Jiangsu, P. R. CHINA
TEL: (0512) 58568866, 58568829
FAX: (0512) 58550366, 58550818

订货单位CUSTOMER		用户代码CUSTOMER CODE		合同号CONTRACT NO.	X57A0064Q010
牌号STEEL GRADE	SWRCH35K	提货单号DELIVERY	250717200002	发货日期DATE OF DELIVERY	20250718
交 货 标 准 SPECIFICATION	Q/320582 SGY303-2024	质证书号CERTIFICATE NO.	2507172000 028235	1 签发日期DATE OF ISSUE	20250718
		用途USE		精炼方式REFINING MATHOD	炉外精炼

序号 NO	炉号 HEAT NO.	直径 Dia. mm.	盘数 Coils	重量 kg	化学成分CHEMICAL COMPOSITION %										拉伸试验TENSILE TEST				顶锻 试验 H. T.	硬度 试验 HRB	脱碳层 D. of. D	晶粒度 Micro- Grade	索氏体 Sorbite %	备注 REMARKS		
					C	Si	Mn	P	S	Cr	Ni	Cu			Rm	ReL	A11.3	Z								
					2	2	2	3	3	2	2	2														
1= $\times 10^{-1}$ 2= $\times 10^{-2}$ 3= $\times 10^{-3}$ 4= $\times 10^{-4}$ 5= $\times 10^{-5}$										MPa		%														
1	G533005940	26.0	6	13398	35	12	71	16	3	2	1	2			578			40.0	0	81.00	0.01	8				
2	G533005941	26.0	9	20237	35	14	73	11	4	3	1	2			578			40.0	1/3	82.00	0.01	8				
															569			41.0	0	81.00	0.01	8				
															569			41.0	1/3	83.00	0.01	8				
合计 Total			15	33635	说明 NOTES		1. 本质量证明书适用于合金类线材; 本产品不含有任何辐射元素。It is guaranteed that the products don't contain radiochemical imparities. 3. We, SHAGANG, hereby certify that the products specified in the present certificate have been fully processed in china. (facility and address information is stated above). *1. H. T.—Head-colding Test; *2 D. of D.—Depth of Decarburization;																			
综合判定 FINAL RESULT		合格 PASS		注意事项 ATTENTIVE ITEMS		1. 质量证明书复印件不作有效证明文件, 除非盖章; The copy of this Certificate is not valid except stamped. 2. 用户验货后使用如有异议应及时告知炉号、牌号, 并保留实物及标志。Please inform us the steel grade and the heat number of under quanlified material(s) found in inspection on time and keep the material(s) and the marking card																	质检印章 SEAL		签证人 VISA 周建新	