

苏州苏德兰铁路配件有限公司尺寸检测报告

DIMENSIONAL TEST REPORT



品名 Product Name: 螺纹道钉 Screw Spike

合同编号 Contract NO: CA2506193

规格 Size: $\varnothing 23 \times 175$

检测日期 Inspection date: 2026.02.03

等级 Grade: ISO 898-1 5.6

发货日期 Date of shipment: 2026.02.03

标记 Mark: SDL 3V 26 N34

序号 No	检测项目 Test feature	技术要求 Specification	实测数值 Actual Size	结果 Result
1	圆盘直径 head diameter	$\varnothing 52 +0/-1$	$\varnothing 51.5 \sim 51.9$	OK
2	方头顶宽度 top of head breadth	$21 +0/-1$	$20.4 \sim 20.8$	OK
3	方头底宽度 bottom of head breadth	$23 +0/-1$	$22.1 \sim 22.6$	OK
4	头部高度 head total length	$20 +2/-0$	$20.6 \sim 21.4$	OK
5	头部高度 head total length	$31 +2/-0$	$31.5 \sim 32.4$	OK
6	头部R radius of head	R50	R50	OK
7	头部R radius of head	R10	R10	OK
8	头部R radius of head	R2.5	R2.5	OK
9	头部R radius of head	R1.6	R1.5	OK
10	白杆长度 unthreaded shank length	40 ± 5	$36.7 \sim 41.3$	OK
11	杆部直径 shank diameter	$\varnothing 23 \pm 1$	$22.2 \sim 22.5$	OK
12	螺纹内径 ID	$\varnothing 12.5 \pm 0.5$	$\varnothing 12.3 \sim 12.8$	OK
13	螺纹内径 ID	$\varnothing 16 \pm 0.5$	$\varnothing 15.8 \sim 16.3$	OK
14	螺纹外径 OD	$\varnothing 23 +0.5/-0.7$	$22.8 \sim 23.3$	OK
15	螺纹外径 OD	$\varnothing 23 +0.5/-0.7$	$23.1 \sim 23.4$	OK
16	杆部总长 shank length	175 ± 5	$170.3 \sim 176.1$	OK
17	单牙距 single screw pitch	12.5 ± 0.1	$12.4 \sim 12.6$	OK
18	螺纹底部R角 Thread R angle	R2	OK	OK
19	螺纹底部R角 Thread R angle	R3	OK	OK
20	表面处理 surface treatment	热镀锌 $\geq 50 \mu\text{m}$ Hot-dip Galvanise	$64 \sim 132$	OK
数量 Quantity			10000 件 (Pieces)	
检验 Inspector			张全恢 Zhang-QuanHui	
审核 In Charge			杨黎程 Yang-LiCheng	

苏州苏德兰铁路配件有限公司性能检测报告

PERFORMANCE TEST REPORT

品名Product Name: 螺纹道钉 Screw Spike

合同编号 Contract NO: CA2506193

规格 Size: $\varnothing 23 \times 175$

检测日期 Inspection date: 2026.02.01

等级 Grade: Gr5.6, UIC864-1

发货日期 Date of shipment: 2026.02.03

标记 Mark : SDL 3V 26 N34

数量 Quantity: 10000 (件 piece)



规格 Size	材料 Material	炉批号 Raw material Heat No	化学成分 Chemical composition (%)					机械性能 Mechanical properties				结果 Result
			C	Si	Mn	P	S	屈服强度 Yield strength	抗拉强度 Tensile Strength	延伸率 Elongation $\delta 5$	冷弯 Bend Test	
$\varnothing 23 \times 175$	35K	G532012382	0.35	0.14	0.72	0.012	0.002	$\geq 300\text{Mpa}$	$\geq 500\text{Mpa}$	Min20%	30°	
								427	633	21	OK	OK
								415	624	21	OK	OK
								402	618	22	OK	OK
$\varnothing 23 \times 175$	35K	G532012382	0.35	0.14	0.72	0.012	0.002	397	595	23	OK	OK
								413	602	22	OK	OK

检验 Inspector: 张全恢 Zhang-QuanHui

审核 In Charge: 杨黎程 Yang-LiCheng



江苏沙钢钢铁有限公司
Jiangsu Shagang Steel CO., LTD.
高速线材质量证明书

SG03B-1914E

江苏省张家港市锦丰镇 邮编: 215625
Jinfeng, Zhangjiagang, Jiangsu, P. R. CHINA
TEL: (0512) 58568866, 58568829
FAX: (0512) 58550366, 58550818

沙 钢

High-speed Wire Rod Quality Certificate

订货单位CUSTOMER	浙江沙钢物资贸易有限公司	用户代码CUSTOMER CODE		合同号CONTRACT NO.	X5CA00050018
牌号STEEL GRADE	SWRCH35K	提货单号DELIVERY	2512222306002	发货日期DATE OF DELIVERY	20251222
交货标准 SPECIFICATION	Q/320582 SGY303-2024	质证书号CERTIFICATE NO.	25122223060 020738	签发日期DATE OF ISSUE	20251222
		用途USE		精炼方式REFINING METHOD	炉外精炼

序号 NO	炉号 HEAT NO.	直径 Dia. mm.	盘数 Coils	重量 kg	化学成分CHEMICAL COMPOSITION %										拉伸试验TENSILE TEST			顶锻 试验 H. T.	硬度 试验 HRB	脱碳层 D. of. D	晶粒度 Micro- Grade	索氏体 Sorbite %	备注 REMARKS
					C	Si	Mn	P	S	Cr	Ni	Cu			Rm	Rel	A11.3	Z					
					1= $\times 10^{-1}$	2= $\times 10^{-2}$	3= $\times 10^{-3}$	4= $\times 10^{-4}$	5= $\times 10^{-5}$						MPa		%						
1	G532012382	24.0	15	33658	35	14	72	12	2	2	1	2			589 589			47.0 47.0	0 1/3	83.00 84.00	0.01 0.01	8 8	
合计 Total					15	33658	说明 NOTES										1. 质量证明书适用于合金线材; 本产品不含有任何辐射元素。It is guaranteed that the products don't contain radiochemical impurities. 3. We, SHAGANG, hereby certify that the products specified in the present certificate have been fully processed in china. (facility and address information is stated above. *1. H. T.—Head-colding Test; *2 D. of D.—Depth of Decarburization;						
综合判定 FINAL RESULT					合格 PASS					注意事项 ATTENTIVE ITEMS					1. 质量证明书复印件不作有效证明文件, 除非盖章; The copy of this Certificate is not valid except stamped. 2. 用户验货后使用如有异议应及时告知炉号、牌号, 并保留实物及标志。Please inform us the steel grade and the heat number of under quanlified material(s) found in inspection on time and keep the material(s) and the marking card					质检印章 SEAL			签证人 VISA