

苏州苏德兰铁路配件有限公司尺寸检测报告

DIMENSIONAL TEST REPORT



品名 Product Name: 螺纹道钉 Screw Spike

合同编号 Contract NO: CA2504666

规格 Size: $\varnothing 25 \times 179$

检测日期 Inspection date: 2025.09.26

等级 Grade: Gr5.6, UIC864-1

发货日期 Date of shipment: 2025.09.30

标记 Mark: PANDROL 25 5.6 GS195-J11 SDL

序号 No	检测项目 Test feature	技术要求 Specification	实测数值 Actual Size	结果 Result
1	对边尺寸 opposite side	27 +0/-1	26.1~26.4	OK
2	头部厚度 head thickness	15.5 $\pm$ 0.5	15.3~15.7	OK
3	头部R radius of head	R2	R2	OK
4	头部R radius of head	R2 $\pm$ 0.5	R2	OK
5	头部角度 Head Angle	15°	15°	OK
6	头部总高 head total length	20 +1.5/-0	20.3~20.8	OK
7	圆盘直径 head diameter	$\varnothing 40$ +0/-1	39.6~39.8	OK
8	圆盘直径 head diameter	$\varnothing 42$ +3/-1	41.4~41.7	OK
9	杆部直径 shank diameter	$\varnothing 25 \pm 0.5$	24.6~25.1	OK
10	白杆长度 unthreaded shank length	75 $\pm$ 5	71.7~75.9	OK
11	杆部总长 shank length	179 $\pm$ 3	176.2~180.8	OK
12	螺纹内径 ID	$\varnothing 19$ +0/-1	18.2~18.7	OK
13	螺纹外径 OD	$\varnothing 25$ +0/-1	24.2~24.7	OK
14	5牙距 screw pitch	60 $\pm$ 0.5	59.7~60.3	OK
15	单牙距 single screw pitch	12 $\pm$ 0.1	11.95~12.05	OK
16	螺纹底部R角 Thread R angle	R0.5 +0.5/-0	R1	OK
17	螺纹底部R角 Thread R angle	R1 +1/-0.5	R1	OK
18	螺纹头部R角 Thread R angle	R0.5 +0.5/-0	R1	OK
19	螺纹头部R角 Thread R angle	R1 +1/-0.5	R1	OK
20	牙高 screw height	3	2.9~3.1	OK
21	螺纹角度 Thread angle	30°	30°	OK
22	螺纹角度 Thread angle	30°	30°	OK
23	尖部深度 Point depth	≤ 8	4.5~5.9	OK
24	表面处理 surface treatment	电镀白锌 $\geq 12 \mu\text{m}$ White Zinc plating	盐雾试验200小时无红锈 Salt spray test 200 hours without red rust	OK
数量 Quantity			1600件 (Pieces)	
检验 Inspector			张全恢 Zhang-QuanHui	
审核 In Charge			杨黎程 Yang-LiCheng	

苏州苏德兰铁路配件有限公司性能检测报告

PERFORMANCE TEST REPORT

品名 Product Name: 螺纹道钉 Screw Spike
规格 Size: $\varnothing 25\times 179$
等级 Grade: Gr5.6 , UIC864-1
标记 Mark : PANDROL 25 5.6 GS195-J11 SDL

合同编号 Contract NO : C1504666
检测日期 Inspection date: 2025.09.26
发货日期 Date of shipment: 2025.09.30
数量 Quantity: 1600 (件 Pieces)



规格 Size	材料 Material	炉批号 Raw material Heat No	化学成分 Chemical composition (%)					机械性能 Mechanical properties				结果 Result
			C	S	Si	Mn	P	屈服强度 Yield strength	抗拉强度 Tensile Strength	延伸率 Elongation δ5"	冷弯 Bend Test	
								≥300Mpa	≥500Mpa	Min20%	15°	
$\varnothing 25\times 179$	35K	G533005941	0.35	0.004	0.14	0.73	0.011	361	602	23	OK	OK
								379	595	24	OK	OK
								374	613	22	OK	OK
								387	620	21	OK	OK

检验 Inspector: 张全恢 Zhang-QuanHui

审核 In Charge: 杨黎程 Yang-LiCheng



江苏沙钢钢铁有限公司
Jiangsu Shagang Steel CO., LTD.
高速线材质量证明书

High-speed Wire Rod Quality Certificate

SG03B-1914E

江苏省张家港市锦丰镇 邮编: 215625
Jinfeng, Zhangjiagang, Jiangsu, P. R. CHINA
TEL: (0512) 58568866, 58568829
FAX: (0512) 58550355, 58550815

订单号 ORDER NO.	用户/经销商代码 USER/DEALER CODE	合同号 CONTRACT NO.	X57100610010
牌号 SPEC. GRADE	SA50B55K	发货日期 DATE OF DELIVERY	20250718
交货状态 DELIVERY CONDITION	Q 355MS2 SQ1302-2021	交货日期 DATE OF ISSUE	20250718
用途 USE		检验方式 INSPECTION METHOD	炉外复验

序号 NO.	炉号 HEAT NO.	直径 Dia. mm.	盘数 Coils	重量 kg	化学成分 CHEMICAL COMPOSITION %										拉伸试验 TENSILE TEST			顶锻试验 H.T.	硬度试验 H.R.B.	脱碳层 D. of D.	晶粒度 Micro-Grade	索氏体 Sorbitle %	备注 REMARKS
					C	Si	Mn	P	S	Cr	Ni	Cu			Rm	Rel	Al. 3	Z					
					1	2	3	4	5	6	7	8	9	10	MPa	%	%						
1	330065910	26.0	6	3338	56	12	71	16	3	2	1	2			578			40.0	0	81.00	0.01	8	
2	0514003911	26.0	6	36237	56	14	73	11	4	3	1	2			578			40.0	0	81.00	0.01	8	
															569			41.0	0	81.00	0.01	8	
																		41.0	0	83.00	0.01	8	

合计 Total	3338																						
1. 本质量证明书适用于合金线材材料, 本厂不承担任何热处理义务。 It is guaranteed that the products don't contain radioactive impurities. 2. 本公司 (SAGANG) hereby certifies that the products specified in the present certificate have been fully processed in accordance with the relevant standards and the heat number of under qualified material(s) found in inspection on time and keep the material(s) and the marking card. 3. 用户 (User) 在收货后使用应保留好炉号、牌号, 并保留实物及标志。 Please inform us the steel grade and the heat number of under qualified material(s) found in inspection on time and keep the material(s) and the marking card. *1. E.T. -head rolling Test. *2. D of D -depth of Decarburization.																							

综合判定 FINAL RESULT	合格 PASS	注意事项 ATTENTIVE ITEMS	1. 质量证明书复印件不作为有效证明文件, 除非盖印。 The copy of this Certificate is not valid except stamped. 2. 用户收货后使用应保留好炉号、牌号, 并保留实物及标志。 Please inform us the steel grade and the heat number of under qualified material(s) found in inspection on time and keep the material(s) and the marking card.	质检印章 QUALITY INSPECTION SEAL	签证人 SIGNATURE
-------------------	---------	----------------------	---	------------------------------	---------------