

Quality Control Plan

STOCK-QP-031_A


HSR 602E Screwspike

Revision	Date	Author	Checked By	Amendments
A	12/06/2026			Initial Issue

Project	STOCK	Part Number	HSR 602E
Specification	SPEC-ACC-Ss8	Drawing Number	HSR 602E

Quality Control Plan

Sample ☐ Trial-production ☐ Mass production ☒	Main contact/Tel:	Prepared Date: 10/03/2026	Revise Date:
Core Team:		Approved date about the project (if necessary):	
		Approved date about the quality (if necessary):	
Supplier: SUDELAN	Supplier No.:	Approved date (if necessary):	Approved date about others (if necessary):

No.	Description	Characteristic			Method					FAT
		Item	Part Name	Content	Criteria/ Nominal Value / Tolerance	Relevant Standard / Document	Measuring Equipment	Min Sample Frequency	Control Method	
1	Material	1	Raw Material	Tensile Strength	$\geq 500 \text{ MPa}$	SPEC-ACC-Ss8	Universal Testing Machine	1 per batch of raw material	Test report	Document review only
				Yield Strength	$\sigma \geq 300 \text{ MPa}$					
				Elongation	$\delta \geq 20\%$					
2	Finished Product	1	HSR 602E	Dimensional Accuracy	Inspection dimensions shown in reference document as per example below: 	HSR 602E	Various	Single Sampling Plan, General Inspection Level I, AQL 2.5 (ISO 2859-1)	Test report	Document review only
				Identification	As per drawing					
				Straightness	<1mm from shank centreline	UIC864-1V	Various			
				Coating Thickness	Hot dip galvanised Mean $\geq 55 \mu\text{m}$	ISO 1461 / AS 1214	Thickness Gauge	Single Sampling Plan, Special Inspection Level S-1, AQL 2.5 (ISO 2859-1)		