

SECTION A-A

SCALE 1:1

ISOMETRIC VIEW

SCALE 1:1

NOTE:

Dimensions to be measured on the finished part after coating.

Designation

ØD

Ød

E

MARKING

ULS type MARKING "ULSy"

COATING / FINISH

STANDARD FOR COATING

ITEM CODE

FORMER DRAWING REFERENCE

Uls5-HDG

50

22

4

REQUIRED

/

Hot dip galvanized - thickness 50 µm mini

ISO 1461 or ASTM A153/A153M

NBVR0095

/

Uls6-RAW

47

23

4

REQUIRED

Uls6

Raw finih - Without protection

/

NBVR0050

E323/031e

Uls6-ELZN

REQUIRED

Zn white 12µm mini
withstanding to salt spray 96h white rust 200h red rust without chromium VI

ISO 4042

NBVR0033

Uls6-GEOMET

REQUIRED

Geomet 500 grade B

ISO 10683

NBVR0077

Uls6-HDG

24

REQUIRED

Hot dip galvanized - thickness 50 µm mini

ISO 1461 or ASTM A153/A153M

NBVR0066

Uls7-RAW

50

25

4

REQUIRED

Uls7

Raw finih - Without protection

/

NBVR0059

E323/034h

Uls7-ELZN

REQUIRED

Zn white 12µm mini
withstanding to salt spray 96h white rust 200h red rust without chromium VI

ISO 4042

NBVR0031

Uls7-GEOMET

REQUIRED

Geomet 500 grade B

ISO 10683

NBVR0036

Uls7-HDG

26

REQUIRED

Hot dip galvanized - thickness 50 µm mini

ISO 1461 or ASTM A153/A153M

NBVR0092

Uls8-ELZN

50

27

4

NO MARKING

/

Zn white 12µm mini
withstanding to salt spray 96h white rust 200h red rust without chromium VI

ISO 4042

NBVR0088

E323/053a

Uls8-SHE

Sherardized class 30

ISO 17668

NBVR0090

* MARKING:

4 mm high characters.

At the locations defined in the drawing.

ULSy = "ULS" type (see table),
example: ULS7

&&& = manufacturer's brand name (Maximum 3 letters)

AA = 2 last figures of the manufacturing year

* MATERIAL:

- Steel,

DC01-C590 or DC01-690 following standard EN 10139

or

St2 K60 or St44-2 K60 or St52-2 K60 following standard DIN17100.

- Coll-rolled, 590 to 740 N/mm2 tensile strength.

- Hardness: 170 to 220 HV.

ALL DIMENSIONS IN

MILLIMETERS

ORIGINAL SCALE

1:1

GENERAL TOLERANCES UNLESS OTHERWISE STATED

MATERIAL/FINISH

STEEL ACCORDING TO STANDARDS

DRAWN WITH REFERENCE TO PANDROL PRFSS-201

DO NOT SCALE

IF IN DOUBT, ASK!

COPY STATUS

THIS COPY, ALTHOUGH CORRECT AT THE DATE OF ISSUE, WILL NOT BE KEPT UP TO DATE. PANDROL BRAND COMPONENTS ARE UNDER CONTINUOUS DEVELOPMENT. SPECIFIC VARIANTS USUALLY NEED TO BE DEVELOPED TO SUIT SPECIFIC APPLICATIONS AND COMPONENT PARTS WITHIN AN ASSEMBLY NEED TO BE MATCHED TO EACH OTHER TO ENSURE SUCCESSFUL PERFORMANCE. CUSTOMERS AND THEIR PROFESSIONAL ADVISERS INTENDING TO SPECIFY PANDROL BRAND ASSEMBLIES SHOULD REFER TO PANDROL TO CHECK THAT THE DRAWINGS USED AND THE COMPONENTS PROPOSED ARE STILL CURRENT AND CORRECT FOR THE INTENDED APPLICATION. MANUFACTURERS SHOULD CHECK THAT THE DRAWING NUMBER AND ISSUE CODE CORRESPONDS EXACTLY TO THE CODES ON THE PANDROL PURCHASE ORDER. IF YOU WISH TO BE KEPT INFORMED OF UPDATES TO THIS DRAWING, PLEASE REQUEST PANDROL TO ADD YOUR NAME TO THE DRAWING CONTROLLING LIST.

IDI/ECR NUMBER

ECR0574

SHEET

1 OF 1

SIZE

A2

ISSUE STATUS

THE PRINTED NAMES IN EACH BOX BELOW, INDICATE AN AUTHORISED PANDROL EMPLOYEE HAS COMPLETED THE ACTIVITY. UNTIL THIS DRAWING INDICATES APPROVAL, THIS ISSUE MUST BE REGARDED AS PROVISIONAL, RELEASED FOR DISCUSSION AND THE DEVELOPMENT OF SAMPLES ONLY.

DRAWN BY

Th. Brouez

DATE

02.03.2021

REVISED BY

J. Jaubert

DATE

09.09.2022

CHECKED BY

Th. Brouez

DATE

09.09.2022

APPROVED BY

B. Candel

DATE

09.09.2022

PANDROL

205 RUE DE SIN LE NOBLE-BP261
59504 DOUAICEDEX-FRANCE
TÉLÉPHONE: +33 (0)3 27 99 64 00
FAX +33 (0)3 27 99 93 99
E-MAIL: INFO@PANDROL.COM
WWW.PANDROL.COM

TITLE

ULS WASHERS

DRAWING No.

E 323/063

ISSUE

F.1