

Pandrol APAC FAT* Plan	Component: 6161 Screwspike Ss8-150 (Corrosion protected)	
Approved Supplier: Sudelan	Contract: C1368, Singapore	
Issue Date: May 2026	Issue Level: 01	Approved By: I Moore, Quality Manager, Pandrol APAC
Amendment(s) from previous issue level:		
Confidential Information: Pandrol Proprietary Specification		* FAT = Factory Acceptance Testing It is a requirement to supply a copy of a current calibration certificate (signed) for each piece of calibrated inspection and test equipment used during FAT.
FAT Acceptance Criteria: In the event a non-compliant result occurs during the FAT, the following action shall apply: For every failed component, a further 3 components shall be selected. Inspection or testing of the non-compliant feature shall be carried out on these 3 components. If 2 or more of these 3 components give a non-compliant result, the batch shall be rejected.		

Document Ref. PAN-C1638-QD-0061

Item	Compliance Specification	Reference Document	FAT Sample Size	Witness Inspection Activity
Raw material	Complies with steel grade 5.6 to ISO 898-1	Pandrol specification LC-L issue 6	1 raw material certificate	Review the certificate
Dimensions	Complies with Pandrol drawing	Pandrol drawing 6161/SNG issue A1	3 pieces	Measurement of samples to the dimensions (shown with a tolerance) in the Pandrol drawing
Markings	Complies with Pandrol drawing	Pandrol drawing 6161/SNG issue A1	3 pieces	Visual inspection
Appearance	Free from harmful burrs and sharp edges. Threads uniform and complete	Pandrol specification LC-L issue 6	3 pieces	Visual inspection
Corrosion protection	Complies with hot dip galvanising to ISO10684 min 50um batch ave thickness	Pandrol specification LC-L issue 6	1 certificate	Review the certificate

Equivalent inspection to T250A