

Pandrol APAC Quality Plan	Component: 6161 Screwspike Ss8-150 (Corrosion protected)	
Approved Supplier: Sudelan	Contract: C1368, Singapore	
Issue Date: April 2026	Issue Level: 01	Approved By: Ian Moore Quality Manager, Pandrol APAC
Amendment(s) from previous issue level:		
Confidential Information: Pandrol Proprietary Specification		

Document Ref. PAN-C1368-QD-0059

Activity	Item	Specification	Reference Document	Minimum Inspection Frequency	Measurement Technique	Reaction Plan
Raw material	Composition	Complies with steel grade 5.6 to ISO 898-1	Pandrol specification LC-L issue 6	Per batch of raw material	Raw material certificate	Quarantine suspect product. Take corrective action. Re-sample to quality plan requirements.
Manufacture	Dimensions	Complies with Pandrol drawing	Pandrol drawing 6161/SNG issue A1	3 pieces at start-up. Then 1 piece per 5000 parts.	Calibrated measuring equipment	
	Appearance	Free from harmful burrs and sharp edges. Threads uniform and complete	Pandrol specification LC-L issue 6	3 pieces at start-up. Then 1 piece per 5000 parts.	Visual	
	Markings	Present legible and correct,	Pandrol drawing 6161/SNG issue A1	3 pieces at start-up. Then 1 piece per 5000 parts.	Visual	
Corrosion protection	Preventive coating	Complies with hot dip galvanising to ISO10684 min 50um batch ave thickness	Pandrol specification LC-L issue 6	3 pieces at start-up. Then 1 piece per 5000 parts.	Calibrated measuring equipment	
Packing	Packaged Product	Correct type and quantity. Correct packaging methods, Correct labels.	Pandrol packing list	Every outer package	Visual and calibrated weigh / count equipment	

Equivalent inspection to T250A Project

Quality Plan complies with ISO 10005