

Package ‘LACE’

February 29, 2020

Version 1.0.0

Date 2020-02-29

Title Longitudinal Analysis of Cancer Evolution (LACE)

Maintainer Daniele Ramazzotti <daniele.ramazzotti@yahoo.com>

Depends R (>= 3.6.0)

Imports parallel, Rfast, stats

Suggests BiocGenerics, BiocStyle, testthat, knitr

Name LACE: an R package for the inference of longitudinal cancer evolution models

Description LACE is an algorithmic framework that processes single-cell somatic mutation profiles from cancer samples collected at different time points and in distinct experimental settings, to produce longitudinal models of cancer evolution. The approach solves a Boolean Matrix Factorization problem with phylogenetic constraints, by maximizing a weighed likelihood function computed on multiple time points.

Encoding UTF-8

LazyData TRUE

License file LICENSE

URL <https://github.com/BIMIB-DISCo/LACE>

BugReports <https://github.com/BIMIB-DISCo/LACE>

biocViews BiomedicalInformatics

RoxygenNote 7.0.2

VignetteBuilder knitr

NeedsCompilation no

Author Daniele Ramazzotti [cre, aut],
Fabrizio Angaroni [aut],
Davide Maspero [aut],
Alex Graudenzi [aut]

R topics documented:

data	2
inference	2
LACE	3

Index	5
-------	---

data	<i>mutation data from Rambow, Florian, et al. "Toward minimal residual disease-directed therapy in melanoma." Cell 174.4 (2018): 843-855.</i>
------	---

Description

mutation data from Rambow, Florian, et al. "Toward minimal residual disease-directed therapy in melanoma." Cell 174.4 (2018): 843-855.

Usage

```
data(data)
```

Format

list of mutation data for four time points

Value

list of mutational data for a total of 475 single cells

Source

Rambow, Florian, et al. "Toward minimal residual disease-directed therapy in melanoma." Cell 174.4 (2018): 843-855.

inference	<i>results obtained with the function LACE on the provided input data from Rambow, Florian, et al. "Toward minimal residual disease-directed therapy in melanoma." Cell 174.4 (2018): 843-855.</i>
-----------	--

Description

results obtained with the function LACE on the provided input data from Rambow, Florian, et al. "Toward minimal residual disease-directed therapy in melanoma." Cell 174.4 (2018): 843-855.

Usage

```
data(inference)
```

Format

results obtained with the function LACE on the provided input data

Value

results obtained with the function LACE on the provided input data

LACE

LACE

Description

Perform inference of the maximum likelihood clonal tree from longitudinal data.

Usage

```
LACE(
  D,
  lik_w = NULL,
  alpha = NULL,
  beta = NULL,
  initialization = NULL,
  keep_equivalent = TRUE,
  num_rs = 50,
  num_iter = 10000,
  n_try_bs = 500,
  learning_rate = 1,
  marginalize = FALSE,
  num_processes = Inf,
  seed = NULL,
  verbose = TRUE,
  log_file = ""
)
```

Arguments

D	Mutation data from multiple experiments for a list of driver genes.
lik_w	Weight for each data point. If not provided, weights to correct for sample sizes are used.
alpha	False positive error rate provided as list of elements; if a vector of alpha (and beta) is provided, the inference is performed for multiple values and the solution at maximum-likelihood is returned.
beta	False negative error rate provided as list of elements; if a vector of beta (and alpha) is provided, the inference is performed for multiple values and the solution at maximum-likelihood is returned.
initialization	Starting point of the mcmc; if not provided, a random starting point is used.
keep_equivalent	Boolean. Shall I return results (B and C) at equivalent likelihood with the best returned solution?
num_rs	Number of restarts during mcmc inference.
num_iter	Maximum number of mcmc steps to be performed during the inference.
n_try_bs	Number of steps without change in likelihood of best solution after which to stop the mcmc.

<code>learning_rate</code>	Parameter to tune the probability of accepting solutions at lower values during mcmc. Value of <code>learning_rate</code> = 1 (default), set a probability proportional to the difference in likelihood; values of <code>learning_rate</code> greater than 1 increase the chance of accepting solutions at lower likelihood during mcmc while values lower than 1 decrease such probability.
<code>marginalize</code>	Boolean. Shall I marginalize C when computing likelihood?
<code>num_processes</code>	Number of processes to be used during parallel execution. To execute in single process mode, this parameter needs to be set to either NA or NULL.
<code>seed</code>	Seed for reproducibility.
<code>verbose</code>	Boolean. Shall I print to screen information messages during the execution?
<code>log_file</code>	log file where to print outputs when using parallel. If parallel execution is disabled, this parameter is ignored.

Value

A list of 8 elements: B, C, clones_prevalence, relative_likelihoods, joint_likelihood, clones_summary and error_rates. Here, B returns the maximum likelihood longitudinal clonal tree, C the attachment of cells to clones and clones_prevalence clones' prevalence; relative_likelihoods and joint_likelihood are respectively the likelihood of the solutions at each individual time points and the joint likelihood; clones_summary provide a summary of association of mutations to clones. In equivalent_solutions, solutions (B and C) with likelihood equivalent to the best solution are returned. Finally error_rates provides the best values of alpha and beta among the considered ones.

Examples

```
data(data)
inference = LACE(D = data,
  lik_w = c(0.2308772,0.2554386,0.2701754,0.2435088),
  alpha = list(c(0.10,0.05,0.05,0.05)),
  beta = list(c(0.10,0.05,0.05,0.05)),
  keep_equivalent = FALSE,
  num_rs = 5,
  num_iter = 10,
  n_try_bs = 5,
  num_processes = NA,
  seed = 12345,
  verbose = FALSE)
```

Index

data, [2](#)

inference, [2](#)

LACE, [3](#)