

The MCMC Procedure

| | |
|-----------------------------|-----|
| Number of Observations Read | 414 |
| Number of Observations Used | 414 |

| Parameters | | | | |
|------------|--------------|-----------------|---------------|--------------------------------------|
| Block | Parameter | Sampling Method | Initial Value | Prior Distribution |
| 1 | betaint | N-Metropolis | 0 | normal(mean = 0, var = 1000) |
| 2 | betaharddrug | N-Metropolis | 0 | normal(mean = 0, var = 1000) |
| 3 | betabase | N-Metropolis | 0 | normal(mean = 0, var = 1000) |
| 4 | sigma2 | Conjugate | 1.0000 | igamma(shape = 2.001, scale = 1.001) |

The MCMC Procedure


| Posterior Summaries and Intervals | | | | | |
|-----------------------------------|-------|---------|--------------------|------------------|---------|
| Parameter | N | Mean | Standard Deviation | 95% HPD Interval | |
| betaint | 15000 | 26.5951 | 1.7499 | 23.2197 | 30.0566 |
| betaharddrug | 15000 | -1.0041 | 1.8353 | -4.6234 | 2.5043 |
| betabase | 15000 | -0.5296 | 0.0367 | -0.6030 | -0.4603 |
| sigma2 | 15000 | 98.8732 | 6.8421 | 85.3062 | 111.9 |

The MCMC Procedure


| Effective Sample Sizes | | | |
|------------------------|---------|----------------------|------------|
| Parameter | ESS | Autocorrelation Time | Efficiency |
| betaint | 2643.3 | 5.6747 | 0.1762 |
| betaharddrug | 13648.6 | 1.0990 | 0.9099 |
| betabase | 2680.3 | 5.5965 | 0.1787 |
| sigma2 | 15000.0 | 1.0000 | 1.0000 |

| Deviance Information Criterion | |
|--|----------|
| Dbar (posterior mean of deviance) | 3079.370 |
| Dmean (deviance evaluated at posterior mean) | 3075.404 |
| pD (effective number of parameters) | 3.966 |
| DIC (smaller is better) | 3083.337 |


The MCMC Procedure



The MCMC Procedure



The MCMC Procedure



The MCMC Procedure

