

# Clustering



# K-Means Clustering



# Divisive Methods

“...tending to cause disagreements that separate people into opposing groups...”

This uses nonparametric algorithms:

- the number and nature of the parameters are flexible and not fixed in advance
- the number of clusters unknown

# Divisive Methods

We split the data into a small number of clusters

1. an initial allocation of seeds (randomly picked initial cluster centres)
2. allocation of points to closest centre
3. reallocation of each point (centre adjusted)
4. Repeat (until no changes or iterations max)

# How to Choose the Number of Clusters

1. Plot it and see...
2. Elbow Method
3. Silhouette Method
4. Gap Method
5. Compare and Choose!

# 1. Plot it and see...

```
library(factoextra)


p <- fviz_cluster(k1, data = df)


p <- fviz_cluster(k2, data = df)

p <- fviz_cluster(k3, data = df)

p <- fviz_cluster(k4, data = df)

p <- fviz_cluster(k5, data = df)
```






## 2. Elbow Method...

Looking for when the *marginal total within sum of squares* for an additional cluster begins to decrease at a linear rate

### 3. Silhouette Method


Looks at the mean within distance and the mean nearest-cluster between distance for each sample






## 4. Gap Method


Looking for which organisation of clusters gives the biggest 'gap'





Hubert Statistic values



Hubert statistic second differences





```
fviz_nbclust(cluster_30_indexes) +  
  theme_minimal() +  
  labs(title = "Frequency of Optimal Clusters using 30 indexes in NbClust Package")
```

```
## Among all indices:  
## =====  
## * 2 proposed 0 as the best number of clusters  
## * 1 proposed 1 as the best number of clusters  
## * 5 proposed 2 as the best number of clusters  
## * 6 proposed 3 as the best number of clusters  
## * 1 proposed 4 as the best number of clusters  
## * 4 proposed 5 as the best number of clusters  
## * 1 proposed 8 as the best number of clusters  
## * 3 proposed 9 as the best number of clusters  
## * 3 proposed NA's as the best number of clusters
```

# Hierarchical Agglomerati ve Clustering



# Hierarchical Agglomerative Clustering


Hierarchical  $\Rightarrow$  Ranking, ordered


Agglomeration  $\Rightarrow$  "...a large group of many different

things collected or brought together..."

<https://dictionary.cambridge.org/dictionary/english/agglomeration>

## Cluster Dendrogram









- Fuse zero distance observations
- Fuse until two clusters are close enough to fuse
- Fuse until all the clusters have been fused into one big one




# Nearest-Neighbour (single linkage)

## Clustering

The smallest distance between any two points  
in the two clusters

Chaining often leads to  
uninformative dendrograms


Adaptive for well separated  
data; robust to the choice of  
measure



# Farthest-Neighbour (complete linkage) Clustering

The largest distance between any two points  
in the two clusters

Can be sensitive to tied  
distances



Clusters are often compact,  
spherical and well defined;  
robust to a certain amount of  
measurement error and  
choice of distance

# Group Average Linkage (UPGMA)


The distance between two clusters is the average of the distances between the members of the two groups



# Ward's Method

Minimises the increase in total sum of squared distances within the clusters

A bad start can mean it will never reach the global optimum for a given number of clusters; tends to form spherical clusters of equal size



It is not allowed to swap points between clusters

Method	Pros	Cons
Single linkage	number of clusters	comb-like trees.
Complete linkage	compact clusters	one obs. can alter groups
Average linkage	similar size and variance	not robust
Centroid	robust to outliers	smaller number of clusters
Ward	minimising an inertia	clusters small if high variability

**[code along `ants`, script  
below]**

Data were collected on the distribution of ant species at 30 sites across the Auckland region using pitfall traps. Twenty pitfall traps at each site were left open for ten days and the number of individuals captured counted for the four most abundant species: *Nylanderia* spp, *Pheidole rugosula*, *Tetramorium grassii*, and *Pachycondyla* sp.

```
glimpse(ants)
```

```
## Rows: 30
```

```
## Columns: 8
```

```
## $ Location <chr> "West", "West", "West", "West", "West", "West", "West", "West..."
```

```
## $ Habitat <chr> "Forest", "Grass", "Urban", "Forest", "Grass", "Forest", "Gra..."
```

```
## $ Month <dbl> 1, 1, 1, 2, 2, 3, 3, 3, 1, 1, 1, 2, 2, 2, 2, 3, 3, 3, 3, 1, 1...
```

```
## $ Site <chr> "WF1", "WG1", "WU1", "WF2", "WG2", "WF3", "WG3", "WU3", "CF1"...
```

```
## $ Nyl <dbl> 0, 0, 3, 0, 5, 0, 0, 0, 0, 0, 1, 0, 0, 22, 15, 0, 0, 10, 2, 0...
```


```
## $ Phe <dbl> 0, 2, 7, 0, 0, 0, 3, 1, 0, 3, 0, 0, 7, 109, 1, 0, 13, 47, 0, ...
```

```
## $ Tet <dbl> 0, 7, 0, 0, 25, 0, 2, 0, 0, 22, 5, 0, 30, 54, 35, 0, 14, 7, 4...
```


```
## $ Pac <dbl> 157, 37, 0, 31, 0, 21, 1, 0, 1, 2, 1, 3, 1, 0, 4, 1, 2, 0, 0,...
```




# Nearest-Neighbour Clustering




# Farthest-Neighbour Clustering



# Group Average Linkage (UPGMA)




# Ward's Method




# Nearest Neighbour

Cluster Dendrogram




# Furthest Neighbour

Cluster Dendrogram




# Average Linkage

Cluster Dendrogram



# Ward's Method

Cluster Dendrogram



In your groups, discuss the cluster/cutree plot and the prompt at the end of your script.