



TOP VIEW






BOTTOM VIEW





Dept.	Technical reference	Created by Oshiro Takashi 2021-11-06	Approved by		
図面番号: 6 All dimensions are in mm Scale: 2:1 Material 材料: A6061-T6 No of Components 個数: 1		Document type 6_1U_STD	Document status		
		Title Frame 5	DWG No.		
			Rev. 9	Date of issue 2021-11-06	Sheet 1/4





Dept.	Technical reference	Created by Oshiro Takashi 2021-11-06	Approved by			
図面番号:6 All dimensions are in mm Scale: 1:1 Material 材料:A6061-T6 No of Components 個数:1		Document type 6_1U_STD	Document status			
		Title Frame 5	DWG No.			
			Rev. 9	Date of issue 2021-11-06	Sheet 3/4	

# ISOMETRIC VIEW



E

注1)指示のない公差はJIS B 0405-fとする。


0.5-6	±0.05
6-30	±0.1
30-120	±0.15

注2)指示なき角は糸面取りのこと。

注3)機械加工後、ハードアノダイズ処理を施行する。

ハードアノダイズ処理はMIL-A-8625, Type 3 とし、膜厚は10 μ m以上とする。

E (2:1)



Dept.	Technical reference	Created by Oshiro Takashi 2021-11-06	Approved by		
図面番号:6 All dimensions are in mm Scale: 1:1 Material 材料:A6061-T6 No of Components 個数:1		Document type 6_1U_STD	Document status		
		Title Frame 5	DWG No.		
			Rev. 9	Date of issue 2021-11-06	Sheet 4/4