

CS 1510 Homework 5

Brian Falkenstein, Brian Knotten, Brett Schreiber

September 6, 2018

11

a

SJF is not optimal on the following input I :

$J_1 = (0, 2)$

$J_2 = (1, 2)$

For each time t :

1. Run J_1 (it is the only choice)
2. Run J_2 (arbitrarily, since J_1 and J_2 are the same size.)
3. Run J_2 (arbitrarily). J_2 is completed now, so $C_2 = 3$
4. Run J_1 (it is the only choice). J_1 is completed now, so $C_1 = 4$

The total completion time for *SJF*(I) is $C_1 + C_2 = 4 + 3 = 7$

But a more optimal solution *opt*(I) exists. For each time t :

1. Run J_1
2. Run J_1 . J_1 is now finished, so $C_1 = 2$.
3. Run J_2 .
4. Run J_2 . J_2 is now finished, so $C_2 = 4$.

The total completion time for *opt*(I) is $C_1 + C_2 = 2 + 4 = 6$

SJF(I) is not optimal therefore *SJF* is incorrect.

17

Consider the following algorithm A :

Given rooted tree T :

Sort the leaves by value in descending order.

For each leaf l (from greatest value to least):

If any ancestor's current capacity is less than 0, do not include l in the output

Otherwise, include l , and for each ancestor of l set its new capacity to be its current capacity - 1

Proof: Assume to reach a contradiction that our algorithm, hereafter referred to as A , is incorrect. Then there exists an input I on which A produces a suboptimal output. Let $OPT(I)$ be the optimal solution to the problem that agrees with $A(I)$ for the max number of steps i.e. up to leaf n $OPT(I)$ and $A(I)$ have included and excluded the same leaves. Because each step is either including or excluding a leaf, the disagreement can be one of two cases:

1. $A(I)$ excluded leaf n and $OPT(I)$ included leaf n :
Because $A(I)$ and $OPT(I)$ agreed on every leaf up to this step and A always considers the next highest possible value and only excludes leaves when a leaf's ancestors' capacity does not accommodate it, it cannot be the case that $OPT(I)$ includes n and $A(I)$ does not.

2. $A(I)$ included leaf n and $OPT(I)$ excluded leaf n :
 $OPT(I)$ excludes a leaf that $A(I)$ includes either because the parent nodes are at capacity or because there is a better leaf it will select later on. The first case cannot occur, as $OPT(I)$ and $A(I)$ have the same capacity because they have agreed on every leaf up to this point. In the second case, because A always selects the next highest possible value and $OPT(I)$ has agreed with $A(I)$ up to this point, it is impossible for there to be a leaf with greater value than n available for $OPT(I)$ to select later on. Therefore the leaf $OPT(I)$ would select instead of n has to be of equal or lesser value than n and $OPT(I)$'s solution is equivalent to or lesser than $A(I)$'s solution.

Therefore $OPT(I)$ can be modified into $OPT'(I)$ where $OPT'(I)$ agrees with $A(I)$ for one more step (including or excluding n), contradicting the statement that $OPT(I)$ is the optimal solution that agrees with $A(I)$ for the most number of steps.

Thus, by contradiction, $A(I)$ is correct.