# Homework 14

## Joe Baker, Brett Schreiber, Brian Knotten

#### February 13, 2018

### 21

#### $\mathbf{a}$

Any Boolean function F for an input size n can be encoded into a string s of size  $2^n$ , where each bit represents an output for a given input. For example, if n = 4, the first bit of s, either a 0 or 1, represents the output for the input 0000. The second bit of s represents the output for input 1111

The formula for F can be naively implemented through the following algorithm:

List all binary numbers of length n from 0 to  $2^n$ . Let B be this list. For each number b in B:

for each bit  $b_i$  in b:

if  $b_i = 0$ , write out  $\neg x_i$ 

if  $b_i = 1$ , write out  $x_i$ 

Join together all of these boolean expressions with  $\wedge$ 's

Join together all of these boolean expressions with  $\vee$ 's

Here is an example Boolean function f encoded as 1011. This means f has the following outputs:

f(00) = 1

f(01) = 0

f(10) = 1

f(11) = 1

The corresponding boolean formula using the naive implementation is:  $f(x_1x_2) = (\neg x_1 \land \neg x_2) \lor$ 

 $\neg(\neg x_1 \land x_2) \lor (x_1 \land \neg x_2) \lor$ 

 $(x_1 \wedge x_2)$ 

So every boolean function on n bits has a formula of size at most  $2^n$ . Since  $\land$ ,  $\lor$ , and  $\neg$  exist as gates in circuits, this formula can be converted into a circuit with size at most  $2^n$  gates.

#### b

First, show that f computed by circuit  $|C| = S \to f$  computed by S-line program:

For each Boolean gate (NOT, AND, OR) in C, there exists an equivalent straight-line program statement with a left-side assignment variable corresponding to the output of the gate and a right side consisting of either a boolean operation  $(\land, \lor)$  performing the gate's operation on input variables corresponding to the input of the gate, or the negation  $(\neg)$  of an input variable corresponding to the input of the gate.

Therefore, given a circuit |C| = S, we can construct an equivalent straight-line program with S statements by iterating over each gate in C and converting it to an equivalent straight-line program statement.

Next, show that f computed by S-line program  $\rightarrow f$  computed by circuit |C| = S:

For every straight-line program statement there exists an equivalent Boolean gate with inputs corresponding to the right-side variable(s) of the statement that performs the corresponding Boolean operation of the right-side of the statement and an output corresponding to the left-side assignment variable of the statement.