

Congratulations! You passed!

TO PASS 80% or higher

Keep Learning

GRADE
90%

Special applications: Face recognition & Neural style transfer

LATEST SUBMISSION GRADE

90%

1. Face verification requires comparing a new picture against one person's face, whereas face recognition requires comparing a new picture against K person's faces. 1 / 1 point

✓ Correct

2. Why do we learn a function $d(img1, img2)$ for face verification? (Select all that apply.) 1 / 1 point

✓ Correct

3. In order to train the parameters of a face recognition system, it would be reasonable to use a training set comprising 100,000 pictures of 100,000 different persons. 1 / 1 point


✓ Correct

4. Which of the following is a correct definition of the triplet loss? Consider that $\alpha > 0$. (We encourage you to figure out the answer from first principles, rather than just refer to the lecture.) 1 / 1 point

✓ Correct

5. Consider the following Siamese network architecture:

1 / 1 point



The upper and lower neural networks have different input images, but have exactly the same parameters.

✓ Correct

6. You train a ConvNet on a dataset with 100 different classes. You wonder if you can find a hidden unit which responds strongly to pictures of cats. (I.e., a neuron so that, of all the input/training images that strongly activate that neuron, the majority are cat pictures.) You are more likely to find this unit in layer 4 of the network than in layer 1.

1 / 1 point

✓ Correct

7. Neural style transfer is trained as a supervised learning task in which the goal is to input two images (x), and train a network to output a new, synthesized image (y).

0 / 1 point

! Incorrect

8.

1 / 1 point

In the deeper layers of a ConvNet, each channel corresponds to a different feature detector. The style matrix $G^{[l]}$ measures the degree to which the activations of different feature detectors in layer l vary (or correlate) together with each other.

✓ **Correct**

9. In neural style transfer, what is updated in each iteration of the optimization algorithm? **1 / 1 point**

✓ **Correct**

10. You are working with 3D data. You are building a network layer whose input volume has size **1 / 1 point**
32x32x32x16 (this volume has 16 channels), and applies convolutions with 32 filters of dimension 3x3x3 (no padding, stride 1). What is the resulting output volume?

✓ **Correct**