```
provider "aws" {
  region = "ap-south-1"  # Change to your AWS region
}
# ◆ Fetch default VPC
# ◆ Fetch default public and private subnets (Modify for custom subnets)
data "aws_subnets" "public" {
  filter {
    name   = "tag:Name"
    values = ["public-*"]  # Adjust based on your subnet tags
  }
}
# ◆ Security Group for ALB (Allow HTTP & HTTPS) = ingress 80 80 tcp egress anywhere
# ◆ Security Group for EC2 (Allow ALB traffic only) = ingress 80 80 tcp egress anywhere
# ◆ Create an Application Load Balancer (ALB)
resource "aws_lb" "app_alb" {
  name             = "app-load-balancer"
  internal         = false
  load_balancer_type = "application"
  security_groups    = [aws_security_group.alb_sg.id]
  subnets          = data.aws_subnets.public.ids
  enable_deletion_protection = false
}
# ◆ Create a Target Group
resource "aws_lb_target_group" "tg" {
  name     = "alb-target-group"
  port     = 80
  protocol = "HTTP"
  vpc_id   = data.aws_vpc.default.id
}
# ◆ Attach EC2 Instances to Target Group
resource "aws_lb_target_group_attachment" "tg_attach" {
  target_group_arn = aws_lb_target_group.tg.arn
  target_id        = "i-xxxxxxxxxxxxxx"  # Replace with your EC2 instance ID
  port             = 80
}
# ◆ Create a Listener for ALB
resource "aws_lb_listener" "http" {
  load_balancer_arn = aws_lb.app_alb.arn
  port              = 80
  protocol          = "HTTP"
  default_action {
    type             = "forward"
    target_group_arn = aws_lb_target_group.tg.arn
  }
}

output "alb_dns_name" {
  value = aws_lb.app_alb.dns_name
}
```