

HA, F, HH, ENV

41

new

Material Safety Data Sheet

Stoner

TraSys[®] 258

Version 2.0

Revision Date 02/3/2014

Ref. 130000010846

This SDS adheres to the standards and regulatory requirements of the United States and may not meet the regulatory requirements in other countries.

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name	:	TraSys [®] 258
MSDS Number	:	130000010846
Product Use	:	Solvent-borne coatings
Manufacturer	:	Stoner Incorporated 1070 Robert Fulton Hwy. Quarryville, PA 17566 United States
Product Information	:	1-800-227-5538 (outside the U.S. 1-717-786-7355)
Emergency & Transport Information	:	CHEMTREC: 1-800-424-9300 (outside the U.S. 1-703-741-5970)
Other information	:	professional use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

The thermal decomposition vapours of fluorinated polymers may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco. Repeated episodes of polymer fume fever may result in persistent lung effects. Dust may cause: Respiratory tract irritation Difficulty in breathing Shortness of breath

Potential Health Effects

Skin

Isopropyl Alcohol	:	Prolonged or repeated contact may dry skin and cause irritation.
Polytetrafluoroethylene	:	Dust may cause: Discomfort, itching, redness, or swelling.

Eyes

Isopropyl Alcohol	:	May cause: Eye irritation, Discomfort, tearing, Blurred vision.
Polytetrafluoroethylene	:	Dust may cause: tearing, Redness, Discomfort.

Inhalation

Material Safety Data Sheet

TraSys® 258

Version 2.0

Ref. 130000010846

Isopropyl Alcohol : May cause respiratory tract irritation. Inhalation of high vapour concentrations can cause CNS-depression and narcosis.

Polytetrafluoroethylene : Dust may cause: Respiratory tract irritation
The thermal decomposition vapours of fluorinated polymers may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco.
Symptoms usually appear after several hours and resolve within 1 to 2 days.
Repeated episodes of polymer fume fever may result in persistent lung effects.
Polymer may extensively decompose if severely overheated or burned.
Inhalation of fluorinated decomposition products may cause lung irritation and pulmonary oedema.
Symptoms may be delayed for several hours.
Symptoms may be severe or life-threatening.

Ingestion
Isopropyl Alcohol : Effects due to ingestion may include: Gastrointestinal disturbance, Incoordination, Lethargy, Aspiration hazard if swallowed - can enter lungs and cause damage..

Repeated exposure
Isopropyl Alcohol : Adverse effects from repeated inhalation may include: Central nervous system depression lung effects Liver effects Kidney effects Spleen effects

Target Organs
Isopropyl Alcohol : Respiratory Tract Central nervous system

Carcinogenicity
None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, or OSHA, as a carcinogen.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No.	Concentration
Isopropyl Alcohol	67-63-0	93.5 - 96.5 %

Material Safety Data Sheet

TraSys® 258

Version 2.0

Ref. 130000010846

Polytetrafluoroethylene	9002-84-0	3.5 - 6.5 %
-------------------------	-----------	-------------

SECTION 4. FIRST AID MEASURES

- Skin contact : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing before re-use. Consult a physician if necessary.
- Eye contact : Immediately flush eye(s) with plenty of water. Remove contact lenses. Seek medical advice.
- Inhalation : Move to fresh air. Oxygen or artificial respiration if needed. Consult a physician.
- Ingestion : DO NOT induce vomiting unless directed to do so by a physician or poison control center. Never give anything by mouth to an unconscious person. Call a physician.
- General advice : When symptoms persist or in all cases of doubt seek medical advice.

SECTION 5. FIRE-FIGHTING MEASURES

- Flammable Properties
- Flash point : 12 °C (54 °F)
(for a component of this mixture)
- Ignition temperature : > 398 °C (> 748 °F)
- Thermal decomposition : 260 - 400 °C (500 - 752 °F)
- Fire and Explosion Hazard : Flammable liquid Vapours may form explosive mixtures with air. Vapours are heavier than air and may spread along floors. Flash back possible over considerable distance. In fire conditions, toxic decomposition products may be formed. (see also section 10)
- Suitable extinguishing media : Dry chemical, Alcohol-resistant foam, Water spray, Carbon dioxide (CO2)

Material Safety Data Sheet

TraSys® 258

Version 2.0

Ref. 130000010846

Firefighting Instructions : Wear self-contained breathing apparatus and protective suit.
Evacuate personnel to safe areas. In the event of fire, cool tanks with water spray.

SECTION 6. ACCIDENTAL RELEASE MEASURES

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

Safeguards (Personnel) : Ventilate spill area. Wear self-contained breathing apparatus and protective suit. Remove all sources of ignition.

Spill Cleanup : Dike spill. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Accidental Release Measures : Prevent material from entering sewers, waterways, or low areas.

SECTION 7. HANDLING AND STORAGE

Handling (Personnel) : Do not breathe vapours or spray mist. Avoid contact with skin, eyes and clothing. Wash hands thoroughly after handling. Remove and wash contaminated clothing before re-use. Do not store or consume food, drink or tobacco in areas where they may become contaminated with this material.

Handling (Physical Aspects) : Keep away from heat and sources of ignition. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).

Storage : Keep containers tightly closed in a dry, cool and well-ventilated place. Freezing will affect the physical condition but will not damage the material. Thaw and mix before using.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering controls : Use only with adequate ventilation.

Personal protective equipment

Material Safety Data Sheet

TraSys® 258

Version 2.0

Ref. 130000010846

- Respiratory protection : Provide adequate ventilation. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
- Hand protection : Material: Impervious gloves
- Eye protection : Wear coverall chemical splash goggles.
- Skin and body protection : Preventive skin protection
Where there is potential for skin contact, have available and wear as appropriate, impervious gloves, apron, pants, jacket, hood and boots.

Exposure Guidelines Exposure Limit Values Isopropyl Alcohol

PEL: (OSHA) 400 ppm 980 mg/m3 8 hr. TWA

TLV (ACGIH) 200 ppm TWA

TLV (ACGIH) 400 ppm STEL

AEL * (DUPONT) 200 ppm 8 & 12 hr. TWA

Polytetrafluoroethylene

AEL * (DUPONT) 10 mg/m3 8 hr. TWA Total dust.

AEL * (DUPONT) 5 mg/m3 8 hr. TWA Respirable dust.

Biological Exposure Indices

Isopropyl Alcohol BEI

(ACGIH) 40 mg/l acetone/Urine
Sampling time: End of shift at end of work week.

* AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Form : liquid
Color : white

Material Safety Data Sheet

TraSys® 258

Version 2.0

Ref. 130000010846

Odor	: alcohol-like
pH	: 4 - 6
Freezing point	: -89 °C (-128 °F)
Melting point	: 323 - 327 °C (613 - 621 °F)
Boiling point	: 82 °C (180 °F)
% Volatile	: 95 %
Vapour Pressure	: 33 mm Hg at 20 °C (68 °F)
Water solubility	: partly soluble
Vapour density	: 2.07 at 25 °C (77 °F) (Air = 1.0)

SECTION 10. STABILITY AND REACTIVITY

Stability	: Stable under recommended storage conditions.
Conditions to avoid	: Heat, flames and sparks. Decomposes on heating. Decomposition temperature 300 °C (572 °F)
Incompatibility	: Strong acids strong oxidizers, Halogenated compounds, Aldehydes, reactive metals, Strong bases, Alkali metals, Alkaline earth metals, molecular sieves
Hazardous decomposition products	: Carbon oxides, Fluorinated compounds
Hazardous reactions	: Reacts with Aluminum above 49 deg C. Polymerization will not occur.

SECTION 11. TOXICOLOGICAL INFORMATION

TraSys® 258

Skin irritation	: slight irritation
Eye irritation	: Irritating to eyes.
Sensitisation	: no data available

Isopropyl Alcohol

Dermal LD50	: 12,900 mg/kg , rabbit
-------------	-------------------------

Material Safety Data Sheet

TraSys® 258

Version 2.0

Ref. 130000010846

Oral LD50	: 4,700 mg/kg , rat Gastrointestinal effects Kidney effects
Inhalation 4 h LC50	: 39.3 mg/l , rat Target Organs: Respiratory Tract, Central nervous system Respiratory tract damage Central nervous system depression
Repeated dose toxicity	: Inhalation Target Organs: Central nervous system, Respiratory Tract Central nervous system effects, Liver effects, Kidney effects, lung effects, Spleen effects, Testes Oral Liver enlargement, Kidney enlargement, Adrenal effects Dermal Drying of skin, Weight loss, Organ weight changes
Carcinogenicity	: Animal testing did not show any carcinogenic effects.
Mutagenicity	: Did not show mutagenic effects in animal experiments. Tests on bacterial or mammalian cell cultures did not show mutagenic effects.
Reproductive toxicity	: Evidence suggests the substance is not a reproductive toxin in animals.
Teratogenicity	: Animal testing showed effects on embryo-fetal development at levels equal to or above those causing maternal toxicity.
Polytetrafluoroethylene Oral LD50	: > 11,280 mg/kg , rat
Repeated dose toxicity	: Oral - feed rat No toxicologically significant effects were found.
Further information	: The substance is a polymer and is not expected to produce toxic effects.

Material Safety Data Sheet

TraSys[®] 258

Version 2.0

Ref. 130000010846

SECTION 12. ECOLOGICAL INFORMATION

Aquatic Toxicity
TraSys[®] 258

: no data available

Isopropyl Alcohol
96 h LC50
24 h EC50

: Pimephales promelas (fathead minnow) 3,200 mg/l
: Daphnia 9,714 mg/l

Polytetrafluoroethylene

: The substance is a polymer and is not expected to produce toxic effects.

Environmental Fate
TraSys[®] 258
Biodegradability

: no data available

Bioaccumulation

: no data available

SECTION 13. DISPOSAL CONSIDERATIONS

Waste Disposal : Dispose of as hazardous waste in compliance with local and national regulations.

Environmental Hazards : Dispose of container properly.
If recycling is not practicable, dispose of in compliance with local regulations.

SECTION 14. TRANSPORT INFORMATION

DOT	UN number	: 1219
	Proper shipping name	: Isopropanol solution
	Class	: 3
	Packing group	: II
	Labelling No.	: 3

8 / 10

Material Safety Data Sheet

TraSys® 258

Version 2.0

Ref. 130000010846

	Reportable Quantity	: 100 lbs Propan-2-ol
IATA_C	UN number	: 1219
	Proper shipping name	: Isopropanol solution
	Class	: 3
	Packing group	: II
	Labelling No.	: 3
IMDG	UN number	: 1219
	Proper shipping name	: Isopropanol solution
	Class	: 3
	Packing group	: II
	Labelling No.	: 3

SECTION 15. REGULATORY INFORMATION

TSCA Status	: On the inventory, or in compliance with the inventory
Title III hazard classification	: Acute Health Hazard: Yes Chronic Health Hazard: No Fire: Yes Reactivity/Physical hazard: No Pressure: No
CERCLA Reportable Quantity	: 107 lbs Based on the percentage composition of this chemical in the product.: Propan-2-ol
California Prop. 65	: Chemicals known to the State of California to cause cancer, birth defects or any other harm: none known
PA Right to Know Regulated Chemical(s)	: Substances on the Pennsylvania Hazardous Substances List present at a concentration of 1% or more (0.01% for Special Hazardous Substances): Polytetrafluoroethylene , Isopropyl Alcohol
NJ Right to Know Regulated Chemical(s)	: Substances on the New Jersey Workplace Hazardous Substance List present at a concentration of 1% or more (0.1% for substances identified as carcinogens, mutagens or teratogens): Isopropyl Alcohol

Material Safety Data Sheet

TraSys® 258

Version 2.0

Ref. 130000010846

SECTION 16. OTHER INFORMATION

HMIS

Health	:	2
Flammability	:	3
Reactivity/Physical hazard	:	0
PPE	:	Personal Protection rating to be supplied by user depending on use conditions.

TraSys® is the registered trademarks of Stoner Incorporated or its affiliates.

Contact person : MSDS Coordinator, Stoner Incorporated, 1070 Robert Fulton Hwy,
Quarryville PA, 17566, 1 800-227-5538

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.