

HH, F, HA

# Material Safety Data Sheet

**LOCTITE®**

*New Maint*



Revision Number: 002.2

Issue date: 02/17/2011

## 1. PRODUCT AND COMPANY IDENTIFICATION

|                               |                                                |                     |               |
|-------------------------------|------------------------------------------------|---------------------|---------------|
| <b>Product name:</b>          | LOCTITE® Thread Sealant With PTFE®             | <b>IDH number:</b>  | 1527514       |
| <b>Product type:</b>          | Sealant                                        | <b>Item number:</b> | 1527514       |
|                               |                                                | <b>Region:</b>      | United States |
| <b>Company address:</b>       | <b>Contact information:</b>                    |                     |               |
| Henkel Corporation            | Telephone: 860.571.5100                        |                     |               |
| One Henkel Way                | MEDICAL EMERGENCY Phone: Poison Control Center |                     |               |
| Rocky Hill, Connecticut 06067 | 1-877-671-4608 (toll free) or 1-303-592-1711   |                     |               |
|                               | TRANSPORT EMERGENCY Phone: CHEMTREC            |                     |               |
|                               | 1-800-424-9300 (toll free) or 1-703-527-3887   |                     |               |
|                               | Internet: www.henkelna.com                     |                     |               |

## 2. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

|                        |           |                             |                    |
|------------------------|-----------|-----------------------------|--------------------|
| <b>Physical state:</b> | Paste     | <b>HEALTH:</b>              | *2                 |
| <b>Color:</b>          | White     | <b>FLAMMABILITY:</b>        | 3                  |
| <b>Odor:</b>           | Alcoholic | <b>PHYSICAL HAZARD:</b>     | 0                  |
|                        |           | <b>Personal Protection:</b> | See MSDS Section 8 |

**WARNING:** FLAMMABLE LIQUID AND VAPOR.  
MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.  
MAY BE HARMFUL IF SWALLOWED OR INHALED.

**Relevant routes of exposure:** Skin, Inhalation, Eyes, Ingestion

### Potential Health Effects

|                      |                                                                                                              |
|----------------------|--------------------------------------------------------------------------------------------------------------|
| <b>Inhalation:</b>   | May be harmful if inhaled. Vapors may cause headaches, nausea, dizziness and respiratory tract irritation.   |
| <b>Skin contact:</b> | May cause skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.  |
| <b>Eye contact:</b>  | May cause mild irritation Symptoms may include stinging, tearing, redness, swelling, and blurred vision.     |
| <b>Ingestion:</b>    | May be harmful if swallowed. Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea. |

**Existing conditions aggravated by exposure:** Eye, skin, and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous components                                                 | CAS NUMBER | %       |
|----------------------------------------------------------------------|------------|---------|
| 2-Propanol                                                           | 67-63-0    | 30 - 60 |
| Talc                                                                 | 14807-96-6 | 10 - 30 |
| Castor oil                                                           | 8001-79-4  | 10 - 30 |
| Polyvinyl butyral - polyvinyl alcohol - polyvinyl acetate terpolymer | 27360-07-2 | 10 - 30 |
| Titanium dioxide                                                     | 13463-67-7 | 1 - 5   |
| Ethene, tetrafluoro-, homopolymer                                    | 9002-84-0  | 1 - 5   |
| Quartz (SiO <sub>2</sub> )                                           | 14808-60-7 | 0.1 - 1 |

### 4. FIRST AID MEASURES

|                      |                                                                                             |
|----------------------|---------------------------------------------------------------------------------------------|
| <b>Inhalation:</b>   | Move to fresh air. If symptoms persist, seek medical advice.                                |
| <b>Skin contact:</b> | Wash with soap and water.                                                                   |
| <b>Eye contact:</b>  | Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention. |
| <b>Ingestion:</b>    | Do not induce vomiting. Keep individual calm. Get medical attention.                        |

### 5. FIRE FIGHTING MEASURES

|                                            |                                                                                              |
|--------------------------------------------|----------------------------------------------------------------------------------------------|
| <b>Flash point:</b>                        | 23 °C (73.4 °F) Tagliabue closed cup                                                         |
| <b>Autoignition temperature:</b>           | 398.3 °C (748.94 °F) Estimated                                                               |
| <b>Flammable/Explosive limits - lower:</b> | 2.3 %                                                                                        |
| <b>Flammable/Explosive limits - upper:</b> | 12.7 %                                                                                       |
| <b>Extinguishing media:</b>                | Water spray (fog), foam, dry chemical or carbon dioxide.                                     |
| <b>Special firefighting procedures:</b>    | Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. |
| <b>Unusual fire or explosion hazards:</b>  | None                                                                                         |
| <b>Hazardous combustion products:</b>      | Oxides of carbon. Toxic fluorides.                                                           |

### 6. ACCIDENTAL RELEASE MEASURES

|                                                                                                                                    |                                                                                                                                                                                                                   |
|------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel. |                                                                                                                                                                                                                   |
| <b>Environmental precautions:</b>                                                                                                  | Ventilate area. Remove all sources of ignition.                                                                                                                                                                   |
| <b>Clean-up methods:</b>                                                                                                           | Remove all sources of ignition. Ventilate area. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Store in a partly filled, closed container until disposal. |

### 7. HANDLING AND STORAGE

|                  |                                                                     |
|------------------|---------------------------------------------------------------------|
| <b>Handling:</b> | Do not get in eyes. Keep away from heat, spark and flame.           |
| <b>Storage:</b>  | Store away from heat, sparks, flames, or other sources of ignition. |

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.



## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous components                                                 | ACGIH TLV                                           | OSHA PEL                                                                                                                             | AIHA WEEL | OTHER                                                                                      |
|----------------------------------------------------------------------|-----------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|-----------|--------------------------------------------------------------------------------------------|
| 2-Propanol                                                           | 200 ppm TWA<br>400 ppm STEL                         | 400 ppm (980 mg/m <sup>3</sup> ) TWA                                                                                                 | None      | None                                                                                       |
| Talc                                                                 | 2 mg/m <sup>3</sup> TWA<br>Respirable fraction.     | 20 MPPCF TWA<br>2.4 MPPCF TWA<br>Respirable.<br>0.1 mg/m <sup>3</sup> TWA<br>Respirable.<br>0.3 mg/m <sup>3</sup> TWA<br>Total dust. | None      | 50 ppm                                                                                     |
| Castor oil                                                           | None                                                | None                                                                                                                                 | None      | None                                                                                       |
| Polyvinyl butyral - polyvinyl alcohol - polyvinyl acetate terpolymer | None                                                | None                                                                                                                                 | None      | None                                                                                       |
| Titanium dioxide                                                     | 10 mg/m <sup>3</sup> TWA                            | 15 mg/m <sup>3</sup> TWA<br>Total dust.                                                                                              | None      | None                                                                                       |
| Ethene, tetrafluoro-, homopolymer                                    | None                                                | None                                                                                                                                 | None      | 10 mg/m <sup>3</sup> TWA<br>Total dust.<br>5 mg/m <sup>3</sup> TWA<br>Respirable fraction. |
| Quartz (SiO <sub>2</sub> )                                           | 0.025 mg/m <sup>3</sup> TWA<br>Respirable fraction. | 2.4 MPPCF TWA<br>Respirable.<br>0.1 mg/m <sup>3</sup> TWA<br>Respirable.<br>0.3 mg/m <sup>3</sup> TWA<br>Total dust.                 | None      | None                                                                                       |

### Engineering controls:

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

### Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

### Eye/face protection:

Safety goggles or safety glasses with side shields.

### Skin protection:

Chemical resistant, impermeable gloves.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:  
Color:  
Odor:  
Odor threshold:  
pH:  
Vapor pressure:  
Boiling point/range:  
Melting point/ range:  
Specific gravity:  
Vapor density:  
Flash point:  
Flammable/Explosive limits - lower:  
Flammable/Explosive limits - upper:  
Autoignition temperature:  
Evaporation rate:  
Solubility in water:  
Partition coefficient (n-octanol/water):  
VOC content:

Paste  
White  
Alcoholic  
Not available  
Not applicable  
33 mm hg (20 °C (68°F))  
82 °C (179.6 °F)  
Not determined  
1.12 at 25 °C (77°F)  
2.07  
23 °C (73.4 °F) Tagliabue closed cup  
2.3 %  
12.7 %  
398.3 °C (748.94 °F) Estimated  
7.7 (Ether = 1)  
partially soluble  
Not determined  
35.98 %; 343.43 g/l

## 10. STABILITY AND REACTIVITY

|                                   |                                                     |
|-----------------------------------|-----------------------------------------------------|
| Stability:                        | Stable                                              |
| Hazardous reactions:              | Will not occur.                                     |
| Hazardous decomposition products: | Toxic fluorides. Oxides of carbon.                  |
| Incompatible materials:           | Oxidizing agents. Acids. Aldehydes. Amines.         |
| Conditions to avoid:              | Heat, flames, sparks and other sources of ignition. |

## 11. TOXICOLOGICAL INFORMATION

| Hazardous components                                                    | NTP Carcinogen    | IARC Carcinogen | OSHA Carcinogen<br>(Specifically Regulated) |
|-------------------------------------------------------------------------|-------------------|-----------------|---------------------------------------------|
| 2-Propanol                                                              | No                | No              | No                                          |
| Talc                                                                    | No                | No              | No                                          |
| Castor oil                                                              | No                | No              | No                                          |
| Polyvinyl butyral - polyvinyl alcohol -<br>polyvinyl acetate terpolymer | No                | No              | No                                          |
| Titanium dioxide                                                        | No                | Group 2B        | No                                          |
| Ethene, tetrafluoro-, homopolymer                                       | No                | No              | No                                          |
| Quartz (SiO <sub>2</sub> )                                              | Known carcinogen. | Group 1         | No                                          |

| Hazardous components                                                    | Health Effects/Target Organs                                                    |
|-------------------------------------------------------------------------|---------------------------------------------------------------------------------|
| 2-Propanol                                                              | Allergen, Blood, Brain, Central nervous system, Irritant, Kidney, Liver, Spleen |
| Talc                                                                    | Irritant, Lung, Some evidence of carcinogenicity                                |
| Castor oil                                                              | Irritant                                                                        |
| Polyvinyl butyral - polyvinyl alcohol - polyvinyl acetate<br>terpolymer | No Records                                                                      |
| Titanium dioxide                                                        | Irritant, Respiratory, Some evidence of carcinogenicity                         |
| Ethene, tetrafluoro-, homopolymer                                       | No Target Organs                                                                |
| Quartz (SiO <sub>2</sub> )                                              | Immune system, Lung, Some evidence of carcinogenicity                           |

## 12. ECOLOGICAL INFORMATION

|                         |               |
|-------------------------|---------------|
| Ecological information: | Not available |
|-------------------------|---------------|

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

|                                 |                                                                           |
|---------------------------------|---------------------------------------------------------------------------|
| Recommended method of disposal: | Follow all local, state, federal and provincial regulations for disposal. |
| Hazardous waste number:         | D001: Ignitable.                                                          |

## 14. TRANSPORT INFORMATION

### U.S. Department of Transportation Ground (49 CFR)

|                           |                                                |
|---------------------------|------------------------------------------------|
| Proper shipping name:     | Resin solution                                 |
| Hazard class or division: | 3                                              |
| Identification number:    | UN 1866                                        |
| Packing group:            | III                                            |
| Exceptions:               | (Not more than 5 L), ORM-D, Consumer Commodity |

### International Air Transportation (ICAO/IATA)

|                           |                                                              |
|---------------------------|--------------------------------------------------------------|
| Proper shipping name:     | Resin solution                                               |
| Hazard class or division: | 3                                                            |
| Identification number:    | UN 1866                                                      |
| Packing group:            | III                                                          |
| Exceptions:               | Consumer Commodity, ID 8000, Class 9, (Not more than 500 ml) |



**Water Transportation (IMO/IMDG)**

Proper shipping name:  
Hazard class or division:  
Identification number:  
Packing group:

RESIN SOLUTION  
3  
UN 1866  
III

**15. REGULATORY INFORMATION****United States Regulatory Information****TSCA 8 (b) Inventory Status:**

All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

**TSCA 12(b) Export Notification:**

None above reporting de minimus

**CERCLA/SARA Section 302 EHS:**

None above reporting de minimus

**CERCLA/SARA Section 311/312:**

Immediate Health, Delayed Health, Fire

**CERCLA/SARA 313:**

None above reporting de minimus

**CERCLA Reportable quantity:**

2-Propanol (CAS# 67-63-0) 100 lbs. (45.4 kg)

**California Proposition 65:**

This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

**Canada Regulatory Information****CEPA DSL/NDSL Status:**

All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

**WHMIS hazard class:**

B.2, D.2.A, D.2.B

**16. OTHER INFORMATION**

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

Prepared by: Kyra Kozak Woods, Manager, Regulatory Affairs

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.