



February 20, 2026

Ms. Lindsey Wells
Michigan Department of Environment, Great Lakes, and Energy
Air Quality Division, Cadillac District Office
120 West Chapin Street
Cadillac, MI 49601

Subject: Alternative Method Request for a Compliance Performance Demonstration of One (1) Utility (Open) Flare at Wexford County Landfill, Manton, Michigan (ROP MI-ROP-N3862-2022)

Dear Ms. Wells:

On behalf of Wexford County Landfill (Wexford), Environmental Information Logistics, LLC. (EIL), is submitting this request for a modification to the approved test plan for a compliance performance demonstration of one (1) utility flare at Wexford County Landfill in Manton, Michigan.

Upon further review of the current flare sampling ports, we have determined that our original plan to measure landfill gas flow rate to the utility flare by utilizing USEPA Methods 1A and 2C will not be feasible. EIL is proposing an alternative method to determine the landfill gas actual exit velocity based on flow rates measured by the calibrated mass flow meter, last calibrated in June 2025. Flow rate data will be recorded by the flare's digital data logger and downloaded for the evaluation. In addition, EIL will read the flow rate at the flare before, during and after each Method 3C gas sample run, and will record the rates in our field notes. These readings will be included in the test report.

Use of a site's in-place flow meter for open flare performance testing was approved by USEPA in 2009, as long as documentation of recent calibration was provided for the flow meter. Flow meter calibration documentation will be included as an attachment to this request and with the final test report. A copy of the 2009 USEPA letter will also be provided as an attachment to this letter.

The average flow rates measured during each sample run by the calibrated flow meter, in standard units of temperature and pressure, will be divided by the unobstructed cross-sectional area of the flare tip.

The other test methods provided in the original test plan submittal will be unchanged. EIL will analyze the landfill gas composition and moisture content by USEPA Method 3C and use the results to calculate the net heating value. Method 22 will be utilized to verify visible emissions. The planned test date of February 27, 2026, remains unchanged.

Please call me at (989) 415-3741 if you have any questions or require additional information.

Sincerely,

Environmental Information Logistics LLC



Benjamin A. Kotrba
Environmental Scientist

Attachments

cc: Lindsey Wells – MI EGLE
Chris Gee – GFL Environmental
Wexford County Landfill Operating Records

Attachments
Flow Meter Calibration Certificate
and
USEPA 2009 Alternative Method Approval Letter

THERMAL INSTRUMENT COMPANY, INC.

CALIBRATION CERTIFICATION

We certify that the calibration accuracies listed below are obtained on equipment, and with methods, that can be traced directly to the US National Institute of Standards and Technology.

FLOWRATE READOUT ACCURACY: $\pm$ 1% Full Scale

Purchase Order: 26541-SPR

PRESSURE TESTED AT:

Standards:

METER SERIAL NUMBER: 2025311

MODEL NUMBER: 62-9TEF/9500PI

The calibration listed above was performed under the following conditions:

0 - 2500 SCFM LANDFILL GAS MIX

40 - 200 DEG F

0 - 25 PSIG

6" SCH 10 LINE

6.357" LINE ID

LFG MIX: 49% CH₄, 38% CO₂, 1% O₂

Customer Address:

Landmarc IL

Kyle Gragg

3516 Ogden Rd.

Springfield

IL 62711

Standard Conditions: 60Deg. F @ 1 ATM

Deviations:

CERTIFIED THAT THE SUPPLIES/SERVICES DETAILED HEREIN HAVE BEEN INSPECTED AND TESTED IN ACCORDANCE WITH THE CONDITIONS AND REQUIREMENTS OF THE CONTRACT OR PURCHASE ORDER, AND UNLESS OTHERWISE SPECIFIED AS AN AGREED DEVIATION FROM THE CONTRACT, CONFORM IN ALL RESPECTS TO THE SPECIFICATION(S) AND DRAWING(S) RELEVANT THERETO

Signature

Date

June 30, 2025

217 Sterner Mill Road, Trevoze, PA 19053

Phone: 215-355-8400 Fax: 215-355-1789

Web: www.thermalinstrument.com



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
RESEARCH TRIANGLE PARK, NC 27711

MAY 20 2009

OFFICE OF
AIR QUALITY PLANNING
AND STANDARDS

David H. Penoyer
SCS Engineers
4041 Park Oaks Boulevard, Suite 100
Tampa, FL 33610

Dear Mr. Penoyer:

In your May 1, 2009 letter, you requested permission to use an alternative procedure to measure the flow rate of gas exiting the candlestick flare at the Richland Creek Road Landfill in Buford, Georgia. The flare is subject to 40 CFR Part 60.18 for an open flare burning landfill gas. You would like to use a mass flowmeter in place of Method 2, 2A, 2C, or 2D to satisfy the requirements of 60.18(f)(4). Your flowmeter will be sent to the manufacturer to assess the calibration prior to conducting the performance test. A copy of the flowmeter calibration certificate will be attached to the test report.

We approve your use of the mass flowmeter in place of Method 2, 2A, 2C or 2D to measure the flare flow rate at the Richland Creek Road Landfill in Buford, Georgia. Since this alternative method is applicable to other similar facilities in this source category, we will be posting this letter on our website at <http://www.epa.gov/ttn/emc/approalt.html> for use by other interested parties.

If you have questions or would like to discuss the matter further, please call Foston Curtis at (919) 541-1063, or you may e-mail him at curtis.foston@epa.gov.

Sincerely,

A handwritten signature in blue ink that reads "Connie Oldham".

Conniesue B. Oldham, Ph.D., Group Leader
Measurements Technology Group

cc: Foston Curtis (E143-02))
Karen Hays, Georgia EPD
David McNeal, Region 4