

MILLER-STEPHENSON CHEMICAL CO, INC -- MS-136W DPMS U0316A2, RELEASE AGENT
FOR HOT MOLDS -- -

===== Product Identification =====

Product ID:MS-136W DPMS U0316A2, RELEASE AGENT FOR HOT MOLDS

MSDS Date:02/01/1999

FSC:NIIN:Submitter:N EN

Status Code:A

MSDS Number: CKYSG

=== Responsible Party ===

Company Name:MILLER-STEPHENSON CHEMICAL CO, INC

Address:55 BACKUS AVE/GEORGE WASHINGTON HIGHWAY

Box:950

City:DANBURY

State:CT

ZIP:06810

Country:US

Info Phone Num:203-743-4447

Emergency Phone Num:203-797-2212

Preparer's Name:JANET STEPHENS

Chemtrec Ind/Phone:(800)424-9300

CAGE:18598

=== Contractor Identification ===

Company Name:MILLER-STEPHENSON CHEMICAL CO INC

Address:55 BACKUS AVE/GEORGE WASHINGTON HWY

Box:950

City:DANBURY

State:CT

ZIP:06810

Country:US

Phone:203-743-4447

CAGE:18598

===== Composition/Information on Ingredients =====

Ingred Name:TELOMER OF TETRAFLUOROETHYLENE

CAS:9002-84-0

RTECS #:KX4025000

= Wt:2.

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Minumum % Wt:96.

Maxumum % Wt:98.

Ingred Name:ALKYL POLYGLYCOL ETHER

CAS:68439-46-3

= Wt:.2

Ingred Name:SURFACTANTS

= Wt:.2

Ingred Name:NITROGEN

CAS:7727-37-9

RTECS #:QW9700000

= Wt:1.

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PRINCIPLE HEALTH HAZARDS (INCLUDING SIGNIFICANT ROUTES, EFFECTS, SYMPTOMS OF OVEREXPOSURE, AND CONDITIONS AGGRAVATED BY EXPOSURE): INHALATION: INHALATION OF FLUORINE COMPOUNDS RELEASED AS DECOMPOSITION PRODUCTS ABOVE 290 DEGREES C (554 DEGREES F) MAY CAUSE LUNG IRRITATION AND PULMONARY EDEMA WHICH REQUIRE MEDICAL TREATMENT. INHALATION OF FUMES OR SMOKE FROM OVERHEATED OR BURNING PTFE MAY CAUSE POLYMER FUME FEVER, A TEMPORARY FLU-LIKE ILLNESS ACCOMPANIED BY FEVER, CHILLS, AND SOMETIMES COUGH, OF APPROXIMATELY 24 HOURS DURATION. REPEATED EPISODES OF POLYMER FUME FEVER MAY CAUSE LUNG DAMAGE. (SIGNS & SYMPTOMS OF OVEREXPOSURE)

Explanation of Carcinogenicity:NONE OF THE COMPONENTS PRESENT IN THIS MATERIAL ARE LISTED BY IARC, NTP, OSHA, OR ACGIH AS A CARCINOGEN.

Effects of Overexposure:HEALTH HAZARDS ACUTE AND CHRONIC (CONT): SKIN & EYE: ALKYL POLYGLYCOL ETHER ON SHORT EXPOSURE IS A SLIGHT SKIN AND EYE IRRITANT. ON PROLONGED EXPOSURE, E.G. 24 HOURS, ALKYL POLYGLYCOL ETHER IS A MODERATE IRRITANT. ORAL: ALTHOUGH ORAL TOXICITY IS LOW, INGESTION IS TO BE AVOIDED.

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH PREEXISTING DISEASES OF THE LUNGS MAY HAVE INCREASED SUSCEPTIBILITY TO THE TOXICITY OF EXCESSIVE EXPOSURE FROM THERMAL DECOMPOSITION PRODUCTS.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE PATIENT TO FRESH AIR. IF NECESSARY, GIVE ARTIFICIAL RESPIRATION OR OXYGEN. PYROLIZED FUME INHALATION: NORMAL RECOVERY OCCURS WITHIN 24 HOURS. EYE: IN CASE OF CONTACT, IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER AT LEAST 15 MINUTES. CONTACT A PHYSICIAN. SKIN: IF MOLTEN MATERIAL GETS ON SKIN, COOL RAPIDLY WITH COLD WATER. DO NOT ATTEMPT TO REMOVE MATERIAL FROM SKIN. OBTAIN MEDICAL TREATMENT FOR THERMAL BURN. INGESTION: NO SPECIFIC INTERVENTION IS INDICATED AS COMPOUND IS NOT LIKELY TO BE HAZARDOUS BY INGESTION. CONSULT A PHYSICIAN IF NECESSARY.

===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:NONE

Autoignition Temp:Autoignition Temp Text:N/D

Lower Limits:NONFLAMMABLE

Upper Limits:NONFLAMMABLE

Extinguishing Media:WATER SPRAY, FOAM, DRY CHEMICAL, CO2.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS (NIOSH APPROVED -). WEAR FULL PROTECTIVE EQUIPMENT. DOES NOT BURN WITHOUT AN EXTERNAL FLAME. PROTECT FROM HYDROGEN FLUORIDE FUMES WHICH REACT WITH WATER TO FORM HYDROFLUORIC ACID. WEAR NEOPRENE GLOVES WHEN HANDLING REFUSE FROM A FIRE INVOLVING "PTFE".

Unusual Fire/Explosion Hazard:HAZARDOUS GASES / VAPORS PRODUCED IN FIRE ARE HYDROGEN FLUORIDE (HF), CARBONYL FLUORIDE, CARBON MONOXIDE AND LOW MOLECULAR WEIGHT FLUOROCARBONS. AUTOIGNITION TEMPERATURE: NOT DETERMINED. AUTODECOMPOSITION TEMPERATURE: NOT DETERMINED.

===== Accidental Release Measures =====

Spill Release Procedures:SWEET UP TO AVOID SLIPPING HAZARD. USE

APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT DURING CLEANUP.

===== Handling and Storage =====

Handling and Storage Precautions: KEEP CONTAINERS CLOSED TO AVOID CONTAMINATION. PRODUCT IS PERISHABLE IF FROZEN. DO NOT FREEZE. ROTATE STOCK TO SHELF LIFE OF ONE YEAR.

Other Precautions: AVOID BREATHING VAPORS, & LIQUID CONTACT WITH SKIN & EYES. AVOID CONTAMINATION OF TOBACCO OR SMOKING WITH CONTAMINATED HANDS. WASH HANDS THOROUGHLY AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: WEAR APPROPRIATE NIOSH APPROVED RESPIRATORY PROTECTION. EXPOSURE LIMITS: MS-136W: TLV (ACGIH): NONE ESTABLISHED. PEL (OSHA): NONE ESTABLISHED. AEL (DUPONT): 10 MG/M3, 8 HOUR TWA, TOTAL DUST; 5 MG/M3, 8 HOUR TWA, RESPIRABLE DUST.

Ventilation: NORMAL VENTILATION FOR STANDARD MANUFACTURING PROCEDURES IS GENERALLY ADEQUATE. LOCAL EXHAUST SHOULD BE USED WHEN LARGE AMOUNTS ARE RELEASED.

Protective Gloves: WEAR AS APPROPRIATE IMPERVIOUS GLOVES.

Eye Protection: ANSI APPROVED CHEMICAL SAFETY GOGGLES.

Other Protective Equipment: WHERE THERE IS POTENTIAL FOR SKIN CONTACT HAVE AVAILABLE AND WEAR AS APPROPRIATE IMPERVIOUS GLOVES, APRON, PANTS, AND JACKET. EYEWASH FOUNTAIN AND DELUGE SHOWER MEETING ANSI DESIGN CRITERIA

Work Hygienic Practices: DO NOT CONSUME FOOD, DRINK OR TOBACCO IN AREAS WHERE THEY MAY BECOME CONTAMINATED WITH THIS MATERIAL.

Supplemental Safety and Health
CHEMICAL FAMILY: NOT APPLICABLE. FORMULA: (CF₂)N. M.W. APPROX. 40,000.

===== Physical/Chemical Properties =====

Boiling Pt: =100.C, 212.F

Vapor Pres: 24 MMHG AT 77F

Vapor Density: >1 (AIR=1)

pH: 9.0 - 10.0

Evaporation Rate & Reference: NOT DETERMINED.

Solubility in Water: 0 MISCIBLE

Appearance and Odor: MILKY, TRANSLUCENT WHITE DISPERSION, FAINT SWEET ODOR.

Percent Volatiles by Volume: 98%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

INCOMPATIBLE WITH CAUSTIC AND CERTAIN MOLECULAR SIEVES.

Stability Condition to Avoid: MATERIAL IS STABLE AT NORMAL TEMPS AND STORAGE CONDITIONS. HEATING ABOVE THE MELTING POINT OR PROLONGED HEATING ABOVE 260 DEG C (500 DEG F) MAY CAUSE EVOLUTION OF PARTICULATE MATTER

Hazardous Decomposition Products: FLUORIDES. DECOMPOSES WITH HEAT (GREATER THAN 330 DEGREES C). HAZARDOUS GASES/VAPORS PRODUCED ARE HYDROGEN FLUORIDE, HYDROGEN CHLORIDE, AND CARBONYL FLUORIDE.

===== Ecological Information =====

Ecological: AQUATIC TOXICITY: ALKYL POLYGLYCOL ETHER: BIODEGRADABILITY:

GREATER THAN 90% (EEC 73/404). FISH TOXICITY: LC50-10 - 15 MG/L.
 BEHAVIOR IN WATER PURIFICATION PLANTS: IN CASE OF JUDICIOUS USES
 ALKYL POL YGLYCOL ETHER DOES NOT CAUSE DISTURBANCES IN WATER
 PURIFICATION PLANTS ACCORDING TO EXPERIENCES MADE SO FAR.

===== Disposal Considerations =====

Waste Disposal Methods:TREATMENT, STORAGE, TRANSPORTATION, AND
 DISPOSAL MUST BE IN ACCORDANCE WITH APPLICABLE FEDERAL,
 STATE/PROVINCIAL, AND LOCAL REGULATIONS. PREFERRED OPTIONS FOR
 DISPOSAL ARE RECYCLING AND LANDFILL. INCINERATE ONLY IN
 INCINERATOR CAPABLE OF SCRUBBING OUT HYDROGEN FLUORIDE AND OTHER
 ACIDIC COMBUSTION PRODUCTS.

===== MSDS Transport Information =====

Transport Information:PROPER SHIPPING NAME: DOMESTIC (DOT): CONSUMER
 COMMODITY ORM-D; INTERNATIONAL AIR (IATA): AEROSOLS, NON-FLAMMABLE.
 HAZARD CLASS: DOMESTIC (DOT): N/P; INTERNATIONAL AIR (IATA):
 NON-FLAMMABLE GAS, 2.2. UN#: DOMESTIC (DOT): N/P; INTERNATIONAL
 AIR (IATA): 1950. DOT/IATA LABEL: DOMESTIC (DOT): N/P;
 INTERNATIONAL AIR (IATA): NON-FLAMMABLE GAS.

===== Regulatory Information =====

SARA Title III Information:SARA/TITLE III STATUS: REPORTED / INCLUDED.
 SARA/TITLE III HAZARD CATEGORIES AND LIST: PRODUCT HAZARD
 CATEGORIES: ACUTE-YES, CHRONIC HEALTH-NO, FIRE HAZARD-NO,
 REACTIVITY HAZARD-NO, PRESSURE HAZARD- NO. LISTS: EXTREMELY
 HAZARDOUS SUBSTANCES-NO. CERCLA HAZARDOUS SUBSTANCES-NO. TOXIC
 CHEMICALS-NO.

Federal Regulatory Information:TSCA INVENTORY STATUS: REPORTED.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):
 This information is formulated for use by elements of the Department
 of Defense. The United States of America in no manner whatsoever,
 expressly or implied, warrants this information to be accurate and
 disclaims all liability for its use. Any person utilizing this
 document should seek competent professional advice to verify and
 assume responsibility for the suitability of this information to their
 particular situation.