




MICHIGAN DEPARTMENT OF
LABOR & ECONOMIC
OPPORTUNITY



NOTIFICATION OF INTENT TO RENOVATE/DEMOLISH (continued)

10. ASBESTOS INFORMATION

Is asbestos present? (i.e. Assumed or identified in asbestos inspection report)

☒ Yes

☐ No

Will asbestos be removed prior to demolition?

☐ Yes

☐ No

Estimate the amount of asbestos: Include RACM (Regulated Asbestos Containing Material) to be removed, encapsulated, etc. Also include the amount and type (floor tile, roofing, etc.) of non-friable Category I and/or Category II ACM that will not be removed prior to demolition. (**NOTE:** In a demolition, cementitious ACM cannot remain in a structure, as it is likely to become regulated in the demolition/handling process. It must be removed prior to demolition. Also, all asbestos must be removed prior to an intentional burn.)

RACM/ACM	RACM to be Encapsulated	Non-friable ACM <u>not</u> removed prior to demo. Category I	Category II	Units of Measure
100				Cu. Ft.

*Volume (cubic ft./meters) should be used only if unable to measure by linear/square measure (example: asbestos has fallen off of surface).

11. PROJECT DESCRIPTION: Complete **A) for Renovation** (asbestos removal/encapsulation) or **B) for Demolition**:

A) RENOVATION: Mark all surfaces/types of RACM to be removed:

- ☐ Piping ☐ Fittings ☐ Boiler(s) ☐ Tanks(s)
☐ Beam(s) ☐ Duct(s) ☐ Tunnel(s) ☐ Ceiling Tile(s)
☐ Mag Block ☒ Other (describe): landfill

Encapsulation (for LARA): Mark surfaces/types to be encapsulated:

- ☐ Piping ☐ Fittings ☐ Boiler(s) ☐ Tanks(s)
☐ Beam(s) ☐ Duct(s) ☐ Tunnel(s) ☐ Ceiling Tile(s)
☐ Other (describe):

Method of removal: Describe how the asbestos will be removed:

- ☐ Glove Bag ☐ Neg. Pressure Cont. ☐ Cut into sections and remove ☐ Hand Scraping
☐ Dry Removal (please provide attachment with a description and explanation) ☒ Other (describe): Any material encountered during construction activities will be relocated to the appropriate disposal area on site

12. ENGINEERING CONTROLS: Describe work practices and engineering controls used to prevent visible emissions before, during, and after removal, and until proper disposal:

- ☒ Water spray to control dust ☐ Place in leak tight containers ☐ Adequately wet material ☐ Other (describe):

13. UNEXPECTED ASBESTOS: Describe the steps you intend to follow in the event that unexpected RACM is found or previously non-friable asbestos becomes friable (crumbled, pulverized, reduced to powder, etc.) and therefore regulated:

- ☒ Stop Work ☐ Wet material ☐ Contact EGLE and abatement contractor ☐ Revise notification ☐ Other (describe):

14. PROCEDURE(S) USED TO DETECT THE PRESENCE OF ASBESTOS:

A) Indicate how you determined whether or not asbestos is in the facility. If analytical sampling was used, describe method of analysis. (The determination of the presence or absence of asbestos must be made prior to submitting a renovation/demolition notification):

- ☐ All suspect materials sampled and analyzed using Polarized Light Microscopy (PLM) ☐ Other (describe): manifests

B) Name, address, and phone number of company performing asbestos survey: NA, , MI ,

C) Name, accreditation number of inspector, and date of inspection: na na, na, February 3, 2025

15. EMERGENCY RENOVATIONS:

Date/time of emergency:

Describe the sudden, unexpected event:

Explain how the event caused unsafe conditions, and/or would cause equipment damage and/or an unreasonable financial burden:

NOTIFICATION OF INTENT TO RENOVATE/DEMOLISH (continued)

16. Additional Requirements

For Projects involving RACM (required by EGLE)

If this notification is for a Planned or Emergency Renovation, I certify that an individual trained in the provisions of 40 CFR Part 61, Subpart M, will be on-site during the renovation and during demolition involving RACM above the threshold and/or during an ordered demolition. Evidence that this person has completed the required training will be available for inspection at the renovation or demolition site.

For Projects with Negative Pressure Enclosures: (required by LEO)

Per Section 221(1)(2) of P.A. 135 of 1986, as amended, clearance air monitoring is required for any asbestos abatement project involving 10 linear feet/15 square feet or more of friable material which is performed within a negative pressure enclosure. I (the building owner or lessee) have been advised by the contractor of my responsibility under Act 135 to have clearance air monitoring performed on this project. *For affected projects, this section of the notification form must be completed and made part of your records before the project begins.*

I certify that the statements in this notification are true and correct. In submitting this notification, I am aware that a false statement may be grounds for civil or criminal enforcement by EGLE or U.S. EPA.

Tami Craig December 16, 2024

Submitted by Owner or Operator: Date