

Package ‘dils’

July 5, 2013

Type Package

Title Data-Informed Link Strength. Combine multiple-relationship networks into a single weighted network.

Version 0.2

Date 2013-07-05

Author Stephen R. Haptonstahl

Maintainer Stephen R. Haptonstahl <srh@haptonstahl.org>

Suggests testthat

Description Combine multiple-relationship networks into a single weighted network. The approach is similar to factor analysis in that the contribution from each constituent network varies so as to maximize the information gleaned from the multinet. This implementation uses Principal Component Analysis calculated using ‘prcomp’ with bootstrap subsampling.

License MIT + file LICENSE

Depends Rcpp (>= 0.9.13)

LinkingTo Rcpp

Collate

‘GetSampleFromDataFrame.R’ ‘RelationStrengthSimilarity.R’ ‘ScalablePCA.R’ ‘GetSampleFromFile.R’ ‘GetSampleFromDb.R’

Archs i386, x64

R topics documented:

dils-package	2
GetSampleFromDataFrame	2
GetSampleFromDb	3
GetSampleFromFile	4
RelationStrengthSimilarity	5
ScalablePCA	6

Index	7
--------------	---

dils-package	<i>Data-Informed Link Strength. Combine multiple-relationship networks into a single weighted network.</i>
--------------	--

Description

Combine multiple-relationship networks into a single weighted network. The approach is similar to factor analysis in that contribution from each constituent network varies so as to maximize the information gleaned from the multinet network. This implementation uses Principal Component Analysis calculated using 'prcomp' with bootstrap subsampling.

Details

Package: dils
 Type: Package
 Version: 0.2
 Date: 2013-07-05
 License: MIT + file LICENSE

Start with a table (data.frame, tab-delimited file, database) where each row/record represents a link between two nodes (a dyad) in a directed or undirected network and each column represents a different relationship between the two nodes, ie. each column is a network. DILS combines these columns/networks into a single network that is a weighted sum of the constituent networks. The resulting DILS network uses information from all of the constituent networks and contains more information than any of the constituent networks. The output is a data.frame of DILS scores for each dyad, therefore is a single network ready for analysis using **igraph** or other social network analysis (SNA) tools.

Author(s)

Stephen R. Haptonstahl Maintainer: Stephen R. Haptonstahl <srh@haptonstahl.org>

References

"Discovering Missing Links in Networks Using Similarity Measures", Hung-Hsuan Chen, Liang Gou, Xiaolong (Luke) Zhang, C. Lee Giles. 2012.

GetSampleFromDataFrame	<i>Short description of the function</i>
------------------------	--

Description

A longer description of the function. This can be perhaps a paragraph, perhaps more than one.

Usage

```
GetSampleFromDataFrame(n, x)
```

Arguments

n numeric, size of sample.
x data.frame, data whose rows will be sampled.

Value

data.frame, size n random subset of the rows of x

Author(s)

Stephen R. Haptonstahl <srh@haptonstahl.org>

References

<http://www.haptonstahl.org/R>

See Also

[ScalablePCA](#), [GetSampleFromFile](#), [GetSampleFromFile](#)

Examples

```
data(iris) # provides example data  
x <- GetSampleFromDataFrame(10, iris)
```

GetSampleFromDb	<i>Sample from the rows of a (possibly large) database table</i>
-----------------	--

Description

Accesses a dataabase table directly. Returns a data.frame whose rows are the sample.

Usage

```
GetSampleFromDb(n, db)
```

Arguments

n numeric, size of sample to be taken.
db connection, connection to the database table containing the data.

Value

data.frame, size n random subset of the rows of filename

Author(s)

Stephen R. Haptonstahl <srh@haptonstahl.org>

References

<http://www.haptonstahl.org/R>

See Also

[ScalablePCA](#), [GetSampleFromDataFrame](#), [GetSampleFromFile](#)

Examples

```
## Not run: x <- GetSampleFromDb(10, my.db)
```

GetSampleFromFile	<i>Sample from the rows of a (possibly large) text file</i>
-------------------	---

Description

Reads a large text file in batches, keeping the rows to be included in the sample. Returns a data.frame whose rows are the sample.

Usage

```
GetSampleFromFile(n, out.of, filename)
```

Arguments

n	numeric, size of sample to be taken.
out.of	numeric, number of rows in the data set not including the header.
filename	character, name of the file containing the data. This must be a tab-delimited file with a header row formatted per the default options for read.delim .

Value

data.frame, size n random subset of the rows of filename

Author(s)

Stephen R. Haptonstahl <srh@haptonstahl.org>

References

<http://www.haptonstahl.org/R>

See Also

[ScalablePCA](#), [GetSampleFromDataFrame](#), [GetSampleFromDb](#)

Examples

```
## Not run: x <- GetSampleFromFile(10, 150, "folder/containing/data.txt")
```

`RelationStrengthSimilarity`*Calculate the RSS from one node to another*

Description

A longer description of the function. This can be perhaps a paragraph, perhaps more than one.

Usage

```
RelationStrengthSimilarity(xadj, v1, v2, radius)
```

Arguments

<code>xadj</code>	numeric matrix, then description of arg1.
<code>v1</code>	numeric Object type, then description of arg2.
<code>v2</code>	numeric Object type, then description of arg2.
<code>radius</code>	numeric, length of longest path examined from v1 to v2.

Value

numeric, the Relation Strength Similarity score from v1 to v2.

Author(s)

Stephen R. Haptonstahl <srh@haptonstahl.org>

References

"Discovering Missing Links in Networks Using Similarity Measures", Hung-Hsuan Chen, Liang Gou, Xiaolong (Luke) Zhang, C. Lee Giles. 2012.

See Also

[ScalablePCA](#)

Examples

```
M.test.1 <- matrix(0, nrow=6, ncol=6)
M.test.1[1,2] <- M.test.1[2,1] <- 1
M.test.1[1,3] <- M.test.1[3,1] <- 1
M.test.1[3,4] <- M.test.1[4,3] <- 1
M.test.1[4,5] <- M.test.1[5,4] <- 1
M.test.1[5,6] <- M.test.1[6,5] <- 1
M.test.1[6,1] <- M.test.1[1,6] <- 1
M.test.1[1,4] <- M.test.1[4,1] <- 1
M.test.1
## Not run: RelationStrengthSimilarity(xadj=M.test.1, v1=5, v2=6, radius=2)
## Not run: RelationStrengthSimilarity(xadj=M.test.1, v1=5, v2=6, radius=3)
## Not run: RelationStrengthSimilarity(xadj=M.test.1, v1=5, v2=6, radius=4)
```

ScalablePCA

Perform Principal Component Analysis on a large data set

Description

Runs 'prcomp' on subsamples of the data set and compiles the results for the first dimension.

Usage

```
ScalablePCA(x, filename = NULL, db = NULL,
  subsample = 10000, n.subsamples = 1000, ignore.cols,
  use.cols, progress.bar = FALSE)
```

Arguments

x	data.frame, data over which to run PCA
filename	character, name of the file containing the data. This must be a tab-delimited file with a header row formatted per the default options for read.delim .
db	Object type, database connection to table containing the data (NOT IMPLEMENTED)
subsample	numeric or logical, If an integer, size of each subsample. If FALSE, runs PCA on entire data set.
n.subsamples	numeric, number of subsamples.
ignore.cols	numeric, indices of columns not to include
use.cols	numeric, indices of columns to use
progress.bar	logical, if TRUE then progress in running subsamples will be shown.

Value

vector, named vector of component weights for first dimension of principal component analysis (see example for comparison to [prcomp](#))

Author(s)

Stephen R. Haptonstahl <srh@haptonstahl.org>

References

<http://www.haptonstahl.org/R>

See Also

[prcomp](#)

Examples

```
data(iris)          # provides example data
prcomp(iris[,1:4], center=FALSE, scale.=FALSE)$rotation[,1]
ScalablePCA(iris, subsample=10, use.cols=1:4)
ScalablePCA(iris, subsample=10, ignore.cols=5)
```

Index

*Topic **network**

dils-package, [2](#)

dils-package, [2](#)

GetSampleFromDataFrame, [2](#), [4](#)

GetSampleFromDb, [3](#), [4](#)

GetSampleFromFile, [3](#), [4](#), [4](#)

prcomp, [6](#)

read.delim, [4](#), [6](#)

RelationStrengthSimilarity, [5](#)

ScalablePCA, [3–5](#), [6](#)