



Primecoin

CS1699: Blockchain Technology and Cryptocurrency

16. More Variations on a Theme: Non-SHA256 Puzzles

Bill Laboon

Is Bitcoin Mining Wasteful?

- ❖ **Lots** of energy used to... solve partial hash-preimage puzzles
- ❖ Couldn't we use all of this computation to cure cancer or something?

Distributed Computing

- ❖ Volunteer projects have found great success in the past
- ❖ Cheating has occurred, but not to a great extent and is generally detectable
- ❖ Examples: Great Internet Mersenne Prime Search, SETI@home, Folding@home
- ❖ However, none of these are good fits for a cryptocurrency!

Challenges

- ❖ Need an *equiprobable solution space* (i.e., no way to “cherry-pick” data, should be puzzle-friendly)
- ❖ Need an *inexhaustible puzzle space* (i.e., not bounded by available data)
- ❖ Needs to be *algorithmically generated* to avoid centralized administrators determining problems and veracity of solutions

Why Wouldn't These Work?

- ❖ **SETI@home** - Lack of equiprobable solution space, lack of inexhaustible puzzle space, data not algorithmically generated
- ❖ **Folding@home** - Lack of equiprobable solution space, inexhaustible puzzle space, data not algorithmically generated
- ❖ **Great Internet Mersenne Prime Search** - Equiprobable solution space (minus some trivialities), puzzle space proven to be inexhaustible, data can be algorithmically generated...
hmmmm.. but on average, one Mersenne Prime found per year

Primecoin

- ❖ The first (and one of the only) proof-of-useful work coins out there
- ❖ Looks for Cunningham chains of primes
- ❖ How “useful” is this work?

Cunningham Chain of Prime Numbers

- ❖ A sequence of k prime numbers $p_1, p_2, p_3, \dots, p_n$ such that $p_i = 2p_{i-1} + 1$ for each number
- ❖ That is, double a prime number and add one, and repeat this for k iterations. However many iterations you can do this with the number still prime is a Cunningham chain of length k .
- ❖ Example: 2, 5, 11, 23, 47, ~~95~~ Chain of length $k = 5$
- ❖ Conjectured but not proven that there are Cunningham chains of length k for any k (although longest known is $k = 19$)

Parameters

- ❖ For a given challenge x (hash of previous block)
 - ❖ Take first m bits of x
 - ❖ Consider valid a chain of length k or greater in which:
 - ❖ the first prime in the chain is an n -bit prime AND
 - ❖ the first prime in the chain has the same m leading bits as x
- ❖ Can adjust n and k to adjust puzzle difficulty (k modifies it exponentially, n polynomially)

Variation - Golem

- ❖ Golem - Runs on Ethereum, allows you to “rent out” computing power to perform large-scale computing tasks
- ❖ Currently used mostly for 3-D rendering
- ❖ How to verify?

Proof of Storage

- ❖ Also known as “proof of retrievability”
- ❖ Represent a large file or collection of data as a very large Merkle tree, and all participants agree on Merkel root
- ❖ Miners each store a subset $F_m \subseteq F$ of data, associated with their key
- ❖ Miners must find a nonce along with the data that when SHA-256 hashed, is less than the target difficulty
- ❖ PermaCoin (never seriously implemented past white paper, as far as I can tell) , Chia (in beta) (*notice a trend?*)

Proof of Useful Work - A Mirage?

- ❖ Many technical drawbacks and few benefits
- ❖ What computations that meet all of the requirements are actually useful?
- ❖ From an economics standpoint, one could argue that you need to have something which is generally NOT useful otherwise in order to have sound money! (See Saifedean Ammous's *The Bitcoin Standard*)

The Problems of Pools

- ❖ Pools perhaps tend to lead to centralization
- ❖ Pools are also targets for malicious actors
- ❖ Pool miners who are not admins aren't running full nodes
- ❖ Pools not part of "Satoshi's Vision"
- ❖ Pools only possible because:
 - ❖ Possibility of shares - can easily prove that they're working to find valid blocks
 - ❖ Impossible to modify the recipient (would modify nonce)

Block-Discarding Attacks

- ❖ Assume you want to harm a pool and don't care about the damage to yourself
- ❖ You could submit shares, but then when you find a valid block, ignore it
- ❖ Not seen much (or at all) in reality, but theoretically a valid attack if you have a few large pools


Nonoutsourceable Puzzles

- ❖ Puzzles which disincentivize pools or collusion in general
- ❖ Easiest solution: require all miners to know a private key
- ❖ Example: find a block whose hash of a signature is below a certain threshold, with signature computed using the public key of the recipient address
- ❖ As far as I can tell, no real implementation of this

Proof of Stake


- ❖ The idea behind mining is that we have “skin in the game” - we have to do something hard to “put our money where our mouth is” in terms of valid blocks
- ❖ But if we already have a valid currency that can be consumed, can't we use that instead of “wasting” electricity?
- ❖ “Virtual mining” - invest the currency itself instead of electricity and mining hardware

Proof of Work



Virtual Mining

Bitcoin network



Benefits

- ❖ Removes all of the mining - much more efficient!
- ❖ Creates a simpler, closed system - easier to analyze from a game-theory perspective
- ❖ Decentralization - No mining hardware, so anyone could buy Bitcoin and mine on the network
- ❖ Physical miners have slightly different incentives than currency holders - if you had to use Bitcoin to mine, incentives are almost 100% in alignment

Drawbacks

- ❖ Security - with no real-world implications, can people game the system?
- ❖ What if someone gets 51% of the currency? They can keep getting more forever and hard for someone else to get on top
- ❖ Not entirely theoretically understood - “here be monsters”
- ❖ Can it even work on a large scale?

Kinds of Stake

- ❖ **Pure proof of stake** - How much currency you own is your share of the mining power (*Example: NavCoin*)
- ❖ **Delegated proof of stake** - Vote for a “representative” to vote for you (*Example: Nano*)
- ❖ **Proof of deposit** - Deposit coins as a “security deposit” to “stake” them for mining (*Example: Ethereum in the far future*)
- ❖ **Hybrid** - Use both a kind of proof-of-stake and proof-of-work, perhaps by making the work easier based on stake (*Example: Ethereum in the near future*)

Nothing-At-Stake Problem

- ❖ Also known as a “stake-grinding attack”
- ❖ Suppose an attacker with $\alpha < 0.5$ is trying to create a fork (for a double-spend attack, say)
- ❖ This would have a high cost in the real world for a proof-of-work currency

Nothing-At-Stake Problem

- ❖ However, this has NO cost to the attacker in a proof-of-stake currency! No opportunity cost!
- ❖ Miner can use stake on longest chain and simultaneously try to create a fork
- ❖ If fork doesn't come into fruition, all of the currency they used to stake will revert right back to them since only longest chain is valid

Solving Proof of Stake

- ❖ Need to have some way to punish bad actors
- ❖ Ethereum “Slasher” - miner has to sign blocks, and if a miner tries to use the same stake to sign two inconsistent chains, they are punished on the longest chain
- ❖ Should work in theory, but in practice...
- ❖ Ethereum has been promising proof-of-stake Real Soon Now since 2015 or so... and there was just a stall of their proof-of-stake system on the Ropsten testnet - <https://xbt.net/blog/ethereum-blog/etheriums-constantinople-fails-to-activate-on-testnet/>