

Sr. No.	Genset Rated →	5kVA - Mech
A	Genset specification ↓	
1	Genset rating	Prime
2	Genset output (kVA/kWe)	5 / 4
3	Genset model	GPA-PIV- 5M
4	Gross engine Power (kWm)	6.1
5	Gross engine Power (HP)	8.3
6	Engine model	LDA 510 1B1
7	Aspiration / Cooling	Air cooled
8	No. of Cylinders / Arrangement	1
9	Displacement (L)	0.51
10	Bore x Stroke (mm)	85 X 90
11	Compression ratio	18.1
12	Rated RPM	3000
13	Overspeed trip (RPM)	3300
14	Governor type / DG Performance Class	Mech / G2
15	Frequency Regulation	-
16	Air cleaner type / Qty	Oil Bath / 01
B	Exhaust system	
1	Max allowable backpressure (kPa)	5
2	Exhaust temperature (Deg C)	550
3	Silencer type	Residential
4	Aftertreatment System	DOC
C	Engine electrical system	
1	Charging alternator VDC / Amps	NA
2	Starter motor rated voltage (DC)	12
3	Battery voltage (DC) / Capacity (AH)	12V / 35 AH
D	Fuel System	
1	Recommended fuel	IS 1460, HSD
2	Fuel tank capacity (L)	15
E	Fuel Consumption @ % load (LPH)(Including radiator fan + other accessories)⁽¹⁾	
1	LPH @ 100%	1.50
2	LPH @ 75%	1.10
F	Lubricating Oil System	
1	Lube oil sump capacity (L)	1.25
2	Lube oil change period (Hrs)	300
3	Lube oil consumption (% of SFC)	≤0.1%
4	Lube oil filter type / Qty	Spin on / 01
5	Recommended lube oil grade	15W40, API CI4+
6	Recommended lube oil	Greaves Maxtherm

G	Alternator Specification	
1	Alternator Make	NSM
2	Voltage (1P/3P)	230 / 415
3	Frequency (Hz)	50
4	Current (1P/3P) (Amps)	21.79 / 6.96
5	Type	2P, rotating field
6	Voltage regulator	Automatic
7	Voltage regulation -%	±5%
8	Insulation class	H
9	Temperature rise (Deg C)	125
10	Bearing (Qty / type)	1, sealed
11	Coupling	Conical Shaft
12	Unbalanced load capability	-
H	Cooling System	
1	Max ambient capability (Deg C)	NA
2	Coolant capacity (Eng + Rad) (L)	NA
I	Controller	
1	Controller Model	DSE 4520
J	DEF System	
1	Recommended fuel	NA
2	DEF Tank Capacity (L)	NA
K	DEF Consumption	
1	LPH @ 100%	NA
2	LPH @ 75%	NA
L	Genset Outer Dimensions	
1	Length(L) X Width(W) X Height(H) (mm)	1110 x 750 x 863
2	Dry Weight (Approx.) (kg)	300
	Disclaimer:	
	- Ref.: ⁽¹⁾Fuel consumption @ 0.85 Specific Gravity with 5% Tolerance, DEF consumption : 5% of FC - PRIME POWER RATING as per ISO 8528-Part I - Conformance standards: Engine - BS 5514, ISO 3046, Alternator - IS 13364 (I) - Genset - ISO 8528 and Tolerances as applicable. Please refer our GA drawing for overall dimension with add on components like silencer, ducts etc. - Product specifications are subject to change without prior notice due to the policy of continuous improvement.	

GREAVES COTTON LIMITED

Corporate Office: Greaves Cotton Ltd. Unit No. 1A, 5th Floor, Tower 3, Equinox Business Park, LBS Marg, Kurla (W), Mumbai – 400070.

Website: www.greavescotton.com/business/greaves-power

Email: info@greavescotton.com | Call Center Number: 1800 266 0670

ISO 9001:2008
certified by



ISO 14001:2
certified by



NETWORK DIESEL SALES AND SERVICE

Branches : Puducherry / Chennai / Vellore & All over Tamilnadu

Website : www.ndsspondy.com/

Email : karthikj@ndsspondy.com

Call/Watsapp : +91 9786 0090 96 / 9047 447 555