

***Enhanced 3rd Party Interface
Programming Specification Guide
v07.00***

*InterCard Inc.
1884 Lackland Hill Parkway
Suite 1
St. Louis, MO 63146
Tel: 1+314-275-8066
E-mail: info@InterCardinc.com*

Revision History

01.00	May 21 2015	• Initial release
02.00	Oct 05 2015	• Added CreditDebitEscrowPoints command • Modified Refund to include DebitToken, DebitTokenBonus and DebitDuration
03.00	Mar 01 2016	• Added Active immediate flag for time play in CreditAccount and PackageSale.
04.00	Aug 03 2016	• Added Activation and Expiration to CreditAccount request.
05.00	Nov 29 2017	• Added GateAccessSale and RemoveGateAccess requests. • Added GameList, GateAccessList
06.00	Dec 20 2017	• Added MembershipList and UpdateMembership requests.
07.00	Mar 30 2020	• Added ability to use bonus as form of payment.

Overview

The Enhanced 3rd Party Interface v6.0 Programming Specification document is designed for developers who are responsible for integrating their system using the InterCard Enhanced 3rd Party Interface. This document contains information that is proprietary to InterCard Inc. and is subject to the terms of a non-disclosure agreement implemented with InterCard, Inc.

Game Card Account Information

Game card account information is made available in real time via the Transaction Server service. Communication with the Transaction Server is made available through several exposed TCP/IP sockets where client applications connect and transmit account transaction requests. These requests consist of account activities that are subsequently replicated to the datacenter over the WAN.

In general, a client application initiates the socket connection; transmits an ASCII buffer describing the request; and waits for the response buffer from the Transaction Server. The format of the request/response buffer is dependent on the client application and the socket port where it connects. The purpose of this document is to define the XML based request for third party systems.

Note: IP Addresses and port numbers must be configurable on site.

The InterCard names, logs, all related trademarks/names (list each), and other intellectual property are the property of InterCard, Inc. and cannot be used without express written permission from InterCard.

Enhanced 3rd Party Interface Supported Transactions Summary

The Element References listed below are supported in the InterCard Enhanced 3rd Party Interface for third party systems. This document describes how each transaction is used.

- The TransactionRequest element indicates a request for a sequence of information exchange and is present in all request types.
- The RequestType is different for each type of transaction.

The following RequestTypes are available.

- | | | | |
|---------------------------|--------------------|--------------------------|------------------------------|
| • AccountHistory | • EncodeCards | • PackageSale | • UpdateCustomerInfo |
| • BalanceInquiry | • EntitlementClaim | • PauseTimePlay | • UpdateMembership |
| • BlockedAccessList | • GameList | • PaymentViaCustomerCard | • VoidCardTransaction |
| • ClearCard | • GateAccessList | • ReasonCodeLists | • VoidPackageSale |
| • CompCard | • GateAccessSale | • RefundCard | • VoidPaymentViaCustomerCard |
| • ConsolidateCards | • LockCard | • RemoveGateAccess | |
| • CreditAccounts | • MembershipList | • SplitCard | |
| • CreditDebitEscrowPoints | • PackageList | • TransferAccount | |

Note: A transaction with the same MacAddress and UTCDateTime as a previous transaction is considered a duplicate transaction and will not be processed.

Table of Contents

ACCOUNTHISTORY TRANSACTION REQUEST/RESPONSE XML DEFINITIONS	5
ACCOUNTHISTORY REQUEST	5
XML Example: AccountHistory Request	6
ACCOUNTHISTORY RESPONSE	7
XML Example: AccountHistory Response	11
BALANCEINQUIRY TRANSACTION REQUEST/RESPONSE XML DEFINITIONS	14
BALANCEINQUIRY REQUEST	14
XML Example: BalanceInquiry Request	15
BALANCEINQUIRY RESPONSE	16
XML Example: BalanceInquiry Response	18
BLOCKEDACCESSLIST TRANSACTION REQUEST/RESPONSE XML DEFINITIONS	20
BLOCKEDACCESSLIST REQUEST	20
XML Example: BlockedAccessList Request	20
BLOCKEDACCESSLIST RESPONSE	21
XML Example: BlockedAccessList Response	21
CLEARCARD TRANSACTION REQUEST/RESPONSE XML DEFINITIONS	22
CLEARCARD REQUEST	22
XML Example: ClearCard Request	23
CLEARCARD RESPONSE	24
XML Example: ClearCard Response	24
COMPCARD TRANSACTION REQUEST/RESPONSE XML DEFINITIONS	24
COMPCARD REQUEST	24
XML Example: CompCard Request	25
COMPCARD RESPONSE	26
XML Example: CompCard Response	26
CONSOLIDATECARDS TRANSACTION REQUEST/RESPONSE XML DEFINITIONS	27
CONSOLIDATECARDS REQUEST	27
XML Example: ConsolidateCards Request	28
CONSOLIDATECARDS RESPONSE	28
XML Example: ConsolidateCards Response	28
CREDITACCOUNTS TRANSACTION REQUEST/RESPONSE XML DEFINITIONS	29
CREDITACCOUNTS REQUEST	29
XML Example: CreditAccounts Request	31
CREDITACCOUNTS RESPONSE	32
XML Example: CreditAccounts Response	32
CREDITDEBITESCROWPOINTS TRANSACTION REQUEST/RESPONSE XML DEFINITIONS	33
CREDITDEBITESCROWPOINTS REQUEST	33
XML Example: CreditDebitEscrowPoints Request	34
CREDITDEBITESCROWPOINTS RESPONSE	35
XML Example: CreditDebitEscrowPoints Response	35

ENCODECARDS TRANSACTION REQUEST/RESPONSE XML DEFINITIONS	35
ENCODECARDS REQUEST	35
XML Example: EncodeCards Request	37
ENCODECARDS RESPONSE	38
XML Example: EncodeCards Response	38
ENTITLEMENTCLAIM SECTION TRANSACTION REQUEST/RESPONSE XML DEFINITIONS	38
ENTITLEMENTCLAIM REQUEST	38
XML Example: EntitlementClaim Request	39
ENTITLEMENTCLAIM RESPONSE	40
XML Example: EntitlementClaim Response	41
GAMELIST TRANSACTION REQUEST/RESPONSE XML DEFINITIONS	41
GAMELIST REQUEST	41
XML Example: GameList Request	42
GAMELIST RESPONSE	42
XML Example: GameList Response	43
GATEACCESSLIST TRANSACTION REQUEST/RESPONSE XML DEFINITIONS	44
GATEACCESSLIST REQUEST	44
XML Example: GateAccessList Request	44
GATEACCESSLIST RESPONSE	45
XML Example: GateAccessList Response	47
GATEACCESSSALE TRANSACTION REQUEST/RESPONSE XML DEFINITIONS	49
GATEACCESSSALE REQUEST	49
XML Example: GateAccessSale Request	50
GATEACCESSSALE RESPONSE	51
XML Example: GateAccessSale Response	51
LOCKCARD TRANSACTION REQUEST/RESPONSE XML DEFINITIONS	51
LOCKCARD REQUEST	51
XML Example: LockCard Request	52
LOCKCARD RESPONSE	53
XML Example: LockCard Response	53
MEMBERSHIPLIST TRANSACTION REQUEST/RESPONSE XML DEFINITIONS	53
MEMBERSHIPLIST REQUEST	53
XML Example: MembershipList Request	54
MEMBERSHIPLIST RESPONSE	55
XML Example: MembershipList Response	55
PACKAGELIST TRANSACTION REQUEST/RESPONSE XML DEFINITIONS	56
PACKAGELIST REQUEST	56
XML Example: PackageList Request	56
PACKAGELIST RESPONSE	57
XML Example: PackageList Response	57
PACKAGESALE TRANSACTION REQUEST/RESPONSE XML DEFINITIONS	59
PACKAGESALE REQUEST	59
XML Example: PackageSale Request	60

PACKAGE SALE RESPONSE	60
<i>XML Example: PackageSale Response</i>	61
PAUSE TIME PLAY TRANSACTION REQUEST/RESPONSE XML DEFINITIONS	61
PAUSE TIME PLAY REQUEST	61
<i>XML Example: PauseTimePlay Request</i>	62
PAUSE TIME PLAY RESPONSE	62
<i>CommandStatus Section</i>	62
<i>XML Example: PauseTimePlay Response</i>	62
PAYMENT VIA CUSTOMER CARD TRANSACTION REQUEST/RESPONSE XML DEFINITIONS	63
PAYMENT VIA CUSTOMER CARD REQUEST	63
<i>XML Example: PaymentViaCustomerCard Request</i>	64
PAYMENT VIA CUSTOMER CARD RESPONSE	65
<i>XML Example: PaymentViaCustomerCard Response</i>	65
REASON CODE LISTS TRANSACTION REQUEST/RESPONSE XML DEFINITIONS	65
REASON CODE LISTS REQUEST	65
<i>XML Example: ReasonCodeLists Request</i>	66
REASON CODE LISTS RESPONSE	66
<i>XML Example: ReasonCodeLists Response</i>	67
REFUND CARD TRANSACTION REQUEST/RESPONSE XML DEFINITIONS	69
REFUND CARD REQUEST	69
<i>XML Example: RefundCard Request</i>	70
REFUND CARD RESPONSE	71
<i>XML Example: RefundCard Response</i>	71
REMOVE GATE ACCESS REQUEST/RESPONSE XML DEFINITION	72
REMOVE GATE ACCESS REQUEST	72
<i>XML Example: RemoveGateAccess Request</i>	73
REMOVE GATE ACCESS RESPONSE	73
<i>XML Example: RemoveGateAccess Response</i>	73
SPLIT CARD TRANSACTION REQUEST/RESPONSE XML DEFINITIONS	74
SPLIT CARD REQUEST	74
<i>XML Example: SplitCard Request</i>	76
SPLIT CARD RESPONSE	77
<i>XML Example: SplitCard Response</i>	77
TRANSFER ACCOUNT TRANSACTION REQUEST/RESPONSE XML DEFINITIONS	78
TRANSFER ACCOUNT REQUEST	78
<i>XML Example: TransferAccount Request</i>	79
TRANSFER ACCOUNT RESPONSE	79
<i>XML Example: TransferAccount Response</i>	80
UPDATE CUSTOMER INFO TRANSACTION REQUEST/RESPONSE XML DEFINITIONS	80
UPDATE CUSTOMER INFO REQUEST	80
<i>XML Example: UpdateCustomerInfo Request</i>	81
UPDATE CUSTOMER INFO RESPONSE	82
<i>XML Example: UpdateCustomerInfo Response</i>	82

UPDATEMEMBERSHIP REQUEST/RESPONSE XML DEFINITIONS	82
UPDATEMEMBERSHIP REQUEST	82
<i>XML Example: UpdateMembership Request</i>	83
UPDATEMEMBERSHIP RESPONSE	84
<i>XML Example: UpdateMembership Response</i>	84
VOIDCARDTRANSACTION TRANSACTION REQUEST/RESPONSE XML DEFINITIONS	84
VOIDCARDTRANSACTION REQUEST	84
<i>XML Example: VoidCardTransaction Request</i>	86
VOIDCARDTRANSACTION RESPONSE	87
<i>XML Example: VoidCardTransaction Response</i>	87
VOIDPACKAGESALE TRANSACTION REQUEST/RESPONSE XML DEFINITIONS	88
VOIDPACKAGESALE REQUEST	88
<i>XML Example: VoidPackageSale Request</i>	89
VOIDPACKAGESALE RESPONSE	89
<i>XML Example: VoidPackageSale Response</i>	89
VOIDPAYMENTVIACUSTOMERCARD TRANSACTION REQUEST/RESPONSE XML DEFINITIONS	90
VOIDPAYMENTVIACUSTOMERCARD REQUEST	90
<i>XML Example: VoidPaymentViaCustomerCard Request</i>	91
VOIDPAYMENTVIACUSTOMERCARD RESPONSE	92
<i>XML Example: VoidPaymentViaCustomerCard Response</i>	92

AccountHistory Transaction Request/Response XML Definitions

The AccountHistory request allows you to retrieve all transactions occurring on the account during the specified start and end date range. All transactions are stored in UTC DateTime and the LocalUTCOffset field adjusts the date/time fields accordingly.

AccountHistory Request

TransactionRequest Section			
Element Name	Type	Required	Description/Value
RequestType	RequestTypeValue	Y	The Request Type must be set to AccountHistory .
MacAddress	string	Y	The MacAddress is the request address of the machine and must be registered in the InterCard system.
TransactionID	string	N	The Transaction ID is associated with the transaction on the requesting machine.
SessionID	string	N	The SessionID is the cash drawer session ID of the requesting machine.
EmployeeID	string	Y	The EmployeeID is the employee ID on the requesting machine.
EmployeeName:	Complex	*	*The Employee Name is not required; however, if used, the Employee Name must include both the first and last names of the employee associated with the transaction.
EmployeeFirstName	string		
EmployeeLastName	string		
LT_DateTime	dateTime (requires millisecond resolution)	Y	This is the current local date/time of the location where the request is made.
UTC_DateTime	dateTime (requires millisecond resolution)	Y	A transaction with the same MacAddress and UTC DateTime as a previous transaction should be sent from the location where the transaction occurred.

AccountHistory Section			
Element Name	Type	Required	Description/Value
AccountNumber	long	Y	The AccountNumber is the primary identifier of the account and is used to retrieve account information.
HistoryStartDate	dateTime	Y	The HistoryStartDate is a date/time field that specifies the beginning date for the transaction list.
HistoryEndDate	dateTime	Y	The HistoryEndDate is a date/time field that specifies the ending date for the transaction list.
LocalUTCOffset	int	Y	The LocalUTCOffset is a positive or negative integer that specifies the time offset in minutes for the location where the transactions occurred.

XML Example: AccountHistory Request

```

<?xml version="1.0"?>
<iEnhancedInterfaceRequest xmlns:xsi=http://www.w3.org/2001/XMLSchema-instance
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <TransactionRequest>
    <RequestType>AccountHistory</RequestType>
    <MacAddress>AAABBBCCCDDD</MacAddress>
    <TransactionID>0001</TransactionID>
    <SessionID>A0001</SessionID>
    <EmployeeID>stester</EmployeeID>
    <EmployeeName>
      <FirstName>Some</FirstName>
      <LastName>Tester</LastName>
    </EmployeeName>
    <LT_DateTime>2014-07-23T15:20:12.0202234-05:00</LT_DateTime>
    <UTC_DateTime>2014-07-23T20:20:12.0202234Z</UTC_DateTime>
  </TransactionRequest>
  <AccountHistoryRequest>
    <AccountNumber>15176</AccountNumber>
    <HistoryStartDate>2014-07-22T16:46:07.2520858-05:00</HistoryStartDate>
    <HistoryEndDate>2014-07-23T16:46:07.2520858-05:00</HistoryEndDate>
    <LocalUTCOffset>-300</LocalUTCOffset>
  </AccountHistoryRequest>
</iEnhancedInterfaceRequest>

```

AccountHistory Response

CommandStatus Section			
Element Name	Type	Returned	Description/Value
ResponseCode	int	Y	A value of 0 indicates success; a non-zero value indicates an error occurred while processing the request.
ResponseDescription	string	Y	A text response providing additional information regarding the status of the request.

AccountHistory Section			
Element Name	Type	Returned	Description/Value
AccountBalance	AccountBalance	Y	The current balance showing on the account.
AccountHistoryList	AccountHistoryItem[]	Y	The list of account transactions showing for the specified date range.
RedemptionHistoryList	RedemptionHistoryItem[]	Y	The list of redemption transactions on the account for the specified date range.

AccountBalance Section			
Element Name	Type	Returned	Description/Value
AccountNumber	long	Y	The account number is a unique value that is assigned to a specific card.
LocID	int	Y	InterCard location ID where the card was first introduced to the system; or if the card is registered then it is the location where the account was registered.
BlockedAccessID	int	Y	ID of the blocked access associated to the account. Optional reference to a predefined blocked access.
Registered	boolean	Y	True if the account is registered; False if the account is unregistered.
MembershipCashPeriodSum	double	Y	The amount of cash put on an account that is above the last membership level.
MembershipDemotionTimeStamp	dateTime	Y	The expiration date of the current membership.

AccountBalance Section			
Element Name	Type	Returned	Description/Value
FirstName	string	Y	The first name of the person to whom the account is registered.
LastName	string	Y	The last name of the person to whom the account is registered; if the account is not registered, an empty string displays.
EmpCredits	int	Y	If this is an employee account, enter the number of credits allowed for the employee; if no credits are allowed, enter 0.
EmpStatus	int	Y	1 displays if this is an employee account; 0 displays if not an employee.
NewCard	boolean	Y	True, if the account has not been introduced to the InterCard system.
CashBalance	double	Y	The cash balance on the account.
CashBonusBalance	double	Y	The cash bonus balance on the account.
TokenBalance	int	Y	The number of tokens on the account.
TokenBonusBalance	int	Y	The number of bonus tokens on the account.
PointBalance	int	Y	The point balance on the account.
TP_StartTime	dateTime	Y	If timeplay is currently active on the account then this is the start time of the timeplay session.
TP_EndTime	dateTime	Y	If timeplay is currently active on the account, this is when the timeplay expires.
TP_Duration	int	Y	If timeplay is associated with the account, this is the number of minutes remaining. If the value is negative, then timeplay is associated; however, the card timeplay has not been activated by a card swipe on a reader.
Discount	int	Y	The percent discount on play for an account.
Status	int	Y	A status of 0 indicates the account is active. Any non-zero status indicates that a lock is on the account.

ActivationDate	dateTime	Y	The time/date stamp when the account will become active.
ExpirationDate	dateTime	Y	The time date stamp when the account will expire.
MembershipPromoID	int	Y	The InterCard membership ID if the account has an associated membership; otherwise 0.
LinkedGA	LinkedGateAccess[]	Y	The list of gate access items on the account.
LinkedPB	LinkedProductBalance[]	Y	The list of product entitlements on the account.

LinkedGateAccess Section			
Element Name	Type	Required	Description/Value
ProductTag	int	Y	The product tag for the gate access.
DeviceTag	long	Y	The device tag of the reader belonging to the gate access.
Actuations	int	Y	The number of swipes permitted for the gate access. Note: The actuations represent the total shared for all matching LinkedGateAccess ProductTag within LinkedGA.

LinkedProductBalance Section			
Element Name	Type	Required	Description/Value
ProductCategory	int	y	The InterCard product category of the product.
ProductTag	int	Y	The product tag for the linked product.
Product	string	Y	The name of the product.
QtyToPayOut	int	Y	The number of available produts to pay out.
QtyPaidOut	int	Y	The number of products to be claimed.

AccountHistoryItem Section			
Element Name	Type	Returned	Description/Value
DeviceName	string	Y	The name of the device where the transaction occurred.
Cash	double	Y	The amount of cash added/deducted to/from the account during the transaction.

CashBonus	double	Y	The amount of cash bonus added/deducted to/from the account during the transaction.
Tokens	int	Y	The number of tokens added/deducted to/from the account during the transaction.
TokenBonus	int	Y	The number of bonus tokens added/deducted to/from the account during the transaction.
Points	int	Y	The number of points added/deducted to/from the account during the transaction.
ActionType	string	Y	The description of the action on the account during the transaction.
Timestamp	dateTime	Y	The local date/time stamp of the transaction.
TransType	string	Y	Description of the transaction type.
EmployeeName	string	Y	Name of the employee involved in the transaction.
Location	string	Y	Name of the location where the transaction took place.

RedemptionHistoryItem Section			
Element Name	Type	Returned	Description/Value
DeviceName	string	Y	The name of the device where the transaction occurred.
Debits	int	Y	The number of points deducted during the transaction.
DeltronicTickets	int	Y	The number of points added during a Deltronic ticket transaction.
PointsBorrowed	int	Y	The number of points borrowed the transaction.
PointsComped	int	Y	The number of points comped during the transaction.
LenderAccount	long	Y	The account number of the lender, if points were borrowed during the transaction.
ProductName	string	Y	The name of the item redeemed during the transaction.
Quantity	int	Y	The number of items given the transaction.
EmployeeName	string	Y	Name of the employee involved during the transaction.
Timestamp	dateTime	Y	The local date time stamp of the transaction.
Location	string	Y	The location name where the transaction took place.

XML Example: AccountHistory Response

```
<?xml version="1.0"?>
<iEnhancedInterfaceResponse xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <CommandStatus>
    <ResponseCode>0</ResponseCode>
    <ResponseDescription>Success</ResponseDescription>
  </CommandStatus>
  <AccountHistory>
    <AccountBalance>
      <AccountNumber>12345</AccountNumber>
      <LocID>4</LocID>
      <BlockedAccessID>0</BlockedAccessID>
      <Registered>false</Registered>
      <MembershipCashPeriodSum>78883.00000</MembershipCashPeriodSum>
      <MembershipDemotionTimeStamp>2019-03-05T15:17:00.000
    </MembershipDemotionTimeStamp>
      <FirstName></FirstName>
      <LastName></LastName>
      <EmpCredits>0</EmpCredits>
      <EmpStatus>0</EmpStatus>
      <NewCard>false</NewCard>
      <CashBalance>78883.00000</CashBalance>
      <CashBonusBalance>6559.00000</CashBonusBalance>
      <TokenBalance>20</TokenBalance>
      <TokenBonusBalance>0</TokenBonusBalance>
      <PointBalance>390</PointBalance>
      <TP_StartTime>2014-10-15T10:21:00.000</TP_StartTime>
      <TP_EndTime>2014-10-15T10:21:00.000</TP_EndTime>
      <TP_Duration>-105</TP_Duration>
      <Discount>10</Discount>
      <Status>0</Status>
      <ActivationDate>2014-10-15T05:21:00.000</ActivationDate>
      <ExpirationDate>2019-10-15T10:21:00.000</ExpirationDate>
      <MembershipPromoID>25</MembershipPromoID>
      <LinkedGA>
        <LinkedGateAccess>
          <ProductTag>1417</ProductTag>
          <DeviceTag>10018</DeviceTag>
          <Actuations>3</Actuations>
        </LinkedGateAccess>
        <LinkedGateAccess>
          <ProductTag>1417</ProductTag>
          <DeviceTag>4359</DeviceTag>
          <Actuations>3</Actuations>
        </LinkedGateAccess>
      </LinkedGA>
    </AccountBalance>
  </AccountHistory>
</iEnhancedInterfaceResponse>
```

```
</LinkedGateAccess>
</LinkedGA>
<LinkedPB>
  <LinkedProductBalance>
    <ProductCategory>0</ProductCategory>
    <ProductTag>1192</ProductTag>
    <Product>Large Soda</Product>
    <QtyToPayout>1</QtyToPayout>
    <QtyPaidOut>0</QtyPaidOut>
  </LinkedProductBalance>
</LinkedPB>
</AccountBalance>
<AccountHistoryList>
  <AccountHistoryItem>
    <DeviceName>Test ETPI Program</DeviceName>
    <Cash>5</Cash>
    <CashBonus>10.00</CashBonus>
    <Tokens>0</Tokens>
    <TokenBonus>0</TokenBonus>
    <Points>0</Points>
    <ActionType>null</ActionType>
    <Timestamp>2018-03-08T14:28:47.413</Timestamp>
    <TransType>Credit</TransType>
    <EmployeeName>N/A</EmployeeName>
    <Location>St. Louis</Location>
  </AccountHistoryItem>
  <AccountHistoryItem>
    <DeviceName>iReader2</DeviceName>
    <Cash>1.0000</Cash>
    <CashBonus>0.0000</CashBonus>
    <Tokens>0</Tokens>
    <TokenBonus>0</TokenBonus>
    <Points>0</Points>
    <ActionType>null</ActionType>
    <Timestamp>2018-03-08T15:15:14.932</Timestamp>
    <TransType>Game Play</TransType>
    <EmployeeName>N/A</EmployeeName>
    <Location>St. Louis</Location>
  </AccountHistoryItem>
  <AccountHistoryItem>
    <DeviceName>iCashier Dev 1</DeviceName>
    <Cash>0</Cash>
    <CashBonus>0</CashBonus>
    <Tokens>0</Tokens>
    <TokenBonus>0</TokenBonus>
```

```
<Points>500</Points>
<ActionType>null</ActionType>
<Timestamp>2018-03-08T14:35:14.932</Timestamp>
<TransType>Comped</TransType>
<EmployeeName>Smith, John</EmployeeName>
<Location>St. Louis</Location>
</AccountHistoryItem>
</AccountHistoryList>
<RedemptionHistoryList>
  <RedemptionHistoryItem>
    <DeviceName>iCashier Dev 1</DeviceName>
    <Debits>0</Debits>
    <DeltronicTickets>0</DeltronicTickets>
    <PointsBorrowed>0</PointsBorrowed>
    <PointsComped>500</PointsComped>
    <LenderAccount>0</LenderAccount>
    <ProductName>N/A</ProductName>
    <Quantity>0</Quantity>
    <EmployeeName>Smith, John</EmployeeName>
    <Timestamp>2018-03-08T09:35:14.932</Timestamp>
    <Location>St. Louis</Location>
  </RedemptionHistoryItem>
  <RedemptionHistoryItem>
    <DeviceName>iCashier Dev 1</DeviceName>
    <Debits>-50</Debits>
    <DeltronicTickets>0</DeltronicTickets>
    <PointsBorrowed>0</PointsBorrowed>
    <PointsComped>0</PointsComped>
    <LenderAccount>0</LenderAccount>
    <ProductName>24 PC/DB HAND BUZZERS</ProductName>
    <Quantity>1</Quantity>
    <EmployeeName>Smith, John</EmployeeName>
    <Timestamp>2018-03-08T09:35:40.119</Timestamp>
    <Location>St. Louis</Location>
  </RedemptionHistoryItem>
  <RedemptionHistoryItem>
    <DeviceName>iCashier Dev 1</DeviceName>
    <Debits>-20</Debits>
    <DeltronicTickets>0</DeltronicTickets>
    <PointsBorrowed>0</PointsBorrowed>
    <PointsComped>0</PointsComped>
    <LenderAccount>0</LenderAccount>
    <ProductName>ASSORTEDPENCILS</ProductName>
    <Quantity>1</Quantity>
    <EmployeeName>Smith, John</EmployeeName>
```



```

        <Timestamp>2018-03-08T09:36:11.932</Timestamp>
        <Location>St. Louis</Location>
    </RedemptionHistoryItem>
    <RedemptionHistoryItem>
        <DeviceName>iCashier Dev 1</DeviceName>
        <Debits>-40</Debits>
        <DeltronicTickets>0</DeltronicTickets>
        <PointsBorrowed>0</PointsBorrowed>
        <PointsComped>0</PointsComped>
        <LenderAccount>0</LenderAccount>
        <ProductName>ASSORTEDPENCILS</ProductName>
        <Quantity>2</Quantity>
        <EmployeeName>Smith, John</EmployeeName>
        <Timestamp>2018-03-08T09:36:16.201</Timestamp>
        <Location>St. Louis</Location>
    </RedemptionHistoryItem>
</RedemptionHistoryList>
</AccountHistory>
</iEnhancedInterfaceResponse>hancedInterfaceResponse>

```

BalanceInquiry Transaction Request/Response XML Definitions

BalanceInquiry allows you to retrieve balance information for the specified account number.

BalanceInquiry Request

TransactionRequest Section			
Element Name	Type	Required	Description/Value
RequestType	RequestTypeValue	Y	The RequestTypeValue must be set to BalanceInquiry .
MacAddress	string	Y	This is the MAC address of the request machine. <i>Note: The MAC address must be registered in the InterCard system.</i>
TransactionID	string	N	This is the transaction ID associated with the transaction on the requesting machine.
SessionID	string	N	The SessionID is the cash drawer session ID of the requesting machine.
EmployeeID	string	Y	<i>EmployeeID</i> , this is the employeeID on the requesting machine.

TransactionRequest Section			
Element Name	Type	Required	Description/Value
EmployeeName:	Complex	*	*The Employee Name is not required; however, if used, the Employee Name must include both the first and last names of the employee associated with the transaction.
EmployeeFirstName	string		
EmployeeLastName	string		
LT_DateTime	dateTime (requires millisecond resolution)	Y	This is the current local date/time of the location where the request is made.
UTC_DateTime	dateTime (requires millisecond resolution)	Y	UTC DateTime is the current UTCDateTime for the location where the transaction occurred.

BalanceInquiry Section			
Element Name	Type	Required	Description/Value
AccountNumber	long	Y	The AccountNumber is a unique number assigned to each customer card and is the primary identifier of the account. The AccountNumber is used to retrieve account information.

XML Example: BalanceInquiry Request

```

<?xml version="1.0"?>
<iEnhancedInterfaceRequest xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <TransactionRequest>
    <RequestType>BalanceInquiry</RequestType>
    <MacAddress>AAABBBCCDDDD</MacAddress>
    <TransactionID>0001</TransactionID>
    <SessionID>A0001</SessionID>
    <EmployeeID>stester</EmployeeID>
    <EmployeeName>
      <FirstName>Some</FirstName>
      <LastName>Tester</LastName>
    </EmployeeName>
    <LT_DateTime>2014-07-23T15:20:12.0202234-05:00</LT_DateTime>
    <UTC_DateTime>2014-07-23T20:20:12.0202234Z</UTC_DateTime>
  </TransactionRequest>
  <BalanceInquiry>
    <AccountNumber>15176</AccountNumber>
  </BalanceInquiry>
</iEnhancedInterfaceRequest>

```

BalanceInquiry Response

CommandStatus Section			
Element Name	Type	Returned	Description/Value
ResponseCode	int	Y	A value of 0 indicates success; a non-zero value indicates an error occurred while processing the request.
ResponseDescription	string	Y	A text response providing additional information regarding the status of the request.

AccountBalance Section			
Element Name	Type	Returned	Description/Value
AccountNumber	long	Y	The account number that the balance inquiry belongs.
LocID	int	Y	InterCard location ID where the card was first introduced to the system or if the card is register then it is the location where the account was registered.
BlockedAccessID	int	Y	ID of the blocked access associated to the account.
Registered	boolean	Y	True if account is registered, false otherwise.
MembershipCashPeriodSum	double	Y	The amount of cash put on an account that is above the last membership level.
MembershipDemotionTimeStamp	dateTime	Y	The date when the current membership expires.
FirstName	string	Y	The first name if the account is registered, empty string if account not registered.
LastName	string	Y	The last name if the account is registered, empty string if account not registered.
EmpCredits	int	Y	If the account is an employee account then the amount of plays allowed otherwise 0.
EmpStatus	int	Y	1 if the account is an employee, 0 otherwise.
NewCard	boolean	Y	True if the account has not been introduced to the InterCard system.
CashBalance	double	Y	The cash balance of the account.
CashBonusBalance	double	Y	The cash bonus balance of the account.

AccountBalance Section			
Element Name	Type	Returned	Description/Value
TokenBalance	int	Y	The token balance of the account.
TokenBonusBalance	int	Y	The token bonus balance of the account.
PointBalance	int	Y	The point balance of the account.
TP_StartTime	dateTime	Y	If timeplay is currently active on the account then the start time of the timeplay session.
TP_EndTime	dateTime	Y	If timeplay is currently active on the account then this is the time when the timeplay will expire.

AccountBalance Section			
Element Name	Type	Returned	Description/Value
TP_Duration	int	Y	If timeplay is associated with the account then it is the number of minutes remaining. If the value is negative, timeplay is associated; however the card timeplay has not been activated by a card swipe on a reader.
Discount	int	Y	The percent discount on play for an account.
Status	int	Y	A status of 0 indicates the account is active. Any non-zero status indicates that there is a lock on the account.
ActivationDate	dateTime	Y	The time date stamp when the account will start being active.
ExpirationDate	dateTime	Y	The time/date stamp when the account will expire.
MembershipPromoID	int	Y	The InterCard membership ID if the account has a membership associated with it; otherwise 0.
LinkedGA	LinkedGateAccess[]	Y	The list of gate access items on the account.
LinkedPB	LinkedProductBalance[]	Y	The list of product entitlements on the account.

LinkedGateAccess Section			
Element Name	Type	Required	Description/Value
ProductTag	int	Y	The product tag for the gate access.
DeviceTag	long	Y	The device tag of the reader belonging to the gate access.
Actuations	int	Y	The number of swipes permitted for the gate access. Note: The actuations represent the total shared for all matching LinkedGateAccess ProductTag within LinkedGA.

LinkedProductBalance Section			
Element Name	Type	Required	Description/Value
ProductCategory	int	y	The InterCard product category of the product.
ProductTag	int	Y	The product tag for the linked product.
Product	string	Y	The name of the product.
QtyToPayOut	int	Y	The number of available products to pay out.
QtyPaidOut	int	Y	The number of products to be claimed.

XML Example: BalanceInquiry Response

```

<?xml version="1.0"?>
<iEnhancedInterfaceResponse xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <CommandStatus>
    <ResponseCode>0</ResponseCode>
    <ResponseDescription>Success</ResponseDescription>
  </CommandStatus>
  <AccountBalance>
    <AccountNumber>12345</AccountNumber>
    <LocID>4</LocID>
    <BlockedAccessID>0</BlockedAccessID>
    <Registered>>false</Registered>
    <MembershipCashPeriodSum>78883.00000</MembershipCashPeriodSum>
    <MembershipDemotionTimeStamp>2019-03-05T15:17:00.000
  </MembershipDemotionTimeStamp>
    <FirstName></FirstName>
    <LastName></LastName>
    <EmpCredits>0</EmpCredits>
    <EmpStatus>0</EmpStatus>
    <NewCard>>false</NewCard>
  </AccountBalance>
</iEnhancedInterfaceResponse>

```

```
<CashBalance>78883.00000</CashBalance>
<CashBonusBalance>6559.00000</CashBonusBalance>
<TokenBalance>20</TokenBalance>
<TokenBonusBalance>0</TokenBonusBalance>
<PointBalance>390</PointBalance>
<TP_StartTime>2014-10-15T10:21:00.000</TP_StartTime>
<TP_EndTime>2014-10-15T10:21:00.000</TP_EndTime>
<TP_Duration>-105</TP_Duration>
<Discount>10</Discount>
<Status>0</Status>
<ActivationDate>2014-10-15T05:21:00.000</ActivationDate>
<ExpirationDate>2019-10-15T10:21:00.000</ExpirationDate>
<MembershipPromoID>25</MembershipPromoID>
<LinkedGA>
  <LinkedGateAccess>
    <ProductTag>1417</ProductTag>
    <DeviceTag>10018</DeviceTag>
    <Actuations>3</Actuations>
  </LinkedGateAccess>
  <LinkedGateAccess>
    <ProductTag>1417</ProductTag>
    <DeviceTag>4359</DeviceTag>
    <Actuations>3</Actuations>
  </LinkedGateAccess>
</LinkedGA>
<LinkedPB>
  <LinkedProductBalance>
    <ProductCategory>0</ProductCategory>
    <ProductTag>1192</ProductTag>
    <Product>Description Not Available</Product>
    <QtyToPayout>1</QtyToPayout>
    <QtyPaidOut>0</QtyPaidOut>
  </LinkedProductBalance>
</LinkedPB>
</AccountBalance>
</iEnhancedInterfaceResponse>
```

BlockedAccessList Transaction Request/Response XML Definitions

To retrieve the list of blocked access IDs and descriptions. A blocked access defines a group of games that are to be blocked from play for the account(s).

BlockedAccessList Request

TransactionRequest Section			
Element Name	Type	Required	Description/Value
RequestType	RequestTypeValue	Y	The RequestTypeValue must be set to BlockedAccessList .
MacAddress	string	Y	This is the MAC address of the request machine. <i>Note: The MAC address must be registered in the InterCard system.</i>
TransactionID	string	N	This is the transaction ID associated with the transaction on the requesting machine.
SessionID	string	N	The SessionID is the cash drawer session ID of the requesting machine.
EmployeeID	string	Y	<i>EmployeeID</i> , this is the employeeID on the requesting machine.
EmployeeName:	Complex	*	*The Employee Name is not required; however, if used, the Employee Name must include both the first and last names of the employee associated with the transaction.
EmployeeFirstName	string		
EmployeeLastName	string		
LT_DateTime	dateTime (requires millisecond resolution)	Y	This is the current local date/time of the location where the request is made.
UTC_DateTime	dateTime (requires millisecond resolution)	Y	UTC DateTime is the current UTCDateTime for the location where the transaction occurred.

XML Example: BlockedAccessList Request

```
<?xml version="1.0"?>
<iEnhancedInterfaceRequest xmlns:xsi=http://www.w3.org/2001/XMLSchema-instance
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <TransactionRequest>
    <RequestType>BlockedAccessList</RequestType>
    <MacAddress>AAABBBCCDDDD</MacAddress>
    <TransactionID>0001</TransactionID>
    <SessionID>A0001</SessionID>
    <EmployeeID>stester</EmployeeID>
    <EmployeeName>
```

```

    <FirstName>Some</FirstName>
    <LastName>Tester</LastName>
  </EmployeeName>
  <LT_DateTime>2014-07-24T11:25:51.5118057-05:00</LT_DateTime>
  <UTC_DateTime>2014-07-24T16:25:51.5118057Z</UTC_DateTime>
</TransactionRequest>
</iEnhancedInterfaceRequest>

```

BlockedAccessList Response

CommandStatus Section			
Element Name	Type	Returned	Description/Value
ResponseCode	int	Y	A value of 0 indicates success; a non-zero value indicates an error occurred while processing the request.
ResponseDescription	string	Y	A text response providing additional information regarding the request status.

BlockedAccessList Section			
Element Name	Type	Returned	Description/Value
BlockedAccessList	BlockedAccessDetail[]	Y	An array of blocked access details.

BlockedAccessDetail Section			
Element Name	Type	Returned	Description/Value
BlockedAccessID	int	Y	The ID of the blocked access.
BlockedAccessDescription	string	Y	A brief description of the blocked access.

XML Example: BlockedAccessList Response

```

<?xml version="1.0"?>
<iEnhancedInterfaceResponse xmlns:xsi=http://www.w3.org/2001/XMLSchema-instance
  xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <CommandStatus>
    <ResponseCode>0</ResponseCode>
    <ResponseDescription>Success</ResponseDescription>
  </CommandStatus>
  <BlockedAccessList>
    <BlockedAccessDetail>
      <BlockedAccessID>0</BlockedAccessID>
      <BlockedAccessDescription>NO BLOCKS</BlockedAccessDescription>
    </BlockedAccessDetail>
  </BlockedAccessList>
</iEnhancedInterfaceResponse>

```



```

</BlockedAccessDetail>
<BlockedAccessDetail>
  <BlockedAccessID>1</BlockedAccessID>
  <BlockedAccessDescription>Nonredemption Games Only
</BlockedAccessDescription>
</BlockedAccessDetail>
<BlockedAccessDetail>
  <BlockedAccessID>2</BlockedAccessID>
  <BlockedAccessDescription>21 and older</BlockedAccessDescription>
</BlockedAccessDetail>
<BlockedAccessDetail>
  <BlockedAccessID>33</BlockedAccessID>
  <BlockedAccessDescription>ice rink access</BlockedAccessDescription>
</BlockedAccessDetail>
</BlockedAccessList>
</iEnhancedInterfaceResponse>

```

ClearCard Transaction Request/Response XML Definitions

The ClearCard transaction request allows one or more cards to be cleared of all information in the InterCard system; cleared cards are reusable.

Important! To ensure the card is cleared before using, InterCard recommends waiting at least 24 hours before reusing a cleared card.

ClearCard Request

TransactionRequest Section			
Element Name	Type	Required	Description/Value
RequestType	RequestTypeValue	Y	The RequestType must be set to ClearCard .
MacAddress	string	Y	This is the MAC address of the request machine. <i>Note: The MAC address must be registered in the InterCard system.</i>
TransactionID	string	N	This is the transaction ID associated with the transaction on the requesting machine.
SessionID	integer	N	The SessionID is the cash drawer session ID of the requesting machine.
EmployeeID	integer	Y	<i>EmployeeID</i> , this is the employeeID on the requesting machine.
EmployeeName:	Complex	*	*The Employee Name is not required; however, if used, the Employee Name must
EmployeeFirstName	string		

TransactionRequest Section			
Element Name	Type	Required	Description/Value
EmployeeLastName	string		include both the first and last names of the employee associated with the transaction.
LT_DateTime	dateTime (requires millisecond resolution)	Y	This is the current local date/time of the location where the request is made.
UTC_DateTime	dateTime (requires millisecond resolution)	Y	UTC DateTime is the current UTCDateTime for the location where the transaction occurred.

ClearCard Section			
Element Name	Type	Required	Description/Value
AccountNumbersList	AccountNumber[]	Y	The AccountNumbersList displays the account numbers associated with the cards that were cleared in the ClearCard process.
AccountNumber	long	Y	Account number to clear from the InterCard system.

XML Example: ClearCard Request

```

<?xml version="1.0"?>
<iEnhancedInterfaceRequest xmlns:xsi="http://www.w3.org/2001/XMLSchema-
instancexmlns:xsd="http://www.w3.org/
2001/XMLSchema">
  <TransactionRequest>
    <RequestType>ClearCard</RequestType>
    <MacAddress>AAABBBCCDDDD</MacAddress>
    <TransactionID>0001</TransactionID>
    <SessionID>A0001</SessionID>
    <EmployeeID>stester</EmployeeID>
    <EmployeeName>
      <FirstName>Some</FirstName>
      <LastName>Tester</LastName>
    </EmployeeName>
    <LT_DateTime>2014-07-24T11:34:42.1701576-05:00</LT_DateTime>
    <UTC_DateTime>2014-07-24T16:34:42.1701576Z</UTC_DateTime>
  </TransactionRequest>
  <ClearCard>
    <AccountNumbersList>
      <AccountNumber>15307</AccountNumber>
      <AccountNumber>25454</AccountNumber>
    </AccountNumbersList>
  </ClearCard>
</iEnhancedInterfaceRequest>

```

```

    </AccountNumbersList>
  </ClearCard>
</iEnhancedInterfaceRequest>

```

ClearCard Response

CommandStatus Section			
Element Name	Type	Returned	Description/Value
ResponseCode	int	Y	A value of 0 indicates success; a non-zero value indicates an error occurred while processing the request.
ResponseDescription	string	Y	A text response providing additional information regarding the status of the request.

XML Example: ClearCard Response

```

<?xml version="1.0"?>
<iEnhancedInterfaceResponse xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <CommandStatus>
    <ResponseCode>0</ResponseCode>
    <ResponseDescription>Success</ResponseDescription>
  </CommandStatus>
</iEnhancedInterfaceResponse>

```

CompCard Transaction Request/Response XML Definitions

CompCard provides the capability to comp the specified account with bonus cash, cash, tokens, bonus tokens, or points.

CompCard Request

TransactionRequest Section			
Element Name	Type	Required	Description/Value
RequestType	RequestTypeValue	Y	The RequestType must be set to CompCard .
MacAddress	string	Y	This is the MAC address of the request machine. <i>Note: The MAC address must be registered in the InterCard system.</i>
TransactionID	string	N	This is the transaction ID associated with the transaction on the requesting machine.
SessionID	int	N	The SessionID is the cash drawer session ID of the requesting machine.

TransactionRequest Section			
Element Name	Type	Required	Description/Value
EmployeeID	int	Y	This is the employee ID on the requesting machine.
EmployeeName:	Complex	*	*The Employee Name is not required; however, if used, the Employee Name must include both the first and last names of the employee associated with the transaction.
EmployeeFirstName	string		
EmployeeLastName	string		
LT_DateTime	dateTime (requires millisecond resolution)	Y	This is the current local date/time of the location where the request is made.
UTC_DateTime	dateTime (requires millisecond resolution)	Y	UTC DateTime is the current UTCDateTime for the location where the transaction occurred.

CompCard Section			
Element Name	Type	Required	Description/Value
AccountNumber	long	Y	The account number to be comped.
Cash	double	Y	The amount of cash to comp on the account.
CashBonus	double	Y	This is the amount of bonus cash to comp on the account.
Tokens	int	Y	The number of tokens to comp on the account.
TokenBonus	int	Y	The number of bonus tokens to comp on the account.
Points	int	Y	The number of points to comp on the account.
ReasonCode	int	N	ReasonCode allows the user to select a predefined reason to comp an account.

XML Example: CompCard Request

```

<?xml version="1.0"?>
<iEnhancedInterfaceRequestxmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <TransactionRequest>
    <RequestType>CompCard</RequestType>
    <MacAddress>AAABBBCCDDDD</MacAddress>
  </TransactionRequest>
</iEnhancedInterfaceRequest>

```

```

<TransactionID>0001</TransactionID>
<SessionID>A0001</SessionID>
<EmployeeID>stester</EmployeeID>
<EmployeeName>
  <FirstName>Some</FirstName>
  <LastName>Tester</LastName>
</EmployeeName>
<LT_DateTime>2015-01-22T15:02:36.0098048-06:00</LT_DateTime>
<UTC_DateTime>2015-01-22T21:02:36.0098048Z</UTC_DateTime>
</TransactionRequest>
<CompCard>
  <AccountNumber>19097</AccountNumber>
  <Cash>0</Cash>
  <CashBonus>10.00</CashBonus>
  <Tokens>0</Tokens>
  <TokenBonus>0</TokenBonus>
  <Points>0</Points>
  <ReasonCode>2</ReasonCode>
</CompCard>
</iEnhancedInterfaceRequest>

```

CompCard Response

CommandStatus Section			
Element Name	Type	Returned	Description/Value
ResponseCode	int	Y	A value of 0 indicates success; a non-zero value indicates an error occurred while processing the request.
ResponseDescription	string	Y	A text response providing additional information regarding the status of the request.

XML Example: CompCard Response

```

<?xml version="1.0"?>
<iEnhancedInterfaceResponse xmlns:xsi=http://www.w3.org/2001/XMLSchema-
instancexmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <CommandStatus>
    <ResponseCode>0</ResponseCode>
    <ResponseDescription>Success</ResponseDescription>
  </CommandStatus>
</iEnhancedInterfaceResponse>

```

ConsolidateCards Transaction Request/Response XML Definitions

The ConsolidateCards transaction allows transferring all values of multiple cards onto a “primary/single” card.

ConsolidateCards Request

TransactionRequest Section			
Element Name	Type	Required	Description/Value
RequestType	RequestTypeValue	Y	The RequestType must be set to ConsolidateCards .
MacAddress	string	Y	This is the MAC address of the request machine. <i>Note: The MAC address must be registered in the InterCard system.</i>
TransactionID	string	N	This is the transaction ID associated with the transaction on the requesting machine.
SessionID	int	N	The SessionID is the cash drawer session ID of the requesting machine.
EmployeeID	int	Y	This is the employee ID on the requesting machine.
EmployeeName:	Complex	*	*The Employee Name is not required; however, if used, the Employee Name must include both the first and last names of the employee associated with the transaction.
EmployeeFirstName	string		
EmployeeLastName	string		
LT_DateTime	dateTime (requires millisecond resolution)	Y	This is the current local date/time of the location where the request is made.
UTC_DateTime	dateTime (requires millisecond resolution)	Y	UTC DateTime is the current UTCDateTime for the location where the transaction occurred.

ConsolidateCards Section			
Element Name	Type	Rqd	Description/Value
TargetAccount	long	Y	The TargetAccount is the account intended to receive the consolidated funds.
ConsolidateSourceAccountList	AccountNumber[]	Y	The list of card numbers being consolidated to the primary card.
AccountNumber	long	Y	Account number to be consolidated.

XML Example: ConsolidateCards Request

```
<?xml version="1.0"?>
<iEnhancedInterfaceRequest xmlns:xsi=http://www.w3.org/2001/XMLSchema-instance
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <TransactionRequest>
    <RequestType>ConsolidateCards</RequestType>
    <MacAddress>AAABBBCCDDDD</MacAddress>
    <TransactionID>0001</TransactionID>
    <SessionID>A0001</SessionID>
    <EmployeeID>stester</EmployeeID>
    <EmployeeName>
      <FirstName>Some</FirstName>
      <LastName>Tester</LastName>
    </EmployeeName>
    <LT_DateTime>2015-01-22T15:04:51.091531-06:00</LT_DateTime>
    <UTC_DateTime>2015-01-22T21:04:51.091531Z</UTC_DateTime>
  </TransactionRequest>
  <ConsolidateCards>
    <TargetAccount>6</TargetAccount>
    <ConsolidateSourceAccountList>
      <AccountNumber>5</AccountNumber>
      <AccountNumber>4</AccountNumber>
    </ConsolidateSourceAccountList>
  </ConsolidateCards>
</iEnhancedInterfaceRequest>
```

ConsolidateCards Response

CommandStatus Section			
Element Name	Type	Returned	Description/Value
ResponseCode	int	Y	A value of 0 indicates success; a non-zero value indicates an error occurred while processing the request.
ResponseDescription	string	Y	A text response providing additional information regarding the status of the request.

XML Example: ConsolidateCards Response

```
<?xml version="1.0"?>
<iEnhancedInterfaceResponse xmlns:xsi=http://www.w3.org/2001/XMLSchema-instance
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <CommandStatus>
    <ResponseCode>0</ResponseCode>
    <ResponseDescription>Success</ResponseDescription>
  </CommandStatus>
</iEnhancedInterfaceResponse>
```

CreditAccounts Transaction Request/Response XML Definitions

The CreditAccounts transaction request applies the appropriate credits to an account for:

- Cash
- Tokens
- Points
- Cash Bonus
- Token Bonus
- TimePlay

CreditAccounts Request

TransactionRequest Section			
Element Name	Type	Required	Description/Value
RequestType	RequestTypeValue	Y	The RequestTypeValue must be set to CreditAccounts .
MacAddress	string	Y	This is the MAC address of the request machine. <i>Note: The MAC address must be registered in the InterCard system.</i>
TransactionID	string	N	This is the transaction ID associated with the transaction on the requesting machine.
SessionID	string	N	The SessionID is the cash drawer session ID of the requesting machine.
EmployeeID	string	Y	This is the employee ID on the requesting machine.
EmployeeName:	Complex	*	*The Employee Name is not required; however, if used, the Employee Name must include both the first and last names of the employee associated with the transaction.
EmployeeFirstName	string		
EmployeeLastName	string		
LT_DateTime	dateTime (requires millisecond resolution)	Y	This is the current local date/time of the location where the request is made.
UTC_DateTime	dateTime (requires millisecond resolution)	Y	UTC DateTime is the current UTCDateTime for the location where the transaction occurred.

CreditAccounts Section			
Element Name	Type	Required	Description/Value
CreditAccountsList	CreditAccount[]	Y	The CreditAccounts transaction allows a user to view the CreditAccountsList which displays a list of all credit accounts.

CreditAccount Section			
Element Name	Type	Required	Description/Value
AccountNumber	long	Y	This is the account number assigned to a specific card.
BlockedAccessID	int	N	The BlockedAccessID allows you to assign profiles to customer cards that allow/disallow the card from being used for games that are cash play, timeplay, or gate play. The NO BLOCKS option is a default option and cannot be modified or deleted. An example for use would be a game room where you want to block all Redemption games for a specified period of time; or to block "adult" games during a children's party.
Cash	double	Y	If yes is selected here, cash can be added to an account.
CashBonus	double	Y	Cash Bonus allows you to specify the monetary amount that a customer must spend to earn "x" amount of cash bonus credit.
Tokens	int	Y	If tokens are used, specify the number of tokens required to play a game.
TokenBonus	int	Y	If tokens are used, specify the number of bonus tokens received for each "x" tokens purchased.
Points	int	Y	A card's points can be used to redeem items. Once redeemed, they are automatically deducted from the card.
TP_Duration	int	Y	If timeplay applies, specify the number of minutes to be added to an account for timeplay.

CreditAccount Section			
Element Name	Type	Required	Description/Value
TP_ActiveImmediate	boolean	N	True time play is active when the card is sold; otherwise, the time play will become active once the card is swiped on a reader.
ActivationDate	dateTime	N	Specifies the time when the account will become active.
ExpirationDate	dateTime	N	Specifies the time when an account will expire.

XML Example: CreditAccounts Request

```

<?xml version="1.0"?>
<iEnhancedInterfaceRequest xmlns:xsi=http://www.w3.org/2001/XMLSchema-instance
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <TransactionRequest>
    <RequestType>CreditAccounts</RequestType>
    <MacAddress>AAABBBCCDDDD</MacAddress>
    <TransactionID>0001</TransactionID>
    <SessionID>A0001</SessionID>
    <EmployeeID>stester</EmployeeID>
    <EmployeeName>
      <FirstName>Some</FirstName>
      <LastName>Tester</LastName>
    </EmployeeName>
    <LT_DateTime>2015-01-22T15:27:15.8074444-06:00</LT_DateTime>
    <UTC_DateTime>2015-01-22T21:27:15.8074444Z</UTC_DateTime>
  </TransactionRequest>
  <CreditAccounts>
    <CreditAccountsList>
      <CreditAccount>
        <AccountNumber>5</AccountNumber>
        <BlockedAccessID>0</BlockedAccessID>
        <Cash>10</Cash>
        <CashBonus>5</CashBonus>
        <Tokens>0</Tokens>
        <TokenBonus>0</TokenBonus>
        <Points>0</Points>
        <TP_Duration>0</TP_Duration>
        <TP_ActiveImmediate>True</TP_ActiveImmediate>
      </CreditAccount>
      <CreditAccount>

```

```

        <AccountNumber>6</AccountNumber>
        <BlockedAccessID>0</BlockedAccessID>
        <Cash>0</Cash>
        <CashBonus>0</CashBonus>
        <Tokens>0</Tokens>
        <TokenBonus>0</TokenBonus>
        <Points>0</Points>
        <TP_Duration>60</TP_Duration>
        <TP_ActiveImmediate>True</TP_ActiveImmediate>
        <ActivationDate>2015-01-22T15:27:15.8074444-06:00</ActivationDate>
        <ExpirationDate>2035-01-22T15:27:15.8074444-06:00</ExpirationDate>
    </CreditAccount>
</CreditAccountsList>
</CreditAccounts>
</iEnhancedInterfaceRequest>

```

CreditAccounts Response

CommandStatus Section			
Element Name	Type	Returned	Description/Value
ResponseCode	int	Y	A value of 0 indicates success; a non-zero value indicates an error occurred while processing the request.
ResponseDescription	string	Y	A text response providing additional information regarding the status of the request.

XML Example: CreditAccounts Response

```

<?xml version="1.0"?>
<iEnhancedInterfaceResponse xmlns:xsi=http://www.w3.org/2001/XMLSchema-instance
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
    <CommandStatus>
        <ResponseCode>0</ResponseCode>
        <ResponseDescription>Success</ResponseDescription>
    </CommandStatus>
</iEnhancedInterfaceResponse>

```

CreditDebitEscrowPoints Transaction Request/Response XML Definitions

The CreditDebitEscrowPoints request allows the third-party POS to hold an account's point balance while using the points for redemption items. This request also allows the third-party POS to return any unused points to the account.

CreditDebitEscrowPoints Request

TransactionRequest Section			
Element Name	Type	Required	Description/Value
RequestType	RequestTypeValue	Y	RequestType must be set to CreditDebitEscrowPoints .
MacAddress	string	Y	This is the MAC address of the request machine. <i>Note: The MAC address must be registered in the InterCard system.</i>
TransactionID	string	N	This is the transaction ID associated with the transaction on the requesting machine.
SessionID	string	N	The SessionID is the cash drawer session ID of the requesting machine.
EmployeeID	string	Y	EmployeeID is the employee ID on the requesting machine.
EmployeeName	Complex	*	*The Employee Name is not required; however, if used, the Employee Name must include both the first and last names of the employee associated with the transaction.
EmployeeFirstName	string		
EmployeeLastName	string		
LT_DateTime	dateTime (requires millisecond resolution)	Y	This is the current local date/time of the location where the request is made.
UTC_DateTime	dateTime (requires millisecond resolution)	Y	UTCDateTime is the current UTCDateTime for the location where the transaction occurred.

CreditDebitEscrowPoints Section			
Element Name	Type	Returned	Description/Value
AccountNumber	long	Y	The account being used to debit or credit escrow points.
PointAmount	int	Y	The number of points to add to the account or remove from the account. - A PointAmount less than 0 will issue an Escrow Debit against the account. The value must not exceed the number of points currently available to this account. - A PointAmount greater than 0 will issue an Escrow Credit to the account.

XML Example: CreditDebitEscrowPoints Request

```

<?xml version="1.0"?>
<iEnhancedInterfaceRequest xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <TransactionRequest>
    <RequestType>CreditDebitEscrowPoints</RequestType>
    <MacAddress>AAABBBCCDDDD</MacAddress>
    <TransactionID>0001</TransactionID>
    <SessionID>A0001</SessionID>
    <EmployeeID>stester</EmployeeID>
    <EmployeeName>
      <FirstName>Some</FirstName>
      <LastName>Tester</LastName>
    </EmployeeName>
    <LT_DateTime>2015-09-17T14:36:29.4234625-05:00</LT_DateTime>
    <UTC_DateTime>2015-09-17T19:36:29.4234625Z</UTC_DateTime>
  </TransactionRequest>
  <CreditDebitEscrowPoints>
    <AccountNumber>3</AccountNumber>
    <PointAmount>-500</PointAmount>
  </CreditDebitEscrowPoints>
</iEnhancedInterfaceRequest>

```

CreditDebitEscrowPoints Response

The CreditDebitEscrowPoints Response is the same as the ClearCard Response.

CommandStatus Section			
Element Name	Type	Returned	Description/Value
ResponseCode	int	Y	A value of 0 indicates success; a non-zero value indicates an error occurred while processing the request.
ResponseDescription	string	Y	A text response providing additional information regarding the request status of the request.

XML Example: CreditDebitEscrowPoints Response

```
<?xml version="1.0"?>
<iEnhancedInterfaceResponse xmlns:xsi=http://www.w3.org/2001/XMLSchema-instance
xmlns:xsd="http://www.w3.org/
2001/XMLSchema">
  <CommandStatus>
    <ResponseCode>0</ResponseCode>
    <ResponseDescription>Success</ResponseDescription>
  </CommandStatus>
</iEnhancedInterfaceResponse>
```

EncodeCards Transaction Request/Response XML Definitions

The EncodeCards transaction provides the capability to encode one or more cards at the same time for a specific event, such as a birthday party, business meeting, etc. Each package associated with group or event sales typically has anywhere from 10 to 1,000 guests.

EncodeCards Request

TransactionRequest Section			
Element Name	Type	Required	Description/Value
RequestType	RequestTypeValue	Y	The RequestType must be set to EncodeCards .
MacAddress	string	Y	This is the MAC address of the request machine. <i>Note: The MAC address must be registered in the InterCard system.</i>
TransactionID	string	N	This is the transaction ID associated with the transaction on the requesting machine.
SessionID	int	N	The SessionID is the cash drawer session ID of the requesting machine.

TransactionRequest Section			
Element Name	Type	Required	Description/Value
EmployeeID	int	Y	This is the employee ID on the requesting machine.
EmployeeName:	Complex	*	*The Employee Name is not required ; however, if used, the Employee Name must include both the first and last names of the employee associated with the transaction.
EmployeeFirstName	string		
EmployeeLastName	string		
LT_DateTime	dateTime (requires millisecond resolution)	Y	This is the current local date/time of the location where the request is made.
UTC_DateTime	dateTime (requires millisecond resolution)	Y	UTC DateTime is the current UTCDateTime for the location where the transaction occurred.

EncodeCards Section			
Element Name	Type	Required	Description/Value
EncodeDescription	string	Y	The Encode Cards feature is can be used for events; i.e. birthday parties, school group outings, bachelor parties, etc. allowing you to bulk encode multiple cards at the same time.
EncodeTenderAmount	double	Y	The amount to be paid for the encoded cards.
AccountNumbersList	AccountNumber[]	Y	A List of account numbers to be encoded.
AccountNumber	long	Y	Account number to encode.
CreditCash	double	Y	The cash amount to be applied to one or more cards.
CreditCashBonus	double	Y	Amount of cash bonus to be applied to each card.
CreditTokens	int	Y	The number of tokens to be applied to each card
CreditTokenBonus	int	N	Amount of bonus credit tokens to be put on each card.
TP_Duration	int	Y	Amount of timeplay to be added to each card.
ActivationDate	dateTime	Y	The date/time that the card becomes active for timeplay.

EncodeCards Section			
Element Name	Type	Required	Description/Value
ExpirationDate	dateTime	Y	The date/time that the card becomes inactive.
PackageID	int	N	Optional reference to a predefined package deal.
BlockedAccessID	int	N	This is the profile attached to the card to describe.

XML Example: EncodeCards Request

```

<?xml version="1.0"?>
<iEnhancedInterfaceRequest xmlns:xsi=http://www.w3.org/2001/XMLSchema-instance
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <TransactionRequest>
    <RequestType>EncodeCards</RequestType>
    <MacAddress>AAABBBCCDDDD</MacAddress>
    <TransactionID>0002</TransactionID>
    <SessionID>A0001</SessionID>
    <EmployeeID>stester</EmployeeID>
    <EmployeeName>
      <FirstName>Some</FirstName>
      <LastName>Tester</LastName>
    </EmployeeName>
    <LT_DateTime>2015-01-22T16:03:41.0804349-06:00</LT_DateTime>
    <UTC_DateTime>2015-01-22T22:03:41.0804349Z</UTC_DateTime>
  </TransactionRequest>
  <EncodeCards>
    <EncodeDescription>Smith Birthday party</EncodeDescription>
    <EncodeTenderAmount>150.00</EncodeTenderAmount>
    <AccountNumbersList>
      <AccountNumber>8</AccountNumber>
      <AccountNumber>9</AccountNumber>
      <AccountNumber>10</AccountNumber>
    </AccountNumbersList>
    <CreditCash>0</CreditCash>
    <CreditCashBonus>10</CreditCashBonus>
    <CreditTokens>0</CreditTokens>
    <CreditTokenBonus>0</CreditTokenBonus>
    <CreditPoints>0</CreditPoints>
    <TP_Duration>0</TP_Duration>
    <ActivationDate>2015-01-22T16:03:41</ActivationDate>
    <ExpirationDate>2025-01-22T16:03:41</ExpirationDate>
    <BlockedAccessID>0</BlockedAccessID>
    <PackageID>50</PackageID>
  </EncodeCards>
</iEnhancedInterfaceRequest>

```



```
</EncodeCards>
</iEnhancedInterfaceRequest>
```

EncodeCards Response

CommandStatus Section			
Element Name	Type	Returned	Description/Value
ResponseCode	int	Y	A value of 0 indicates success; a non-zero value indicates an error occurred while processing the request.
ResponseDescription	string	Y	A text response providing additional information regarding the status of the request.

XML Example: EncodeCards Response

```
<?xml version="1.0"?>
<iEnhancedInterfaceResponse xmlns:xsi=http://www.w3.org/2001/XMLSchema-instance
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <CommandStatus>
    <ResponseCode>0</ResponseCode>
    <ResponseDescription>Success</ResponseDescription>
  </CommandStatus>
</iEnhancedInterfaceResponse>
```

EntitlementClaim Section Transaction Request/Response XML Definitions

The EntitlementClaim transaction allows customers to purchase cards containing a customizable package deal. The card can then be used to redeem items assigned to the package, including food and general merchandise.

EntitlementClaim Request

TransactionRequest Section			
Element Name	Type	Rqd.	Description/Value
RequestType	RequestTypeValue	Y	The RequestType must be set to EntitlementClaim .
MacAddress	string	Y	This is the MAC address of the request machine. <i>Note: The MAC address must be registered in the InterCard system.</i>
TransactionID	string	N	This is the transaction ID associated with the transaction on the requesting machine.

TransactionRequest Section			
Element Name	Type	Rqd.	Description/Value
SessionID	int	N	The SessionID is the cash drawer session ID of the requesting machine.
EmployeeID	int	Y	<i>EmployeeID</i> , this is the employee ID on the requesting machine.
Employee Name:	Complex	*	*The Employee Name is not required; however, if used, the Employee Name must include both the first and last names of the employee associated with the transaction.
EmployeeFirstName	string		
EmployeeLastName	string		
LT_DateTime	dateTime (requires millisecond resolution)	Y	This is the current local date/time of the location where the request is made.
UTC_DateTime	dateTime (requires millisecond resolution)	Y	UTC DateTime is the current UTCDateTime for the location where the transaction occurred.

EntitlementClaim Section			
Element Name	Type	Rqd.	Description/Value
AccountNumber	long	Y	This is the account number associated with the card that was swiped.
ClaimedEntitlementList	ClaimedEntitlement[]	Y	An array of entitlements to be claimed.

ClaimedEntitlement Section			
ElementName	Type	Required	Description/Value
ProductTag	int	Y	The InterCard product tag of the item being claimed.
QtyCreditDebit	int	Y	The number of specified items to be claimed in the transaction.

XML Example: EntitlementClaim Request

```
<?xml version="1.0"?>
<iEnhancedInterfaceRequest xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance
xmlns:xsd="http://www.w3.org/
2001/XMLSchema">
  <TransactionRequest>
```

```

<RequestType>EntitlementsClaim</RequestType>
<MacAddress>AAABBBCCDDDD</MacAddress>
<TransactionID>0004</TransactionID>
<SessionID>A0001</SessionID>
<EmployeeID>stester</EmployeeID>
<EmployeeName>
  <FirstName>Some</FirstName>
  <LastName>Tester</LastName>
</EmployeeName>
<LT_DateTime>2015-01-23T11:54:44.3248986-06:00</LT_DateTime>
<UTC_DateTime>2015-01-23T17:54:44.3248986Z</UTC_DateTime>
</TransactionRequest>
<EntitlementClaim>
  <AccountNumber>19097</AccountNumber>
  <ClaimedEntitlementList>
    <ClaimedEntitlement>
      <ProductTag>1249</ProductTag>
      <QtyCreditDebit>1</QtyCreditDebit>
    </ClaimedEntitlement>
    <ClaimedEntitlement>
      <ProductTag>1191</ProductTag>
      <QtyCreditDebit>1</QtyCreditDebit>
    </ClaimedEntitlement>
    <ClaimedEntitlement>
      <ProductTag>1223</ProductTag>
      <QtyCreditDebit>1</QtyCreditDebit>
    </ClaimedEntitlement>
  </ClaimedEntitlementList>
</EntitlementClaim>
</iEnhancedInterfaceRequest>

```

EntitlementClaim Response

CommandStatus Section			
Element Name	Type	Returned	Description/Value
ResponseCode	int	Y	A value of 0 indicates success; a non-zero value indicates an error occurred while processing the request.
ResponseDescription	string	Y	A text response providing additional information regarding the request.

XML Example: EntitlementClaim Response

```
<?xml version="1.0"?>
<iEnhancedInterfaceResponse xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <CommandStatus>
    <ResponseCode>0</ResponseCode>
    <ResponseDescription>Success</ResponseDescription>
  </CommandStatus>
</iEnhancedInterfaceResponse>
```

GameList Transaction Request/Response XML Definitions

The GameList transaction provides the capability to access a list of all games, regardless of status, for that location.

GameList Request

TransactionRequest Section			
Element Name	Type	Required	Description/Value
RequestType	RequestTypeValue	Y	The RequestType must be set to GameList .
MacAddress	string	Y	This is the MAC address of the request machine. <i>Note: The MAC address must be registered in the InterCard system.</i>
TransactionID	string	N	This is the transaction ID associated with the transaction on the requesting machine.
SessionID	int	N	The SessionID is the cash drawer session ID of the requesting machine.
EmployeeID	int	Y	EmployeeID , this is the employeeID on the requesting machine.
EmployeeName:	Complex	*	*The Employee Name is not required ; however, if used, the Employee Name must include both the first and last names of the employee associated with the transaction.
EmployeeFirstName	string		
EmployeeLastName	string		
LT_DateTime	dateTime (requires millisecond resolution)	Y	This is the current local date/time of the location where the request is made.
UTC_DateTime	dateTime (requires millisecond resolution)	Y	UTC DateTime is the current UTCDateTime for the location where the transaction occurred.

XML Example: GameList Request

```
<?xml version="1.0"?>
<iEnhancedInterfaceRequest xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <TransactionRequest>
    <RequestType>GameList</RequestType>
    <MacAddress>AAABBBCCDD</MacAddress>
    <TransactionID>0001</TransactionID>
    <SessionID>A0001</SessionID>
    <EmployeeID>stester</EmployeeID>
    <EmployeeName>
      <FirstName>Some</FirstName>
      <LastName>Tester</LastName>
    </EmployeeName>
    <LT_DateTime>2018-03-05T15:03:10.693908-06:00</LT_DateTime>
    <UTC_DateTime>2018-03-05T21:03:10.693908Z</UTC_DateTime>
  </TransactionRequest>
</iEnhancedInterfaceRequest>
```

GameList Response

CommandStatus Section			
Element Name	Type	Returned	Description/Value
ResponseCode	int	Y	A value of 0 indicates success; a non-zero value indicates an error occurred while processing the request.
ResponseDescription	string	Y	A text response providing additional information regarding the status of the request.

GameList Section			
Element Name	Type	Returned	Description/Value
DeviceName	string	Y	Name of game machine.
DeviceTag	int	Y	Game machine's ID.

XML Example: GameList Response

```
<?xml version="1.0"?>
<iEnhancedInterfaceResponse xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <CommandStatus>
    <ResponseCode>0</ResponseCode>
    <ResponseDescription>Success</ResponseDescription>
  </CommandStatus>
  <GameList>
    <Game>
      <DeviceName>Go Kart Entrance</DeviceName>
      <DeviceTag>12</DeviceTag>
    </Game>
    <Game>
      <DeviceName>Mini Golf Entrance</DeviceName>
      <DeviceTag>13</DeviceTag>
    </Game>
    <Game>
      <DeviceName>Example Redemption Game</DeviceName>
      <DeviceTag>5</DeviceTag>
    </Game>
    <Game>
      <DeviceName>Example Table Game</DeviceName>
      <DeviceTag>16</DeviceTag>
    </Game>
    <Game>
      <DeviceName>Example Video Game</DeviceName>
      <DeviceTag>15</DeviceTag>
    </Game>
    <Game>
      <DeviceName>Rollercoaster Entrance</DeviceName>
      <DeviceTag>14</DeviceTag>
    </Game>
  </GameList>
</iEnhancedInterfaceResponse>
```

GateAccessList Transaction Request/Response XML Definitions

The GateAccessList function provides the ability to request a list of gate passes and receive a gate access list including each pass' attributes.

GateAccessList Request

TransactionRequest Section			
Element Name	Type	Required	Description/Value
RequestType	RequestTypeValue	Y	The RequestType must be set to GateAccessList .
MacAddress	string	Y	This is the MAC address of the request machine. <i>Note: The MAC address must be registered in the InterCard system.</i>
TransactionID	string	N	This is the transaction ID associated with the transaction on the requesting machine.
SessionID	int	N	The SessionID is the cash drawer session ID of the requesting machine.
EmployeeID	int	Y	EmployeeID , this is the employeeID on the requesting machine.
EmployeeName:	Complex	*	*The Employee Name is not required ; however, if used, the Employee Name must include both the first and last names of the employee associated with the transaction.
EmployeeFirstName	string		
EmployeeLastName	string		
LT_DateTime	dateTime (requires millisecond resolution)	Y	This is the current local date/time of the location where the request is made.
UTC_DateTime	dateTime (requires millisecond resolution)	Y	UTC DateTime is the current UTCDateTime for the location where the transaction occurred.

XML Example: GateAccessList Request

```
<?xml version="1.0"?>
<iEnhancedInterfaceRequest xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <TransactionRequest>
    <RequestType>GateAccessList</RequestType>
    <MacAddress>AAABBBCCDDDD</MacAddress>
    <TransactionID>0001</TransactionID>
    <SessionID>A0001</SessionID>
```

```

<EmployeeID>stester</EmployeeID>
<EmployeeName>
  <FirstName>Some</FirstName>
  <LastName>Tester</LastName>
</EmployeeName>
<LT_DateTime>2018-03-05T15:13:26.1289796-06:00</LT_DateTime>
<UTC_DateTime>2018-03-05T21:13:26.1289796Z</UTC_DateTime>
</TransactionRequest>
</iEnhancedInterfaceRequest>

```

GateAccessList Response

CommandStatus Section			
Element Name	Type	Returned	Description/Value
ResponseCode	int	Y	A value of 0 indicates success; a non-zero value indicates an error occurred while processing the request.
ResponseDescription	string	Y	A text response providing additional information regarding the status of the request.

GateAccessList Section			
Element Name	Type	Returned	Description/Value
GateAccessList	GateAccessDetail[]	Y	An array of gate access details.

GateAccessDetail Section			
Element Name	Type	Returned	Description/Value
GateAccessName	string	Y	The name of the gate access.
Price	double	Y	The price of the gate access.

GateAccessDetail Section			
Element Name	Type	Required	Description/Value
Tax	double	Y	The tax for the gate access.
ProductTag	int	Y	Product tag for the gate access.
CardTag	int	Y	Tag put on the card for the gate access.
GateAccessID	int	Y	ID for the gate access
Actuations	int	Y	Number of actuations for the gate access.
GateAccessCardDefinition	GateAccessCardDefinition	Y	Defines the gate access card.
GateAccessDevices	GateAccessDevice[]	Y	Lists the devices the gate access allows access to.

GateAccessCardDefinition Section			
Element Name	Type	Returned	Description/Value
CardTag	int	Y	Tag placed on the card for the gate access.
CashBalance	double	Y	Cash balance available with gate access.
CashBonusBalance	double	Y	CashBonus balance with gate access.
TokenBalance	int	Y	Token balance with gate access.
Points	int	Y	Points added with gate access.
TP_Duration	int	Y	Duration of timeplay for gate access.
CardGroupID	int	Y	Card ID matching card type/category.
BlockedAccessID	int	Y	ID for any blocked access profiles associated with gate access.

GateAccessDevice Section			
Element Name	Type	Returned	Description/Value
DeviceTag	int	Y	Device ID for game machine.
DeviceName	string	Y	Name of game machine.
GateAccessID	int	Y	Same as above.

XML Example: GateAccessList Response

```
<?xml version="1.0"?>
<iEnhancedInterfaceResponse xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <CommandStatus>
    <ResponseCode>0</ResponseCode>
    <ResponseDescription>Success</ResponseDescription>
  </CommandStatus>
  <GateAccessList>
    <GateAccessDetail>
      <GateAccessName>Bowling Lane</GateAccessName>
      <Price>9.5240</Price>
      <Tax>0.4760</Tax>
      <ProductTag>106</ProductTag>
      <CardTag>23</CardTag>
      <GateAccessID>185</GateAccessID>
      <Actuations>1</Actuations>
      <GateAccessCardDefinition>
        <CardTag>23</CardTag>
        <CashBalance>0.0000</CashBalance>
        <CashBonusBalance>0.0000</CashBonusBalance>
        <TokenBalance>0</TokenBalance>
        <TokenBonusBalance>0</TokenBonusBalance>
        <Points>0</Points>
        <TP_Duration>0</TP_Duration>
        <CardGroupID>0</CardGroupID>
        <BlockedAccessID>22</BlockedAccessID>
      </GateAccessCardDefinition>
      <GateAccessDevices>
        <GateAccessDevice>
          <DeviceTag>9</DeviceTag>
          <DeviceName>Bowling Entrance</DeviceName>
          <GateAccessID>185</GateAccessID>
        </GateAccessDevice>
      </GateAccessDevices>
    </GateAccessDetail>
    <GateAccessDetail>
      <GateAccessName>Four Gate Pass</GateAccessName>
      <Price>45.7140</Price>
      <Tax>2.2860</Tax>
      <ProductTag>210</ProductTag>
      <CardTag>24</CardTag>
      <GateAccessID>186</GateAccessID>
      <Actuations>4</Actuations>
      <GateAccessCardDefinition>
```

```
<CardTag>24</CardTag>
<CashBalance>0.0000</CashBalance>
<CashBonusBalance>0.0000</CashBonusBalance>
<TokenBalance>0</TokenBalance>
<TokenBonusBalance>0</TokenBonusBalance>
<Points>0</Points>
<TP_Duration>0</TP_Duration>
<CardGroupID>0</CardGroupID>
<BlockedAccessID>0</BlockedAccessID>
</GateAccessCardDefinition>
<GateAccessDevices>
  <GateAccessDevice>
    <DeviceTag>9</DeviceTag>
    <DeviceName>Bowling Entrance</DeviceName>
    <GateAccessID>186</GateAccessID>
  </GateAccessDevice>
  <GateAccessDevice>
    <DeviceTag>12</DeviceTag>
    <DeviceName>Go Kart Entrance</DeviceName>
    <GateAccessID>186</GateAccessID>
  </GateAccessDevice>
  <GateAccessDevice>
    <DeviceTag>13</DeviceTag>
    <DeviceName>Mini Golf Entrance</DeviceName>
    <GateAccessID>186</GateAccessID>
  </GateAccessDevice>
  <GateAccessDevice>
    <DeviceTag>14</DeviceTag>
    <DeviceName>Rollercoaster Entrance</DeviceName>
    <GateAccessID>186</GateAccessID>
  </GateAccessDevice>
</GateAccessDevices>
</GateAccessDetail>
</GateAccessList>
</iEnhancedInterfaceResponse>
```

GateAccessSale Transaction Request/Response XML Definitions

The GateAccessSale transaction gives the user the capability of processing the sale of gate access passes.

GateAccessSale Request

TransactionRequest Section			
Element Name	Type	Required	Description/Value
RequestType	RequestTypeValue	Y	The RequestType must be set to GateAccessSale .
MacAddress	string	Y	This is the MAC address of the request machine. <i>Note: The MAC address must be registered in the InterCard system.</i>
TransactionID	string	N	This is the transaction ID associated with the transaction on the requesting machine.
SessionID	int	N	The SessionID is the cash drawer session ID of the requesting machine.
EmployeeID	int	Y	EmployeeID , this is the employeeID on the requesting machine.
EmployeeName:	Complex	*	*The Employee Name is not required ; however, if used, the Employee Name must include both the first and last names of the employee associated with the transaction.
EmployeeFirstName	string		
EmployeeLastName	string		
LT_DateTime	dateTime (requires millisecond resolution)	Y	This is the current local date/time of the location where the request is made.
UTC_DateTime	dateTime (requires millisecond resolution)	Y	UTC DateTime is the current UTCDateTime for the location where the transaction occurred.

GateAccessSale Section			
Element Name	Type	Required	Description/Value
GateAccessCreditList	GateAccessCreditItem[]	Y	Items credited from the gate access sale.

GateAccessCreditItem Section			
Element Name	Type	Required	Description/Value
AccountNumber	int	Y	Account number associated with purchase.

GateAccessCreditItem Section			
Element Name	Type	Required	Description/Value
GateAccessProductList	GateProduct[]	Y	List of products sold with gate access.

GateProduct Section			
Element Name	Type	Required	Description/Value
GateProductTag	int	Y	Product tag for the gate access.
GateProductCost	double	Y	Cost of the gate access pass.

XML Example: GateAccessSale Request

```

<?xml version="1.0"?>
<iEnhancedInterfaceRequest xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <TransactionRequest>
    <RequestType>GateAccessSale</RequestType>
    <MacAddress>AAABBBCCDDDD</MacAddress>
    <TransactionID>0001</TransactionID>
    <SessionID>A0001</SessionID>
    <EmployeeID>stester</EmployeeID>
    <EmployeeName>
      <FirstName>Some</FirstName>
      <LastName>Tester</LastName>
    </EmployeeName>
    <LT_DateTime>2018-03-05T15:18:34.2419931-06:00</LT_DateTime>
    <UTC_DateTime>2018-03-05T21:18:34.2419931Z</UTC_DateTime>
  </TransactionRequest>
  <GateAccessSale>
    <GateAccessCreditList>
      <GateAccessCreditItem>
        <AccountNumber>12345</AccountNumber>
        <GateAccessProductList>
          <GateProduct>
            <GateProductTag>1422</GateProductTag>
            <GateProductCost>15.0000</GateProductCost>
          </GateProduct>
        </GateAccessProductList>
      </GateAccessCreditItem>
    </GateAccessCreditList>
  </GateAccessSale>
</iEnhancedInterfaceRequest>

```

GateAccessSale Response

CommandStatus Section			
Element Name	Type	Required	Description/Value
ResponseCode	int	Y	A value of 0 indicates success; a non-zero value indicates an error occurred while processing the request.
ResponseDescription	string	Y	A text response providing additional information regarding the status of the request.

XML Example: GateAccessSale Response

```
<?xml version="1.0"?>
<iEnhancedInterfaceResponse xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <CommandStatus>
    <ResponseCode>0</ResponseCode>
    <ResponseDescription>Success</ResponseDescription>
  </CommandStatus>
</iEnhancedInterfaceResponse>
```

LockCard Transaction Request/Response XML Definitions

The LockCard transaction provides the capability for an attendant to lock a card at the system which then disables the card from further use.

Important! *Locked cards cannot* be reused.

LockCard Request

TransactionRequest Section			
Element Name	Type	Required	Description/Value
RequestType	RequestTypeValue	Y	The RequestType must be set to LockCard .
MacAddress	string	Y	This is the MAC address of the request machine. <i>Note: The MAC address must be registered in the InterCard system.</i>
TransactionID	string	N	This is the transaction ID associated with the transaction on the requesting machine.
SessionID	int	N	The SessionID is the cash drawer session ID of the requesting machine.

TransactionRequest Section			
Element Name	Type	Required	Description/Value
EmployeeID	int	Y	EmployeeID , this is the employeeID on the requesting machine.
EmployeeName:	Complex	*	*The Employee Name is not required ; however, if used, the Employee Name must include both the first and last names of the employee associated with the transaction.
EmployeeFirstName	string		
EmployeeLastName	string		
LT_DateTime	dateTime (requires millisecond resolution)	Y	This is the current local date/time of the location where the request is made.
UTC_DateTime	dateTime (requires millisecond resolution)	Y	UTC DateTime is the current UTCDateTime for the location where the transaction occurred.

LockCard Section			
Element Name	Type	Required	Description/Value
AccountNumber	long	Y	This is the account number associated with the card that was swiped.
ReasonCode	int	N	The ReasonCode allows a user to select a predefined reason for preventing further use of the card.

XML Example: LockCard Request

```

<?xml version="1.0"?>
<iEnhancedInterfaceRequest xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <TransactionRequest>
    <RequestType>LockCard</RequestType>
    <MacAddress>AAABBBCCDDDD</MacAddress>
    <TransactionID>0004</TransactionID>
    <SessionID>A0001</SessionID>
    <EmployeeID>stester</EmployeeID>
    <EmployeeName>
      <FirstName>Some</FirstName>
      <LastName>Tester</LastName>
    </EmployeeName>
    <LT_DateTime>2015-01-23T11:32:55.7920548-06:00</LT_DateTime>
    <UTC_DateTime>2015-01-23T17:32:55.7920548Z</UTC_DateTime>
  </TransactionRequest>
</iEnhancedInterfaceRequest>

```

```

</TransactionRequest>
<LockCard>
  <AccountNumber>14563</AccountNumber>
  <ReasonCode>1</ReasonCode>
</LockCard>
</iEnhancedInterfaceRequest>

```

LockCard Response

CommandStatus Section			
Element Name	Type	Returned	Description/Value
ResponseCode	int	Y	A value of 0 indicates success; a non-zero value indicates an error occurred while processing the request.
ResponseDescription	string	Y	A text response providing additional information regarding the status of the request.

XML Example: LockCard Response

```

<?xml version="1.0"?>
<iEnhancedInterfaceResponse xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <CommandStatus>
    <ResponseCode>0</ResponseCode>
    <ResponseDescription>Success</ResponseDescription>
  </CommandStatus>
</iEnhancedInterfaceResponse>

```

MembershipList Transaction Request/Response XML Definitions

The MembershipList transaction request allows users to access the full list of available memberships.

MembershipList Request

TransactionRequest Section			
Element Name	Type	Required	Description/Value
RequestType	RequestTypeValue	Y	The RequestType must be set to MembershipList .
MacAddress	string	Y	This is the MAC address of the request machine. <i>Note: The MAC address must be registered in the InterCard system.</i>

TransactionRequest Section			
Element Name	Type	Required	Description/Value
TransactionID	string	N	This is the transaction ID associated with the transaction on the requesting machine.
SessionID	int	N	The SessionID is the cash drawer session ID of the requesting machine.
EmployeeID	int	Y	EmployeeID , this is the employeeID on the requesting machine.
EmployeeName:	Complex	*	*The Employee Name is not required ; however, if used, the Employee Name must include both the first and last names of the employee associated with the transaction.
EmployeeFirstName	string		
EmployeeLastName	string		
LT_DateTime	dateTime (requires millisecond resolution)	Y	This is the current local date/time of the location where the request is made.
UTC_DateTime	dateTime (requires millisecond resolution)	Y	UTC DateTime is the current UTCDateTime for the location where the transaction occurred.

XML Example: MembershipList Request

```

<?xml version="1.0"?>
<iEnhancedInterfaceRequest xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <TransactionRequest>
    <RequestType>MembershipList</RequestType>
    <MacAddress>AAABBBCCDDDD</MacAddress>
    <TransactionID>0001</TransactionID>
    <SessionID>A0001</SessionID>
    <EmployeeID>stester</EmployeeID>
    <EmployeeName>
      <FirstName>Some</FirstName>
      <LastName>Tester</LastName>
    </EmployeeName>
    <LT_DateTime>2018-03-05T15:14:56.6525829-06:00</LT_DateTime>
    <UTC_DateTime>2018-03-05T21:14:56.6525829Z</UTC_DateTime>
  </TransactionRequest>
</iEnhancedInterfaceRequest>

```

MembershipList Response

CommandStatus Section			
Element Name	Type	Returned	Description/Value
ResponseCode	int	Y	A value of 0 indicates success; a non-zero value indicates an error occurred while processing the request.
ResponseDescription	string	Y	A text response providing additional information regarding the status of the request.

MembershipList Section			
Element Name	Type	Returned	Description/Value
MembershipList	MembershipDetail[]	Y	Membership list details.

MembershipDetail Section			
Element Name	Type	Required	Description/Value
MembershipID	int	Y	ID for the membership.
MembershipTitle	string	Y	Name of the membership.
MembershipDiscountPercentage	int	Y	Discount for the membership.

XML Example: MembershipList Response

```

<?xml version="1.0"?>
<iEnhancedInterfaceResponse xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <CommandStatus>
    <ResponseCode>0</ResponseCode>
    <ResponseDescription>Success</ResponseDescription>
  </CommandStatus>
  <MembershipList>
    <MembershipDetail>
      <MembershipID>0</MembershipID>
      <MembershipTitle>No membership</MembershipTitle>
      <MembershipDiscountPercentage>0</MembershipDiscountPercentage>
    </MembershipDetail>
    <MembershipDetail>
      <MembershipID>25</MembershipID>
      <MembershipTitle>newPurch</MembershipTitle>
      <MembershipDiscountPercentage>5</MembershipDiscountPercentage>
    </MembershipDetail>
  </MembershipList>
</iEnhancedInterfaceResponse>

```

PackageList Transaction Request/Response XML Definitions

The PackageList Request is a transaction request only and returns a list of all packages.

PackageList Request

TransactionRequest Section			
Element Name	Type	Required	Description/Value
RequestType	RequestTypeValue	Y	The RequestType must be set to PackageList .
MacAddress	string	Y	This is the MAC address of the request machine. <i>Note: The MAC address must be registered in the InterCard system.</i>
TransactionID	string	N	This is the transaction ID associated with the transaction on the requesting machine.
SessionID	int	N	The SessionID is the cash drawer session ID of the requesting machine.
EmployeeID	int	Y	<i>EmployeeID</i> , this is the employeeID on the requesting machine.
EmployeeName:	Complex	*	*The Employee Name is not required; however, if used, the Employee Name must include both the first and last names of the employee associated with the transaction.
EmployeeFirstName	string		
EmployeeLastName	string		
EmployeeName	string		
LT_DateTime	dateTime (requires millisecond resolution)	Y	This is the current local date/time of the location where the request is made.
UTC_DateTime	dateTime (requires millisecond resolution)	Y	UTC DateTime is the current UTCDateTime for the location where the transaction occurred.

XML Example: PackageList Request

```
<?xml version="1.0"?>
<iEnhancedInterfaceRequest xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <TransactionRequest>
    <RequestType>PackageList</RequestType>
    <MacAddress>AAABBBCCDDDD</MacAddress>
    <TransactionID>0002</TransactionID>
    <SessionID>A0001</SessionID>
    <EmployeeID>stester</EmployeeID>
```

```

    <EmployeeName>
      <FirstName>Some</FirstName>
      <LastName>Tester</LastName>
    </EmployeeName>
    <LT_DateTime>2015-01-22T16:11:57.421824-06:00</LT_DateTime>
    <UTC_DateTime>2015-01-22T22:11:57.421824Z</UTC_DateTime>
  </TransactionRequest>
</iEnhancedInterfaceRequest>

```

PackageList Response

CommandStatus Section			
Element Name	Type	Returned	Description/Value
ResponseCode	int	Y	A value of 0 indicates success; a non-zero value indicates an error occurred while processing the request.
ResponseDescription	string	Y	A text response providing additional information regarding the status of the request

PackageList Section			
Element Name	Type	Returned	Description/Value
PackageList	PackageDetail[]	Y	An array of Package details.

PackageDetail Section			
Element Name	Type	Returned	Description/Value
PackageID	int	Y	Package ID in the InterCard system.
ProductTag	int	Y	Product tag of the package in the InterCard system.
PackageDescription	string	Y	Package Name in the InterCard system.
SuggestedPrice	double	Y	Suggested package price.

XML Example: PackageList Response

```

<?xml version="1.0"?>
<iEnhancedInterfaceResponse xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <CommandStatus>
    <ResponseCode>0</ResponseCode>
    <ResponseDescription>Success</ResponseDescription>
  </CommandStatus>
  <PackageList>
    <PackageDetail>

```

```
<Package ID>44</PackageID>
<ProductTag>1200</ProductTag>
<PackageDescription>Silver Package</PackageDescription>
<SuggestedPrice>2</SuggestedPrice>
</PackageDetail>
<PackageDetail>
  <PackageID>42</PackageID>
  <ProductTag>1198</ProductTag>
  <PackageDescription>Total Package</PackageDescription>
  <SuggestedPrice>10</SuggestedPrice>
</PackageDetail>
<PackageDetail>
  <PackageID>43</PackageID>
  <ProductTag>1199</ProductTag>
  <PackageDescription>Gold Package</PackageDescription>
  <SuggestedPrice>5</SuggestedPrice>
</PackageDetail>
<PackageDetail>
  <PackageID>47</PackageID>
  <ProductTag>1280</ProductTag>
  <PackageDescription>Platinum</PackageDescription>
  <SuggestedPrice>2</SuggestedPrice>
</PackageDetail>
<PackageDetail>
  <PackageID>50</PackageID>
  <ProductTag>1403</ProductTag>
  <PackageDescription>TimePlayGateAccess</PackageDescription>
  <SuggestedPrice>2</SuggestedPrice>
</PackageDetail>
</PackageList>
</iEnhancedInterfaceResponse>
```

PackageSale Transaction Request/Response XML Definitions

The PackageSale transaction is the sale of a predefined package that is created in the InterCard system.

PackageSale Request

TransactionRequest Section			
Element Name	Type	Required	Description/Value
RequestType	RequestTypeValue	Y	The RequestType must be set to PackageSale .
MacAddress	string	Y	This is the MAC address of the request machine. <i>Note: The MAC address must be registered in the InterCard system.</i>
TransactionID	string	N	This is the transaction ID associated with the transaction on the requesting machine.
SessionID	string	N	The SessionID is the cash drawer session ID of the requesting machine.
EmployeeID	int	Y	This is the employeeID on the requesting machine.
EmployeeName:	Complex	*	*The Employee Name is not required; however, if used, the Employee Name must include both the first and last names of the employee associated with the transaction.
EmployeeFirstName	string		
EmployeeLastName	string		
LT_DateTime	dateTime (requires millisecond resolution)	Y	This is the current local date/time of the location where the request is made.
UTC_DateTime	dateTime (requires millisecond resolution)	Y	UTC DateTime is the current UTCDateTime for the location where the transaction occurred.

PackageSale Section			
Element Name	Type	Required	Description/Value
AccountNumber	long	Y	The AccountNumber is the number assigned to the card used to purchase the package.
PackageID	int	Y	The InterCard system generates individual id numbers associated with each package.
PackageCost	double	Y	The PackageCost is the predefined value of the package purchased using this card.

PackageSale Section			
Element Name	Type	Required	Description/Value
TP_ActiveImmediate	boolean	N	True time play is active when the card is sold; otherwise, the time play will become active once the card is swiped on a reader.

XML Example: PackageSale Request

```
<?xml version="1.0"?>
<iEnhancedInterfaceRequest xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <TransactionRequest>
    <RequestType>PackageSale</RequestType>
    <MacAddress>AAABBBCCDDDD</MacAddress>
    <TransactionID>0002</TransactionID>
    <SessionID>A0001</SessionID>
    <EmployeeID>stester</EmployeeID>
    <EmployeeName>
      <FirstName>Some</FirstName>
      <LastName>Tester</LastName>
    </EmployeeName>
    <LT_DateTime>2015-01-22T16:09:29.8653842-06:00</LT_DateTime>
    <UTC_DateTime>2015-01-22T22:09:29.8653842Z</UTC_DateTime>
  </TransactionRequest>
  <PackageSale>
    <AccountNumber>11</AccountNumber>
    <PackageID>50</PackageID>
    <PackageCost>25.00</PackageCost>
    <TP_ActiveImmediate>True</TP_ActiveImmediate>
  </PackageSale>
</iEnhancedInterfaceRequest>
```

PackageSale Response

CommandStatus Section			
Element Name	Type	Returned	Description/Value
ResponseCode	int	Y	A value of 0 indicates success; a non-zero value indicates an error occurred while processing the request.
ResponseDescription	string	Y	A text response providing additional information regarding the status of the request.

XML Example: PackageSale Response

```
<?xml version="1.0"?>
<iEnhancedInterfaceResponse xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <CommandStatus>
    <ResponseCode>0</ResponseCode>
    <ResponseDescription>Success</ResponseDescription>
  </CommandStatus>
</iEnhancedInterfaceResponse>
```

PauseTimePlay Transaction Request/Response XML Definitions

Timeplay cards do not activate at purchase; instead, they activate on the first swipe and once swiped, the time continues to run down until depleted; unless interrupted by an attendant. Time resumes on the next card swipe.

PauseTimePlay Request

TransactionRequest Section			
Element Name	Type	Required	Description/Value
RequestType	RequestTypeValue	Y	The RequestType must be set to PauseTimePlay .
MacAddress	string	Y	This is the MAC address of the request machine. <i>Note: The MAC address must be registered in the InterCard system.</i>
TransactionID	string	N	This is the transaction ID associated with the transaction on the requesting machine.
SessionID	int	N	The SessionID is the cash drawer session ID of the requesting machine.
EmployeeID	int	Y	<i>EmployeeID</i> , this is the employeeID on the requesting machine.
EmployeeName:	Complex	*	*The EmployeeName is not required; however, if used, the Employee Name must include both the first and last names of the employee associated with the transaction.
EmployeeFirstName	string		
EmployeeLastName	string		
LT_DateTime	dateTime (requires millisecond resolution)	Y	This is the current local date/time of the location where the request is made.
UTC_DateTime	dateTime (requires millisecond resolution)	Y	UTC DateTime is the current UTCDateTime for the location where the transaction occurred.

PauseTimePlay Section			
Element Name	Type	Required	Description/Value
AccountNumber	long	Y	The account number is the primary account identifier.

XML Example: PauseTimePlay Request

```
<?xml version="1.0"?>
<iEnhancedInterfaceRequest xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <TransactionRequest>
    <RequestType>PauseTimePlay</RequestType>
    <MacAddress>AAABBBCCDDDD</MacAddress>
    <TransactionID>0001</TransactionID>
    <SessionID>A0001</SessionID>
    <EmployeeID>stester</EmployeeID>
    <EmployeeName>
      <FirstName>Some</FirstName>
      <LastName>Tester</LastName>
    </EmployeeName>
    <LT_DateTime>2015-01-23T11:11:49.8846491-06:00</LT_DateTime>
    <UTC_DateTime>2015-01-23T17:11:49.8846491Z</UTC_DateTime>
  </TransactionRequest>
  <PauseTimePlay>
    <AccountNumber>19475</AccountNumber>
  </PauseTimePlay>
</iEnhancedInterfaceRequest>
```

PauseTimePlay Response

CommandStatus Section			
Element Name	Type	Returned	Description/Value
ResponseCode	int	Y	A value of 0 indicates success; a non-zero value indicates an error occurred while processing the request.
ResponseDescription	string	Y	A text response providing additional information regarding the status of the request.

XML Example: PauseTimePlay Response

```
<?xml version="1.0"?>
<iEnhancedInterfaceResponse xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
```

```

<CommandStatus>
  <ResponseCode>0</ResponseCode>
  <ResponseDescription>Success</ResponseDescription>
</CommandStatus>
</iEnhancedInterfaceResponse>

```

PaymentViaCustomerCard Transaction Request/Response XML Definitions

The PaymentViaCustomerCard feature allows customers to use their card as payment.

PaymentViaCustomerCard Request

TransactionRequest Section			
Element Name	Type	Required	Description/Value
RequestType	RequestTypeValue	Y	The RequestType must be set to PaymentViaCustomerCard .
MacAddress	string	Y	This is the MAC address of the request machine. <i>Note: The MAC address must be registered in the InterCard system.</i>
TransactionID	string	N	This is the transaction ID associated with the transaction on the requesting machine.
SessionID	int	N	The SessionID is the cash drawer session ID of the requesting machine.
EmployeeID	int	Y	<i>EmployeeID</i> , this is the employeeID on the requesting machine.
EmployeeName:	Complex	*	*The Employee Name is not required; however, if used, the Employee Name must include both the first and last names of the employee associated with the transaction.
EmployeeFirstName	string		
EmployeeLastName	string		
LT_DateTime	dateTime (requires millisecond resolution)	Y	This is the current local date/time of the location where the request is made.
UTC_DateTime	dateTime (requires millisecond resolution)	Y	UTC DateTime is the current UTCDateTime for the location where the transaction occurred.

PaymentViaCustomerCard Section			
Element Name	Type	Rqd.	Description/Value
CustomerCardPaymentList	CardUsedAsPayment[]	Y	The CustomerCardPaymentList contains a list of cards used as payment.

CardUsedAsPayment Section			
ElementName	Type	Rqd.	Description/Value
AccountNumber	long	Y	Account being used for payment.
DebitCash	double	Y	Amount to deduct from account.
DebitCashBonus	double	N	Amount Bonus to deduct from account.

XML Example: PaymentViaCustomerCard Request

```

<?xml version="1.0"?>
<iEnhancedInterfaceRequest xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <TransactionRequest>
    <RequestType>PaymentViaCustomerCard</RequestType>
    <MacAddress>AAABBBCCDDDD</MacAddress>
    <TransactionID>0004</TransactionID>
    <SessionID>A0001</SessionID>
    <EmployeeID>stester</EmployeeID>
    <EmployeeName>
      <FirstName>Some</FirstName>
      <LastName>Tester</LastName>
    </EmployeeName>
    <LT_DateTime>2015-01-23T11:18:46.0974551-06:00</LT_DateTime>
    <UTC_DateTime>2015-01-23T17:18:46.0974551Z</UTC_DateTime>
  </TransactionRequest>
  <PaymentViaCustomerCard>
    <CustomerCardPaymentList>
      <CardUsedAsPayment>
        <AccountNumber>19097</AccountNumber>
        <DebitCash>5.00</DebitCash>
        <DebitCashBonus>1.00</DebitCashBonus>
      </CardUsedAsPayment>
    </CustomerCardPaymentList>
  </PaymentViaCustomerCard>
</iEnhancedInterfaceRequest>

```

PaymentViaCustomerCard Response

CommandStatus Section			
Element Name	Type	Returned	Description/Value
ResponseCode	int	Y	A value of 0 indicates success; a non-zero value indicates an error occurred while processing the request.
ResponseDescription	string	Y	A text response providing additional information regarding the status of the request.

XML Example: PaymentViaCustomerCard Response

```
<?xml version="1.0"?>
<iEnhancedInterfaceResponse xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <CommandStatus>
    <ResponseCode>0</ResponseCode>
    <ResponseDescription>Success</ResponseDescription>
  </CommandStatus>
</iEnhancedInterfaceResponse>
```

ReasonCodeLists Transaction Request/Response XML Definitions

The ReasonCodeLists is a Transaction Request only and displays all Reason Codes.

- Comp • Lock • Refund • Transfer

ReasonCodeLists Request

TransactionRequest Section			
Element Name	Type	Required	Description/Value
RequestType	RequestTypeValue	Y	The RequestTypeValue must be set to ReasonCodeLists .
MacAddress	string	Y	This is the MAC address of the request machine. <i>Note: The MAC address must be registered in the InterCard system.</i>
TransactionID	string	N	This is the transaction ID associated with the transaction on the requesting machine.
SessionID	string	N	The SessionID is the cash drawer session ID of the requesting machine.
EmployeeID	string	Y	This is the employee ID on the requesting machine.

TransactionRequest Section			
Element Name	Type	Required	Description/Value
EmployeeName:	Complex	*	*The Employee Name is not required; however, if used, the Employee Name must include both the first and last names of the employee associated with the transaction.
EmployeeFirstName	string		
EmployeeLastName	string		
LT_DateTime	dateTime (requires millisecond resolution)	Y	This is the current local date/time of the location where the request is made.
UTC_DateTime	dateTime (requires millisecond resolution)	Y	UTC DateTime is the current UTCDateTime for the location where the transaction occurred.

XML Example: ReasonCodeLists Request

```
<?xml version="1.0"?>
<iEnhancedInterfaceRequest xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <TransactionRequest>
    <RequestType>ReasonCodeLists</RequestType>
    <MacAddress>AAABBBCCDDDD</MacAddress>
    <TransactionID>0001</TransactionID>
    <SessionID>A0001</SessionID>
    <EmployeeID>stester</EmployeeID>
    <EmployeeName>
      <FirstName>Some</FirstName>
      <LastName>Tester</LastName>
    </EmployeeName>
    <LT_DateTime>2015-01-23T11:15:33.0734147-06:00</LT_DateTime>
    <UTC_DateTime>2015-01-23T17:15:33.0734147Z</UTC_DateTime>
  </TransactionRequest>
</iEnhancedInterfaceRequest>
```

ReasonCodeLists Response

CommandStatus Section			
Element Name	Type	Returned	Description/Value
ResponseCode	int	Y	A value of 0 indicates success; a non-zero value indicates an error occurred while processing the request.
ResponseDescription	string	Y	A text response providing additional information regarding the status of the request.

ReasonCodes Section			
Element Name	Type	Returned	Description/Value
LockReasonCodeList	ReasonCode[]	Y	List of reason codes for use when locking an account.
CompReasonCodeList	ReasonCode[]	Y	List of reason codes for use when comping an account.
TransferReasonCodeList	ReasonCode[]	Y	List of reason codes for use when transferring one account to another.
RefundReasonCodeList	ReasonCode[]	Y	List of reason codes for use when refunding an account.

ReasonCode Section			
Element Name	Type	Returned	Description/Value
ReasonCodeID	int	Y	The ID of the reason code in the InterCard system.
Description	string	Y	A brief description of the reason code.
Order	int	Y	Indicates the order in which the reason codes are to be displayed.

XML Example: ReasonCodeLists Response

```

<?xml version="1.0"?>
<iEnhancedInterfaceResponse xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <CommandStatus>
    <ResponseCode>0</ResponseCode>
    <ResponseDescription>Success</ResponseDescription>
  </CommandStatus>
  <ReasonCodes>
    <LockReasonCodeList>
      <ReasonCode>
        <ReasonCodeID>1</ReasonCodeID>
        <Description>Stolen Card</Description>
        <Order>9999</Order>
      </ReasonCode>
      <ReasonCode>
        <ReasonCodeID>2</ReasonCodeID>
        <Description>Other</Description>
        <Order>9999</Order>
      </ReasonCode>
    </LockReasonCodeList>
  </ReasonCodes>
</iEnhancedInterfaceResponse>

```

```
</ReasonCode>
</LockReasonCodeList>
<CompReasonCodeList>
  <ReasonCode>
    <ReasonCodeID>1</ReasonCodeID>
    <Description>Bad Service</Description>
    <Order>9999</Order>
  </ReasonCode>
  <ReasonCode>
    <ReasonCodeID>2</ReasonCodeID>
    <Description>Good Customer</Description>
    <Order>9999</Order>
  </ReasonCode>
</CompReasonCodeList>
<TransferReasonCodeList>
  <ReasonCode>
    <ReasonCodeID>1000</ReasonCodeID>
    <Description>lost card</Description>
    <Order>0</Order>
  </ReasonCode>
  <ReasonCode>
    <ReasonCodeID>1001</ReasonCodeID>
    <Description>stolen card</Description>
    <Order>1</Order>
  </ReasonCode>
</TransferReasonCodeList>
<RefundReasonCodeList>
  <ReasonCode>
    <ReasonCodeID>1</ReasonCodeID>
    <Description>Returned Merchandise</Description>
    <Order>9999</Order>
  </ReasonCode>
  <ReasonCode>
    <ReasonCodeID>2</ReasonCodeID>
    <Description>Bad Service</Description>
    <Order>9999</Order>
  </ReasonCode>
</RefundReasonCodeList>
</ReasonCodes>
</iEnhancedInterfaceResponse>
```

RefundCard Transaction Request/Response XML Definitions

The RefundCard transaction request allows full/partial cash or credit card refunds to a card.

RefundCard Request

TransactionRequest Section			
Element Reference	Type	Required	Description/Value
RequestType	RequestTypeValue	Y	RequestTypeValue must be set to the element name RefundCard .
MacAddress	string	Y	This is the MAC address of the request machine. <i>Note: The MAC address must be registered in the InterCard system.</i>
TransactionID	string	N	This is the transaction ID associated with the transaction on the requesting machine.
SessionID	int	N	The SessionID is the cash drawer session ID of the requesting machine.
EmployeeID	int	Y	This is the employee ID on the requesting machine.
EmployeeName:	Complex	*	*The Employee Name is not required; however, if used, the Employee Name must include both the first and last names of the employee associated with the transaction.
EmployeeFirstName	string		
EmployeeLastName	string		
LT_DateTime	dateTime (requires millisecond resolution)	Y	This is the current local date/time of the location where the request is made.
UTC_DateTime	dateTime (requires millisecond resolution)	Y	UTC DateTime is the current UTCDateTime for the location where the transaction occurred.

RefundCard Section			
Element Name	Type	Required	Description/Value
AccountNumber	long	Y	This is the account number of the card containing the values to be refunded to the customer.
DebitCash	double	Y	DebitCash is the amount of cash being refunded to the customer.

RefundCard Section			
Element Name	Type	Required	Description/Value
DebitCashBonus	double	Y	DebitCashBonus is the amount of cash bonus being refunded to the customer.
DebitToken	int	N	DebitToken is the number of tokens to be removed from the account.
DebitTokenBonus	int	N	DebitTokenBonus is the number of bonus tokens to remove from the account.
DebitDuration	int	N	DebitDuration is the number of time play minutes to remove from the account.
ReasonCode	int	N	The ReasonCode allows a user to select a predefined reason for preventing further use of the card.
AuthorizationEmployeeID	string	Y	The AuthorizationEmployeeID displays the ID of the employee authorizing the refund.
AuthorizationName	Complex	N	The AuthorizationName is the name of the employee associated with the employee ID number. The AuthorizationName is not required, but if it is provided, then both the first and last names are required, just like the EmployeeName field in the TransactionRequest section.
FirstName	string		
LastName	string		

XML Example: RefundCard Request

```

<?xml version="1.0"?>
<iEnhancedInterfaceRequest xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <TransactionRequest>
    <RequestType>RefundCard</RequestType>
    <MacAddress>AAABBBCCDDDD</MacAddress>
    <TransactionID>0004</TransactionID>
    <SessionID>A0001</SessionID>
    <EmployeeID>stester</EmployeeID>
    <EmployeeName>
      <FirstName>Some</FirstName>
      <LastName>Tester</LastName>
    </EmployeeName>
    <LT_DateTime>2015-01-23T11:25:11.1514789-06:00</LT_DateTime>
    <UTC_DateTime>2015-01-23T17:25:11.1514789Z</UTC_DateTime>
  </TransactionRequest>

```

```

<RefundCard>
  <AccountNumber>19097</AccountNumber>
  <DebitCash>10.00</DebitCash>
  <DebitCashBonus>0</DebitCashBonus>
  <DebitToken>0</DebitToken>
  <DebitTokenBonus>0</DebitTokenBonus>
  <DebitDuration>0</DebitDuration>
  <ReasonCode>5</ReasonCode>
  <AuthorizationEmployeeID>sleader</AuthorizationEmployeeID>
  <AuthorizationEmployeeName>
    <FirstName>Shift</FirstName>
    <LastName>Leader</LastName>
  </AuthorizationEmployeeName>
</RefundCard>
</iEnhancedInterfaceRequest>

```

RefundCard Response

CommandStatus Section			
Element Name	Type	Returned	Description/Value
ResponseCode	int	Y	A value of 0 indicates success; a non-zero value indicates an error occurred while processing the request.
ResponseDescription	string	Y	A text response providing additional information regarding the request status.

XML Example: RefundCard Response

```

<?xml version="1.0"?>
<iEnhancedInterfaceResponse xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <CommandStatus>
    <ResponseCode>0</ResponseCode>
    <ResponseDescription>Success</ResponseDescription>
  </CommandStatus>
</iEnhancedInterfaceResponse>

```

RemoveGateAccess Request/Response XML Definition

The RemoveGateAccess transaction enables users to remove gate access passes from user accounts attached to cards.

RemoveGateAccess Request

TransactionRequest Section			
Element Name	Type	Required	Description/Value
RequestType	RequestTypeValue	Y	The RequestTypeValue must be set to RemoveGateAccess .
MacAddress	string	Y	This is the MAC address of the request machine. <i>Note: The MAC address must be registered in the InterCard system.</i>
TransactionID	string	N	This is the transaction ID associated with the transaction on the requesting machine.
SessionID	int	N	The SessionID is the cash drawer session ID of the requesting machine.
EmployeeID	int	Y	<i>EmployeeID</i> , this is the employeeID on the requesting machine.
EmployeeName:	Complex	*	*The Employee Name is not required ; however, if used, the Employee Name must include both the first and last names of the employee associated with the transaction.
EmployeeFirstName	string		
EmployeeLastName	string		
LT_DateTime	dateTime (requires millisecond resolution)	Y	This is the current local date/time of the location where the request is made.
UTC_DateTime	dateTime (requires millisecond resolution)	Y	UTC DateTime is the current UTCDateTime for the location where the transaction occurred.

RemoveGateAccess Section			
Element Name	Type	Required	Description/Value
AccountNumber	int	Y	Account number where gate access will be removed.
GateProductTag	int	Y	Product number for gate access pass.

XML Example: RemoveGateAccess Request

```
<?xml version="1.0"?>
<iEnhancedInterfaceRequest xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <TransactionRequest>
    <RequestType>RemoveGateAccess</RequestType>
    <MacAddress>AAABBBCCDD</MacAddress>
    <TransactionID>0001</TransactionID>
    <SessionID>A0001</SessionID>
    <EmployeeID>stester</EmployeeID>
    <EmployeeName>
      <FirstName>Some</FirstName>
      <LastName>Tester</LastName>
    </EmployeeName>
    <LT_DateTime>2018-03-05T15:20:20.1026574-06:00</LT_DateTime>
    <UTC_DateTime>2018-03-05T21:20:20.1026574Z</UTC_DateTime>
  </TransactionRequest>
  <RemoveGateAccess>
    <AccountNumber>12345</AccountNumber>
    <GateProductTag>1422</GateProductTag>
  </RemoveGateAccess>
</iEnhancedInterfaceRequest>
```

RemoveGateAccess Response

CommandStatus Section			
Element Name	Type	Returned	Description/Value
ResponseCode	int	Y	A value of 0 indicates success; a non-zero value indicates an error occurred while processing the request.
ResponseDescription	string	Y	A text response providing additional information regarding the request status.

XML Example: RemoveGateAccess Response

```
<?xml version="1.0"?>
<iEnhancedInterfaceResponse xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <CommandStatus>
    <ResponseCode>0</ResponseCode>
    <ResponseDescription>Success</ResponseDescription>
  </CommandStatus>
</iEnhancedInterfaceResponse>
```

SplitCard Transaction Request/Response XML Definitions

The SplitCard feature allows a card's cash balance to be split between two or more cards in equal amounts. In addition, SplitCard also allows you to add the following fields:

- Cash Balance
- Bonus Cash
- Tokens
- Bonus Tokens
- Points

SplitCard Request

TransactionRequest Section			
Element Name	Type	Required	Description/Value
RequestType	RequestTypeValue	Y	The RequestTypeValue must be set to SplitCard .
MacAddress	string	Y	This is the MAC address of the request machine. <i>Note: The MAC address must be registered in the InterCard system.</i>
TransactionID	string	N	This is the transaction ID associated with the transaction on the requesting machine.
SessionID	int	N	The SessionID is the cash drawer session ID of the requesting machine.
EmployeeID	int	Y	<i>EmployeeID</i> , this is the employeeID on the requesting machine.
EmployeeName:	Complex	*	*The Employee Name is not required ; however, if used, the Employee Name must include both the first and last names of the employee associated with the transaction.
EmployeeFirstName	string		
EmployeeLastName	string		
LT_DateTime	dateTime (requires millisecond resolution)	Y	This is the current local date/time of the location where the request is made.
UTC_DateTime	dateTime (requires millisecond resolution)	Y	UTC DateTime is the current UTCDateTime for the location where the transaction occurred.

SplitCard Section			
Element Name	Type	Required	Description/Value
SourceAccount	long	Y	The Source Account is the account where a specified value is transferred from. Note that when value is transferred from one card to multiple cards simultaneously, the system must first confirm that the amount is available. The transferred value will be the same for each card.
SourceStartingCashValue	double	Y	The amount displayed here is the initial cash value source.
SourceStartingBonusCashValue	double	Y	The amount displayed is the initial amount of the bonus cash value prior to the split on the Source Account Card.
SourceStartingTokenValue	int	Y	The amount displayed here is the initial amount of the token value prior to the split on the Source Account card.
SourceStartingTokenBonusValue	int	Y	The amount displayed is the initial amount of the token bonus value prior to the split.
SourceStartingPointsValue	int	Y	The SourceStartingPointsValue is the initial number of points prior to the split.
SourceDebitCashValue	double	Y	The amount displayed is the amount of cash that will be debited from the Source card.
SourceDebitBonusCashValue	double	Y	The amount displayed is the amount of cash bonus that will be debited from the Source card
SourceDebitTokenValue	int	Y	The amount displayed is the amount of tokens that will be debited from the Source card

SplitCard Section			
Element Name	Type	Required	Description/Value
SourceDebitTokenBonusValue	int	Y	The amount displayed is the amount of token bonus that will be debited from the Source card
SourceDebitPointsValue	int	Y	The number of points that will be debited from the Source card.
TargetAccountsList	AccountNumber[]	Y	The list of accounts that will be split.
AccountNumber	long	Y	Account to be credited from split.
TargetCreditCashValue	double	Y	Amount of cash that will be credited on each target card.
TargetCreditBonusCashValue	double	Y	Amount of bonus cash that will be credited to the target card.
TargetCreditTokenValue	int	Y	Number of tokens that will be credited to the target card.
TargetCreditTokenBonusValue	int	Y	The amount displayed here is the token bonus amount that will be credited to the target card
TargetCreditPointsValue	int	Y	The amount of points to be transferred to the target card.

XML Example: SplitCard Request

```

<?xml version="1.0"?>
<iEnhancedInterfaceRequest xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <TransactionRequest>
    <RequestType>SplitCard</RequestType>
    <MacAddress>AAABBBCCDDDD</MacAddress>
    <TransactionID>0004</TransactionID>
    <SessionID>A0001</SessionID>
    <EmployeeID>stester</EmployeeID>
    <EmployeeName:>
      <FirstName>Some</FirstName>
      <LastName>Tester</LastName>
    </EmployeeName>
    <LT_DateTime>2015-01-23T13:55:42.1890247-06:00</LT_DateTime>
  </TransactionRequest>
</iEnhancedInterfaceRequest>

```

```

    <UTC_DateTime>2015-01-23T19:55:42.1890247Z</UTC_DateTime>
  </TransactionRequest>
  <SplitCard>
    <SourceAccount>15176</SourceAccount>
    <SourceStartingCashValue>20.00</SourceStartingCashValue>
    <SourceStartingBonusCashValue>20.00</SourceStartingBonusCashValue>
    <SourceStartingTokenValue>10</SourceStartingTokenValue>
    <SourceStartingTokenBonusValue>10</SourceStartingTokenBonusValue>
    <SourceStartingPointsValue>560</SourceStartingPointsValue>
    <SourceDebitCashValue>13.34</SourceDebitCashValue>
    <SourceDebitBonusCashValue>13.34</SourceDebitBonusCashValue>
    <SourceDebitTokenValue>6</SourceDebitTokenValue>
    <SourceDebitTokenBonusValue>6</SourceDebitTokenBonusValue>
    <SourceDebitPointsValue>372</SourceDebitPointsValue>
    <TargetAccountsList>
      <AccountNumber>14860</AccountNumber>
      <AccountNumber>19438</AccountNumber>
    </TargetAccountsList>
    <TargetCreditCashValue>6.67</TargetCreditCashValue>
    <TargetCreditBonusCashValue>6.67</TargetCreditBonusCashValue>
    <TargetCreditTokenValue>3</TargetCreditTokenValue>
    <TargetCreditTokenBonusValue>3</TargetCreditTokenBonusValue>
    <TargetCreditPointsValue>186</TargetCreditPointsValue>
  </SplitCard>
</iEnhancedInterfaceRequest>

```

SplitCard Response

CommandStatus Section			
Element Name	Type	Returned	Description/Value
ResponseCode	int	Y	A value of 0 indicates success; a non-zero value indicates an error occurred while processing the request.
ResponseDescription	string	Y	A text response providing additional information regarding the status of the request.

XML Example: SplitCard Response

```

<?xml version="1.0"?>
<iEnhancedInterfaceResponse xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <CommandStatus>
    <ResponseCode>0</ResponseCode>
    <ResponseDescription>Success</ResponseDescription>
  </CommandStatus>
</iEnhancedInterfaceResponse>

```


TransferAccount Transaction Request/Response XML Definitions

The TransferAccount function allows you to transfer the customer card information to a different account/card.

TransferAccount Request

TransactionRequest Section			
Element Name	Type	Required	Description/Value
RequestType	RequestTypeValue	Y	The RequestType must be set to TransferAccount .
MacAddress	string	Y	This is the MAC address of the request machine. <i>Note: The MAC address must be registered in the InterCard system.</i>
TransactionID	string	N	This is the transaction ID associated with the transaction on the requesting machine.
SessionID	string	N	The SessionID is the cash drawer session ID of the requesting machine.
EmployeeID	string	Y	<i>EmployeeID</i> , this is the employeeID on the requesting machine.
EmployeeName:	Complex	*	The *Employee Name is not required; however, if used, the Employee Name must include both the first and last names of the employee associated with the transaction.
EmployeeFirstName	string		
EmployeeLastName	string		
LT_DateTime	dateTime (requires millisecond resolution)	Y	This is the current local date/time of the location where the request is made.
UTC_DateTime	dateTime (requires millisecond resolution)	Y	UTC DateTime is the current UTCDateTime for the location where the transaction occurred.

TransferAccount Section			
Element Name	Type	Required	Description/Value
TargetAccount	long	Y	The Target Account is the account that the current card is being transferred to.
SourceAccount	long	Y	The Source Account is the account that contains the value being transferred.

TransferAccount Section			
Element Name	Type	Required	Description/Value
ReasonCode	int	N	The ReasonCode allows a user to select a predefined reason for the account transfer.

XML Example: TransferAccount Request

```

<?xml version="1.0"?>
<iEnhancedInterfaceRequest xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <TransactionRequest>
    <RequestType>TransferAccount</RequestType>
    <MacAddress>AAABBBCCDDDD</MacAddress>
    <TransactionID>0004</TransactionID>
    <SessionID>A0001</SessionID>
    <EmployeeID>stester</EmployeeID>
    <EmployeeName>
      <FirstName>Some</FirstName>
      <LastName>Tester</LastName>
    </EmployeeName>
    <LT_DateTime>2015-01-23T11:27:46.9323891-06:00</LT_DateTime>
    <UTC_DateTime>2015-01-23T17:27:46.9323891Z</UTC_DateTime>
  </TransactionRequest>
  <TransferAccount>
    <TargetAccount>15176</TargetAccount>
    <SourceAccount>19097</SourceAccount>
    <ReasonCode>1000</ReasonCode>
  </TransferAccount>
</iEnhancedInterfaceRequest>

```

TransferAccount Response

CommandStatus Section			
Element Name	Type	Returned	Description/Value
ResponseCode	int	Y	A value of 0 indicates success; a non-zero value indicates an error occurred while processing the request.
ResponseDescription	string	Y	A text response providing additional information regarding the status of the request.

XML Example: TransferAccount Response

```
<?xml version="1.0"?>
<iEnhancedInterfaceResponse xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <CommandStatus>
    <ResponseCode>0</ResponseCode>
    <ResponseDescription>Success</ResponseDescription>
  </CommandStatus>
</iEnhancedInterfaceResponse>
```

UpdateCustomerInfo Transaction Request/Response XML Definitions

UpdateCustomerInfo enables the ability to modify an existing customer's registration information.

UpdateCustomerInfo Request

TransactionRequest Section			
Element Name	Type	Required	Description/Value
RequestType	RequestTypeValue	Y	The RequestTypeValue must be set to UpdateCustomerInfo .
MacAddress	string	Y	This is the MAC address of the request machine. <i>Note: The MAC address must be registered in the InterCard system.</i>
TransactionID	string	N	This is the transaction ID associated with the transaction on the requesting machine.
SessionID	string	N	The SessionID is the cash drawer session ID of the requesting machine.
EmployeeID	string	Y	<i>EmployeeID</i> , this is the employeeID on the requesting machine.
EmployeeName:	Complex	*	*The Employee Name is not required; however, if used, the Employee Name must include both the first and last names of the employee associated with the transaction.
EmployeeFirstName	string		
EmployeeLastName	string		
LT_DateTime	dateTime (requires millisecond resolution)	Y	This is the current local date/time of the location where the request is made.
UTC_DateTime	dateTime (requires millisecond resolution)	Y	UTC DateTime is the current UTCDateTime for the location where the transaction occurred.

UpdateCustomerInfo Section			
Element Name	Type	Required	Description/Value
AccountNumber	long	Y	The account number is a set of individual numbers that are unique to a given card.
FirstName	string	Y	The first name of the cardholder assigned to the account.
LastName	string	Y	The last name of the cardholder assigned to the account.
Phone	string	N	The cardholder's phone number.
Email	string	N	The cardholder's email address.
PostalCode	string	N	The postal code for the cardholder's address.
DateOfBirth	dateTime	N	The cardholder's date of birth.
Gender	string	N	The cardholder's gender – Male/Female.

XML Example: UpdateCustomerInfo Request

```

<?xml version="1.0"?>
<iEnhancedInterfaceRequest xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <TransactionRequest>
    <RequestType>UpdateCustomerInfo</RequestType>
    <MacAddress>AAABBBCCDDDD</MacAddress>
    <TransactionID>0004</TransactionID>
    <SessionID>A0001</SessionID>
    <EmployeeID>stester</EmployeeID>
    <EmployeeName:>
      <FirstName>Some</FirstName>
      <LastName>Tester</LastName>
    </EmployeeName>
    <LT_DateTime>2015-01-23T12:03:30.0399678-06:00</LT_DateTime>
    <UTC_DateTime>2015-01-23T18:03:30.0399678Z</UTC_DateTime>
  </TransactionRequest>
  <UpdateCustomerInfo>
    <AccountNumber>19097</AccountNumber>
    <FirstName>Susan</FirstName>
    <LastName>Anthony</LastName>
    <Phone>555-555-1212</Phone>
    <Email>sa@email.com</Email>
    <PostalCode>555555</PostalCode>
    <DateOfBirth>1989-06-17T00:00:00</DateOfBirth>
  </UpdateCustomerInfo>
</iEnhancedInterfaceRequest>

```

```

    <Gender>female</Gender>
  </UpdateCustomerInfo>
</iEnhancedInterfaceRequest>

```

UpdateCustomerInfo Response

CommandStatus Section			
Element Name	Type	Returned	Description/Value
ResponseCode	int	Y	A value of 0 indicates success; a non-zero value indicates an error occurred while processing the request.
Response Description	string	Y	A text response providing additional information regarding the status of the request.

XML Example: UpdateCustomerInfo Response

```

<?xml version="1.0"?>
<iEnhancedInterfaceResponse xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <CommandStatus>
    <ResponseCode>0</ResponseCode>
    <ResponseDescription>Success</ResponseDescription>
  </CommandStatus>
</iEnhancedInterfaceResponse>

```

UpdateMembership Request/Response XML Definitions

UpdateMembership allows an account to change from the current membership to the selected, new membership.

UpdateMembership Request

TransactionRequest Section			
Element Name	Type	Required	Description/Value
RequestType	RequestTypeValue	Y	The RequestTypeValue must be set to UpdateMembership .
MacAddress	string	Y	This is the MAC address of the request machine. <i>Note: The MAC address must be registered in the InterCard system.</i>
TransactionID	string	N	This is the transaction ID associated with the transaction on the requesting machine.

TransactionRequest Section			
Element Name	Type	Required	Description/Value
SessionID	int	N	The SessionID is the cash drawer session ID of the requesting machine.
EmployeeID	int	Y	<i>EmployeeID</i> , this is the employeeID on the requesting machine.
EmployeeName:	Complex	*	*The Employee Name is not required ; however, if used, the Employee Name must include both the first and last names of the employee associated with the transaction.
EmployeeFirstName	string		
EmployeeLastName	string		
LT_DateTime	dateTime (requires millisecond resolution)	Y	This is the current local date/time of the location where the request is made.
UTC_DateTime	dateTime (requires millisecond resolution)	Y	UTC DateTime is the current UTCDateTime for the location where the transaction occurred.

UpdateMembership Section			
Element Name	Type	Required	Description/Value
AccountNumber	int	Y	The Account Number associated with the card for updating membership.
MembershipID	int	Y	Membership ID the Account is updating to from previous membership.,

XML Example: UpdateMembership Request

```

<?xml version="1.0"?>
<iEnhancedInterfaceRequest xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <TransactionRequest>
    <RequestType>UpdateMembership</RequestType>
    <MacAddress>AAABBBCCCDDD</MacAddress>
    <TransactionID>0001</TransactionID>
    <SessionID>A0001</SessionID>
    <EmployeeID>stester</EmployeeID>
    <EmployeeName>
      <FirstName>Some</FirstName>
      <LastName>Tester</LastName>
    </EmployeeName>
    <LT_DateTime>2018-03-05T15:16:45.4788146-06:00</LT_DateTime>
  </TransactionRequest>
</iEnhancedInterfaceRequest>

```

```

        <UTC_DateTime>2018-03-05T21:16:45.4788146Z</UTC_DateTime>
    </TransactionRequest>
    <UpdateMembership>
        <AccountNumber>12345</AccountNumber>
        <MembershipID>25</MembershipID>
    </UpdateMembership>
</iEnhancedInterfaceRequest>

```

UpdateMembership Response

CommandStatus Section			
Element Name	Type	Returned	Description/Value
ResponseCode	int	Y	A value of 0 indicates success; a non-zero value indicates an error occurred while processing the request.
ResponseDescription	string	Y	A text response providing additional information regarding the status of the request.

XML Example: UpdateMembership Response

```

<?xml version="1.0"?>
<iEnhancedInterfaceResponse xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
    <CommandStatus>
        <ResponseCode>0</ResponseCode>
        <ResponseDescription>Success</ResponseDescription>
    </CommandStatus>
</iEnhancedInterfaceResponse>

```

VoidCardTransaction Transaction Request/Response XML Definitions

VoidCardTransaction provides the capability to cancel an existing credit/debit transaction on a card. To void the transaction, the TP_TransactionID (Third Party TransactionID) must be unique and provided with the CreditAccounts transaction.

VoidCardTransaction Request

TransactionRequest Section			
Element Name	Type	Required	Description/Value
RequestType	RequestTypeValue	Y	The RequestType must be set to VoidCardTransaction .
MacAddress	string	Y	This is the MAC address of the request machine. <i>Note: The MAC address must be registered in the InterCard system.</i>

TransactionRequest Section			
Element Name	Type	Required	Description/Value
TransactionID	string	N	This is the transaction ID associated with the transaction on the requesting machine.
SessionID	int	N	The SessionID is the cash drawer session ID of the requesting machine.
EmployeeID	int	Y	<i>EmployeeID</i> , this is the employeeID on the requesting machine.
EmployeeName:	Complex	*	*The Employee Name is not required; however, if used, the Employee Name must include both the first and last names of the employee associated with the transaction.
EmployeeFirstName	string		
EmployeeLastName	string		
LT_DateTime	dateTime (requires millisecond resolution)	Y	This is the current local date/time of the location where the request is made.
UTC_DateTime	dateTime (requires millisecond resolution)	Y	UTC DateTime is the current UTCDateTime for the location where the transaction occurred.

VoidCardTransaction Section			
Element Name	Type	Required	Description/Value
AuthorizationEmployeeID	string	Y	This is the EmployeeID of the employee who authorized the void card transaction.
AuthorizationName:	Complex	*	The Authorization Name is not required; however, if used, the AuthorizationName must include both the first and last names of the employee who is authorized to void the transaction Format the rows with colon and Type values.
FirstName	string		
LastName	string		
VoidedTP_TransactionID	string	Y	The third party initial transaction ID.
VoidedCardsList	VoidedCard[]	Y	The list of voided cards.

VoidedCard Section			
Element Name	Type	Required	Description/Value
AccountNumber	long	Y	This is the account number associated with the voided card.
CreditedCash	double	Y	This field contains the amount of cash that is available on the card.
CreditedCashBonus	double	Y	This is the amount of bonus cash that is available on the card.
CreditedTokens	int	Y	This is the number of tokens that are available on the card.
CreditedTokenBonus	int	Y	This is the amount of bonus tokens available on the card.
CreditedPoints	int	Y	This is the amount of credited points available on the card.
CreditedDuration	int	Y	This is the length of time during which the credit is valid.

XML Example: VoidCardTransaction Request

```

<?xml version="1.0"?>
<iEnhancedInterfaceRequest xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <TransactionRequest>
    <RequestType>VoidCardTransaction</RequestType>
    <MacAddress>AAABBBCCDDDD</MacAddress>
    <TransactionID>0002</TransactionID>
    <SessionID>A0001</SessionID>
    <EmployeeID>stester</EmployeeID>
    <EmployeeName>
      <FirstName>Some</FirstName>
      <LastName>Tester</LastName>
    </EmployeeName>
    <LT_DateTime>2015-01-22T15:50:42.7309158-06:00</LT_DateTime>
    <UTC_DateTime>2015-01-22T21:50:42.7309158Z</UTC_DateTime>
    <TransactionRequest>
      <VoidCardTransaction>
        <AuthorizationEmployeeID>sleader</AuthorizationEmployeeID>
        <AuthorizationEmployeeName>
          <FirstName>Shift</FirstName>
          <LastName>Leader</LastName>
        </AuthorizationEmployeeName>
      </VoidCardTransaction>
    </TransactionRequest>
  </TransactionRequest>
</iEnhancedInterfaceRequest>

```

```

</AuthorizationEmployeeName>
<VoidedTransactionID>0001</VoidedTransactionID>
<VoidedCardsList>
  <VoidedCard>
    <AccountNumber>5</AccountNumber>
    <CreditedCash>10</CreditedCash>
    <CreditedBonusCash>5</CreditedBonusCash>
    <CreditedTokens>0</CreditedTokens>
    <CreditedTokenBonus>0</CreditedTokenBonus>
    <CreditedPoints>0</CreditedPoints>
    <CreditedDuration>0</CreditedDuration>
  </VoidedCard>
  <VoidedCard>
    <AccountNumber>6</AccountNumber>
    <CreditedCash>0</CreditedCash>
    <CreditedBonusCash>0</CreditedBonusCash>
    <CreditedTokens>0</CreditedTokens>
    <CreditedTokenBonus>0</CreditedTokenBonus>
    <CreditedPoints>0</CreditedPoints>
    <CreditedDuration>60</CreditedDuration>
  </VoidedCard>
</VoidedCardsList>
</VoidCardTransaction>
</iEnhancedInterfaceRequest>

```

VoidCardTransaction Response

CommandStatus Section			
Element Name	Type	Returned	Description/Value
ResponseCode	int	Y	A value of 0 indicates success; a non-zero value indicates an error occurred while processing the request.
ResponseDescription	string	Y	A text response providing additional information regarding the status of the request.

XML Example: VoidCardTransaction Response

```

<?xml version="1.0"?>
<iEnhancedInterfaceResponse xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <CommandStatus>
    <ResponseCode>0</ResponseCode>
    <ResponseDescription>Success</ResponseDescription>
  </CommandStatus>
</iEnhancedInterfaceResponse>

```

VoidPackageSale Transaction Request/Response XML Definitions

The VoidPackageSale option offers the capability to negate/nullify a package sale.

VoidPackageSale Request

TransactionRequest Section			
Element Name	Type	Required	Description/Value
RequestType	RequestTypeValue	Y	The RequestType must be set to VoidPackageSale .
MacAddress	string	Y	This is the MAC address of the request machine. <i>Note: The MAC address must be registered in the InterCard system.</i>
TransactionID	string	N	This is the transaction ID associated with the transaction on the requesting machine.
SessionID	string	N	The SessionID is the cash drawer session ID of the requesting machine.
EmployeeID	string	Y	<i>EmployeeID</i> , this is the employeeID on the requesting machine.
EmployeeName:	Complex	*	*The Employee Name is not required; however, if used, the Employee Name must include both the first and last names of the employee associated with the transaction.
EmployeeFirstName	string		
EmployeeLastName	string		
LT_DateTime	dateTime (requires millisecond resolution)	Y	This is the current local date/time of the location where the request is made.
UTC_DateTime	dateTime (requires millisecond resolution)	Y	UTC DateTime is the current UTCDateTime for the location where the transaction occurred.

VoidPackageSale Section			
Element Name	Type	Required	Description/Value
AccountNumber	long	Y	This is the account number assigned to the customer card used to make the purchase.
PackageID	int	Y	A text response providing additional information regarding the status of the request.

XML Example: VoidPackageSale Request

```
<?xml version="1.0"?>
<iEnhancedInterfaceRequest xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <TransactionRequest>
    <RequestType>VoidPackageSale</RequestType>
    <MacAddress>AAABBBCCDDDD</MacAddress>
    <TransactionID>0002</TransactionID>
    <SessionID>A0001</SessionID>
    <EmployeeID>stester</EmployeeID>
    <EmployeeName>
      <FirstName>Some</FirstName>
      <LastName>Tester</LastName>
    </EmployeeName>
    <LT_DateTime>2015-01-22T16:11:57.421824-06:00</LT_DateTime>
    <UTC_DateTime>2015-01-22T22:11:57.421824Z</UTC_DateTime>
  </TransactionRequest>
  <VoidPackageSale>
    <AccountNumber>10</AccountNumber>
    <PackageID>50</PackageID>
  </VoidPackageSale>
</iEnhancedInterfaceRequest>
```

VoidPackageSale Response

CommandStatus Section			
Element Name	Type	Returned	Description/Value
ResponseCode	int	Y	A value of 0 indicates success; a non-zero value indicates an error occurred while processing the request.
ResponseDescription	string	Y	A text response providing additional information regarding the status of the request.

XML Example: VoidPackageSale Response

```
<iEnhancedInterfaceResponse xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <CommandStatus>
    <ResponseCode>0</ResponseCode>
    <ResponseDescription>Success</ResponseDescription>
  </CommandStatus>
</iEnhancedInterfaceResponse>
```

VoidPaymentViaCustomerCard Transaction Request/Response XML Definitions

The VoidPaymentViaCustomerCardTransaction negates the PaymentViaCustomerCardTransaction. To void the transaction, the TP_TransactionID must be unique and provided with the Credit Accounts Transaction.

VoidPaymentViaCustomerCard Request

TransactionRequest Section			
Element Name	Type	Required	Description/Value
RequestType	RequestTypeValue	Y	The RequestType must be set to VoidPaymentViaCustomerCard transaction.
MacAddress	string	Y	This is the MAC address of the request machine. <i>Note: The MAC address must be registered in the InterCard system.</i>
TransactionID	string	N	This is the transaction ID associated with the transaction on the requesting machine.
SessionID	int	N	The SessionID is the cash drawer session ID of the requesting machine.
EmployeeID	int	Y	<i>EmployeeID</i> , this is the employeeID on the requesting machine.
EmployeeName:	Complex	*	*The Employee Name is not required; however, if used, the Employee Name must include both the first and last names of the employee associated with the transaction.
EmployeeFirstName	string		
EmployeeLastName	string		
LT_DateTime	dateTime (requires millisecond resolution)	Y	This is the current local date/time of the location where the request is made.
UTC_DateTime	dateTime (requires millisecond resolution)	Y	UTC DateTime is the current UTCDateTime for the location where the transaction occurred.

VoidPaymentViaCustomerCard Section			
Element Name	Type	Required	Description/Value
AuthorizationEmployeeID	string	Y	This field specifies the ID number of the employee who authorized the transaction.
AuthorizationName:	Complex	N	This field identifies the name of the employee who authorized the transaction.
FirstName	string	N	If the AuthorizationName is provided, then the first and last names are required.
LastName	string	N	If the AuthorizationName is provided, then the first and last names are required.
VoidedTP_TransactionID	string	Y	The voided third party initial transaction ID.
VoidedPaymentCardsList	VoidedPaymentCard[]	Y	A list of cards used in the voided transaction.

VoidedPaymentCard Section			
Element Name	Type	Required	Description/Value
AccountNumber	long	Y	Account Number to credit for voided payment.
PaymentCreditCash	double	Y	Amount of cash to credit the account.
PaymentCreditCashBonus	double	N	Amount of cash bonus to credit the account.

XML Example: VoidPaymentViaCustomerCard Request

```

<?xml version="1.0"?>
<iEnhancedInterfaceRequest xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <TransactionRequest>
    <RequestType>VoidPaymentViaCustomerCard</RequestType>
    <MacAddress>AAABBBCCDDDD</MacAddress>
    <TransactionID>0004</TransactionID>
    <SessionID>A0001</SessionID>
    <EmployeeID>stester</EmployeeID>
    <EmployeeName>
      <FirstName>Some</FirstName>
      <LastName>Tester</LastName>
    </EmployeeName>
  </TransactionRequest>
</iEnhancedInterfaceRequest>

```

```

<LT_DateTime>2015-01-23T11:22:10.6961575-06:00</LT_DateTime>
<UTC_DateTime>2015-01-23T17:22:10.6961575Z</UTC_DateTime>
</TransactionRequest>
<VoidPaymentViaCustomerCardTransaction>
  <VoidedPaymentCardsList>
    <VoidedPaymentCard>
      <AccountNumber>19097</AccountNumber>
      <PaymentCreditCash>5.00</PaymentCreditCash>
      <PaymentCreditCashBonus>1.00<PaymentCreditCashBonus>
    </VoidedPaymentCard>
  </VoidedPaymentCardsList>
  <AuthorizationEmployeeID>sleader</AuthorizationEmployeeID>
  <AuthorizationEmployeeName>
    <FirstName>Shift</FirstName>
    <LastName>Leader</LastName>
  </AuthorizationEmployeeName>
  <VoidedTransactionID>0004</VoidedTransactionID>
</VoidPaymentViaCustomerCardTransaction>
</iEnhancedInterfaceRequest>

```

VoidPaymentViaCustomerCard Response

CommandStatus Section			
Element Name	Type	Returned	Description/Value
ResponseCode	int	Y	A value of 0 indicates success; a non-zero value indicates an error occurred while processing the request.
ResponseDescription	string	Y	A text response providing additional information regarding the status of the request.

XML Example: VoidPaymentViaCustomerCard Response

```

<?xml version="1.0"?>
<iEnhancedInterfaceResponse xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <CommandStatus>
    <ResponseCode>0</ResponseCode>
    <ResponseDescription>Success</ResponseDescription>
  </CommandStatus>
</iEnhancedInterfaceResponse>

```