Amazon Fire TV — Install and Set Up BM TV Enabler

Install the Android phone enabler, choose the correct Fire TV and enable BM Remote Control.

1. Prepare and install the phone app

01 Check what you need

An Android phone, your Fire TV/Firestick, their home Wi-Fi and BM Remote Helper already installed and open on the TV. BM TV Enabler is for an Android phone, not iPhone or the TV. It enables BM Remote Control; it cannot switch on the TV's ADB debugging setting remotely.

02 Switch on TV debugging

On the TV: Settings > My Fire TV > Developer options > ADB debugging > ON. If Developer options is missing: My Fire TV > About, highlight the device name and press Select seven times, then go Back. Leave the TV awake. Do not expose debugging to the internet or forward its port on your router.

03 Get the official Enabler download

In BM Support Install Guides, choose TV Remote Enabler and press Get the app link. Scan the QR with your Android phone's camera, or tap Already on your phone? Tap here to download. Download the APK on the phone, not on the Fire TV.

04 Install on your Android phone

Open the downloaded APK from your browser's Downloads or the phone's Files app. If blocked, choose Settings and allow installs from that browser/Files app, then return and press Install. Open BM TV Enabler. If Android refuses the file or shows a warning you do not understand, ask BM Support rather than disabling phone security features.

Amazon Fire TV — Installation

2. Select and enable the right Fire TV

05 Join the same home Wi-Fi

Connect the Android phone to the same home network as the Fire TV; do not use mobile data or an isolated guest network. Different Wi-Fi bands are fine if your router allows devices to communicate. Keep BM Remote Helper open on the TV and note the TV’s address.

06 Find your TV

In BM TV Enabler, press Find my TV. It lists discoverable Amazon Fire TVs by name and address. Choose the one matching the address shown by BM Remote Helper, then press Use this TV. If several devices have similar names, the address is the deciding check. Searching does not enable any TV automatically.

07 Deal with an unreachable-debugging label

A listed TV with unreachable debugging may have ADB debugging off, be asleep or be blocked by Wi-Fi isolation. Check the TV’s debugging switch and wake it. The label is not proof that debugging is off. If no TV appears, type the address shown in the helper; not every Fire TV advertises itself.

08 Start enabling and approve on the TV

Press Turn on remote control on the phone and keep the app open. Watch the TV for Allow USB debugging? / Allow debugging? Tick Always allow from this computer if offered, then choose Allow. This approval authorises the Enabler’s connection from your phone; it is separate from screen-sharing consent.

Amazon Fire TV — Installation

3. Confirm setup and solve problems

09 Wait for the success message

Wait while the Enabler checks the TV, installs BM Remote Control if needed and enables its service. Continue only when the phone says Remote control is on. You can close this app. If an error appears, read it and complete the missing step before pressing Try again.

10 Return to remote help

Leave BM Remote Helper installed on the TV. Use the separate Amazon Fire TV — Use Remote Help guide to connect through a staff invitation in your own ticket or secure order. Enabling the control service alone does not start a screen share.

11 If connection or permission fails

Check the helper’s address again, same Wi-Fi, TV awake and ADB debugging ON. If you refused the debugging prompt, retry and approve the new prompt. If a previously saved permission does not work, ask staff to guide you through the TV’s debugging authorisations; do not factory-reset the TV. Router isolation can also prevent connection.

12 Understand what stays saved

Debugging and the enabled control service normally stay saved across ordinary TV restarts. You do not normally repeat this setup every time the TV powers on. The router may change the TV’s address; check it before retrying. A factory reset, app removal or some system updates may require setup again. If you turn debugging off after support, turn it on again before any future Enabler setup.