

# Cifrado Seguro Tomcat

Editar el archivo server.xml ubicado en la carpeta tomcat:

/etc/tomcat/server.xml

```
<Connector executor="tomcatThreadPool"
  port="8080" protocol="HTTP/1.1"
  connectionTimeout="20000"
  redirectPort="8443" />

-->
<!-- Define a SSL HTTP/1.1 Connector on port 8443
This connector uses the BIO implementation that requires the JSSE
style configuration. When using the APR/native implementation, the
OpenSSL style configuration is required as described in the APR/native
documentation -->

<Connector port="8443" protocol="org.apache.coyote.http11.Http11Protocol"
  maxThreads="150" SSLEnabled="true" scheme="https" secure="true"
  SSLCertificateKeyStoreFile="/etc/certificado.jks" sslProtocol="T
LS" />

<!-- Define an AJP 1.3 Connector on port 8009 -->
<Connector port="8009" protocol="AJP/1.3" redirectPort="8443" />

<!-- An Engine represents the entry point (within Catalina) that processes
every request. The Engine implementation for Tomcat stand alone
analyzes the HTTP headers included with the request, and passes them
on to the appropriate Host (virtual host).
```

Buscar el atributo ciphers en el Connector port="8443".

En caso que no esté agregarlo al final de este.

```
ciphers="TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_AES_256_
_GCM_SHA384,
TLS_ECDH_RSA_WITH_AES_256_GCM_SHA384,TLS_ECDH_ECDSA_WITH_AES_256_GCM_SHA
384,
TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SH
A256,
TLS_ECDH_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDH_ECDSA_WITH_AES_128_GCM_SHA
256,
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384,TLS_ECDHE_ECDSA_WITH_AES_256_CBC_SHA
384,
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA,TLS_ECDHE_ECDSA_WITH_AES_256_CBC_SHA,
TLS_ECDH_RSA_WITH_AES_256_CBC_SHA384,TLS_ECDH_ECDSA_WITH_AES_256_CBC_SHA3
84, TLS_ECDH_RSA_WITH_AES_256_CBC_SHA,TLS_ECDH_ECDSA_WITH_AES_256_CBC_SHA,
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_ECDSA_WITH_AES_128_CBC_SHA
256,
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA,TLS_ECDHE_ECDSA_WITH_AES_128_CBC_SHA,
TLS_ECDH_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDH_ECDSA_WITH_AES_128_CBC_SHA2
56, TLS_ECDH_RSA_WITH_AES_128_CBC_SHA,TLS_ECDH_ECDSA_WITH_AES_128_CBC_SHA"
```

Reiniciar el tomcat: service tomcat restart

**Nota:**

|            | Java 6 | Java 7 | Java 8 | Java 9 | Java 10 |
|------------|--------|--------|--------|--------|---------|
| Tomcat 7   | C      | B      | A      | A      | A       |
| Tomcat 8   | N/A    | B      | A      | A      | A       |
| Tomcat 8.5 | N/A    | B      | A      | A      | A       |
| Tomcat 9   | N/A    | N/A    | A      | A      | A       |

- Los resultados de SSL Labs arrojarán como máximo C en Java 6 porque no soporta TLS 1.1 o 1.2.
- Los resultados de SSL Labs arrojarán como máximo B en Java 7 porque no soporta cifrados AEAD.

Para más información ingresar a [Tomcat Wiki](#)