

Instalación SSL Zimbra

Archivos necesarios:

- Llave privada
- Certificado de servidor
- Certificados Root e Intermediario en un solo archivo (en ese orden).

Pasos:

1. Accedemos con el usuario zimbra

```
[root@mail ~]# su zimbra
[zimbra@mail root]$
```

2. Copiamos los certificados a la carpeta /opt/zimbra/ssl/zimbra/commercial (se recomienda hacer backup del certificado anterior)

```
[zimbra@mail commercial]$ pwd
/opt/zimbra/ssl/zimbra/commercial
[zimbra@mail commercial]$ ll
total 16
-rw-r-----. 1 zimbra zimbra 2786 ene 21 12:20 ChainBundle2.crt
drwxr-xr-x. 2 zimbra zimbra 123 ene 21 12:04 old
-rw-r--r--. 1 zimbra zimbra 1675 ene 21 12:17 private.key
-rw-r-----. 1 zimbra zimbra 4620 ene 21 12:20 ServerCertificate.crt
```

Nota: Todos los archivos deben pertenecer al usuario zimbra, en caso no sea así, modificar los permisos con: `chown zimbra:zimbra <nombre-archivo>`

3. Verificamos los certificados ejecutando el comando desde el usuario Zimbra:
`zmcertmgr verifycrt comm <ruta de la llave privada> <ruta del certificado de servidor> <ruta de la cadena de certificados>`

Ejemplo:

`zmcertmgr verifycrt comm private.key ServerCertificate.crt ChainBundle2.crt`

```
[zimbra@mail commercial]$ zmcertmgr verifycrt comm private.key ServerCertificate
.crt ChainBundle2.crt
** Verifying 'ServerCertificate.crt' against 'private.key'
Certificate 'ServerCertificate.crt' and private key 'private.key' match.
** Verifying 'ServerCertificate.crt' against 'ChainBundle2.crt'
Valid certificate chain: ServerCertificate.crt: OK
```

4. Copiar la llave privada renombrándola como commercial.key

```
[zimbra@mail commercial]$ cp private.key commercial.key
[zimbra@mail commercial]$ ll
total 20
-rw-r-----. 1 zimbra zimbra 2786 ene 21 12:20 ChainBundle2.crt
-rw-r-----. 1 zimbra zimbra 1675 ene 21 13:59 commercial.key
drwxr-xr-x. 2 zimbra zimbra 123 ene 21 12:04 old
-rw-r--r--. 1 zimbra zimbra 1675 ene 21 12:17 private.key
-rw-r-----. 1 zimbra zimbra 4620 ene 21 12:20 ServerCertificate.crt
```

5. Desplegamos el certificado en el servidor:
`/opt/zimbra/bin/zmcertmgr deploycrt comm <ruta del certificado de servidor> <ruta de la cadena de certificados>`

Ejemplo:

zmcertmgr deploycrt comm ServerCertificate.crt ChainBundle2.crt

```
[zimbra@mail commercial]$ zmcertmgr deploycrt comm ServerCertificate.crt ChainBundle2.crt
** Keeping first certificate in 'ServerCertificate.crt'
** Verifying 'ServerCertificate.crt' against '/opt/zimbra/ssl/zimbra/commercial/commercial.key'
Certificate 'ServerCertificate.crt' and private key '/opt/zimbra/ssl/zimbra/commercial/commercial.key' match.
** Verifying 'ServerCertificate.crt' against 'ChainBundle2.crt'
Valid certificate chain: ServerCertificate.crt: OK
** Copying 'ServerCertificate.crt' to '/opt/zimbra/ssl/zimbra/commercial/commercial.crt'
```

...

```
** Copying CA to /opt/zimbra/conf/ca
** Copying '/opt/zimbra/ssl/zimbra/ca/ca.key' to '/opt/zimbra/conf/ca/ca.key'
** Copying '/opt/zimbra/ssl/zimbra/ca/ca.pem' to '/opt/zimbra/conf/ca/ca.pem'
** Creating CA hash symlink '616a0386.0' -> 'ca.pem'
** Creating /opt/zimbra/conf/ca/commercial_ca_1.crt
** Creating CA hash symlink '8d33f237.0' -> 'commercial_ca_1.crt'
** Creating /opt/zimbra/conf/ca/commercial_ca_2.crt
** Creating CA hash symlink '2e5ac55d.0' -> 'commercial_ca_2.crt'
[zimbra@mail commercial]$
```

6. Verificamos el certificado instalado:

/opt/zimbra/bin/zmcertmgr viewdeployedcrt

```
[zimbra@mail commercial]$ zmcertmgr viewdeployedcrt
- imapd: /opt/zimbra/conf/imapd.crt
notBefore=Jan  4 19:36:57 2021 GMT
notAfter=Apr  4 19:36:57 2021 GMT
subject= /CN=*.bmtech.pe
issuer= /C=US/O=Let's Encrypt/CN=R3
SubjectAltName=*.bmtech.pe
- ldap: /opt/zimbra/conf/slapd.crt
notBefore=Jan  4 19:36:57 2021 GMT
notAfter=Apr  4 19:36:57 2021 GMT
subject= /CN=*.bmtech.pe
issuer= /C=US/O=Let's Encrypt/CN=R3
SubjectAltName=*.bmtech.pe
```

...

```
- proxy: /opt/zimbra/conf/nginx.crt
notBefore=Jan  4 19:36:57 2021 GMT
notAfter=Apr  4 19:36:57 2021 GMT
subject= /CN=*.bmtech.pe
issuer= /C=US/O=Let's Encrypt/CN=R3
SubjectAltName=*.bmtech.pe
[zimbra@mail commercial]$
```

7. Reiniciar el zimbra: zmcontrol restart

```
[zimbra@zimbra commercial]$ zmcontrol restart
Host zimbra.bmcert.com.br
    Stopping vmware-ha...skipped.
    /opt/zimbra/bin/zmhactl missing or not executable.
    Stopping zmconfigd...Done.
    Stopping zimlet webapp...Done.
    Stopping zimbraAdmin webapp...Done.
    Stopping zimbra webapp...Done.
    Stopping service webapp...Done.
    Stopping stats...Done.
    Stopping mta...Done.
    Stopping spell...Done.
    Stopping snmp...Done.
    Stopping cbpolicyd...Done.
    Stopping archiving...Done.
    Stopping opendkim...Done.
    Stopping amavis...Done.
    Stopping antivirus...Done.
    Stopping antispam...Done.
    Stopping proxy...Done.
    Stopping memcached...Done.
    Stopping mailbox...Done.
    Stopping logger...Done.
    Stopping dnscache...Done.
    Stopping ldap...Done.
Host zimbra.bmcert.com.br
    Starting ldap...Done.
    Starting zmconfigd...Done.
    Starting dnscache...Done.
    Starting logger...Done.
    Starting mailbox...Done.
    Starting memcached...Done.
    Starting proxy...Done.
    Starting amavis...Done.
    Starting antispam...Done.
    Starting antivirus...Done.
    Starting opendkim...Done.
    Starting snmp...Done.
    Starting spell...Done.
    Starting mta...Done.
    Starting stats...Done.
    Starting service webapp...Done.
    Starting zimbra webapp...Done.
    Starting zimbraAdmin webapp...Done.
    Starting zimlet webapp...Done.
```

Una vez termine de reiniciar, el certificado habrá sido correctamente instalado.