



IPG Gateway

VOID v 4.0 April 10, 2020

Notice: The information in this document is confidential and proprietary to BOIPA and is only intended for use by merchant customers of BOIPA, internal staff, and authorised business partners of BOIPA.

This document is protected by copyright restricting its use, replication in any format, and distribution. No part of this document may be reproduced in any form by any means without the express permission of BOIPA.

BOIPA reserves the right to amend, delete or add to the contents of the document, at any time, and to make improvements and/or changes to the products and/or programmes described in this document.

Every reasonable attempt will be made to ensure that the contents of the document are accurate, and a true reflection of the products and programmes described herein. However, BOIPA will not be held liable for any inaccuracies of any nature, however communicated by BOIPA.

BOIPA and other trademarks are trademarks or registered trademarks of their respective owners.

All other product names mentioned in this document are the trademarks of their respective owners.

© BOIPA 2017

Table of Contents

Document Purpose.....	2
1 Session Token API Operation	3
1.1 Session Token Request	3
1.1.1 Format	3
1.1.2 Definition.....	3
1.1.3 Example.....	3
1.2 Session Token Response – Processed	4
1.2.1 Format	4
1.2.2 Definition.....	4
1.2.3 Example.....	4
1.3 Session Token Response – Not Processed	5
1.3.1 Format	5
1.3.2 Definition.....	5
1.3.3 Example.....	5
2 VOID API Operation.....	6
2.1 Void Request	6
2.1.1 Format	6
2.1.2 Definition.....	6
2.1.3 Example.....	6
2.2 Void Response - Processed	6
2.2.1 Format	6
2.2.2 Definition.....	6
2.2.3 Example.....	7
2.3 Void Response – Not Processed.....	8
2.3.1 Format	8
2.3.2 Definition.....	8
2.3.3 Example.....	8

Document Purpose

The purpose of this document is to describe the VOID API Operation to enable merchant developers to integrate their webpages with the IPG Gateway. Refer to the *BOIPA Gateway – 0 – Overview* document for how this API Operation is used in the merchant processes.

VOID – API Operations can only be performed on transactions with a status of NOT_SET_FOR_CAPTURE, after an AUTH API operation. The VOID – API Operation effectively cancels the AUTH API operation.

1 Session Token API Operation

1.1 Session Token Request

1.1.1 Format

POST Request to Session Token Request URL (see Section 3 of the *BOIPA Gateway – 0 – Overview* document)

1.1.2 Definition

Parameter	Data Type	Mandatory	Description
merchantId	Integer (18)	Y	The identifier for the merchant in the IPG Gateway provided at on-boarding
password	String (64)	Y	The merchant's password to the IPG Gateway provided at on-boarding
action	String (enum)	Y	Must be "VOID"
timestamp	Integer (18)	Y	Milliseconds since 1970-01-01 00:00:00
allowOriginUrl	String (253)	Y	The merchant's URL that will make the Void Request (section 2.1) Cross-Origin Resource Sharing (CORS) headers will allow only this origin.
originalTxId	Integer (18)	N	The IPG Gateway transaction Id of the transaction to be voided This will have been returned in the <i>txId</i> field of the Auth/Purchase Response – Processed (see <i>BOIPA Gateway – 2 – AUTH-PURCHASE-VERIFY – Direct API</i> or <i>BOIPA Gateway – 2 – AUTH-PURCHASE-VERIFY – Hosted Payment Page</i> , as appropriate to the integration method)
originalMerchantTxId	String (50)	Y	The merchant's original transaction identifier of the transaction to be voided, that was provided in the <i>merchantTxId</i> field of the Auth/Purchase Session Token Request and Auth/Purchase Request (see <i>BOIPA Gateway – 2 – AUTH-PURCHASE-VERIFY – Direct API</i> or <i>BOIPA Gateway – 2 – AUTH-PURCHASE-VERIFY – Hosted Payment Page</i> , as appropriate to the integration method)
agentId	String (18)	N	Identifier of the merchant's operator or agent on behalf of the end customer, if the operation is not performed by the merchant, and the merchant wants to track the operator who performed the transaction Note: this is not the same as the <i>operatorId</i> or <i>userAgent</i> fields of the Auth/Purchase Session Token Request and Auth/Purchase/Verify Request (see <i>BOIPA Gateway – 2 – AUTH-PURCHASE-VERIFY – Direct API</i> or <i>BOIPA Gateway – 2 – AUTH-PURCHASE-VERIFY – Hosted Payment Page</i> , as appropriate to the integration method)

1.1.3 Example

merchantId=1111111&password=klw74U6yt40mNo&originalTxId=1234&originalMerchantTxId=12345&allowOriginUrl=www.merchantsite.com

1.2 Session Token Response – Processed

1.2.1 Format

JSON

1.2.2 Definition

Parameter	Data Type	Description
result	String (40)	Will always be "success"
merchantId	Integer (18)	The <i>merchantId</i> value received in the Session Token Request (section 1.1)
token	String (40)	The Session Token that is a one-time use, hexadecimal string The Session Token that must only be used for the Void Request (see Section 2.1) Session tokens are valid for 3600 second (1 hour) after which they expire Any requests with expired session tokens will be rejected
resultId	String (40)	Hexadecimal string that is to be used in any support request calls
processingTime	Integer (18)	The time in seconds for the process to complete
additionalDetails	Array	Not used – will always be "{}" or not included

1.2.3 Example

```
{
  "result": "success",
  "resultId": "85034083-22dd-49ff-9906-495098c42501",
  "merchantId": "167738",
  "additionalDetails": {},
  "processingTime": 33,
  "token": "72102985-5a92-4cde-a51b-9459d37d97a9"
}
```

1.3 Session Token Response – Not Processed

1.3.1 Format

JSON

1.3.2 Definition

Parameter	Data Type	Description
result	String (40)	Will always be "failure"
resultId	String (40)	Hexadecimal string that is to be used in any support request calls
processingTime	Integer (18)	The time in seconds for the process to complete
additionalDetails	Array	Not used – will always be "{}" or not included
errors	String Array	List of issues

1.3.3 Example

```
{
  "result": "failure",
  "resultId": "99392fc1-bcd9-4fb0-8838-7dc37256cb51",
  "additionalDetails": {},
  "errors": [
    { "messageCode": "This field is required in [REQUEST]", "fieldName": "password" }
  ],
  "processingTime": 4
}
```

2 VOID API Operation

2.1 Void Request

2.1.1 Format

POST Request to Action Request URL (see Section 3 of the *BOIPA Gateway – 0 – Overview* document)

2.1.2 Definition

Parameter	Data Type	Mandatory	Description
merchantId	Integer (18)	Y	The identifier for the merchant in the IPG Gateway provided at on-boarding This must be the same as that sent in the Session Token Request (section 1.1)
token	String (40)	Y	Session Token received in the Session Token Response – Processed (section 1.2)

2.1.3 Example

merchantId=1111111&token=fghij67890fghij67890

2.2 Void Response - Processed

2.2.1 Format

JSON

2.2.2 Definition

Parameter/Label	Data Type	Description	
result	String (40)	Will always be “success”	
merchantId	Integer (18)	The <i>merchantId</i> value sent in the Session Token Request (section 1.1)	
action	String (enum)	Will always be “VOID”	
originalMerchantTxId	String (50)	The merchant transaction identifier of the transaction that was voided	
originalTxId	Integer (18)	The IPG Gateway transaction Id of the transaction voided sent in the Session Token Request (section 1.1)	
amount	BigDecimal (15.2 or 15.3)	The transaction amount voided sent in the Session Token Request (section 1.1)	
currency	String (enum)	The transaction ISO alpha-3 currency code, as defined in the ISO 4217 standard , used in the original and void transactions	
customerId	String (20)	The IPG Gateway customer identifier used in the original and void transactions	
pan	String (100)	The customer account value/number used in the original and the void transactions	
brandId	Integer (18)	The <i>brandId</i> value for the original and the void transaction	
paymentSolutionId	Integer (18)	The <i>paymentSolutionId</i> value used in the original and void transactions	
status	String (enum)	The status of the transaction in IPG Gateway:	
		Status	Condition
		VOID	If “VOID” successful
		ERROR	If an error was returned by the payment process
errors	String (400)	Any errors that occurred during the successful processing of a transaction	
resultId	String (40)	Hexadecimal string that is to be used in any support request calls	
processingTime	Integer (18)	The time in seconds for the process to complete	
additionalDetails	Array	Not used – will always be “{}” or not included	

Parameter/Label	Data Type	Description
customParameter1Or... customParameter20Or	String (50)	The original 20x (50 character) free text fields provided by the merchant in the Session Token Request of the Auth/Purchase/Verify API Operation
customParameter1... customParameter20	String (50)	The 20x (50 character) free text fields provided by the merchant in the Session Token Request of the Auth/Purchase/Verify API Operation with the non-Basic Latin characters replaced by a space character. These values will have been sent for payment processing.

2.2.3 Example

```
{
  "result": "success",
  "resultId": "4fd9f223-bb1a-4879-a6e6-81a10b53bdca",
  "merchantId": 111111,
  "originalMerchantTxId": "abc123",
  "originalTxId": 123,
  "amount": 12.50,
  "currency": "GBP",
  "customerId": "mgn456",
  "action": "VOID",
  "pan": "45ae201ghy23498FjMj701",
  "brandId": 3,
  "paymentSolutionId": 500,
  "status": "VOID",
  "additionalDetails": {},
  "processingTime": 948
}
```

2.3 Void Response – Not Processed

2.3.1 Format

JSON

2.3.2 Definition

Parameter	Data Type	Description
result	String (40)	Will always be "failure"
txId	Integer (18)	The unique identifier for the void transaction attempt in the IPG Gateway
errors	String Array	List of errors.
resultId	String (40)	Hexadecimal string that is to be used in any support request calls
processingTime	Integer (6)	The time in seconds for the process to complete
customParameter1Or ... customParameter20Or	String (50)	The original 20x (50 character) free text fields provided by the merchant in the Session Token Request of the Auth/Purchase/Verify API Operation
customParameter1 ... customParameter20	String (50)	The 20x (50 character) free text fields provided by the merchant in the Session Token Request of the Auth/Purchase/Verify API Operation with the non-Basic Latin characters replaced by a space character. These values will have been sent for payment processing.

2.3.3 Example

```
{
  "result": "failure",
  "resultId": "308802f2-224d-44f5-b256-8d9443a72770",
  "additionalDetails": {},
  "errors": [
    { "messageCode": "This field is required in [TOKEN]", "fieldName": "amount" }
  ],
  "processingTime": 173
}
```