



PRODUCT PHOTO — EPFA STAINLESS HOUSING, ACCESS DOORS
OPEN SHOWING FILTER ROWS

Enviro-Pak Filter Assembly

Serious exhaust filtration. Zero plumbing.

Three stages of high-efficiency dry filtration remove smoke, grease vapor, and odor from light-duty kitchen exhaust — in a fully welded stainless steel housing that installs anywhere between your hood and the point of discharge. No water. No pumps. No chemistry.

MERV 14

HIGH-EFFICIENCY FINAL
FILTRATION

3-Stage

PRE-FILTER, HE, OPTIONAL
CARBON

UL 8782

LISTED POLLUTION CONTROL UNIT

Visible smoke and odor invite complaints — and code enforcement.

Cooking emissions become a neighborhood nuisance fast, and visible smoke or odor can alert authorities to compliance problems.

For light-duty commercial kitchens, the Enviro-Pak Filter Assembly removes those concerns with straight-through dry filtration — indoors or outdoors, at any point between the kitchen hood and the exhaust discharge.

Three Stages of Clean

1

Pre-Filter

Fiberbond DustLok MERV 9 multi-pocket filters capture grease and coarse particulate, protecting the stages behind them.

2

High-Efficiency

Camfil Hi-Flo MERV 14 multi-pocket filters strip fine smoke particles from the airstream.

3

High-Efficiency or Carbon

A second MERV 14 bank finishes the job — or swap in Cameron V-Bank carbon filters where odor is the priority.



AIRFLOW DIAGRAM — HOUSING SIDE VIEW, THREE LABELED FILTER ROWS F1 / F2 / F3

WHICH MOLITRON SYSTEM DO YOU NEED?

Light-duty cooking (limited smoke/grease load): Enviro-Pak Filter Assembly. **Heavy-duty cooking** (solid fuel, high-volume frying, wok lines): step up to the Enviro-Clean Air Scrubber. **Persistent odor either way:** add the Molitron Odor Abatement System. Not sure? One call: 303.969.8888.

Why operators choose the Enviro-Pak



Simple by Design

No water supply, no pumps, no solution dosing. One 115 VAC connection powers the monitoring system — that's the whole utility list for operation.



Always-On Monitoring

A remote lighted monitor panel in your kitchen or office tells you at a glance: green means running, red means filters need service. No guesswork, no surprise failures.



Fire-Suppression Ready

Pre-piped for building sprinkler connection — or order factory Ansul pre-piping where local code requires it.



Built to Last

Fully welded 18 Ga Type 304 stainless steel, gasketed access doors, and filter channels sealed with high-temperature silicone.



Fast, Tool-Free Service

Three removable access doors (optionally on both sides) open every filter row for a routine four-week filter check.



Fits Tight Spaces

Twelve widths (24"–144") on a 63"-long footprint — and units can be stacked for space savings. Consult the factory.

Technical Specifications

Construction

Housing	18 Ga Type 304 stainless steel, fully welded; sloped full-width top panel
Access	3 removable gasketed doors (option: doors both sides)
Filter channels	Three 1" welded T304 channels, sealed with high-temperature silicone
Base	Two full-width T304 rails, 1.5" × 4" × ⅛" wall, welded to housing bottom
Duct connection	1.5" perimeter flange for welding to connecting ductwork (ductwork by others)
Suspension	½"-13 hanger angles at each top corner with removable eyebolts; spring hangers, rods, hardware by others
Footprint	Width "W" × 63" long

Filtration

STAGE	FILTER	RATING
F1 — Pre-filter	Fiberbond DustLok multi-pocket, 23.31" × 23.31" × 12"	MERV 9
F2 — High-efficiency	Camfil Hi-Flo multi-pocket, 23.31" × 23.31" × 12"	MERV 14
F3 — Final	Camfil Hi-Flo MERV 14 — or Cameron V-Bank carbon (odor option), 23.375" × 23.375" × 12"	MERV 14 / carbon

Exhaust Fan Requirements

Listing	UL Listed for kitchen exhaust applications
Type	Backward-inclined utility fan with easily adjustable RPM
Sizing	[CONFIRM: 1.54" WG SP initial resistance per drawing / 2.5" WG SP per manual], plus hood and duct static losses

Capacity & Weights by Model

MODEL	WIDTH	CFM CAPACITY	APPROX. WEIGHT
EPFA-24	24"	[CONFIRM]	[CONFIRM]
EPFA-36 ... EPFA-144	36"-144"	[CONFIRM — from spec chart]	[CONFIRM]

Specifications subject to change without notice.

Installation & Contractor Scope

ITEM	REQUIREMENT	BY
Electrical	115 VAC supply to monitoring system (115 V → 24 V transformer furnished)	Contractor
Monitor cable	3-wire 18 Ga plenum cable, static pressure enclosure to monitor panel	Contractor
Drains	Three 1½" SS FPT cleaning drains to a common 2½" drain, routed to grease interceptor	Contractor
Ductwork	Welded to 1.5" perimeter flanges	Contractor
Suspension	Spring hangers, ½" threaded rods, hardware	Contractor

Clearances: 30" on the service-access side; 18" to combustibles and building insulation elsewhere; 0" to non-combustible materials. Above-ceiling installations require a permanent service platform (by others) level with the unit bottom.

The System Monitor — your early warning



Green: exhaust system on, airflow verified (1.5" WG switch).



Red / blinking red: static pressure has hit the adjustable high-limit (2–5" WG) — airflow is dropping. Inspect all filters and replace grease-laden rows immediately. Mount the panel where staff will see it: kitchen or office.

Fire Suppression Options

Building sprinkler: ¾" NPT stainless coupling furnished for connection to the building system (connection by others).
Ansul pre-piping (in lieu of water): where required by local code, order factory Ansul pre-piping with mechanical fusible-link detectors. On-site Ansul installer provides tanks, agent, final piping, actuators, permits, submittals, and testing.

Compliance



UL 8782 · File MH45752 · Models EPFA-24 through EPFA-144. Verify at iq.ulprospector.com. Install per Molitron instructions; local code compliance by installing contractor.

Why Molitron

The right size of solution.

We won't sell you a wet scrubber when dry filtration does the job — and the EPFA proves it: clean air with the lowest possible complexity and operating cost.

Name-brand filtration.

Fiberbond, Camfil, and Cameron media — industry-standard filters you can source and price transparently for the life of the system.

One family, one vendor.

EPFA, the Enviro-Clean Air Scrubber, and MOAS share one UL file and one engineering team. Grow from filtration to full scrubbing without starting over.

Monitoring included, not extra.

Every EPFA ships with static pressure monitoring and a remote status panel — so filter service happens when it's needed, not after the complaints start.

Size yours in one phone call.

- | | |
|--------------------------|--|
| → Request a Quote | cleanair@molitron.com |
| → Sizing & Stacking Help | 303.969.8888 |
| → Full Product Line | molitron.com |

Molitron Co Inc · Arvada, Colorado

© 2026 Molitron Company. Specifications subject to change without notice. UL and the UL Mark are trademarks of UL LLC. Ansul is a trademark of Johnson Controls. Camfil, Fiberbond, and Cameron are trademarks of their respective owners.