

**Blockchain Security | Smart Contract Audits | KYC** 

MADE IN GERMANY

# Audit

Security Assessment 30. September, 2021

For



Disclaimer	3
Description	5
Project Engagement	5
Logo	5
Contract Link	5
Methodology	7
Used Code from other Frameworks/Smart Contracts (direct imports)	8
Tested Contract Files	9
Source Lines	10
Risk Level	10
Capabilities	11
Scope of Work	13
Inheritance Graph	13
Verify Claims	14
CallGraph	19
Source Units in Scope	20
Critical issues	21
High issues	21
Medium issues	21
Low issues	21
Informational issues	21
Audit Comments	22
SWC Attacks	23

## **Disclaimer**

<u>SolidProof.io</u> reports are not, nor should be considered, an "endorsement" or "disapproval" of any particular project or team. These reports are not, nor should be considered, an indication of the economics or value of any "product" or "asset" created by any team. SolidProof.io do not cover testing or auditing the integration with external contract or services (such as Unicrypt, Uniswap, PancakeSwap etc'...)

SolidProof.io Audits do not provide any warranty or guarantee regarding the absolute bug- free nature of the technology analyzed, nor do they provide any indication of the technology proprietors. SolidProof Audits should not be used in any way to make decisions around investment or involvement with any particular project. These reports in no way provide investment advice, nor should be leveraged as investment advice of any sort.

SolidProof.io Reports represent an extensive auditing process intending to help our customers increase the quality of their code while reducing the high level of risk presented by cryptographic tokens and blockchain technology. Blockchain technology and cryptographic assets present a high level of ongoing risk. SolidProof's position is that each company and individual are responsible for their own due diligence and continuous security. SolidProof in no way claims any guarantee of security or functionality of the technology we agree to analyze.

Version	Date	Description
1.0	30. September 2021	<ul><li>Layout project</li><li>Automated- /Manual-Security Testing</li><li>Summary</li></ul>

### **Network**

Binance Smart Chain (BEP20)

#### Website

https://www.robmusk.com/

## **Telegram**

https://t.me/RobMusk

## **Twitter**

https://twitter.com/Rob\_Musk

## **Description**

RobMusk is a game base on BSC with a low threshold high playability interesting mechanisms.

## **Project Engagement**

During the 25th of September 2021, **RobMusk Token Team** engaged Solidproof.io to audit smart contracts that they created. The engagement was technical in nature and focused on identifying security flaws in the design and implementation of the contracts. They provided Solidproof.io with access to their code repository and whitepaper.



# Contract Link v1.0

https://bscscan.com/address/ 0xA53d857f0C3731b72C7e7013526442A09fcC7833#code

# **Vulnerability & Risk Level**

Risk represents the probability that a certain source-threat will exploit vulnerability, and the impact of that event on the organization or system. Risk Level is computed based on CVSS version 3.0.

Level	Value	Vulnerability	Risk (Required Action)
Critical	9 - 10	A vulnerability that can disrupt the contract functioning in a number of scenarios, or creates a risk that the contract may be broken.	Immediate action to reduce risk level.
High	7 – 8.9	A vulnerability that affects the desired outcome when using a contract, or provides the opportunity to use a contract in an unintended way.	Implementation of corrective actions as soon aspossible.
Medium	4 – 6.9	A vulnerability that could affect the desired outcome of executing the contract in a specific scenario.	Implementation of corrective actions in a certain period.
Low	2 – 3.9	A vulnerability that does not have a significant impact on possible scenarios for the use of the contract and is probably subjective.	Implementation of certain corrective actions or accepting the risk.
Informational	0 – 1.9	A vulnerability that have informational character but is not effecting any of the code.	An observation that does not determine a level of risk

# Auditing Strategy and Techniques Applied

Throughout the review process, care was taken to evaluate the repository for security-related issues, code quality, and adherence to specification and best practices. To do so, reviewed line-by-line by our team of expert pentesters and smart contract developers, documenting any issues as there were discovered.

## Methodology

The auditing process follows a routine series of steps:

- 1. Code review that includes the following:
  - i) Review of the specifications, sources, and instructions provided to SolidProof to make sure we understand the size, scope, and functionality of the smart contract.
  - ii) Manual review of code, which is the process of reading source code line-byline in an attempt to identify potential vulnerabilities.
  - iii) Comparison to specification, which is the process of checking whether the code does what the specifications, sources, and instructions provided to SolidProof describe.
- 2. Testing and automated analysis that includes the following:
  - i) Test coverage analysis, which is the process of determining whether the test cases are actually covering the code and how much code is exercised when we run those test cases.
  - ii) Symbolic execution, which is analysing a program to determine what inputs causes each part of a program to execute.
- 3. Best practices review, which is a review of the smart contracts to improve efficiency, effectiveness, clarify, maintainability, security, and control based on the established industry and academic practices, recommendations, and research.
- 4. Specific, itemized, actionable recommendations to help you take steps to secure your smart contracts.

# **Used Code from other Frameworks/Smart Contracts (direct imports)**

### Imported packages:

- · OpenZeppelin
  - Address
  - · Ownable
  - SafeMath
  - Context
  - · IERC20
- Uniswap
  - UniswapV2Factory
  - UniswapV2Pair
  - UniswapV2Router01
  - UniswapV2Router02

## **Tested Contract Files**

This audit covered the following files listed below with a SHA-1 Hash.


A file with a different Hash has been modified, intentionally or otherwise, after the security review. A different Hash could be (but not necessarily) an indication of a changed condition or potential vulnerability that was not within the scope of this review.

#### **v1.0**

File Name	SHA-1 Hash		
contracts/robmusm_token.sol	255759e4b3d8e5b295716853189ed0341a210906		

# **Metrics**

# Source Lines v1.0



# **Capabilities**

## **Components**

Version	Contracts	Libraries	Interfaces	Abstract
1.0	2	2	5	1

## **Exposed Functions**

This section lists functions that are explicitly declared public or payable. Please note that getter methods for public stateVars are not included.

Version	Public	Payable
1.0	106	8

Version	External	Internal Private		Pure	View
1.0	69	89	23	19	47

# **State Variables**

Version	Total	Public
1.0	33	8

# **Capabilities**

Version	Solidity Versions observed	Experim ental Features	Can Receive Funds	Uses Assembl Y	Has Destroya ble Contract s
1.0	>=0.4.2 2 <0.8.1 ^0.6.12 >=0.4.2 2 <0.8.0 >=0.6.2 >=0.5.0		yes	yes (2 asm blocks)	

Version	Transf ers ETH	Low- Level Calls	Delega teCall	Uses Hash Functi ons	ECRec over	New/ Create/ Create 2
1.0	yes			yes		


## **Scope of Work**

The above token Team provided us with the files that needs to be tested (Github, Bscscan, Etherscan, files, etc.). The scope of the audit is the main contract (usual the same name as team appended with .sol).

We will verify the following claims:

- 1. Correct implementation of Token standard
- 2. Deployer cannot mint any new tokens
- 3. Deployer cannot burn or lock user funds
- 4. Deployer cannot pause the contract
- 5. Overall checkup (Smart Contract Security)

# Inheritance Graph v1.0



# **Verify Claims**

# **Correct implementation of Token standard**



Function	Description	Exist	Tested	Verified
TotalSupply	provides information about the total token supply	$\checkmark$	<b>√</b>	$\checkmark$
BalanceOf	provides account balance of the owner's account	$\checkmark$	$\checkmark$	✓
Transfer	executes transfers of a specified number of tokens to a specified address	<b>√</b>	<b>√</b>	<b>√</b>
TransferFrom	executes transfers of a specified number of tokens from a specified address	<b>√</b>	<b>√</b>	<b>√</b>
Approve	allow a spender to withdraw a set number of tokens from a specified account	<b>√</b>	<b>√</b>	<b>√</b>
Allowance	returns a set number of tokens from a spender to the owner	<b>√</b>	1	<b>√</b>

# **Optional implementations**

Function	Description		Tested	Verified
renounceOwnership	Owner renounce ownership for more trust	$\checkmark$	<b>√</b>	X

# Deployer cannot mint any new tokens

Name	Exist	Tested	Verified	File
Deployer cannot mint	$\checkmark$	✓	✓	Main
Comment	Line: -			

## Max / Total Supply: 250.000.000.000



# Deployer cannot burn or lock user funds

Name	Exist	Tested	Verified
Deployer cannot lock	$\checkmark$	<b>√</b>	X
Deployer cannot burn	<b>√</b>	<b>√</b>	✓

#### Comments:

### **v1.0**

•




## Deployer cannot pause the contract

Name	Exist	Tested	Verified
Deployer cannot pause	$\checkmark$	$\checkmark$	$\checkmark$

#### Comments:

#### **v1.0**




## **Overall checkup (Smart Contract Security)**

Tested	Verified
$\checkmark$	✓

#### Legend

Attribute	Symbol
Verfified / Checked	$\checkmark$
Partly Verified	
Unverified / Not checked	X
Not available	-

# **CallGraph**



# **Source Units in Scope** v1.0

Туре	File	Logic Contracts	Interfaces	Lines	nLines	nSLOC	Comment Lines	Complex. Score	Capabilities
9	contracts/Kojitoken.sol	1		617	554	373	91	285	
2	Totals	1		617	554	373	91	285	

## Legend

Attribute	Description
Lines	total lines of the source unit
nLines	normalized lines of the source unit (e.g. normalizes functions spanning multiple lines)
nSLOC	normalized source lines of code (only source-code lines; no comments, no blank lines)
Comment Lines	lines containing single or block comments
Complexity Score	a custom complexity score derived from code statements that are known to introduce code complexity (branches, loops, calls, external interfaces,)

# **Audit Results**

# **AUDIT PASSED**

## **Critical issues**

- no critical issues found -

## **High issues**

- no high issues found -

## **Medium issues**

- no medium issues found -

### Low issues

Issue	File	Туре	Line	Description
#1	Main	Contract doesn't import npm packages from source (like OpenZeppelin etc.)		We recommend to import all packages from npm directly without flatten the contract. Functions could be modified or can be susceptible to vulnerabilities
#2	Main	A floating pragma is set	6	The current pragma Solidity directive is "">=0.4.22<0.8.1"".
#3	Main	Missing Zero Address Validation (missing- zero-check)	829, 981, 846	
#4	Main	State variable visibility is not set	747	It is best practice to set the visibility of state variables explicitly

## Informational issues

Issue	File	Туре	Line	Description
#1	Main	State variables that could be declared constant (constable-states)	722	Add the `constant` attributes to state variables that never change

#2	Main	Functions that are not used (dead-code)	1054-4056	Remove unused functions
----	------	---	-----------	-------------------------

## **Audit Comments**

## **30. September 2021:**

- · There is still an owner (Owner still has not renounced ownership)
- Deployer can
  - renounceOwnership
  - transferOwnership
  - Lock
  - Draw to wallet
  - · Set game pool wallet
  - Transfer to specific address
  - getBuildLvPayByAddress
  - getMuskLvPayByAddress
  - getTotalPayByAddress
  - setUniswap
    - Router
    - Pair
  - Exclude from fee
  - Include in fee
  - setShouldSwapToBnb
  - setSwapAndLiquifyEnabled
- · There are two transfer functions in the contract
  - One for sending tokens
  - One for sending bnb
- If you want to use muskLvUpgrade, you must send a number above 0
  of the tokens and ethers to use the function

# **SWC Attacks**

ID	Title	Relationships	Status
<u>SW</u> <u>C-13</u> <u>6</u>	Unencrypted Private Data On-Chain	CWE-767: Access to Critical Private Variable via Public Method	PASSED
<u>SW</u> <u>C-13</u> <u>5</u>	Code With No Effects	CWE-1164: Irrelevant Code	PASSED
<u>SW</u> <u>C-13</u> <u>4</u>	Message call with hardcoded gas amount	CWE-655: Improper Initialization	PASSED
<u>SW</u> <u>C-13</u> <u>3</u>	Hash Collisions With Multiple Variable Length Arguments	CWE-294: Authentication Bypass by Capture-replay	PASSED
<u>SW</u> <u>C-13</u> <u>2</u>	Unexpected Ether balance	CWE-667: Improper Locking	PASSED
<u>SW</u> <u>C-13</u> <u>1</u>	Presence of unused variables	CWE-1164: Irrelevant Code	PASSED
<u>SW</u> <u>C-13</u> <u>O</u>	Right-To-Left- Override control character (U+202E)	CWE-451: User Interface (UI) Misrepresentation of Critical Information	PASSED
<u>SW</u> <u>C-12</u> <u>9</u>	Typographical Error	CWE-480: Use of Incorrect Operator	PASSED
<u>SW</u> <u>C-12</u> <u>8</u>	DoS With Block Gas Limit	CWE-400: Uncontrolled Resource Consumption	PASSED

<u>SW</u> <u>C-12</u> <u>7</u>	Arbitrary Jump with Function Type Variable	CWE-695: Use of Low-Level Functionality	PASSED
<u>SW</u> <u>C-12</u> <u>5</u>	Incorrect Inheritance Order	CWE-696: Incorrect Behavior Order	PASSED
<u>SW</u> <u>C-12</u> <u>4</u>	Write to Arbitrary Storage Location	CWE-123: Write-what-where Condition	PASSED
<u>SW</u> <u>C-12</u> <u>3</u>	Requirement Violation	CWE-573: Improper Following of Specification by Caller	PASSED
<u>SW</u> <u>C-12</u> <u>2</u>	Lack of Proper Signature Verification	CWE-345: Insufficient Verification of Data Authenticity	PASSED
<u>SW</u> <u>C-12</u> <u>1</u>	Missing Protection against Signature Replay Attacks	CWE-347: Improper Verification of Cryptographic Signature	PASSED
<u>SW</u> <u>C-12</u> <u>0</u>	Weak Sources of Randomness from Chain Attributes	CWE-330: Use of Insufficiently Random Values	PASSED
<u>SW</u> <u>C-11</u> <u>9</u>	Shadowing State Variables	CWE-710: Improper Adherence to Coding Standards	PASSED
<u>SW</u> <u>C-11</u> <u>8</u>	Incorrect Constructor Name	CWE-665: Improper Initialization	PASSED
<u>SW</u> <u>C-11</u> <u>7</u>	Signature Malleability	CWE-347: Improper Verification of Cryptographic Signature	PASSED

<u>SW</u> <u>C-11</u> <u>6</u>	Timestamp Dependence	CWE-829: Inclusion of Functionality from Untrusted Control Sphere	PASSED
<u>SW</u> <u>C-11</u> <u>5</u>	Authorization through tx.origin	CWE-477: Use of Obsolete Function	PASSED
<u>SW</u> <u>C-11</u> <u>4</u>	Transaction Order Dependence	CWE-362: Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition')	PASSED
<u>SW</u> <u>C-11</u> <u>3</u>	DoS with Failed Call	CWE-703: Improper Check or Handling of Exceptional Conditions	PASSED
<u>SW</u> <u>C-11</u> <u>2</u>	Delegatecall to Untrusted Callee	CWE-829: Inclusion of Functionality from Untrusted Control Sphere	PASSED
<u>SW</u> <u>C-111</u>	Use of Deprecated Solidity Functions	CWE-477: Use of Obsolete Function	PASSED
<u>SW</u> <u>C-11</u> <u>O</u>	Assert Violation	CWE-670: Always-Incorrect Control Flow Implementation	PASSED
<u>SW</u> <u>C-10</u> <u>9</u>	Uninitialized Storage Pointer	CWE-824: Access of Uninitialized Pointer	PASSED
<u>SW</u> <u>C-10</u> <u>8</u>	State Variable Default Visibility	CWE-710: Improper Adherence to Coding Standards	NOT PASSED
<u>SW</u> <u>C-10</u> <u>7</u>	Reentrancy	CWE-841: Improper Enforcement of Behavioral Workflow	PASSED
<u>SW</u> <u>C-10</u> <u>6</u>	Unprotected SELFDESTRUC T Instruction	CWE-284: Improper Access Control	PASSED

<u>SW</u> <u>C-10</u> <u>5</u>	Unprotected Ether Withdrawal	CWE-284: Improper Access Control	PASSED
<u>SW</u> <u>C-10</u> <u>4</u>	Unchecked Call Return Value	CWE-252: Unchecked Return Value	PASSED
<u>SW</u> <u>C-10</u> <u>3</u>	Floating Pragma	CWE-664: Improper Control of a Resource Through its Lifetime	NOT PASSED
<u>SW</u> <u>C-10</u> <u>2</u>	Outdated Compiler Version	CWE-937: Using Components with Known Vulnerabilities	PASSED
<u>SW</u> <u>C-10</u> <u>1</u>	Integer Overflow and Underflow	CWE-682: Incorrect Calculation	PASSED
<u>SW</u> <u>C-10</u> <u>0</u>	Function Default Visibility	CWE-710: Improper Adherence to Coding Standards	PASSED



**Blockchain Security | Smart Contract Audits | KYC** 

