



## Chapter 2

### Console Input and Output

Slides prepared by Rose Williams,  
*Binghamton University*

Kennick Mock, *University of Alaska Anchorage*

PEARSON

ALWAYS LEARNING

#### `System.out.println` for console output

- `System.out` is an object that is part of the Java language
- `println` is a method invoked by the `System.out` object that can be used for *console output*
  - The data to be output is given as an argument in parentheses
  - A plus sign is used to connect more than one item
  - Every invocation of `println` ends a line of output

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-2

## Formatting Output with `printf`

- Starting with version 5.0, Java includes a method named `printf` that can be used to produce output in a specific format
- The Java method `printf` is similar to the `print` method
  - Like `print`, `printf` does not advance the output to the next line
- `System.out.printf` can have any number of arguments
  - The first argument is always a *format string* that contains one or more *format specifiers* for the remaining arguments
  - All the arguments except the first are values to be output to the screen

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-4

#### `printf` Format Specifier

- The code

```
double price = 19.8;
System.out.print("$");
System.out.printf("%6.2f", price);
System.out.println(" each");
```

will output the line

```
$ 19.80 each
```
- The format string "%6.2f" indicates the following:
  - End any text to be output and start the format specifier (%)
  - Display up to 6 right-justified characters, pad fewer than six characters on the left with blank spaces (i.e., *field width* is 6)
  - Display exactly 2 digits after the decimal point (.2)
  - Display a floating point number, and end the format specifier (i.e., the *conversion character* is `f`)

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-5

#### `println` Versus `print`

- Another method that can be invoked by the `System.out` object is `print`
- The `print` method is like `println`, except that it does not end a line
  - With `println`, the next output goes on a new line
  - With `print`, the next output goes on the same line

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-3

#### Right and Left Justification in `printf`

- The code

```
double value = 12.123;
System.out.printf("Start%8.2fEnd", value);
System.out.println();
System.out.printf("Start%-8.2fEnd", value);
System.out.println();
```

will output the following

```
Start    12.12End
Start12.12    End
```
- The format string "Start%8.2fEnd" produces output that is right justified with three blank spaces before the 12.12
- The format string "Start%-8.2fEnd" produces output that is left justified with three blank spaces after the 12.12

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-6

## Multiple arguments with `printf`

- The following code contains a `printf` statement having three arguments

- The code

```
double price = 19.8;  
String name = "magic apple";  
System.out.printf("$%.2f for each %s.",  
    price, name);  
System.out.println();  
System.out.println("Wow");  
will output  
$ 19.80 for each magic apple.
```

Wow

- Note that the first argument is a format string containing two format specifiers (%6.2f and %s)

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved. These format specifiers match up with the two arguments that

2-7

## Line Breaks with `printf`

- Line breaks can be included in a format string using %n

- The code

```
double price = 19.8;  
String name = "magic apple";  
System.out.printf("$%6.2f for each %s.%n", price,  
    name);  
System.out.println("Wow");  
will output  
$ 19.80 for each magic apple.
```

Wow

Copyright © 2012 Pearson Addison-Wesley.

2-8

## Format Specifiers for `System.out.printf`

Display 2.1 Format Specifiers for `System.out.printf`

CONVERSION CHARACTER	TYPE OF OUTPUT	EXAMPLES
d	Decimal (ordinary) integer	%5d %d
f	Fixed-point (everyday notation) floating point	%6.2f %f
e	E-notation floating point	%8.3e %e
g	General floating point (Java decides whether to use E-notation or not)	%8.3g %g
s	String	%12s %s
c	Character	%2c %c

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-9

## The `printf` Method (Part 1 of 3)

Display 2.2 The `printf` Method

```
1 public class PrintfDemo  
2 {  
3     public static void main(String[] args)  
4     {  
5         String aString = "abc";  
6  
6         System.out.println("String output:");  
7         System.out.println("START1234567890");  
8         System.out.printf("START%nEND %n", aString);  
9         System.out.printf("START%4sEND %n", aString);  
10        System.out.printf("START%2sEND %n", aString);  
11        System.out.println();
```

(continued)

Copyright © 2012 Pearson Addison-Wesley.

2-10

## The `printf` Method (Part 2 of 3)

Display 2.2 The `printf` Method

```
12 char oneCharcter = 'Z';  
13  
13     System.out.println("Character output:");  
14     System.out.println("START1234567890");  
15     System.out.printf("START%nEND %n", oneCharcter);  
16     System.out.printf("START%cEND %n", oneCharcter);  
17     System.out.println();  
18  
18     double d = 12345.123456789;  
19  
19     System.out.println("Floating-point output:");  
20     System.out.println("START1234567890");  
21     System.out.printf("START%FEND %n", d);  
22     System.out.printf("START%4FEND %n", d);  
23     System.out.printf("START%2FEND %n", d);  
24     System.out.printf("START%12.4FEND %n", d);  
25     System.out.printf("START%eEND %n", d);  
26     System.out.printf("START%12.5eEND %n", d);  
27     System.out.println();  
28 }
```

(continued)

Copyright © 2012 Pearson Addison-Wesley.

2-11

## The `printf` Method (Part 3 of 3)

Display 2.2 The `printf` Method

### SAMPLE DIALOGUE

String output:  
START1234567890  
STARTabcEnd  
START abcEnd  
STARTabcEnd

The value is always output. If the specified field width is too small, extra space is taken.

Character output:  
START1234567890  
STARTZEND  
START ZEND

Floating-point output:  
START1234567890  
START12345.123457END  
START12345.1235END  
START12345.12END  
START 12345.1235END  
START1.234512e+04END  
START 1.23451e+04END

Note that the output is rounded, not truncated, when digits are discarded.

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-12

## Formatting Money Amounts with `printf`

- A good format specifier for outputting an amount of money stored as a double type is `% .2f`
- It says to include exactly two digits after the decimal point and to use the smallest field width that the value will fit into:  
`double price = 19.99;`  
`System.out.printf("The price is $%.2f each.");`  
produces the output:  
`The price is $19.99 each.`

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-13

## Legacy Code

- Code that is "old fashioned" but too expensive to replace is called *legacy code*
- Sometimes legacy code is translated into a more modern language
- The Java method `printf` is just like a C language function of the same name
- This was done intentionally to make it easier to translate C code into Java

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-14

## Money Formats

- Using the `NumberFormat` class enables a program to output amounts of money using the appropriate format
  - The `NumberFormat` class must first be *imported* in order to use it
  - An object of `NumberFormat` must then be created using the `getCurrencyInstance()` method
  - The `format` method takes a floating-point number as an argument and returns a `String` value representation of the number in the local currency

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-15

## Money Formats

```
import java.text.NumberFormat;  
  
public class CurrencyFormatDemo  
{  
    public static void main(String[] args)  
    {  
        System.out.println("Default location:");  
        NumberFormat moneyFormater =  
            NumberFormat.getCurrencyInstance();  
  
        System.out.println(moneyFormater.format(19.8));  
        System.out.println(moneyFormater.format(19.81111));  
        System.out.println(moneyFormater.format(19.89999));  
        System.out.println(moneyFormater.format(19));  
        System.out.println();  
    }  
}
```

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-16

## Money Formats

- Output of the previous program

**Default location:**  
`$19.80`  
`$19.81`  
`$19.90`  
`$19.00`

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-17

## Specifying Locale

- Invoking the `getCurrencyInstance()` method without any arguments produces an object that will format numbers according to the default location
- In contrast, the location can be explicitly specified by providing a location from the `Locale` class as an argument to the `getCurrencyInstance()` method
  - When doing so, the `Locale` class must first be imported

`import java.util.Locale;`

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-18

## Specifying Locale

```
import java.text.NumberFormat;
import java.util.Locale;

public class CurrencyFormatDemo
{
    public static void main(String[] args)
    {
        System.out.println("US as location:");
        NumberFormat moneyFormater2 =
            NumberFormat.getCurrencyInstance(Locale.US);

        System.out.println(moneyFormater2.format(19.8));
        System.out.println(moneyFormater2.format(19.81111));
        System.out.println(moneyFormater2.format(19.89999));
        System.out.println(moneyFormater2.format(19));
    }
}
```

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-19

## Importing Packages and Classes

- Libraries in Java are called *packages*

- A package is a collection of classes that is stored in a manner that makes it easily accessible to any program
- In order to use a class that belongs to a package, the class must be brought into a program using an *import* statement
- Classes found in the package `java.lang` are imported automatically into every Java program

```
import java.text.NumberFormat;
// import the NumberFormat class only
import java.text.*;
// import all the classes in package java.text
```

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-22

## Specifying Locale

- Output of the previous program

**US as location:**  
**\$19.80**  
**\$19.81**  
**\$19.90**  
**\$19.00**

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-20

## Locale Constants for Currencies of Different Countries

Display 2.4 Locale Constants for Currencies of Different Countries	
Locale.CANADA	Canada (for currency, the format is the same as US)
Locale.CHINA	China
Locale.FRANCE	France
Locale.GERMANY	Germany
Locale.ITALY	Italy
Locale.JAPAN	Japan
Locale.KOREA	Korea
Locale.TAIWAN	Taiwan
Locale.UK	United Kingdom (English pound)
Locale.US	United States

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-21

## The DecimalFormat Class

- Using the `DecimalFormat` class enables a program to format numbers in a variety of ways
- The `DecimalFormat` class must first be *imported*
  - A `DecimalFormat` object is associated with a pattern when it is created using the new command
  - The object can then be used with the method `format` to create strings that satisfy the format
  - An object of the class `DecimalFormat` has a number of different methods that can be used to produce numeral strings in various formats

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-23

## The DecimalFormat Class (Part 1 of 3)

Display 2.5 The DecimalFormat Class

```
1 import java.text.DecimalFormat;
2 public class DecimalFormatDemo
3 {
4     public static void main(String[] args)
5     {
6         DecimalFormat pattern00dot000 = new DecimalFormat("00.000");
7         DecimalFormat pattern0dot00 = new DecimalFormat("0.00");
8
8         double d = 12.3456789;
9         System.out.println("Pattern 00.000");
10        System.out.println(pattern00dot000.format(d));
11        System.out.println("Pattern 0.00");
12        System.out.println(pattern0dot00.format(d));
13
14        double money = 19.8;
15        System.out.println("Pattern 0.00");
16        System.out.println("$" + pattern0dot00.format(money));
17
18        DecimalFormat percent = new DecimalFormat("0.00%");
19    }
20}
```

(continued)

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-24

## The DecimalFormat Class (Part 2 of 3)

Display 2-5 The DecimalFormat Class

```
18 System.out.println("Pattern 0.00%");  
19 System.out.println(percent.format(0.308));  
  
20 DecimalFormat eNotation1 =  
21     new DecimalFormat("#0.###E0");//1 or 2 digits before point  
22 DecimalFormat eNotation2 =  
23     new DecimalFormat("00.###E0");//2 digits before point  
  
24 System.out.println("Pattern #0.###E0");  
25 System.out.println(eNotation1.format(123.456));  
26 System.out.println("Pattern 00.###E0");  
27 System.out.println(eNotation2.format(123.456));  
  
28 double smallNumber = 0.0000123456;  
29 System.out.println("Pattern 0.###E0");  
30 System.out.println(eNotation1.format(smallNumber));  
31 System.out.println("Pattern 00.###E0");  
32 System.out.println(eNotation2.format(smallNumber));  
33 }  
34 }
```

(continued)

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-25

## The DecimalFormat Class (Part 3 of 3)

Display 2-5 The DecimalFormat Class

### SAMPLE DIALOGUE

```
Pattern 00.000  
12.346  
Pattern 0.00  
12.35  
Pattern 0.00  
$19.80  
Pattern 0.00%  
30.80%  
Pattern #0.###E0  
1.2346E2  
Pattern 00.###E0  
12.346E1  
Pattern #0.###E0  
12.346E-6  
Pattern 00.###E0  
12.346E-6
```

*The number is always given, even if this requires violating the format pattern.*

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-26

## Console Input Using the Scanner Class

- The following line creates an object of the class **Scanner** and names the object **keyboard**:  
`Scanner keyboard = new Scanner(System.in);`
- Although a name like **keyboard** is often used, a **Scanner** object can be given any name
  - For example, in the following code the **Scanner** object is named **scannerObject**  
`Scanner scannerObject = new Scanner(System.in);`
- Once a **Scanner** object has been created, a program can then use that object to perform keyboard input using methods of the **Scanner** class

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-28

## Console Input Using the Scanner Class

- The method **nextInt** reads one **int** value typed in at the keyboard and assigns it to a variable:  
`int numberOfPods = keyboard.nextInt();`
- The method **nextDouble** reads one **double** value typed in at the keyboard and assigns it to a variable:  
`double d1 = keyboard.nextDouble();`
- Multiple inputs must be separated by *whitespace* and read by multiple invocations of the appropriate method
  - Whitespace is any string of characters, such as blank spaces, tabs, and line breaks that print out as white space

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-29

## Console Input Using the Scanner Class

- Starting with version 5.0, Java includes a class for doing simple keyboard input named the **Scanner** class
- In order to use the **Scanner** class, a program must include the following line near the start of the file:  
`import java.util.Scanner`
- This statement tells Java to
  - Make the **Scanner** class available to the program
  - Find the **Scanner** class in a library of classes (i.e., Java package) named **java.util**

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-27

## Console Input Using the Scanner Class

- The method **next** reads one string of non-whitespace characters delimited by whitespace characters such as blanks or the beginning or end of a line
- Given the code  
`String word1 = keyboard.next();`  
`String word2 = keyboard.next();`  
and the input line  
`jelly beans`  
The value of **word1** would be **jelly**, and the value of **word2** would be **beans**

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-30

## Console Input Using the Scanner Class

- The method `nextLine` reads an entire line of keyboard input
- The code,  
`String line = keyboard.nextLine();`  
 reads in an entire line and places the string that is read into the variable `line`
- The end of an input line is indicated by the escape sequence '`\n`'
  - This is the character input when the `Enter` key is pressed
  - On the screen it is indicated by the ending of one line and the beginning of the next line
- When `nextLine` reads a line of text, it reads the '`\n`' character, so the next reading of input begins on the next line
  - However, the '`\n`' does not become part of the string value returned (e.g., the string named by the variable `line` above does not end with the '`\n`' character)

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-31

## Keyboard Input Demonstration (Part 1 of 2)

Display 2.6 Keyboard Input Demonstration

```
1 import java.util.Scanner;           Makes the Scanner class available to
2 public class ScannerDemo          your program.
3 {                                     Creates an object of the class
4     public static void main(String[] args)  Scanner and names the
5     {                                         object keyboard.
6         Scanner keyboard = new Scanner(System.in);
```

7 System.out.println("Enter the number of pods followed by");  
8 System.out.println("the number of peas in a pod:");  
9 int numberOfPods = keyboard.nextInt(); Each reads one int
10 int peasPerPod = keyboard.nextInt(); from the keyboard

11 int totalNumberOfPeas = numberOfPods\*peasPerPod;  
12 System.out.print(numberOfPods + " pods and ");  
13 System.out.println(peasPerPod + " peas per pod.");  
14 System.out.println("The total number of peas = "  
15 + totalNumberOfPeas);  
16 }  
17 }

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-32 (continued)

## Keyboard Input Demonstration (Part 2 of 2)

Display 2.6 Keyboard Input Demonstration

**SAMPLE DIALOGUE 1**

Enter the number of pods followed by  
the number of peas in a pod:  
22 10  
22 pods and 10 peas per pod.  
The total number of peas = 220

The numbers that are  
input must be  
separated by  
whitespace, such as  
one or more blanks.

**SAMPLE DIALOGUE 2**

Enter the number of pods followed by  
the number of peas in a pod:  
22  
10  
22 pods and 10 peas per pod.  
The total number of peas = 220

A line break is also  
considered whitespace and  
can be used to separate the  
numbers typed in at the  
keyboard.

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-33

## Another Keyboard Input Demonstration (Part 1 of 3)

Display 2.7 Another Keyboard Input Demonstration

```
1 import java.util.Scanner;
```

2 public class ScannerDemo Creates an object of  
3 { the class Scanner  
4 public static void main(String[] args) and names the object  
5 { scannerObject.

6 int n1, n2; ←  
7 Scanner scannerObject = new Scanner(System.in);

8 System.out.println("Enter two whole numbers");  
9 System.out.println("separated by one or more spaces:");  
10 n1 = scannerObject.nextInt(); ← Reads one int from the  
11 n2 = scannerObject.nextInt(); keyboard.  
12 System.out.println("You entered " + n1 + " and " + n2);  
13 System.out.println("Next enter two numbers.");  
14 System.out.println("Decimal points are allowed.");

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-34

(continued)

## Another Keyboard Input Demonstration (Part 2 of 3)

Display 2.7 Another Keyboard Input Demonstration

```
15 double d1, d2;           Reads one double from
16 d1 = scannerObject.nextDouble();   the keyboard.
17 d2 = scannerObject.nextDouble();
18 System.out.println("You entered " + d1 + " and " + d2);
```

19 System.out.println("Next enter two words:");  
20 String word1 = scannerObject.next(); ← Reads one word from
21 String word2 = scannerObject.next(); the keyboard.  
22 System.out.println("You entered '" + word1 + "' and '" + word2 + "'");  
23 String junk = scannerObject.nextLine(); //To get rid of '\n'

24 System.out.println("Next enter a line of text:");  
25 String line = scannerObject.nextLine(); ← This line is
26 System.out.println("You entered: " + line + "\n"); explained in the
27 } ← Detail section
28 } ← Dealing with the
29 } ← Line terminator,
 ← '\n'

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-35

(continued)

## Another Keyboard Input Demonstration (Part 3 of 3)

Display 2.7 Another Keyboard Input Demonstration

**SAMPLE DIALOGUE**

Enter two whole numbers  
separated by one or more spaces:  
42 43  
You entered 42 and 43  
Next enter two numbers.  
A decimal point is OK.  
9.99 57  
You entered 9.99 and 57.0  
Next enter two words:  
jelly beans  
You entered "jelly" and "beans"  
Next enter a line of text:  
Java flavored jelly beans are my favorite.  
You entered "Java flavored jelly beans are my favorite."

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-36

## Pitfall: Dealing with the Line Terminator, '\n'

- The method `nextLine` of the class `Scanner` reads the remainder of a line of text starting wherever the last keyboard reading left off
- This can cause problems when combining it with different methods for reading from the keyboard such as `nextInt`

```
Given the code,  
Scanner keyboard = new Scanner(System.in);  
  
int n = keyboard.nextInt();  
  
String s1 = keyboard.nextLine();  
  
String s2 = keyboard.nextLine();  
  
and the input,  
2  
  
Heads are better than  
1 head.
```

What are the values of `n`, `s1`, and `s2`?  
Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-37

## Pitfall: Dealing with the Line Terminator, '\n'

- Given the code and input on the previous slide  
`n` will be equal to "2",  
`s1` will be equal to "", and  
`s2` will be equal to "heads are better than"
- If the following results were desired instead  
`n` equal to "2",  
`s1` equal to "heads are better than", and  
`s2` equal to "1 head"  
then an extra invocation of `nextLine` would be needed to get rid of the end of line character ('\n')

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-38

## Methods in the Class `Scanner` (Part 2 of 3)

Display 2.8 Methods of the Scanner Class

<code>Scanner_Object_Name.nextLong()</code>
Returns the next value of type long that is typed on the keyboard.
<code>Scanner_Object_Name.nextByte()</code>
Returns the next value of type byte that is typed on the keyboard.
<code>Scanner_Object_Name.nextShort()</code>
Returns the next value of type short that is typed on the keyboard.
<code>Scanner_Object_Name.nextDouble()</code>
Returns the next value of type double that is typed on the keyboard.
<code>Scanner_Object_Name.nextFloat()</code>
Returns the next value of type float that is typed on the keyboard.

(continued)

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-40

## Methods in the Class `Scanner` (Part 3 of 3)

Display 2.8 Methods of the Scanner Class

<code>Scanner_Object_Name.nextLine()</code>
Returns the String value consisting of the next keyboard characters up to, but not including, the first delimiter character. The default delimiters are whitespace characters.
<code>Scanner_Object_Name.nextBoolean()</code>
Returns the next value of type boolean that is typed on the keyboard. The values of true and false are entered as the strings "true" and "false". Any combination of upper- and/or lowercase letters is allowed in spelling "true" and "false".
<code>Scanner_Object_Name.nextLine()</code>
Reads the rest of the current keyboard input line and returns the characters read as a value of type String. Note that the line terminator '\n' is read and discarded; it is not included in the string returned.
<code>Scanner_Object_Name.useDelimiter(New_Delimiter);</code>
Changes the delimiter for keyboard input with <code>Scanner_Object_Name</code> . The <code>New_Delimiter</code> is a value of type String. After this statement is executed, <code>New_Delimiter</code> is the only delimiter that separates words or numbers. See the subsection "Other Input Delimiters" for details.

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-41

## Methods in the Class `Scanner` (Part 1 of 3)

Display 2.8 Methods of the Scanner Class

The `Scanner` class can be used to obtain input from files as well as from the keyboard. However, here we are assuming it is being used only for input from the keyboard.  
To set things up for keyboard input, you need the following at the beginning of the file with the keyboard input code:  
  
`import java.util.Scanner;`  
You also need the following before the first keyboard input statement:  
  
`Scanner Scanner_Object_Name = new Scanner(System.in);`  
The `Scanner_Object_Name` can then be used with the following methods to read and return various types of data typed on the keyboard.  
Values to be read should be separated by whitespace characters, such as blanks and/or new lines. When reading values, these whitespace characters are skipped. (It is possible to change the separators from whitespace to something else, but whitespace is the default and is what we will use.)  
  
`Scanner_Object_Name.nextInt()`  
Returns the next value of type int that is typed on the keyboard.

(continued)

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-39

## Programming Tip: Prompt for Input

- A program should always prompt the user when he or she needs to input some data:  
`System.out.println("Enter the number of pods followed by");`  
`System.out.println("the number of peas in a pod:");`

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-42

## Programming Tip: Echo Input

- Always echo all input that a program receives from the keyboard
- In this way a user can check that he or she has entered the input correctly
  - Even though the input is automatically displayed as the user enters it, echoing the input may expose subtle errors (such as entering the letter "O" instead of a zero)

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-43

## The Empty String

- A string can have any number of characters, including zero characters
  - "" is the empty string
- When a program executes the **nextLine** method to read a line of text, and the user types nothing on the line but presses the **Enter** key, then the **nextLine** Method reads the empty string

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-46

## Self-Service Checkout Line (Part 1 of 2)

Display 2.9 Self-Service Check Out Line

```
1 import java.util.Scanner;
2 public class SelfService
3 {
4     public static void main(String[] args)
5     {
6         Scanner keyboard = new Scanner(System.in);
7
8         System.out.println("Enter number of items purchased.");
9         System.out.println("followed by the cost of one item.");
10        System.out.println("Do not use a dollar sign.");
11
12        int count = keyboard.nextInt();
13        double price = keyboard.nextDouble();
14        double total = count*price;
15
16        System.out.printf("%d items at %.2f each.%n", count, price);
17        System.out.printf("Total amount due %.2f.%n", total);
18
19        System.out.println("Please take your merchandise.");
20        System.out.println("Place %.2f in an envelope.%n", total);
21        System.out.println("and slide it under the office door.");
22        System.out.println("Thank you for using the self-service line.");
23        System.out.println("The dot after %.2f is a period in the");
24        System.out.println("text, not part of the format specifier.");
25    }
26 }
```

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

(continued)

2-44

## Other Input Delimiters

- The delimiters that separate keyboard input can be changed when using the **Scanner** class
- For example, the following code could be used to create a **Scanner** object and change the delimiter from whitespace to "##"

```
Scanner keyboard2 = new Scanner(System.in);
Keyboard2.useDelimiter("##");
```
- After invocation of the **useDelimiter** method, "##" and not whitespace will be the only input delimiter for the input object **keyboard2**

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-47

## Self-Service Checkout Line (Part 2 of 2)

Display 2.9 Self-Service Check Out Line

SAMPLE DIALOGUE

```
Enter number of items purchased
followed by the cost of one item.
Do not use a dollar sign.
10 19.99
10 items at $19.99 each.
Total amount due $199.90.
Please take your merchandise.
Place $199.90 in an envelope
and slide it under the office door.
Thank you for using the self-service line.
```

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-45

## Changing the Input Delimiter (Part 1 of 3)

Display 2.10 Changing the Input Delimiter

```
1 import java.util.Scanner;
2 public class DelimiterDemo
3 {
4     public static void main(String[] args)
5     {
6         Scanner keyboard1 = new Scanner(System.in);
7         Scanner keyboard2 = new Scanner(System.in);
8         keyboard2.useDelimiter("#");
9         //Delimiter for keyboard1 is whitespace.
10        //Delimiter for keyboard2 is #.
```

(continued)

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-48

## Changing the Input Delimiter (Part 2 of 3)

Display 2.10 Changing the Input Delimiter

```
11     String word1, word2;
12     System.out.println("Enter a line of text:");
13     word1 = keyboard1.next();
14     word2 = keyboard1.next();
15     System.out.println("For keyboard1 the two words read are:");
16     System.out.println(word1);
17     System.out.println(word2);
18     String junk = keyboard1.nextLine(); //To get rid of rest of line.
19
20     System.out.println("Reenter the same line of text:");
21     word1 = keyboard2.next();
22     word2 = keyboard2.next();
23     System.out.println("For keyboard2 the two words read are:");
24     System.out.println(word1);
25     System.out.println(word2);
26 }
```

(continued)

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-49

## Text Input

- Import the necessary classes in addition to **Scanner**  
`import java.io.FileInputStream;`  
`import java.io.FileNotFoundException;`
- Open the file inside a **try/catch** block
  - If an error occurs while trying to open the file then execution jumps to the catch block
  - This is discussed in more detail in Chapter 9
- Use **nextInt()**, **nextLine()**, etc. to read from the Scanner like reading from the console, except the input comes from the file

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-52

## Changing the Input Delimiter (Part 3 of 3)

Display 2.10 Changing the Input Delimiter

SAMPLE DIALOGUE

```
Enter a line of text:
one two##three##
For keyboard1 the two words read are:
one
two##three##
Reenter the same line of text:
one two##three##
For keyboard2 the two words read are:
one two
three
```

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-50

## Try/Catch Block

```
Scanner fileIn = null; // initializes fileIn to empty
try
{
    // Attempt to open the file
    fileIn = new Scanner( new FileInputStream("PathToFile"));
}
catch (FileNotFoundException e)
{
    // If the file could not be found, this code is executed
    // and then the program exits
    System.out.println("File not found.");
    System.exit(0);
}
... Code continues here
```

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-53

## Introduction to File Input/Output

- The Scanner class can also be used to read from files on the disk
- Here we only present the basic structure of reading from text files
  - Some keywords are introduced without full explanation
  - More detail in Chapter 10
  - By covering the basics here your programs can work with real-world data that would otherwise be too much work to type into your program every time it is run

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-51

## Text File to Read

Display 2.11 Sample Text File, player.txt, to Store a Player's High Score and Name

```
100510
Gordon Freeman
```

This file should be stored in the same folder as the Java program in the following display

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-54

## Program to Read a Text File

Display 2.12 Program to Read the Text File in Display 2.11

```
1 import java.util.Scanner;
2 import java.io.FileInputStream;
3 import java.io.FileNotFoundException;
4
5 public class TextFileDemo
6 {
7     public static void main(String[] args)
8     {
9         Scanner fileIn = null; // Initializes fileIn to empty
10        try
11        {
12            // Attempt to open the file
13            fileIn = new Scanner(
14                new FileInputStream("player.txt"));
15        }
16        catch (FileNotFoundException e)
17        {
18            // This block executed if the file is not found
19            // and then the program exits
20            System.out.println("File not found.");
21            System.exit(0);
22        }
23    }
24 }
```

*try and catch is explained in more detail in Chapter 9.*

*The file player.txt should be in the same directory as the Java program. You can also supply a full pathname to the file.*

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-55

## Program to Read a Text File

```
24 // If the program gets here then
25 // the file was opened successfully
26 int highscore;
27 String name;
28
29 System.out.println("Text left to read? " +
30     fileIn.hasNextLine());
31 highscore = fileIn.nextInt();
32 fileIn.nextLine(); // Read newline left from nextInt()
33 name = fileIn.nextLine();
34
35 System.out.println("Name: " + name);
36 System.out.println("High score: " + highscore);
37 System.out.println("Text left to read? " +
38     fileIn.hasNextLine());
39
40     fileIn.close();
41 }
```

*This line is explained earlier in this chapter in the Pitfall section "Dealing with the Line Terminator '\n'".*

Sample Dialogue

```
Text left to read? true
Name: Gordon Freeman
High score: 100510
Text left to read? False
```

Copyright © 2012 Pearson Addison-Wesley.  
All rights reserved.

2-56