

# JEngine Interface API Specification v0.2.2

## API Core Pfad:

http://domain.com:port/jengine/interface/{version}/{language}/scenario/{scenarioID}/

fragment/{fragmentID}/instance/{instanceID}/?  
activity/{activityID} instance/{instanceID}/?  
instance/{instanceID}/activityinstance/{activityinstanceID}/?

if id = 0, all content should be displayed.

If only id is provided, display details for this ID (e.g. label, timestamp..)

## Optionen:

| Option   | Value       | Beschreibung                                |
|----------|-------------|---|
| version  | e.g. v1     |   |
| language | e.g. de; en | ISO 3166-1 alpha-2 Country Code description |

## The following parameters are supported:

### Core Parameter

| Parameter  | Value (if null, display all)         | Dependency id | Beschreibung   |
|------------|--------------------------------------|---------------|--|
| status     | {init, enabled, terminated, skipped} |               |  |
| simulation | {true, false}                        |               | If true, value will be evaluated but not stored in database; usage: forecast model |
| limit      | integer                              |               |  |

## Get all Scenarios

http GET *http://domain.com:port/jengine/interface/{version}/{language}/scenario/0/*

returns JSON String with a list of available scenarios: {"ids":[1,2,3,100,101]}

## Get all Instances for a Scenario

http GET *http://domain.com:port/jengine/interface/{version}/{language}/scenario/1/instance/0/*

returns JSON String with a list of available instances of the scenario 1: {"ids":[47,48,49,50,51,52,53,54,55,58 5]}

## Get all Activities for an Instance of a Scenario

http GET *http://domain.com:port/jengine/interface/{version}/{language}/scenario/1/instance/47/?status=enabled*

returns JSON String with a list of enabled activities for the instance 47 of the scenario 1:  
{"ids":[5,4,16],"label":{"16":"ActivityFragment4","4":"Activity1Fragment2","5":"Activity2Fragment1"}}

## Get details for an ActivityInstanceID

http GET *http://domain.com:port/jengine/interface/{version}/{language}/scenario/1/instance/47/activityinstance/43/*

returns JSON String with a list of enabled activities for the instance 47 of the scenario 1:  
{"ids":[5,4,16],"label":{"16":"ActivityFragment4","4":"Activity1Fragment2","5":"Activity2Fragment1"}}

## Post update for an ActivityID

http POST *http://domain.com:port/jengine/interface/{version}/{language}/scenario/1/instance/47/activityinstance/43*

returns true

## POST start a new Instance of a Scenario

http POST *http://domain.com:port/jengine/interface/{version}/{language}/?scenario=1&instance=47&action=start*

returns new Instance ID.