

JEngine Interface API Specification v 0.3

API Core Pfad:

http://domain.com:port/jengine/api/ | interface/{version}/
config/{version}/
comparser/{version}/

Category Description

Interface	all calls related to the jFrontend and end user interaction
Config	All calls related to the configuration of the jcore
comparser	All calls related to the jComparser and its interaction

Optionen:

Option Value Description

version	e.g. v2	Currently, we are at version v2
language	e.g. de; en	ISO 3166-1 alpha-2 CountryCode description

The following parameters are supported:

Parameter	Value (if null, display all)	Dependency id	Description
status simulation	{init, enabled, terminated, skipped} {true, false}		If true, value will be evaluated but not stored in database; usage: forecast model
filter	string		

Examples - interface

Get all Scenarios

http GET *http://domain.com:port/jengine/interface/{version}/scenario/*

returns JSON String with a list of available scenarios:

```
{"ids":{"26645095":"Sprintplanung","791216108":"ReiseTestScenario","1216953148":"TT2Scenario","748715910":"szenario","2668923940096947866":"scenario"}}
```

Get detail information for a specific Scenario

http GET *http://domain.com:port/jengine/interface/{version}/scenario/1/*

returns JSON String with a list of available scenarios:

```
{"ids":{"26645095":"Sprintplanung","791216108":"ReiseTestScenario","1216953148":"TT2Scenario","748715910":"szenario","2668923940096947866":"scenario"}}
```

Get all Instances for a Scenario

http GET *http://domain.com:port/jengine/interface/{version}/scenario/1/instance/*

returns JSON String with a list of available instances of the scenario 1: {"ids":[47,48,49,50,51,52,53,54,55,58 5]}

Get detail information for a Scenario Instance

http GET *http://domain.com:port/jengine/interface/{version}/scenario/1/instance/47/*

returns JSON String with a list of enabled activities for the instance 47 of the scenario 1:

```
{"ids":[5,4,16],"label":{"16":"ActivityFragment4","4":"Activity1Fragment2","5":"Activity2Fragment1"}}
```

Get all Activities for an Instance of a Scenario

http GET *http://domain.com:port/jengine/interface/{version}/scenario/1/instance/47/activity/?status=enabled*

returns JSON String with a list of enabled activities for the instance 47 of the scenario 1:

```
{"ids":[5,4,16],"label":{"16":"ActivityFragment4","4":"Activity1Fragment2","5":"Activity2Fragment1"}}
```

Get details for an ActivityID

http GET *http://domain.com:port/jengine/interface/{version}/scenario/1/instance/47/activity/43/*

returns JSON String with a list of enabled activities for the instance 47 of the scenario 1

Get all Dataobjects

http GET *http://domain.com:port/jengine/interface/{version}/scenario/1/instance/328/dataobject/*

returns JSON String with a list of enabled activities for the instance 47 of the scenario 1:
{ "states": { "1": "bearbeitet", "2": "init" }, "ids": [1,2], "label": { "1": "object1", "2": "object2" } }

Get detail information for a specific Dataobject

http GET *http://domain.com:port/jengine/interface/{version}/scenario/1/instance/328/dataobject/45/*

returns JSON String with a list of enabled activities for the instance 47 of the scenario 1:
{ "states": { "1": "bearbeitet", "2": "init" }, "ids": [1,2], "label": { "1": "object1", "2": "object2" } }

POST update for an ActivityID

http POST *http://domain.com:port/jengine/interface/{version}/scenario/1/instance/47/activity/23/*

returns true / false

POST update state for an ActivityID

http POST *http://domain.com:port/jengine/interface/{version}/scenario/1/instance/47/activity/23/?status=terminated*

returns true / false

POST start a new Instance of a Scenario

http POST *http://domain.com:port/jengine/interface/{version}/scenario/1/instance/*

returns new Instance ID.

POST start a new Instance of a Scenario

http POST *http://domain.com:port/jengine/interface/{version}/scenario/1/instance/*

body {name}

returns true / false

Examples - config

Get all eMail tasks

http GET *http://domain.com:port/jengine/config/{version}/emailtask/*

returns JSON String with a list of available scenarios:

```
{ "ids": { "26645095": "Sprintplanung", "791216108": "ReiseTestScenario", "1216953148": "TT2Scenario", "748715910": "szenario", "2668923940096947866": "scenario" } }
```

Get detail information for a specific eMail tasks

http GET *http://domain.com:port/jengine/config/{version}/emailtask/23/*

returns JSON String with a list of available scenarios:

```
{ "ids": { "26645095": "Sprintplanung", "791216108": "ReiseTestScenario", "1216953148": "TT2Scenario", "748715910": "szenario", "2668923940096947866": "scenario" } }
```

Post update email task

http POST *http://domain.com:port/jengine/config/{version}/emailtask/23/*

returns true / false

Examples - jcomparser

Get all scenarios

http GET *http://domain.com:port/jengine/jcomparser/{version}/scenarios/*

returns JSON String with a list of available scenarios:

```
{ "ids": { "26645095": "Sprintplanung", "791216108": "ReiseTestScenario", "1216953148": "TT2Scenario", "748715910": "szenario", "2668923940096947866": "scenario" } }
```

Get images for scenarios

http GET *http://domain.com:port/jengine/jcomparser/{version}/scenarios/34/image/*

returns JSON String with a list of available scenarios:

```
{ "ids": { "26645095": "Sprintplanung", "791216108": "ReiseTestScenario", "1216953148": "TT2Scenario", "748715910": "szenario", "2668923940096947866": "scenario" } }
```

Post launch import of scenario

http POST *http://domain.com:port/jengine/jcomparser/{version}/launch/234/*

returns true / false